### NT 55/2 TACT<sup>2</sup> ME I

High performance dust extractor vacuum with Tact<sup>2</sup> automatic filter clean and stainless steel set-down container







Order no.

1.667-237.0

- Mobile stainless steel container
- Set-down mechanism
- Automatic Filter Cleaning System Tact²

| Technical data             |             |                         |
|----------------------------|-------------|-------------------------|
| EAN code                   |             | 4039784538092           |
| Supply voltage             | Ph / V / Hz | 1 / 220 - 240 / 50 - 60 |
| Air flow                   | I/s         | 2 × 74                  |
| Vacuum                     | mbar / kPa  | 254 / 25.4              |
| Container content          | 1           | 55                      |
| Container material         |             | Stainless steel         |
| Rated input power          | W           | max. 2760               |
| Standard nominal width     |             | ID 40                   |
| Cable length               | m           | 10                      |
| Sound pressure level       | dB(A)       | 73                      |
| Colour                     |             | silver                  |
| Weight without accessories | kg          | 43                      |
| Weight incl. packaging     | kg          | 51.7                    |
| Dimensions (L × W × H)     | mm          | 710 × 570 × 1070        |
|                            |             |                         |

| Equipment  |                  |  |
|--|------------------|--|
| Suction hose                                       | m                | 4 / electrically conductive                        |
| Bend   |                  | electrically conductive                            |
| Suction tube                                       | Piece(s) ×<br>mm | 2 × 550 / Stainless steel                          |
| Wet/dry floor nozzle                               | mm               | 360  |
| Crevice nozzle                                     |                  |  |
| Automatic cut-out features at max. filling quality |                  | •  |
| Antistatic preparation                             |                  |  |
| Stainless steel container                          |                  |  |
| Flat pleated filter                                |                  | Paper  |
| Filter cleaning                                    |                  | Automatic Filter Cleaning System Tact <sup>2</sup> |
| Push handle  |                  |  |
| Protection class                                   |                  | I  |
| Stop swivel castor                                 |                  |  |

■ Included in the scope of supply.



#### Set-down mechanism

- Easy raising and lowering of the container.
- Only the container is removed for emptying. The device and chassis remain at the location of use.

#### Real wet and dry vacuum cleaner

 When vacuuming liquids, the vacuum automatically switches itself off if the maximum filling level is reached, thanks to automatic filling level control.

#### Mobile stainless steel container

 The deposited container can be conveniently removed from the chassis and driven for disposal/emptying.





















|  |     | Order no.     | Description   |     |
|--|-----|---------------|---|-----|
| FLAT PLEATED FILTER, STANDARD, BIA C OR UF   | тог |               | Description   | _   |
| Flat pleated filter, paper   |     | OST CERSS III |   | _   |
| Flat pleated filter, paper   | 1   | 6.907-276.0   | Flat pleated filter dust class M, nano-coated paper. Suitable for fine dust and dry dirt pick up.   | ī   |
| Flat pleated filter, PTFE  |     |               |   | +   |
| Flat pleated filter, PTFE  | 2   | 6.907-449.0   | Polyester fleece with PTFE coating, dust class M, for Tact <sup>2</sup> vacuum cleaners. Particularly suitable for very adhesive materials.   | r   |
| BENDS  |     | '             |   |     |
| Bend, plastic  |     |               |   |     |
| Bend, NT, DN 40, plastic, electrically<br>conductive, clip 2.0 at hose end, cone at<br>accessory end | 3   | 2.889-172.0   | Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end.                     | •   |
| Bend, NT, DN 35, plastic, clip 1.0 at hose end, cone at accessory end                                | 4   | 5.031-718.0   | DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.   |     |
| Bend, NT, DN 35, plastic, electrically<br>conductive, clip 1.0 at hose end, cone at<br>accessory end | 5   | 5.031-939.0   | Electrically conductive DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.                     |     |
| Bend, NT, DN 40, plastic, electrically<br>conductive, clip 1.0 at hose end, cone at<br>accessory end | 6   | 5.032-427.0   | Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.                     |     |
| Bend, other  |     |               |   |     |
| Bend, NT, DN 35, chrome-plated metal, cone at hose end, cone at accessory end                        | 7   | 6.900-519.0   | DN 35 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.   |     |
| Bend, NT, DN 35, stainless steel, cone at hose end, cone at accessory end                            | 8   | 6.903-141.0   | Robust DN 35 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.  |     |
| Bend, NT, DN 40, chrome-plated metal, cone at hose end, cone at accessory end                        | 9   | 6.900-276.0   | DN 40 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The robust bend has a cone connection at both the hose end and the accessory end.                                    |     |
| Bend, NT, DN 40, stainless steel, cone at hose end, cone at accessory end                            | 10  | 6.902-079.0   | Robust DN 40 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.  |     |
| SUCTION NOZZLES  |     |               |   |     |
| Floor nozzies  |     |               |   |     |
| Wet/dry floor nozzle, advanced plastic, DN 40, width 360 mm  | 11  | 2.889-153.0   | 360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees.  |     |
| Wet/dry floor nozzle, standard plastic, DN 35  | 12  | 2.889-173.0   | 300 millimetre width, anthracite coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Incl. brush strips and squeegees.   |     |
| Wet/dry floor nozzle, standard plastic, DN 40  | 13  | 2.889-174.0   | Standard floor nozzle, anthracite, in nominal diameter 40, with brush strips and squeegees. Suitable for all wet and dry applications.  | e [ |
| Wet and dry floor nozzle, aluminium, DN 40   | 14  | 6.903-018.0   | All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners. |     |

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.

### **KÄRCHER**

























|   |    |             |   | _   |
|---|----|-------------|---|-----|
|   |    |             |   |     |
|   |    | Order no.   | Description   |     |
| SUCTION NOZZLES                                     |    |             |   |     |
| Floor nozzles                                       |    |             |   |     |
| Wet/dry floor nozzle, aluminium, DN 40              | 15 | 6.906-383.0 | All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners. |     |
| Wet/dry floor nozzle, aluminium, DN 35              | 16 | 6.906-384.0 | All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners. |     |
| Wet/dry floor nozzle, advanced plastic, DN 40       | 17 | 2.889-117.0 | The wet/dry floor nozzle (DN 40) permits a quick squeegee/brush change and is suitable for wet vacuum cleaning of large areas.  |     |
| Crevice nozzles                                     |    |             |   |     |
| Crevice nozzle, NT, DN 40, plastic, 300 mm          | 18 | 5.130-655.0 | Plastic crevice nozzle in nominal width DN 40 for Kärcher wet and dry vacuum cleaners. Especially suitable for vacuuming out areas that are difficult to reach, such as joints, crevices and corners.   | · 🔳 |
| Crevice nozzle, DN 35, plastic, length 210 mm       | 19 | 2.889-130.0 | With the DN 35 plastic crevice nozzle, corners and crevices can be vacuumed quickly and thoroughly. Length: 210 mm.   |     |
| Crevice nozzle, NT, DN 35, metal, 500 mm long       | 20 | 6.900-922.0 | The metal crevice nozzle (DN 35) enables vacuuming in crevices and corners. Length: 500 mm.   |     |
| Crevice nozzle, NT, DN 40, metal, 400 mm            | 21 | 6.905-817.0 | Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.   |     |
| All-purpose brushes                                 |    | ·           |   |     |
| All-purpose brush                                   | 22 | 6.903-863.0 | Natural bristles (ox hair), bristle element 120 × 45 mm.  |     |
| Car cleaning nozzles                                |    |             |   |     |
| Car nozzle, ID 40, 90 mm                            | 23 | 6.900-952.0 | For retrofitting older Kärcher wet and dry vacuum cleaner models with bends in DN 40: Flat angled, convenient, plastic car cleaning nozzle with a working width of approx. 90 mm.                       |     |
|   | 24 | 2.840-095.0 | Flat angled, convenient, plastic, DN 40 car cleaning nozzle specially designed for new Kärcher wet and dry vacuum cleaners with a clip system at the suction hose. Working width: Approx. 90 mm.        |     |
| Rubber suction tools, nose 45°                      |    | •           |   |     |
| Rubber suction tool, nose 45°                       | 25 | 6.902-104.0 | 45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.  |     |
| NT rubber suction nozzle, bevelled at 45°,<br>DN 40 | 26 | 6.902-105.0 | $45^\circ$ rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.   |     |
| Pipe dusting nozzles                                |    |             |   |     |
| Pipe brush 35/100                                   | 27 | 6.903-035.0 | Plastic, pipe diameter 100 mm   |     |
| Pipe brush 35/200                                   | 28 | 6.903-036.0 | Plastic, pipe diameter 200 mm   |     |

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\square$  Available accessories.

























|  |      |               |   | _ |
|--|------|---------------|---|---|
|  |      |               |   |   |
|  |      | Order no.     | Description   |   |
| SUCTION TUBES  |      |               |   |   |
| Suction tubes, stainless steel   |      |               |   |   |
| Suction tube, 2 x, NT, DN 40, 550 mm long, stainless steel, suitable for: NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 75/2   | 29   | 2.889-194.0   | The suction tube set consists of 2 suction tubes made of high-quality stainless steel (DN 40 and 550 mm long each). For Kärcher wet and dry vacuum cleaners.            |   |
| Suction tube, DN 35, 505 mm, stainless steel   | 30   | 6.902-154.0   | Suction tube made of high-quality stainless steel in DN 35 and 505 mm long for wet and dry vacuum cleaners from Kärcher.  |   |
| Suction tube, NT, DN 40, 550 mm long,<br>stainless steel, suitable for: AP 100/50, NT<br>55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT<br>75/2, NT 561, NT 611, NT 802 IV   | 31   | 6.902-081.0   | Suction tube made of high-quality stainless steel in nominal width DN 40 and 550 mm long for wet and dry vacuum cleaners from Kärcher.                                  |   |
| Suction tube, NT, DN 40, 1000 mm long,<br>stainless steel, suitable for: NT 55/2, NT 65/2,<br>NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561,<br>NT 611, NT 802 IV   | 32   | 6.906-531.0   | The suction tube made of high-quality stainless steel (DN 40 and 1000 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.                                |   |
| Suction tubes, metal   |      |               |   |   |
| Suction tube, 2 x, NT, DN 35, 550 mm long, chrome-plated steel, suitable for: NT 27/1, NT 30/1, NT 40/1, NT 50/1, NT 55/1, NT 65/2, NT 75/2  | 33   | 2.889-191.0   | The suction tube set consists of 2 chrome-plated steel suction tubes for Kärcher wet and dry vacuum cleaners, nominal width DN 35 and each suction tube is 550 mm long. |   |
| Suction tube, NT, DN 35, 505 mm long, chrome-plated steel, suitable for: NT 25/1, NT 27/1, NT 30/1, NT 35/1, NT 40/1, NT 48/1, NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/1, NT 75/2, NT 611, NT 802 IV | 34   | 6.900-514.0   | The suction tube made of chrome-plated steel (DN 35, 505 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.   |   |
| SUCTION HOSES  |      |               |   |   |
| Suction hoses with clip system 2.0 (compatible   | with | vacuum cleane | rs from model year 2017 on)   |   |
| Suction hose, NT, DN 40, length 4 m, electrically conductive, clip 2.0, bayonet 2.0  | 35   | 2.889-141.0   | The electrically conductive suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.                               |   |
| Suction hose, NT, DN 35, length 4 m, electrically conductive, clip 2.0, bayonet 2.0  | 36   | 2.889-137.0   | The electrically conductive suction hose in nominal width DN 35 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.                  |   |
| Suction hose, NT, DN 40, length 4 m, clip 2.0, bayonet 2.0   | 37   | 2.889-138.0   | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.   |   |
| Suction hose, NT, DN 40, length 2.5 m, clip 2.0, bayonet 2.0 $$  | 38   | 2.889-139.0   | The suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.  |   |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 2.0, bayonet 2.0  | 39   | 2.889-140.0   | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.                            |   |
| Suction hose, NT, DN 40, length 2.5 m, electrically conductive, clip 2.0, bayonet 2.0  | 40   | 2.889-142.0   | The electrically conductive suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.                             |   |
| Extension hose, NT, DN 40, length 2.5 m, clip 2.0, connecting adapter  | 41   | 2.889-146.0   | The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.                                      |   |
| Hose connection  |      |               |   |   |
| Adapter, ID 32/35, with internal thread  | 42   | 6.902-077.0   | Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.                             |   |

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.

























|  |      |               |  | $\top$ |
|--|------|---------------|--|--------|
|  |      |               |  |        |
|  |      | Order no.     | Description  |        |
| SUCTION HOSES  |      |               |  |        |
| Hose connection  |      |               |  |        |
| Connecting adapter, ID 40, with internal thread  | 43   | 6.900-286.0   | Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.                                       |        |
| Suction hoses with clip system 1.0 (compatible   | with | vacuum cleane | ers up to model year 2016)   |        |
| Extension hose, NT, DN 35, length 2.5 m, clip 1.0, connecting adapter  | 44   | 6.906-237.0   | The extension hose in nominal width DN 35 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.  |        |
| Repair kit for suction hoses DN 40 Clip 1.0  | 45   | 2.639-873.0   | Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.                                     |        |
| Extension hose, NT, DN 40, length 2.5 m, clip 1.0, connecting adapter  | 46   | 6.906-344.0   | The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.  |        |
| Suction hose with bend, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0   | 47   | 4.440-678.0   | The suction hose with bend in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.  |        |
| Suction hose, NT, DN 40, length 10 m, clip 1.0, bayonet 1.0  | 48   | 6.906-279.0   | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.   | у 🗆    |
| Suction hose, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0   | 49   | 6.906-321.0   | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.  |        |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 1.0, bayonet 1.0  | 50   | 6.906-714.0   | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.                                    |        |
| Suction hose with bend and PFC module, NT,<br>DN 40, length 4 m, electrically conductive, clip<br>1.0, bayonet 1.0 | 51   | 4.440-728.0   | The electrically conductive suction hose with bend and PFC module in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners. |        |
| Suction hose, NT, DN 40, length 16 m, clip 1.0, bayonet 1.0  | 52   | 6.906-635.0   | The suction hose in nominal width DN 40 and with 16 m length is suitable for use with wet and dry vacuum cleaners.   | у 🗆    |
| Suction hose, NT, DN 40, length 10 m, electrically conductive, clip 1.0, bayonet 1.0                               | 53   | 6.906-877.0   | The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.                         |        |
| Suction hoses with cone connection   |      |               |  |        |
| Suction hose, NT, DN 40, length 4 m, cone, bayonet 1.0   | 54   | 4.440-263.0   | The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.  |        |
| Suction hose, NT, DN 40, length 4 m, oil-resistant, cone, bayonet 1.0  | 55   | 4.440-303.0   | The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.                                    |        |
| Suction hose, NT, DN 40, length 10 m, cone, bayonet 1.0  | 56   | 4.440-463.0   | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.   | у 🗆    |

 $<sup>\</sup>hfill \square$  Available accessories.

### KÄRCHER

### ACCESSORIES FOR NT 55/2 TACT<sup>2</sup> ME I

### 1.667-237.0



























| SUSTION HOSES  | <u> </u> | Order no.   | Description   | L   |
|--|----------|-------------|---|-----|
| SUCTION HOSES  |          |             |   |     |
| Suction hoses with cone connection   | 1        | 1           |   | 1.  |
| Suction hose, NT, DN 40, length 10 m, electrically conductive, cone, bayonet 1.0 | 57       | 4.440-466.0 | The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.  |     |
| Suction hose, NT, DN 40, length 10 m, oil-resistant, cone, bayonet 1.0           | 58       | 4.440-612.0 | The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.  | / [ |
| Suction hose, NT, DN 50, length 4 m, cone, bayonet 1.0                           | 59       | 4.440-264.0 | The suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.   |     |
| Suction hose, NT, DN 50, length 3 m, cone, bayonet 1.0                           | 60       | 4.440-328.0 | The suction hose in nominal width DN 50 and with 3 m length is suitable for use with wet and dry vacuum cleaners.   |     |
| Suction hose, NT, DN 50, length 10 m, cone, bayonet 1.0                          | 61       | 4.440-467.0 | The suction hose in nominal width DN 50 and with 10 m length is suitable for use with wet and dry vacuum cleaners.  | / [ |
| Suction hose, NT, DN 50, length 4 m, oil-resistant, cone, bayonet 1.0            | 62       | 4.440-613.0 | The oil-resistant suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.   | [   |
| Suction hose, NT, DN 50, length 4 m, electrically conductive, cone, bayonet 1.0  | 63       | 4.440-616.0 | The electrically conductive suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.   | r [ |
| FILTER T/ NT   |          | '           |   |     |
| Flat pleated filter HEPA, dust class H   |          |             |   |     |
| HEPA-14 flat pleated filter  | 64       | 6.904-364.0 | For Kärcher wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter. Suitable for vacuuming hazardous dusts, coarse dirt and liquids.  |     |
| Fabric filter  |          |             |   | Ť   |
| Candle filter Wood, NT 65/2, NT 75/2   | 65       | 2.414-003.0 | Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums. | [   |
| CONNECTING SLEEVES   |          |             |   |     |
| Y-adapter kit  |          |             |   |     |
| Y-adapter kit  | 66       | 2.637-217.0 | Plastic distributor - suitable for NT vacuum cleaners.  | [   |
| Connection adapter C ID (clip to cone)   |          |             |   |     |
| Adapter clip DN 35 on cone DN 35   | 67       | 5.407-005.0 | Adapter clip system DN 35 for connecting suction tubes and small nozzles to cone DN 35. Perfect for vehicle interior cleaning, even without the connection of other nozzles.                          | [   |
| Adapter clip DN 40 to cone DN 40   | 68       | 5.407-006.0 | For connecting small nozzles and suction tubes with cone DN 40: Adapter clip system DN 40. Ideal for vehicle interior cleaning tasks, with no need to connect additional nozzles.                     |     |
| Connection adapter C DN 35   | 69       | 5.407-112.0 | C 35 hose connector for DN 35 accessory, electrically conductive.   | [   |
| Electrically conductive DN 40 connection adapter for DN 35 accessories           | 70       | 5.407-109.0 | Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.                         | [   |

<sup>☐</sup> Available accessories.



























|  |      |               |   | Т   |
|--|------|---------------|---|-----|
|  |      |               |   |     |
| CONNECTING OF PEACE  |      | Order no.     | Description   | _   |
| CONNECTING SLEEVES   |      |               |   | _   |
| Connection adapter C ID (clip to cone)   | l ¬. | l = 407 444 0 | C 40 have according to DN 40 according to the string the same destricts   | L   |
| Connection adapter C DN 40   | 71   | 5.407-111.0   | C 40 hose connector for DN 40 accessory, electrically conductive.   |     |
| Connection adapter for power tools, clip conne                                   |      | ı             |   | ,   |
| Power tool connection adapter, DN 26-36, electrically conductive                 | 72   | 5.453-042.0   | 3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.  | [   |
| Connection adapter for power tools, C 35,  | 73   | 5.453-048.0   | Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.   | [   |
| electrically conductive  | 74   | 5.453-050.0   | Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.  | [   |
| Adapter for electric power tools, screwable                                      |      |               |   | İ   |
| Adapter for electric power tools, screwable, ID 35                               | 75   | 5.453-016.0   | 3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.  | [   |
|  | 76   | 5.453-026.0   | Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.   | [   |
|  | 77   | 6.902-059.0   | Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.  | [   |
|  | 78   | 6.902-095.0   | 2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.                   | [   |
| Reducing sleeves   |      |               |   | Ť   |
| NT reducer from DN 40 to DN 35, electrically conductive                          | 79   | 5.407-108.0   | Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.   | [   |
| Reducer adapter from DN 40 to DN 35  | 80   | 6.902-017.0   | Reducer, enabling accessories (upholstery nozzle, crevice nozzle, etc.) with a DN 35 connection adapter to be connected to accessory parts (bend or suction tube) that have a DN 40 connection adapter. | [   |
| NT reduction bushing with clip system for DN 40 suction hoses on accessory DN 35 | 81   | 5.407-113.0   | Reducer (C $40$ to C $35$ ) for connecting accessories with C- $35$ clip connection to suction hoses with C $40$ clip system.   | : [ |
| Reducer from ID 35 to ID 32  | 82   | 6.902-072.0   | Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.  | [   |
| Reduction/expansion adapter kit  |      |               |   | Ť   |
| Set of reducers / adapter sleeves  | 83   | 2.860-117.0   | DN 40/35, DN 35/32 (tube -> nozzle), plastic.   |     |
| TARGET-GROUP-SPECIFIC ACCESSORY KITS FOR   | VAC  | UUM CLEANERS  | 5   | Ė   |
| Professional cleaning kit NT DN 40   | 84   | 2.637-353.0   | Single parts: 4 m suction hose (4.440-263.0), metal bend (6.900-276.0), 2x 0.5 m metal suction tubes (6.900-275.0), crevice nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).              | [   |

<sup>☐</sup> Available accessories.













|  |     | Order no.    | Description   |  |
|--|-----|--------------|---|--|
| TARGET-GROUP-SPECIFIC ACCESSORY KITS FOR         | VAC | JUM CLEANERS |   |  |
| NT accessory kit for vacuuming chips, DN 50      | 85  | 2.640-760.0  | Target group-specific robust connection set in DN 61 for cleaning work in combination with oil-resistant suction hose and rubber nozzle.  |  |
| OTHER ACCESSORIES NT                             |     |              |   |  |
| Cyclone preseparator CS 40 Me                    | 86  | 2.863-026.0  | The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry. |  |
| Adapter for NT hoses with bayonet connection 1.0 | 87  | 5.031-436.0  | Electroconductive adapter for connecting NT hoses with bayonet 1.0 connection of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher.           |  |
| OTHER ACCESSORIES SCRUBBER DRIERS                |     | '            |   |  |
| Miscellaneous                                    |     |              |   |  |
| Extension cable                                  | 88  | 6.647-022.0  | Extension cable, 20 m, 3x1.5 mm². With splash-proof earthing pin plug, strain relief and anti-kink sleeve.  |  |
| EMPTYING SUPPORTS                                |     |              |   |  |
| Emptying bags                                    |     |              |   |  |
| Disposal bag PE Ø 510 mm 100 l                   | 89  | 6.904-348.0  | Disposal bags made from PE for low-dust container emptying.   |  |

<sup>☐</sup> Available accessories.