

32" Industrial Battery-Operated Floor Scrubber

Kärcher's most powerful walk-behind scrubber









BD 80/120 W Bp



Kärcher's most powerful walk-behind floor scrubber

The BD 80/120 W Bp is Kärcher's largest walk behind floor scrubber and the most efficient machine in its range. The BD 80/120 W handles all cleaning jobs quickly, efficiently and with amazing maneuverability. It's heavy-duty design includes pneumatic tires, an industrial squeegee, 23-gallon solution and 25-gallon recovery tanks to support continuous cleaning of up to 3-hours. The BD 80/120 W also features tool-free, easy access brushes and batteries.





- 1 Significantly restricted line guidance of the casing
- For quick cleaning speeds.
- Allows a clear view of the area to be cleaned.
- 2 Easy access to brushes, batteries and recovery water tank
- Quick maintenance with no tools required.
- The recovery water tank can be easily cleaned.
- Optimum access to the batteries, motors or other components.

Standard Accessories - Brush Configuration

| Otanaara 7 | tooosones Brasil Comigaration | | |
|--|--|--|--|
| Order No. | Description | | |
| 8.600-033.0 | Brush, 16" Mild Grit, Blue with Wear Indicators | | |
| 8.600-753.0 | Skirt, Scrub Deck, Left Side | | |
| 8.600-754.0 | Skirt, Scrub Deck, Right Side | | |
| 8.600-143.0 | Blade, AQ, Left, 16" | | |
| 8.600-142.0 | Blade, AQ, Right, 16" | | |
| 8.600-749.0 | Squeegee, Rear Blade, Linatex | | |
| 8.600-983.0 | Squeegee, Front Blade, Linatex | | |
| Optional Accessories - Brush Configuration | | | |
| 8.600-031.0 | Brush, 16" Nylon, Scrub, with Wear Indicators (field installation required) | | |
| 8.600-032.0 | Brush, 16" Nylon Polishing, White with Wear Indicators (field installation required) | | |
| 8.600-033.0 | Brush, 16" Mid-grit with Wear Indicators (field installation required) | | |
| 8.600-034.0 | Brush, 16" Super Aggressive, Grey with Wear Indicators (field installation required) | | |
| 8.613-704.0 | Squeegee, Rear Blade, Urethane (field installation required) | | |
| 8.613-705.0 | Squeegee, Front Blade, Urethane (field installation required) | | |
| 8.613-516.0 | Blade, Aqua-Mizer™, Left, Urethane (field installation required) | | |
| 8.613-517.0 | Blade, Aqua-Mizer™, Right, Urethane (field installation required) | | |
| 8.609-064.0 | Wheel Assembly, 12" Non-Marking (2 required) (field installation required) | | |
| 8.613-741.0 | Wheel Assembly, 12" Solid Rubber (2 required) (field installation required) | | |
| 9.840-549.0 | Emergency Shut-off Kit (field installation required) | | |
| 9.840-555.0 | Pump Kit with flip tool, hose assembly and coupler (field installation required) | | |



Technical data

| | BD 80/120 W Bp (Brush Configuration) | BD 80/120 W Bp (Pad Configuration) |
|----------------------------|---|---|
| | | |
| | Includes curved vacuum barClearly arranged and flexibleRugged industrial machines | |
| Technical data | | |
| Brush working width | 32" (813 mm) | 32" (813 mm) |
| Working width, vacuum | 40" (1,016 mm) | 40" (1,016 mm) |
| Fresh/recovered water tank | 23 gallon / 25 gallon (87 / 95 l) | 23 gallon / 25 gallon (87 / 95 l) |
| Practical working capacity | 28,800 f ² /h (2,675 m ² /h) | 28,800 f²/h (2,675 m²/h) |
| Pad rotation speed | 200 rpm | 200 rpm |
| Brush contact pressure | 0 - 150 psi | 0 - 150 psi |
| Battery | 36 V | 36 V |
| Weight | 375 lbs (170 kg) | 375 lbs (170 kg) |
| Dimensions (L x W x H) | 62" x 24" x 45" (1800 mm x 710 mm x 1170 mm) | 62" x 24" x 45" (1800 mm x 710 mm x 1170 mm) |
| | | |
| Equipment | | |
| Roller brush | - | - |
| Disc brush | | |
| Traction drive | • | |
| 2-tank system | | |
| Curved vacuum bar | • | |
| Battery included | $\square / \blacksquare^{1)} / \blacksquare^{2)} / \blacksquare^{3)} / \blacksquare^{4)}$ | $\square / \blacksquare^{1)} / \blacksquare^{2)} / \blacksquare^{3)} / \blacksquare^{4)}$ |

9.840-732.0/-733.0/-734.0/-735.0/-736.0 9.840-822.0/-823.0/-824.0/-825.0/-826.0

Standard Accessories - Pad Configuration

| Order No. | Description | |
|--|--|--|
| 8.600-029.0 | Pad Driver, 16" SD | |
| 8.600-507.0 | Lock, Pad Center Snap, Two Step | |
| 8.600-753.0 | Skirt, Scrub Deck, Left Side | |
| 8.600-754.0 | Skirt, Scrub Deck, Right Side | |
| 8.600-143.0 | Blade, Aqua-Mizer™, Left, 16" | |
| 8.600-142.0 | Blade, Aqua-Mizer™, Right, 16" | |
| 8.600-749.0 | Squeegee, Rear Blade, Linatex | |
| 8.600-983.0 | Squeegee, Front Blade, Linatex | |
| Optional Accessories - Pad Configuration | | |
| 8.613-704.0 | Squeegee, Rear Blade, Urethane (field installation required) | |
| 8.613-705.0 | Squeegee, Front Blade, Urethane (field installation required) | |
| 8.613-516.0 | Left Scrub Deck Skirt, oil resistant polyurethane (field installation required) | |
| 8.613-517.0 | Right Scrub Deck Skirt, oil resistant polyurethane (field installation required) | |
| 8.609-064.0 | Wheel Assembly, 12" Non-Marking (2 required) (field installation required) | |
| 8.613-741.0 | Wheel Assembly, 12" Solid Rubber (2 required) (field installation required) | |
| 9.840-549.0 | Emergency Shut-off Kit (field installation required) | |
| 9.840-555.0 | Pump Kit with flip tool, hose assembly and coupler (field installation required) | |

[■] Included in delivery. ☐ Optional. 1)260 Ah, low-maintenance 2)330 Ah, low-maintenance 3)335 Ah, low-maintenance 4)312 Ah, AGM



Your Authorized Kärcher Floor Care Dealer: