



FloorPro Deep Cleaner RM 69 eco!efficiency

Powerful cleaning agent for flooring and industrial floors effortlessly removes stubborn oil, grease, soot and mineral contamination. With the eco!efficiency formulation, it is especially economical, effective and environmentally friendly.



NTA-free



Properties

- Powerful, environmentally friendly basic cleaner for heavily soiled industrial floors
- Dissolves heavy oil, grease and mineral stains
- Pleasant, fresh fragrance
- Effective quickly
- Rapidly separates oil/water in the oil separator (easy to separate=asf)
- NTA free

Areas:

- Car dealership and garage:** Floor cleaning
- Contract cleaning:** Floor cleaning
- Industry:** Floor cleaning
- Haulage contractors, bus operators:** Floor cleaning


Application

- Scrubber-dryers
- manual

Part number

2.5 l	6.295-650.0
10 l	6.295-651.0
20 l	6.295-652.0
200 l	6.295-653.0
1000 l	6.296-156.0

pH



Application:**Scrubber-driers - deep cleaning**

- Remove coarse dirt by sweeping.
- Use appropriate brush/roller/pad and squeegee for scrubber drier.
- Combine the product with the appropriate dosage and fresh water.
- Wet surface evenly with product (using brush/roller/pad as required).
- Allow to soak.
- Reaction time 5-10 minutes, depending on the degree of soiling.
- Vacuum the dirty water from the surface in overlapping sections.
- Rinse with plenty of clear water and soak in water until all dirt and cleaning agent residues have been removed.

Scrubber-driers - maintenance cleaning

- Remove coarse dirt by sweeping.
- Use appropriate brush/roller/pad and squeegee for scrubber drier.
- Combine the product with the appropriate dosage and fresh water.
- On DOSE machines, set the dosing only on the device.
- Clean the surface in overlapping sections.

manual

- Remove coarse dirt by sweeping.
- Combine the product with the appropriate dosage and fresh water.
- Clean surface manually.

Directions for use:

- Test on an inconspicuous part for material compatibility.
- Do not apply to wood, linoleum or unsealed parquet flooring.
- Do not apply to alkali-sensitive surfaces.
- Do not let the cleaning solution dry out.
- Store away from frost.

Warnings and safety recommendations according to EC Directives:

- Danger
- H314 Causes severe skin burns and eye damage
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P405 Store locked up.
- P501a Dispose of contents/container in accordance with local/regional/national/international regulations.

Further information:

- Material Safety Data Sheet (MSDS)

Dosage and yield:

Content:	Cleaning method:	Primary mixture:	Dosage:	Contamination:	Productivity:
1000 ml	Machine - maintenance cleaning		0.5-3 %		4890 m ²
1000 ml	Machine - intermediate cleaning		3-10 %	medium-strong	2000 m ²

Please contact us for more information:

Kärcher UK Ltd

Kärcher House
Brookhill Way
Banbury
Oxon OX16 3ED