



PressurePro Soaking Agent, alkaline RM 92 Agri

The soaking agent loosens dried dung to reduce cleaning time and water consumption. Corrosion inhibitors preserve stable fixtures. Ideal for stables and milk parlours.









Properties

- has excellent grease-dissolving properties and easily removes organic material such as dung, dirt and food remains.
- Penetrates even dried dung
- 100% biodegradable
- Does not damage any stable facilities (corrosion inhibitors)
- No negative effects on drain systems and biogas plants

Areas:

Agriculture:

Stable fixtures, milk parlours

Application

■ High-pressure washers

Part number 6.295-656.0

рΗ

14







10 I











Application:

High-pressure washers

- Apply evenly with cup foam lance or foam nozzle.
- Allow to soak for 10 30 minutes but do not let it dry out
- Then hose down with a high-pressure jet
- Repeat procedure for stubborn dirt

Warnings and safety recommendations according to EC Directives:

- Danger
- H290 May be corrosive to metals
- H314 Causes severe skin burns and eye damage
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P405 Store locked up.
- P501a Dispose of contents/container in accordance with local/regional/ national/international regulations.

Dosage and yield:

Content:	Cleaning method:	Primary mixture:	Dosage:	Contamination:	Productivity:
1000 ml	High-pressure washers		1-3 %	heavy	70 m²

Please contact us for more information:

Kärcher UK Ltd

Kärcher House Brookhill Way Banbury Oxon OX16 3ED