

## TankPro Cleaner, alkaline RM 875

Alkaline tank interior cleaner for thorough removal of heavy oil and grease contamination in tanks, silos, containers and more. Foam-reduced, powerful and gentle cleaning action.

**pH 13.2**  
in concentrate



### Properties

- Powerful, alkaline cleaner for tank interior cleaning systems
- Active dirt remover for efficient removal of food residue
- Effectively removes food residue such as sugar, egg yolk, oils, fats, chocolate
- With corrosion inhibitors for gentle cleaning of stainless steel and aluminium
- Without colourants or fragrances
- Suitable for use on food-contact surfaces
- Thermally stable in application up to 90°C
- Foam-reduced

### Usage options

- Manual - spray units
- High-pressure cleaner
- Cleaning station - tank interior cleaning

### Application areas

#### Forwarding agency, logistics

Tanker, Silo container, Intermediate Bulk Container (IBC), ISO container

#### Chemicals industry

Tanker, Silo container, ISO container

#### Food and drink industry

Tanker, Silo container, Intermediate Bulk Container (IBC), ISO container

### Technical data

Container sizes	Packaging unit	Part number
20 l	1 Piece(s)	6.295-919.0
200 l	1 Piece(s)	6.295-920.0
1000 l	1 Piece(s)	6.295-921.0

## Application

### Manual – spray units

- Adjust dosage according to level of dirt
- Apply product in sections to the surface to be treated.
- Allow to soak.
- Contact time 10-15 minutes, depending on the degree of soiling.
- Rinse thoroughly using a pressure washer

### High-pressure cleaner

- Apply primary mixture with fresh water.
- Set the dosage and temperature on the device
- 1-80°C processing temperature.
- Clean object, working in overlapping sections.
- Allow to soak.
- Contact time 1-5 minutes, depending on the degree of soiling.
- Rinse surface well with clear water.
- In food-processing applications, rinse thoroughly with drinking water.

### Cleaning station – tank interior cleaning

- Combine the product with the appropriate dosage and fresh water.
- Adjust dosage on the device.
- 60-80°C processing temperature.
- Start washing programme.
- Rinse surface well with clear water.

## Instructions for use

- Do not let the cleaning solution dry out.
- In the food sector, rinse thoroughly with drinking water.
- Wear protective clothing when using the product.

## Warnings and safety recommendations according to EC Directives

- Danger
- H290 May be corrosive to metals
- H314 Causes severe skin burns and eye damage
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P405 Store locked up.
- P501a Dispose of contents/container in accordance with local/regional/national/international regulations.

## Further information

- Material Safety Data Sheet (MSDS)

## Dosage and yield

Contents	Cleaning method	Primary mixture	Dosage	Soiling
1000 ml	Cleaning station – tank interior cleaning	1+3	0.5 – 3 %	heavy
1000 ml	Cleaning station – tank interior cleaning	1+10	0.5 – 3 %	medium
1000 ml	Manual – spray units		10 – 50 %	heavy
1000 ml	High-pressure cleaner		0.5 – 3 %	medium