

FloorPro Allround Deep Cleaner RM 754

Highly efficient coating removal agent for easy removal of wax and polymer coatings on water-resistant and alkali-sensitive floors. No time-consuming rinsing required.

pH value 10.5
in concentrate



Properties

- Powerful deep cleaner for removing protective coatings and dirt
- Removes heavy wax and polymer coatings
- Removes oil, grease and mineral contamination
- Can be used anywhere
- Wide range of applications: can be used for all water-resistant, alkali-sensitive (e.g. linoleum) and alkali-resistant (e.g. PVC) surfaces
- Very good material compatibility
- Low pH value in application concentration
- No time-consuming rinsing required
- Also suitable for maintenance cleaning
- High level of user safety and user-friendliness
- Pleasant, fresh citrus scent
- Low-foam formulation

Usage options

- Scrubber driers
- Single disc machines
- Wet and dry vacuum cleaners
- Manual

Application areas

Building cleaning	Floor cleaning
Nursing and retirement homes, doctor's surgeries	Floor cleaning
Hotels, gastronomy, catering	Floor cleaning
Municipal	Floor cleaning
Retail	Floor cleaning

Technical data

Container sizes	Packaging unit	Part number
10 l	1 Piece(s)	6.295-811.0

Application

Deep cleaning (dirt)

- Remove coarse dirt by sweeping.
- Use appropriate brush/roller/pad or squeegee for scrubber drier or single disc machine.
- Dose the product with clean water accordingly.
- Wet surface evenly with product (using brush/roller/pad as required).
- Allow to soak.
- Contact time 1-10 minutes, depending on the degree of soiling.
- Clean surface with machine and appropriate accessories.
- Suck the dirt from the surface.
- Remove all dirt and cleaning agent residues with clear water (damp mop with low dose as required, rinse with clear water and soak in water with high dose).

Deep cleaning (care film)

- Remove coarse dirt by sweeping.
- Use appropriate brush/roller/pad or squeegee for scrubber drier or single disc machine.
- Dose the product with clean water accordingly.
- Wet surface evenly with product (using brush/roller/pad as required).
- Allow to soak.
- Contact time 5-10 minutes, depending on the thickness of the care film.
- Clean surface with machine and appropriate accessories.
- Clean inaccessible areas manually.
- Suck the dirt from the surface.
- Remove all dirt and cleaning agent residues with clear water (damp mop with low dose as required, rinse with clear water and soak in water with high dose).

Maintenance cleaning

- Remove coarse dirt by sweeping.
- Use appropriate brush/roller/pad and squeegee for scrubber drier as required.
- Dose the product with clean water accordingly.
- Clean and vacuum the surface with a scrubber dryer using the 1-step method.

Instructions for use

- Test on an inconspicuous part for material compatibility.
- Do not apply to wood or unsealed parquet flooring.
- Do not use on surfaces sensitive to solvents such as asphalt.
- Do not let the cleaning solution dry out.
- Store away from frost.
- Only store in original container between -5 and +30°C.
- Clean the cleaning machine after use.

Warnings and safety recommendations according to EC Directives

- Warning
- H319 Causes serious eye irritation
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash thoroughly after handling.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.

Further information

- Material Safety Data Sheet (MSDS)
- Quick Start
- FIGR expertise (Forschungs- und Prüfinstitut für Facility Management GmbH)

Dosage and yield

Contents	Cleaning method	Dosage	Soiling	Yield
1000 ml	Deep cleaning (care film)	15 - 50 %	medium-strong	30 - 50 m ²
1000 ml	Deep cleaning (dirt)	10 - 20 %	medium-strong	50 - 200 m ²
1000 ml	Maintenance cleaning	1 - 3 %	mild	2500 m ²