



VehiclePro Super Pearl Wax RM 824 Classic

Drying, protection and care all in one. The liquid pearl wax enables the water film to break up quickly, which leads to excellent drying, particularly with hard water.

pH value 4
in concentrate



Properties

- Effective drying aid for use in vehicle wash systems and high-pressure cleaners
- Fast breaking up of the water film over a large area
- Excellent drying result
- Effective with medium to hard water
- Increases the level of shine of the paintwork
- VDA-compliant
- Tensides biodegradable in accordance with EEC 648/2004
- NTA-free
- Free from mineral oils and mineral hydrocarbons

Usage options

- Car washes
- High-pressure cleaners

Application areas

Car dealership and garage	Cars
Haulage contractors, bus operators	Commercial vehicle cleaning
Vehicle wash system	Cars

Technical data

Container sizes	Packaging unit	Part number
10 l	1 Piece(s)	6.296-160.0
20 l	1 Piece(s)	6.295-438.0
200 l	1 Piece(s)	6.295-074.0

Application

Car washes

- Insert the product into the system.
- Adjust dosage on the device.
- Start care programme.

High-pressure cleaners

- Apply primary mixture with demineralised water (osmosis water).
- Set the dosage and temperature on the device
- 1-80°C processing temperature.
- Apply the product evenly to the cleaned and rinsed surfaces.
- Leave object to dry.

Instructions for use

- Store away from frost.
- Avoid over-dosage.
- Use only on washed, well rinsed surfaces.

Warnings and safety recommendations according to EC Directives

- Danger
- H318 Causes serious eye damage
- H412 Harmful to aquatic life with long lasting effects
- P273 Avoid release to the environment.
- P280i Wear eye/face protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P501a Dispose of contents/container in accordance with local/regional/national/international regulations.

Further information

- VDA certification
- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Primary mixture	Dosage	Yield
1000 ml	Vehicle wash system	undiluted	0.1 – 0.2 %	50 Car
1000 ml	High-pressure cleaners	1+9	1 – 2 %	83 Car