

PressurePro Solar Cleaner RM 99



Highly efficient, gentle and biodegradable cleaning agent for residue-free, streak-free cleaning of solar and photovoltaic systems. Prevents the formation of limescale. For all water hardness levels. For removing stubborn bird droppings, pollen, rust and dust. Also suitable for aluminium frames.



Properties

- Winner of the Pulire Innovation Award 2013
- For removing stubborn and greasy dirt
- Avoidance of limescale at all water hardness levels, even without switching using water softening systems
- Residue-free, streak-free, drying cleaning
- Reduced subsequent soiling
- No damage to the solar and photovoltaic modules, as well as the glass and plastic coatings, anodised and normal aluminium frame
- Gentle surface treatment thanks to improved sliding characteristics of the cleaning brushes
- DLG-tested (Deutsche Landwirtschafts-Gesellschaft e.V.)
- Very efficient
- non-hazardous classification
- Harmless draining into the sewerage system, which is connected to the municipal sewerage treatment plant
- Easily biodegradable (in accordance with OECD Directive)

Application areas:


- Agriculture:** Solar and photovoltaic systems
- Building cleaning:** Solar and photovoltaic systems
- Industry:** Solar and photovoltaic systems

Usage options

- High-pressure cleaner

Container sizes	Part number
10 l	6.295-798.0
20 l	6.295-799.0

pH



Application:

High-pressure cleaner

- Mix primary mixture.
- Pour cleaning solution into the cleaning device.
- Set the dosage and temperature on the device (application temperature max. 40°C).
- Apply cleaning agent solution with appropriate accessories to the surface to be cleaned and clean the surface from top to bottom.
- Rinsing with fresh water is not required.

Instructions for use:

- Do not apply to heated surfaces.
- Do not mix with other cleaning agents/chemicals.
- Store away from frost.
- Recommended storage and transport temperature: 0°C – 30°C.

Warnings and safety recommendations according to EC Directives:

- Warning
- H319 Causes serious eye irritation
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash thoroughly after handling.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.

Further information:

- Material Safety Data Sheet (MSDS)

Dosage and yield:

Contents:	Cleaning method:	Primary mixture:	Dosage:	Soiling:	Yield:
1000 ml	High-pressure cleaner	1+3	0.5-1 %	medium-strong	50-180 m ²

Please contact us for more information:

Kärcher Cleaning Systems Sdn. Bhd.

No 5, Jln Perintis U1/52, Seksyen U1,
Kawasan Perindustrian Temasya,
Glenmarie, 40150 Shah Alam