




SP 3 Dirt

Reliably pump out and circulate clear and dirty water with a pump capacity of up to 7,000 l/h: with the compact and robust SP 3 Dirt dirty water pump with float switch.




1 Ceramic face seal.

- For an extra long lifetime.




2 Float switch

- Switches the pump on and off again according to the water level, preventing dry running.



3 Quick Connect

- For quick and uncomplicated connection of 1 1/4" hoses to the pump.



4 Designed for dirty water

- Reliable pumping of water with dirt particles up to 20 mm in size.



SP 3 Dirt

Technical data

Order no.	1.645-512.0	
EAN code	4054278169903	
Max. motor rating	W	350
Max. flow rate	l/h	< 7000
Delivery height / Max. pressure	m / bar	6 / 0.6
Max. immersion depth	m	7
Max. grain size	mm	20
Residual water height	mm	25
Delivery temperature, max.	°C	35
Weight without accessories	kg	4.2
Dimensions (L × W × H)	mm	229 × 238 × 303
Power cable	m	H05RN-F / 10

Equipment

Comfortable carrying handle	■
Hose connection piece	1 1/4"
Easy hose connection thanks to Quick Connect	■
Switching between manual/automatic operation	Possibility of fixing the float switch
Ceramic face seal.	■

■ Included in the scope of supply.

SP 3 DIRT 1.645-512.0



		Order no.					Price	Description	
Suction hoses									
Suction hose available in bulk	1	6.997-347.0						Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.	<input type="checkbox"/>
	2	6.997-346.0							<input type="checkbox"/>
Miscellaneous									
Flat hose set	3	2.997-100.0						Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	<input type="checkbox"/>
Adapters / connectors									
Pump adapter including check valve, small	4	6.997-359.0						Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).	<input type="checkbox"/>
Filter									
Prefilter for submersible pumps, small	5	2.997-201.0						Protects the submersible pump and thereby improves its operational reliability: the robust and easy-to-fit prefilter for the SP 1 to SP 5 Flat/Dirt submersible pumps.	<input type="checkbox"/>

Available accessories.

SP 3 DIRT 1.645-512.0



		Order no.						Price	Description	
Hoses										
PrimoFlex® Plus hose 3/4" - 25 m	1	2.645-148.0								<input type="checkbox"/>
PrimoFlex® hose 3/4" - 25 m	2	2.645-142.0							PrimoFlex® quality garden hose (3/4"). 25 m long. With pressure-resistant woven reinforcement. Contains no substances that are harmful to health. Bursting pressure: 24 bar. High temperature resistance from -20 to 65 °C.	<input type="checkbox"/>
PrimoFlex® hose 1" 1 m	3	2.645-247.0								<input type="checkbox"/>

Available accessories.