





## SP 5 Dirt

Quickly pump out and circulate up to 9,500 litres of dirty water per hour: with the robust SP 5 Dirt dirty water pump with height-adjustable float switch for greater flexibility.




### 1 Ceramic face seal.

- For an extra long lifetime.



### 2 Height-adjustable float switch

- Increases the flexibility when setting the switch-on and switch-off point of the pumps and prevents dry running.



### 3 Quick Connect

- Connection thread for quick and uncomplicated connection of 1 1/4" hoses to the pump.



### 4 Designed for dirty water

- Reliable pumping of water with dirt particles up to 20 mm in size.



## SP 5 Dirt

### Technical data

|                                 |               |                 |
|---------------------------------|---------------|-----------------|
| Order no.                       | 1.645-513.0   |                 |
| EAN code                        | 4054278170114 |                 |
| Max. motor rating               | W             | 500             |
| Max. flow rate                  | l/h           | < 9500          |
| Delivery height / Max. pressure | m / bar       | 7 / 0.7         |
| Max. immersion depth            | m             | 7               |
| Max. grain size                 | mm            | 20              |
| Residual water height           | mm            | 25              |
| Delivery temperature, max.      | °C            | 35              |
| Weight without accessories      | kg            | 4.7             |
| Dimensions (L × W × H)          | mm            | 229 × 238 × 303 |
| Power cable                     | m             | H05RN-F / 10    |

### Equipment

|  |  |
|--|--|
| Comfortable carrying handle                  | ■                                      |
| Hose connection piece                        | 1 1/4"                                 |
| Easy hose connection thanks to Quick Connect | ■                                      |
| Switching between manual/automatic operation | Possibility of fixing the float switch |
| Flexible, height-adjustable float switch     | ■                                      |
| Ceramic face seal.                           | ■                                      |
| ■ Included in the scope of supply.           |  |

# SP 5 DIRT 1.645-513.0



|   |   | Order no.   |  |  |  |  | Price | Description   |                          |
|---|---|-------------|--|--|--|--|-------|---|--------------------------|
| <b>Suction hoses</b>                      |   |             |  |  |  |  |       |   |                          |
| Suction hose available in bulk            | 1 | 6.997-347.0 |  |  |  |  |       | Vacuum-resistant spiral hose can be cut to length for connection to submersible, garden, submersible pressure pumps and high-pressure pumps.  | <input type="checkbox"/> |
|   | 2 | 6.997-346.0 |  |  |  |  |       |   | <input type="checkbox"/> |
| <b>Miscellaneous</b>                      |   |             |  |  |  |  |       |   |                          |
| Flat hose set                             | 3 | 2.997-100.0 |  |  |  |  |       | Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding. | <input type="checkbox"/> |
| <b>Adapters / connectors</b>              |   |             |  |  |  |  |       |   |                          |
| Pump adapter including check valve, small | 4 | 6.997-359.0 |  |  |  |  |       | Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).   | <input type="checkbox"/> |
| <b>Filter</b>                             |   |             |  |  |  |  |       |   |                          |
| Prefilter for submersible pumps, small    | 5 | 2.997-201.0 |  |  |  |  |       | Protects the submersible pump and thereby improves its operational reliability: the robust and easy-to-fit prefilter for the SP 1 to SP 5 Flat/Dirt submersible pumps.                        | <input type="checkbox"/> |

Available accessories.

# SP 5 DIRT 1.645-513.0



|                                  |   | Order no.   |  |  |  |  | Price | Description   |  |                          |
|----------------------------------|---|-------------|--|--|--|--|-------|---|--|--------------------------|
| <b>Hoses</b>                     |   |             |  |  |  |  |       |   |  |                          |
| PrimoFlex® Plus hose 3/4" - 25 m | 1 | 2.645-148.0 |  |  |  |  |       |   |  | <input type="checkbox"/> |
| PrimoFlex® hose 3/4" - 25 m      | 2 | 2.645-142.0 |  |  |  |  |       | PrimoFlex® quality garden hose (3/4"). 25 m long. With pressure-resistant woven reinforcement. Contains no substances that are harmful to health. Bursting pressure: 24 bar. High temperature resistance from -20 to 65 °C. |  | <input type="checkbox"/> |
| PrimoFlex® hose 1" 1 m           | 3 | 2.645-247.0 |  |  |  |  |       |   |  | <input type="checkbox"/> |

Available accessories.