



HD 6/15 C EASY!

Cold-water pressure washer with EASY!Force accessories for daily commercial use. With its compact dimensions, robust construction and greatest possible manoeuvrability, this unit is a credit to the compact class.







- 1 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.
- At last work without getting tired: the EASY!Force high-pressure gun
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.
- 2 Variable pressure/water flow control
- Adjustable at the unit.
- For gentle cleaning of sensitive surfaces.

- 3 Telescopic push handle
- Large aluminium profiles provide stability and good manoeuvrability.
- lacksquare Holds accessories in the extended position.
- 4 Outstanding mobility
- For rapid cleaning at different locations.
- Space-saving storage in service vehicles.

TECHNICAL DATA AND EQUIPMENT





HD 6/15 C EASY!

- 3-piston axial pump with ceramic pistons
- Excellent mobility due to compact dimensions and low weight
- Variable pressure

| Technical data | | |
|------------------------|-------------|-------------------|
| Order No. | | 1.150-911.0 |
| EAN code | | 4054278164540 |
| Type of current | Ph / V / Hz | 1 / 240 / 50 |
| Flow rate | l/h | 230 - 560 |
| Operating pressure | bar / MPa | 30 - 150 / 3 - 15 |
| Max. pressure | bar / MPa | 190 / 19 |
| Max. feed temperature | °C | up to 60 |
| Power rating | kW | 3,1 |
| Weight | kg | 23 |
| Dimensions (L x W x H) | mm | 360 × 375 × 925 |

| Equipment | | |
|----------------------------|----|----------------------|
| Trigger gun | | EASY!Force |
| High-pressure hose | m | 10 / Premium quality |
| Spray lance | mm | 840 |
| Triple nozzle (0°/25°/40°) | | Manual |
| ANTI!Twist | | - |
| Pressure cut-off | | I |
| Servo Control | | - |
| | | |

■ Included in delivery.























| | | | 1 | | | | |
|--|-----|-------------|-------|--------------|--------|-------|---|
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | Max. working | | | |
| | | Order No. | ID | pressure | Length | Price | e Description |
| Standard with unions on both sides | | | | 1 | | | - |
| High-pressure hose, 10 m DN 8, | 1 | 6.110-031.0 | ID 8 | 315 bar | 10 m | | 10 m high-pressure hose (M 22 x 1.5) with kink protection. |
| AVS trigger gun connector | 1 | 0.110 031.0 | 10 0 | 313 bai | 10111 | | With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar. |
| High-pressure hose, 15 m DN 8, | 2 | 6.110-030.0 | ID 8 | 315 bar | 15 m | | 15 m high-pressure hose (M 22 x 1.5) with kink protection. |
| AVS trigger gun connector | | | | | | | With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. |
| High-pressure hose, 20 m DN 8, | 3 | 6.110-032.0 | ID 8 | 315 bar | 20 m | | 20 m high-pressure hose (M 22 x 1.5) with kink protection. |
| AVS trigger gun connector | | | | | | | With patented rotating AVS trigger gun connector and manual al coupling. Further data: DN 8/155°C/315 bar. Δ |
| High-pressure hose, 30 m DN 8, | 4 | 6.110-014.0 | ID 8 | 315 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 |
| including rotary coupling | | | | | | | |
| High-pressure hose, 15 m DN 10, 220 bar, extension | 5 | 6.110-042.0 | ID 10 | 220 bar | 15 m | | 15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar. |
| High-pressure hose, 20 m DN 10, | 6 | 6.110-043.0 | ID 10 | 220 bar | 20 m | | with union on both sides M 22 v 1.5 with anti-kink protec- |
| 220 bar, extension | | | | | | | tion. NW 10/155°C/220 bar |
| High-pressure hose, 25 m DN 10, extension, not rotatable | 7 | 6.110-044.0 | ID 10 | 220 bar | 25 m | | |
| Hose assembly premium DN10 22MPa 40m | 8 | 6.110-045.0 | ID 10 | 220 bar | 40 m | | |
| Hose assembly premium DN12 21MPa 15m | 9 | 6.110-059.0 | ID 12 | 210 bar | 15 m | | High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink |
| Hose assembly premium DN12 21MPa 40m | 10 | 6.110-060.0 | ID 12 | 210 bar | 40 m | | protection. |
| Hose assembly TR DN10 22MPa 10m | 11 | 6.110-041.0 | ID 10 | 220 bar | 10 m | | |
| High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- | 12 | 6.110-056.0 | ID 6 | 300 bar | 10 m | | With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with an- |
| tion | | | | | | | ti-kink protection. NW 6/155°C/300 bar |
| High-pressure hose, 10 m DN 6, | | 6.110-034.0 | ID 6 | 250 bar | 10 m | | 10 m high-pressure hose (M 22 x 1.5) with kink protection. |
| AVS trigger gun connector | 14 | 6.110-035.0 | ID 6 | 250 bar | 10 m | | With patented rotating AVS trigger gun connector and manual all coupling. Further data: DN 6/155°C/250 bar. |
| Longlife 400 with unions on both si | des | I. | | | | , | |
| High-pressure hose Longlife 400, | 15 | 6.110-023.0 | ID 8 | 400 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 |
| 30 m ID 8, including rotary cou- | | | | | | | |
| pling | | | | | | | |
| High-pressure hose Longlife 400 | 16 | 6.110-027.0 | ID 8 | 400 bar | 20 m | | High-pressure hose with ANTI!Twist, EASY!Lock hand screw |
| 2x EASY!Lock, ID 8, 400 bar, 20 m, ANTI!Twist | | | | | | | connections and double steel reinforcement. 20 m long, ID 8, EASY!Lock hand screw connection at both ends. |
| High-pressure hose Longlife 400, | 17 | 6.110-029.0 | ID 8 | 400 bar | 15 m | | With rotary coupling, 2 x M 22 x 1.5 |
| 15 m, ID 8, including rotary coupling | 1, | 0.110 023.0 | | 100 54. | 15 | | A |
| High-pressure hose 1.5 m, ID 8, including connectors | 18 | 6.110-024.0 | ID 8 | 400 bar | 1,5 m | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). |
| | 19 | 6.110-069.0 | ID 8 | 400 bar | 1,5 m | | reels with appropriate connector (w 22 x 1.3). |
| High-pressure hose packaged | | 6.110-038.0 | ID 8 | 400 bar | 10 m | | |
| Food industry version with unions | | | | <u> </u> | | | |
| High-pressure hose, 10 m ID 8, suitable for food industry, extension piece | 21 | 6.110-051.0 | ID 8 | 250 bar | 10 m | | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve. |
| | | | 1 | | | | , and rate media jum 22 % 110 When drift ham blocke. |













| | | Order No. | ID | Max. working pressure | Length | Price | Description | |
|---|-------|-----------------|------|-----------------------|--------|-------|--|----|
| High-pressure hose, 20 m ID 8, suitable for food industry, extension piece | 22 | 6.110-052.0 | ID 8 | 250 bar | 20 m | | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar. | • |
| High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey | 23 | 6.110-063.0 | ID 6 | 250 bar | 15 m | | 15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar. | ַ |
| Longlife food industry version with | unior | s on both sides | | | | | | |
| High pressure hose food ID 8 / 10 m | 24 | 6.110-053.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5 | • |
| HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection | 25 | 6.110-054.0 | ID 8 | 400 bar | 20 m | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted) | _] |
| Special hoses | | | | | | | | |
| High-pressure hose 1.5 m, ID 8, including connectors, outlet bend | 26 | 6.110-068.0 | ID 8 | 400 bar | 1,5 m | | [| ٥ |

[■] Included in delivery. □ Available accessories. ▲ Extension hose.















| | | | | | | | T |
|---|---|-------------|-----------|--|-------|---|---|
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | Order No. | Flow rate | | Price | Description | |
| Trigger guns | | | | | | | |
| EASY!Force Advanced | 1 | 4.118-005.0 | | | | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. | - |
| Conversion kit 1 from high pressure hose | 2 | 4.111-050.0 | | | | | |
| Conversion kit 2 from device | 3 | 4.111-051.0 | | | | | |
| Conversion kit 3 only EASY!Force | 4 | 4.111-052.0 | | | | | |
| Quick connect | | | | | | | |
| Quick-fitting pipe union coupler trapezo | 5 | 2.115-000.0 | | | | | |
| Quick-fitting pipe union plug nip- ple tra | 6 | 2.115-001.0 | | | | | |

[■] Included in delivery.

Available accessories.

Extension hose.































| | | Order No. | Max. working pressure | Length | | Price | Description |
|---|------|-------------|-----------------------|----------|-----|-------|---|
| Rotating spray lances | | | | | | | |
| Lance 850 mm, rotatable, ergo- nomic | 1 | 4.112-006.0 | 300 bar | 840 mm | | | 850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure. |
| Nozzle light | 2 | 2.680-002.0 | | 125 mm | | | |
| Lance 250 mm, non-rotatable | 3 | 4.112-027.0 | 300 bar | 250 mm | | | |
| 550 mm lance, non-rotatable | 4 | 4.112-024.0 | 300 bar | 400 mm | | | |
| Rotatable lance, 600 mm, ergo- nomic | 5 | 4.112-007.0 | 300 bar | 600 mm | | | 600 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure. |
| 1050 mm lance, rotatable, ergonomic | 6 | 4.112-000.0 | 300 bar | 1050 mm | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. |
| Lance 1550 mm, rotatable, ergonomic | 7 | 4.112-018.0 | 300 bar | 1550 mm | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. |
| Lance 2050 mm, rotatable, ergonomic | 8 | 4.112-021.0 | 300 bar | 2050 mm | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. |
| Jet pipe extension TR 1000 mm | 9 | 4.112-048.0 | 300 bar | 1000 mm | | | |
| Double lance | | | | | | | |
| Double lance 960 mm | 10 | 2.112-016.0 | 310 bar | 960 mm | | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). |
| Angular spray lance | | | | | | | |
| WC and gutter lance | 11 | 4.112-029.0 | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. |
| Flexible spray lance | | | , | | | | |
| Flexible lance 1050 mm | 12 | 4.112-035.0 | 210 bar | 1050 mm | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. |
| Articulated joint TR 20 | 13 | 4.112-057.0 | 300 bar | | | | |
| Telescopic spray lance | 1 44 | 14442 027 0 | 225 hav | F 400 mm | 1 1 | | |
| Telescopic jet pipe | 14 | 4.112-037.0 | 225 bar | 5400 mm | | | Convenient street for relief when working with the telegrap |
| Restraint belt for telescopic jet pipe | 15 | 6.373-987.0 | | | | | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. |
| Gutter cleaner | | | | | | | |
| Gutter cleaning lance | 16 | 2.112-015.0 | | 960 mm | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. |
| Undercarriage spray lance | | | | | | | |
| Underbody lance | 17 | 4.112-032.0 | | 700 mm | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. |
| Zusatzhandgriff | 1 40 | 4.321-380.0 | | | | | |









| | | Order No. | Max. working pressure | Nozzle size | | Price | Description |
|--|---|-------------|-----------------------|-------------|--|-------|---|
| Triple nozzles | | ' | ' | ' | | | |
| Triple nozzle 034 | 1 | 4.117-029.0 | 300 bar | 34 | | | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5. |
| Dirt Blaster, small | | | | | | | |
| | 2 | 4.114-019.0 | 180 bar | 35 | | | |
| Dirt blaster, large | | | | | | | |
| Dirt blaster - without changeover function | 3 | 4.114-040.0 | 300 bar | 35 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. |

[■] Included in delivery.

Available accessories.

Extension hose.





| | | Order No. | Nozzle size | | Price | Description |
|-------------------------------------|---|-------------|-------------|--|-------|--|
| HP nozzle spray angle 0° | | | | | | |
| High-pressure nozzle spray angle °0 | 1 | 2.113-001.0 | 40 | | | High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$ |
| Power nozzle spray angle 15° | | | | | | |
| Power nozzle 15034 | 2 | 2.113-042.0 | 34 | | | |
| Power nozzle spray angle 25° | | | | | | |
| Power nozzle spray angle 25° | 3 | 2.113-000.0 | 34 | | | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. |
| Power nozzle spray angle 40° | | | | | | |
| Power nozzle spray angle 40° | 4 | 2.113-003.0 | 40 | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. $\hfill\Box$ |

 $[\]blacksquare$ Included in delivery. $\hfill\Box$ Available accessories. $\hfill \triangle$ Extension hose.































| | | Order No. | | | Price | Description | |
|--|--------|-------------|---|--|-------|--|------|
| Nozzle union | | | | | | | |
| Protection part TR only for re- placement | 1 | 4.112-011.0 | | | | | |
| HP detergent injector | | | _ | | | | |
| | 2 | 6.645-758.0 | | | | | |
| Detergent injector for high and low pressure (without nozzles) | 3 | 4.637-032.0 | | | | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. | |
| Detergent injector for high pres- sure | 4 | 4.637-033.0 | | | | Cleaning agent dosage at high pressure 3 - 5 % | |
| Machine-specific nozzle kit with or | der no | . 3.637-170 | | | | | |
| Nozzle insert trapezoidal thread HD-GER. | 5 | 4.769-005.0 | | | | | |
| Nozzle insert with order no. 3.637- | 001 | | | | | | |
| Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h. | 6 | 4.769-003.0 | | | | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h. | |
| Low pressure for units rated up to 1100 l/h | 7 | 4.769-001.0 | | | | For low pressure with machines up to 1.100 l/h | |
| Rotary coupling | | | | | | | _ |
| Rotary coupling | 8 | 4.111-021.0 | | | | Kārcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22×1.5 m. With grip protection. | |
| Coupling | | | | | | | |
| Coupler -2xM22x1,5 | 9 | 4.111-037.0 | | | | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m. | |
| Connector | | | | | | | |
| Nozzle connector/screw connector | 10 | 4.111-022.0 | | | | Nozzle connector/screw connector for connecting high-presure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1x M 22 \times 1.5$ and $1x M 18 \times 1.5$. | l |
| Y distributor | 11 | 4.111-024.0 | | | | | |
| | 12 | 4.111-038.0 | | | | | |
| Adapter EASY!Lock | | | | | | | L, |
| Adapter 1 M22AG-TR22AG | 13 | 4.111-029.0 | | | | | |
| Adapter 2 M22IG-TR22AG | 14 | 4.111-030.0 | | | | | |
| Adapter 3 M22IG-TR22AG | 15 | 4.111-031.0 | | | | | |
| Adapter M22 - Swivel | 16 | 4.111-032.0 | | | | M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection. | - 11 |
| Adapter 5 TR22IG-M22AG | 17 | 4.111-033.0 | | | | | |
| Adapter 6 TR22IG-M22AG | 18 | 4.111-034.0 | | | | | |
| Adapter 7 M18IG-TR20AG | 19 | 4.111-035.0 | | | | 1 | |
| Adapter 8 TR20IG-M18AG | 20 | 4.111-036.0 | | | | | |
| ADAPTER for replacement TR22IG- M22AG Er | 21 | 4.111-046.0 | | | | | |

[■] Included in delivery.

Available accessories.

Extension hose.




















| | | | | | | | | Т |
|---|----|-------------|-----------------------|-------------|---------------|-------|--|------|
| | | | | | | | | |
| | | | | | | | | |
| | | Order No. | Max. working pressure | Nozzle size | Diame- ter | Price | Description | |
| Pipe cleaning hose, ID 6 | | | <u> </u> | | | | | _ |
| Hose assembly TR pipe cleaning DN6 max.2 | 1 | 6.110-046.0 | 250 bar | | | | | |
| Pipe cleaning hose, ID 6, 20 m, max. 250 bar | 2 | 6.110-008.0 | 250 bar | | | | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | or E |
| Hose assembly TR pipe cleaning DN6 max.2 | 3 | 6.110-047.0 | 250 bar | | | | | |
| Hose assembly TR pipe cleaning DN6 14MPa | 4 | 6.110-048.0 | 140 bar | | | | | |
| Pipe cleaning hose | 5 | 6.110-049.0 | 140 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| Pipe cleaning hose, DN 6, 30 m | 6 | 6.110-050.0 | 140 bar | | | | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| Pipe cleaning nozzle | | | | | | | | |
| Dirt blaster pipe cleaning D21/040 | 7 | 4.765-001.0 | | 40 | 21 mm | | | |
| Dirt blaster pipe cleaning D30/040 | 8 | 4.765-004.0 | | 40 | 30 mm | | | |
| Pipe cleaning nozzle | 9 | 5.763-015.0 | | 55 | 16 mm | | 16 mm pipe cleaning nozzle with internal thread. Various jo | |
| | 10 | 5.763-020.0 | | 65 | 16 mm | | directions for environmentally-friendly cleaning of blocked drains and pipes. | _ |
| | 11 | 5.763-017.0 | | 50 | 30 mm | | 30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes. | |
| Rotating pipe cleaning nozzle | 12 | 6.415-428.0 | | 50 | 16 mm | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. | . [|
| Barrel and tank cleaning | | | | | | | | |
| Barrel cleaner BC 14/12 | 13 | 2.112-020.0 | | | | | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachmer 4.115-000.0 4.115-006.0. | _ |

lacktriangle Included in delivery. \Box Available accessories. lacktriangle Extension hose.

























| | 1 | 1 | 1 | | 1 1 | | | _ |
|-------------------------------------|----|-------------|---------------|-------------|--------|-------|--|---|
| | | | | | | | | ı |
| | | | | | | | | ı |
| | | | | | | | | ı |
| | | | | | Diame- | | | ı |
| | | Order No. | Flow rate | Nozzle size | ter | Price | Description | ı |
| FR Classic surface cleaner | | I. | | ' | | | | |
| FR Classic surface cleaner | 1 | 2.111-016.0 | | | 300 mm | | | |
| Hard Surface Cleaner FRV 30 | | | | | | | | |
| Add-on kit rubber lip | 2 | 2.642-910.0 | | | | | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | |
| Extension hose 5 m | 3 | 4.440-939.0 | | | | | 5m extension hose for FRV 30. Connection sleeve included. | |
| Add-on kit hose attachment | 4 | 2.642-528.0 | | | | | | |
| Add-on kit dirt trap | 5 | 2.642-532.0 | | | | | | |
| FRV 30 | 6 | 2.111-010.0 | | | | | | |
| Hard surface cleaner FR 30 | | | | | | | | |
| FR 30 | 7 | 2.111-011.0 | | | 300 mm | | | |
| Hard surface cleaner FR 30 ME | | | | | | | | |
| FR 30 ME surface cleaner | 8 | 2.111-013.0 | | | 300 mm | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | |
| Machine-specific nozzle kit for FR | | | | | | | | |
| Nozzle kit for surface cleaners | 9 | 2.640-401.0 | 500 - 650 l/h | | | | Nozzle kit includes power nozzles and unions. For Kärcher | |
| (type-specific) 500 - 650 l/h | | | | | | | surface cleaners (500 to 650 l/h). | Ľ |
| Machine-specific nozzle kits for FR | 1 | ı | 1 | | | 1 | | |
| Nozzle kit 035 for FRV 30 | | 2.642-430.0 | | 35 | | | | |
| Machine-specific nozzle kits for FR | 1 | 1 | 1 | | 1 | 1 | 1 | |
| | 11 | 2.885-312.0 | | 40 | | | | |
| FRV 30 Me surface cleaner | | 1 | 1 | 1 | | | 1 | |
| Suction hose FRV 30 me | 12 | 4.441-040.0 | | | | | | |
| FRV 30 ME | | 2.111-012.0 | A Fytonsion b | | | | | |

[■] Included in delivery.

Available accessories.

Extension hose.



















| | | Order No. | Flow rate | | | Price | Description |
|---|---|-------------|---------------|---|---|-------|---|
| Cup foam lance | | | <u> </u> | ' | ' | | |
| Foam lance TR | 1 | 4.112-053.0 | 350 - 600 l/h | | | | |
| Bottle cleaning agents 1L | 2 | 5.071-414.0 | | | | | |
| Packing complete for 6.394-969.0 | 3 | 2.112-018.0 | | | | | |
| Tank grey only for replacement 1L | 4 | 6.414-050.0 | | | | | |
| Inno Foam Kit | | | | | | | |
| Inno foam kit with detergent injector | 5 | 2.112-000.0 | | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. |
| Easy Foam Set | | | | | | | |
| Easy Foam Set with RM injector | 6 | 2.112-010.0 | | | | | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. |
| Nozzle kits for Inno/Easy Foam Set | | | | | | | |
| Nozzle kit 060 for Inno/Easy Set 600 - 700 I/h | 7 | 2.111-018.0 | 600 - 700 l/h | | | | Optimal adaptation to different machine outputs for economic use. |
| Foam nozzle mounting kit | | | | | | | |
| Foam nozzle kit | 8 | 2.112-013.0 | | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. |

 $[\]blacksquare$ Included in delivery. $\hfill\square$ Available accessories. $\hfill \blacktriangle$ Extension hose.



















| | | Order No. | Length | | Price | Description |
|--|----|-------------|--------|--|-------|--|
| Automatic, self-winding hose reels | | | | | | |
| Wall-mounted hose reel | 1 | 2.639-257.0 | 15 m | | | |
| Add-on kit hose reel plastics | 2 | 6.392-074.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. |
| Add-on kit hose reel | 3 | 6.392-083.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. |
| Hose reel, automatic, 20 m, painted | 4 | 6.392-106.0 | 20 m | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. |
| Add-on kit hose reel lacquered basaltgra | 5 | 6.392-105.0 | 20 m | | | |
| Hose reel, automatic, 20 m, stain- less steel | 6 | 6.392-076.0 | 20 m | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. |
| ABS hose reel stainless steel | 7 | 6.392-122.0 | 20 m | | | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple. |
| Add-on kit hose reel TR 40m | 8 | 6.392-442.0 | 40 m | | | |
| Swivel holder | 9 | 2.639-931.0 | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. |
| ABS wall fastening stainless steel | 10 | 2.641-867.0 | | | | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. |

[■] Included in delivery.

Available accessories.

Extension hose.









| | | Order No. | Nozzle size | | Price | Description |
|---|--------|-------------|-------------|--|-------|---|
| Wet blasting attachment (without | nozzle |) | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.115-000.0 | | | | Paint, rust and scale removal made easy: Kārcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.115-006.0 | | | | Paint, rust and scale removal made easy: Kārcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. |
| Nozzle pack for wet blasting attach | nment | | | | | |
| Nozzle pack TR wet jet set 0040 | 3 | 2.112-019.0 | 40 | | | |
| Boron carbide nozzle | | | | | | |
| Boron carbide nozzle, for ma- chines as of 1000 l/h | 4 | 6.415-084.0 | 6 mm | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. |

[■] Included in delivery.

Available accessories.

Extension hose.

















| | | Order No. | Pr | De- scrip- ice tion | |
|-------------------------------------|-----|-------------|----|--|--|
| Geka coupling | | order ito. | | 1011 | |
| With hose nozzle, R 1/2" | 1 | 6.388-461.0 | | with hose liner | |
| With hose nozzle, R 3/4" | 2 | 6.388-455.0 | | with hose liner | |
| With hose nozzle, R 1" | 3 | 6.388-465.0 | | | |
| With female thread, R 3/4" | 4 | 6.388-473.0 | | with female thread | |
| Suction filter | | | | | |
| Water filter | 5 | 6.414-956.0 | | | |
| Suction filter with check valve | 6 | 4.730-012.0 | | Brass suction filter suitable for ponds, storage tanks, etc. Witl check valve. | |
| Fine-mesh water filter | | | | | |
| Fine-mesh water filter with adapter | 7 | 4.730-102.0 | | Fine- mesh water filter, 125 µm, max. temper- ature 50°C. Protects the | |
| Water supply hose | ۱ ، | 4 440 000 0 | | L N 11 4 2 | |
| Water supply hose | 8 | | | NW 13 R1" / R 3/4", up to 30 °C | |
| | 9 | 4.440-207.0 | | NW 19 R1" / R 3/4", up to 85 °C for pick-up | |







| Backflow check valve | | Order No. | | Price | De- scrip- tion | |
|---|----|-------------|--|-------|---|--|
| Backflow preventer | 10 | 2.641-374.0 | | | To prevent detergent getting into the drinking water cycle in case of inlet at | |
| Other HP Accessories Starting current limiter | 11 | 2.637-495.0 | | | Reduces starting current in sin- gle- phase supply and protects line fuse. | |

 $[\]blacksquare$ Included in delivery. $\hfill\square$ Available accessories. $\hfill \triangle$ Extension hose.











| | | | | 1 | | | | |
|--------------------------------|---|-------------|---------------|---|--|-------|--|----------|
| | | | | | | | | |
| | | Order No. | Flow rate | | | Price | Description | |
| Push-on washing brush | | | | | | l | | \vdash |
| Push-on washing brush | 1 | 4.762-497.0 | | | | | With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles. | |
| Push-on wash brush, M 18 x 1.5 | 2 | 4.113-001.0 | | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6. | |
| Rotating washing brush | | | | | | | | |
| Washing brush rotary | 3 | 4.113-004.0 | 500 - 800 l/h | | | | | |
| | 4 | 4.113-003.0 | 500 - 800 l/h | | | | | |

[■] Included in delivery.

Available accessories.

Extension hose.