



# HDS 6/14 C

Single-phase hot water high-pressure cleaner with Eco mode, 1-button operation, integrated tanks, Easy Press gun with soft grip, continuous servo-control pressure/water flow regulation, etc.







#### 1 Economical

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

#### 2 Ease of use

- Intuitive operation with one-switch control.
- Intuitive operation with large single-button selector switch.



#### 3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.

#### 4 Mobility

- "Jogger" design with large wheels and castors.
- Large integrated handles in the chassis.

# **TECHNICAL DATA AND EQUIPMENT**

#### KARCHER



#### HDS 6/14 C

Economical	eco!efficiency	/ mode
Constant	and hutton of	

Convenient one-button operationExtensive standard equipment

Technical data		
Order No.		1.169-218.0
EAN code		4039784729476
Type of current	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	240-560
Pressure	bar / MPa	30-140 / 3-14
Max. temperature	°C	80 / 155
Power rating	kW	3.6
Fuel oil consumption, full load	kg/h	3.5
Fuel tank	1	15
Weight	kg	93
Dimensions (L x W x H)	mm	1060 × 650 × 920
Equipment		
Trigger gun		Extended easy-press trigger gun
Trigger gun with Softgrip insert		1
High-pressure hose	m	10 / ID 6, 250 bar
Spray lance	mm	550
Power nozzle		1
SDS system		1
ANTI!Twist		
Pressure cut-off		1
Integrated fuel and cleaning agent tank	I	1
Servo Control		-
Included in delivery.		

HDS 6/14 C, 1.169-218.0, 2019-06-19



		Order No.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides								_
High-pressure hose packaged	1	6.391-342.0	ID 8	315 bar	10 m			
High-pressure hose, 30 m DN 8, including rotary coupling	2	6.390-293.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
Longlife 400 with unions on both si	des							
High pressure hose ID 6, 10 m, drehbar,I	3	6.391-883.0	ID 6	400 bar	10 m		With rotary coupling, 2 x M 22 x 1,5	
High-pressure hose packaged	4	6.391-354.0	ID 8	400 bar	10 m			
High-pressure hose Longlife 400, 30 m ID 8, including rotary coup- ling	5	6.390-294.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose 1.5 m, ID 8, including connectors	6	6.390-178.0	ID 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
Longlife food industry version with	unior	s on both sides	1					
High pressure hose food ID 8 / 10 m	7	6.391-864.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi-	
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	8	6.391-887.0	ID 8	400 bar	20 m		al. With rotary coupling, 2 x M 22 x 1,5	
Standard			1		II			
High-pressure hose, 10 m DN 6, AVS trigger gun connector	9	6.391-238.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling, Further data: DN 6/155°C/250 bar.	
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- tion	10	6.391-875.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot- mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	
High-pressure hose, 10 m DN 8, AVS trigger gun connector	11	6.390-025.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling, Further data: DN 8/155°C/315 bar.	)- C
High-pressure hose, 15 m DN 8, AVS trigger gun connector	12	6.390-185.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 20 m DN 8, AVS trigger gun connector	13	6.390-171.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	ı- C
Longlife 400			1					
High pressure hose DN 6, 10 m, Longlife	14	6.391-882.0	ID 6	400 bar	10 m		With patented AVS connection in the trigger gun (pivot- mounted).	
High-pressure hose packaged	15	6.391-351.0	ID 8	400 bar	10 m			
High-pressure hose Longlife 400, 20 m DN 8, AVS trigger gun con- nector	16	6.390-208.0	ID 8	400 bar	20 m		20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.	
Food industry version								
High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	17	6.391-654.0	ID 6	250 bar	15 m		15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	
High-pressure hose, 10 m, ID 8, AVS trigger gun connection, food	18	6.390-704.0	ID 8	250 bar	10 m		Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar	
industry, grey High-pressure hose, 20 m ID 8, AVS trigger gun connector, suitable for food industry, grey	19	6.390-705.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar.	



				Max. working					
		Order No.	ID	pressure	Length	P	rice	Description	
Longlife food industry version				1	· · · · ·				
Hlgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	20	6.391-888.0	ID 6	400 bar	15 m			Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun-	
HIgh-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun con- nection	21	6.391-885.0	ID 8	400 bar	10 m			ted)	
HIgh-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun con- nection	22	6.391-886.0	ID 8	400 bar	20 m				C
Special hoses					·			·	
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	23	6.388-886.0	ID 8	400 bar	1.5 m				

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill\blacksquare$  Extension hose.



		Order No.	Flow rate			Price	Description	
Easy Press high-pressure gun with	holdin	g power reductio	n (Kärcher paten	:)				-
Extended easy press trigger gun	1	4.775-529.0					Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.	
Easy press high-pressure trigger gun with softgrip	2	4.775-463.0					Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.	
	3	4.775-466.0					Easy press high-pressure trigger gun with integrated adap- ter for connecting to high-pressure hoses M 22 x 1.5.	
Trigger guns								
High end high-pressure trigger gun	4	4.775-823.0						
Quick connect								
Quick coupling	5	6.401-458.0					For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	
Plug nipple	6	6.401-459.0					Hardened stainless steel nipple for quick coupling 6.401- 458. With M22 x 1,5 male.	

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill \blacktriangle$  Extension hose.



		Order No.	Max. working pressure	Length	Price	Description	
Rotating spray lances							
1050 mm lance, rotatable, ergono- mic	1	4.760-660.0	300 bar	1050 mm		1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Rotatable lance, 600 mm, ergono- mic	2	4.760-664.0	300 bar	600 mm		600 mm stainless steel lance (manual coupling) with ergono- mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergono- mic	3	4.760-663.0	300 bar	840 mm		850 mm stainless steel lance (manual coupling) with ergono- mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 1550 mm, rotatable, ergo- nomic	4	4.760-661.0	300 bar	1550 mm		1550 mm stainless steel lance (manual coupling) with ergo-	
Lance 2050 mm, rotatable, ergo- nomic	5	4.760-662.0	300 bar	2050 mm		2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance							
Lance 250 mm, non-rotatable	6	4.760-667.0		250 mm		250 mm stainless steel lance. With manual coupling. Non- rotatable.	
Anti-vibration lance	7	6.415-951.0	250 bar	950 mm		The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.	
Angular spray lance							
WC and gutter lance	8	4.760-073.0				Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance							
Flexible lance 1050 mm	9	6.394-654.0	210 bar	1050 mm		1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Articulated joint M18x1,5	10	4.481-039.0	300 bar				
Telescopic spray lance							
Telescopic jet pipe	11	6.394-690.0	225 bar	5400 mm			
Restraint belt for telescopic jet pipe	12	6.373-987.0				Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner							
Gutter cleaning lance	13	2.642-305.0				The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance							
Underbody lance	14	4.760-245.0		700 mm		Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Weed control							
WR 50	15	2.643-758.0					
WR 20	16	2.643-760.0					
■ Included in delivery. □ Av	ailable	e accessories.	Extension h	ose.			



		Order No.	Nozzle size			Price	Description
Power nozzle spray angle 25°							
Power nozzle spray angle 25°	1	2.883-821.0	36				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
	2	2.884-521.0	250				
Power nozzle spray angle 15°							
Power nozzle 15036 - nur fuer Ersatz	3	2.885-225.0	36				C
Power nozzle spray angle 40°		-		-			
Power nozzle spray angle 40°	4	2.884-522.0	40				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	5	2.884-533.0	40				High-pressure nozzle with powerful jet for extremely stub-



		Order No.	Max. working pressure	Nozzle size		Price	Description	
Dirt Blaster, small	1	4.767-023.0	180 bar	40			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C.	
Dirt blaster, large Dirt blaster 04	2	4.763-252.0	300 bar	40			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

## KARCHER

				5	$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} $	
		Order No.		Price	Description	
Nozzle union	1	5 401 210 0	1	1	For excitation and connection (Aircher power powerlos to	
Nozzle connector	1	5.401-210.0			For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).	
Nozzle union food industry	2	5.401-318.0			Made of special brass alloy for use in the food industry.	
Spacer (including nozzle union)						
Spacer (incl.nozzle union)	3	5.394-294.0			Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	
HP detergent injector						
Detergent injector for high pressu- re		3.637-170.0	 		Cleaning agent dosage at high pressure 3 - 5 %	
Detergent injector for high and low pressure (without nozzles)	5	3.637-001.0			Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Machine-specific nozzle kit with or	der no	. 3.637-170				
Nozzle insert trapezoidal thread	6	4.769-009.0				
HDS-GER			 			
Machine-specific nozzle kit with order no. 3.637-170.0 HD 500- 700 l/h	7	4.769-046.0			For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	r D
Nozzle insert with order no. 3.637-	001					
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.	8	4.769-003.0			Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to	9	4.769-001.0			For low pressure with machines up to 1.100 l/h	
1100 l/h						
Rotary coupling			1	1		1
Rotary coupling	10	4.401-091.0			Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling Coupler -2xM22x1,5	11	4.403-002.0	I		Brass double connector for connecting and extending high-	
CODDIEL -2XIM22X1,5	11	4.405-002.0			pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	
Connector						
Nozzle connector/screw connector	12	4.402-022.0			Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
Adapter					·	
Adapter M22 - Swivel	13	4.424-004.0			M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connec- tion.	e 🗆
Adapter EASY!Lock						-
Adapter 1 M22AG-TR22AG	14	4.111-029.0				
Adapter 2 M22IG-TR22AG	15	4.111-030.0				
Adapter 3 M22IG-TR22AG	16	4.111-031.0				
Adapter M22 - Swivel	17	4.111-032.0			M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connec- tion.	

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill A$  Extension hose.

#### KÄRCHER

## HDS 6/14 C 1.169-218.0



		Order No.			Price	Description
Adapter 5 TR22IG-M22AG	18	4.111-033.0				
Adapter 6 TR22IG-M22AG	19	4.111-034.0				
Adapter 7 M18IG-TR20AG	20	4.111-035.0				
Adapter 8 TR20IG-M18AG	21	4.111-036.0				
Flue pipe						
Flue gas adapter	22	4.656-149.0				Flue gas adapter with draught damper for flue pipe connec- 🗌
	23	4.656-080.0				tion (adapter for HDS burners for connection to a stack system).

## KARCHER





		Order No.	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6							l	_
Pipe cleaning hose	1	6.390-028.0	120 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 30 m	2	6.390-029.0	120 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	3	6.390-030.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Pipe cleaning nozzle								
Dirt blaster pipe cleaning D21/040	4	4.765-001.0		40	21 mm			
Dirt blaster pipe cleaning D30/040	5	4.765-004.0		40	30 mm			
Pipe cleaning nozzle	6	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various je	
	7	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	8	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	9	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blo- cked drains and pipes.	
Drain cleaning dirt blaster D 25/040	10	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Drain cleaning dirt blaster D 30/040	11	6.415-946.0		40	30 mm		necessary forward movement, as well as convenient hand- ling.	
Drain cleaning dirt blaster D 35/040	12	6.415-948.0		40	35 mm			

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill A$  Extension hose.

## KARCHER

				5	5	6		
		Order No.	Flow rate	Nozzle size	Diame- ter	Price	Description	
Hard Surface Cleaner FRV 30								
FRV 30	1	2.642-999.0						
Add-on kit rubber lip	2	2.642-910.0					For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Add-on kit hose attachment	3	2.642-528.0						
Add-on kit dirt trap	4						-	
Hard surface cleaner FR 30						· · · ·		
FR 30	5	2.642-997.0			300 mm			
Hard surface cleaner FR 30 ME								
FR 30 ME surface cleaner	6	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with	
	7	2.640-355.0			300 mm		double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h		2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	
Machine-specific nozzle kits for FR								
Nozzle kit 035 for FRV 30	9	2.642-430.0		35				
FRV 30 Me surface cleaner			1	1				
FRV 30 ME		2.642-911.0					_	
Suction hose FRV 30 me		4.441-040.0						
■ Included in delivery. □ Av	/ailable	e accessories.	Extension h	IOSE				

## KARCHER



		Order No.	Flow rate		Price	Description
Cup foam lance			1		1	1
Cup foam lance	1	6.394-668.0	1200 l/h			Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its com- pact design.
Tank 1L	2	6.414-954.0				C
Inno Foam Kit						
Inno foam kit with detergent injec- tor	3	2.640-151.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and
Inno foam kit	4	2.640-692.0				stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	5	2.640-691.0				HP foam system for use with. HD/HDS units for cleaning and
Easy foam set	6	2.640-693.0				disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h	7	2.640-870.0	500-600 l/h			Optimal adaptation to different machine outputs for econo- mic use.
Foam nozzle mounting kit						
Foam nozzle kit	8	2.637-926.0				Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.

#### KÄRCHER

		4		5	6	C	
		Order No.	Length			Price	Description
Hose reel add-on kit							
Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C	1	2.642-756.0	20 m				
Automatic, self-winding hose reels							
Swivel holder	2	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose.
ABS wall fastening stainless steel	3	2.641-867.0		-			Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.
Add-on kit hose reel plastics	4	6.392-975.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	5	6.392-965.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic.
Hose reel, automatic, 20 m, pain- ted	6	2.639-919.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
Hose reel, automatic, 20 m, stain- less steel	7	6.391-421.0	20 m				Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	8	2.641-866.0	20 m				High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Anbausatz Schlauchtrommel autom							
	9	2.643-052.0				1	
Add-on kit automatic hose reel HDS-C		2.643-181.0					



		Order No.	Nozzle size		Price	Description
Wet blasting attachment (without n	ozzle)					
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0				Paint, rust and scale removal made easy: Karcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle kit for wet blasting attach- ment 040	3	2.637-900.0	40			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.
Boron carbide nozzle						
Boron carbide nozzle, for machi- nes as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill\blacksquare$  Extension hose.



		Order No.				Price	Description
Crane lifting kit							· · · · · · · · · · · · · · · · · · ·
Add-on kit suspension crane HDS C	1	2.642-638.0					
Flame monitoring attachment kit							
ABS flame monitor for HDS C	2	2.642-711.0					
■ Included in delivery. □ Ava	ailable	e accessories.	▲ Extension h	ose.			

## KARCHER

		5		6	7	Â		
10-11								
		Order No.	Length	Diameter		Price	Description	
Geka coupling				1				
With hose nozzle, R 1/2"	1	6.388-461.0					with hose liner	
With hose nozzle, R 3/4"	2	6.388-455.0						
With hose nozzle, R 1"	3	6.388-465.0						
Hose coupling	4	6.388-458.0					with female thread	
Suction filter								
Water filter	5	6.414-956.0						
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter								
Fine-mesh water filter with adap- ter	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contai- ned in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Fine-mesh water filter, 100 $\mu\text{m},$ R 1"	8	2.638-270.0					Fine-mesh water filter, $100 \ \mu$ m, max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protects the high-pressu- re cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	
Water supply hose			·	·			· · · ·	
Water supply hose	9	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	
	10	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	11	4.440-270.0	7.5 m				NW 19 R1" / R1", up to 85 °C	
Other HP Accessories								
Starting current limiter	12	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	



		Order No.	Flow rate		Price	Description
Rotating washing brush						
Washing brush rotary	1	4.762-561.0	500-800 l/h			
			500.000.1/			
	2	4.762-560.0	500-800 l/h			