HDS 6/12 C

1-phase (240 V) hot water high-pressure cleaner HDS 6/12 C with eco!efficiency mode, EASY!Force trigger gun, as well as intuitive single-button operation.











Order No.

1.169-904.0

- Economical eco!efficiency mode
- Convenient one-button operation
- Extensive standard equipment

| Technical data | | |
|---|-----------------------------|--------------------------|
| EAN code | _ | 4054278167206 |
| Type of current | Phases / Volt / Hertz | 1 / 240 / 50 |
| Flow rate | Litres per hour | 240 - 560 |
| Operating pressure | Bar / Mega pascal | 30 - 120 / 3 - 12 |
| Temperature (feed 12 °C) | Celsius | Minimum 80 - Maximum 155 |
| Power rating | Kilowatt | 3 |
| Fuel oil consumption, full load | Kilograms per hour | 3.5 |
| Heating oil consumption, ecolefficiency | Kilograms per hour | 2.8 |
| Power cord | Metre | 5 |
| Fuel tank | Litre | 15 |
| Weight (with accessories) | Kilogram | 107.4 |
| Weight incl. packaging | Kilogram | 115.6 |
| Dimensions (L × W × H) | Millimetre | 1060 × 650 × 920 |

| This | device | requires | instruction |
|------|--------|----------|-------------|
| | | | |

| Equipment | | |
|---|------------|---------------------|
| Trigger gun | | EASY!Force Advanced |
| High-pressure hose | Metre | 10 / DN 6, 250 bar |
| Spray lance | Millimetre | 1050 |
| Power nozzle | | - |
| SDS system | | |
| Pressure cut-off | | |
| Integrated fuel and cleaning agent tank | | |
| Included in delivery. | | |





Economical

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.
- Accurate cleaning agent dosing unit with clear rinse function.



Ease of use

- Intuitive operation with one-switch control.
- Intuitive operation with large single-button selector switch.
- System care bottle can be changed conveniently from the outside.



Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.
- Integrated lance holder for easy transport.

EQUIPMENT FOR HDS 6/12 C 1.169-904.0

























| | | Order No. | Description | |
|---|----|-------------|--|----------|
| TRIGGER GUNS | | | | Ī |
| Trigger guns | | | | |
| EASY!Force Advanced | 1 | 4.118-005.0 | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. | • |
| Conversion kit 1 from high pressure hose | 2 | 4.111-050.0 | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. | |
| Conversion kit 2 from device | 3 | 4.111-051.0 | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. | |
| Servo Control | | | | |
| Servo Control, < 750 Litres per hour | 4 | 4.118-007.0 | Servo control for water flow and pressure control (< 750 l/h) on trigger gun. | |
| SPRAY LANCES | | | | |
| Rotating spray lances | | | | |
| Spray lance, 1050 Millimetre, rotatable | 5 | 4.112-000.0 | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ŀ |
| Spray lance, 600 Millimetre, rotatable | 6 | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 840 Millimetre, rotatable | 7 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 1550 Millimetre, rotatable | 8 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 2050 Millimetre, rotatable | 9 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| ROTARY NOZZLES (DIRT BLASTERS) | | | | |
| Dirt blaster, large | | | | |
| Dirt blaster, large, 050 | 10 | 4.114-027.0 | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | <u> </u> |
| HIGH-PRESSURE HOSES | | | | |
| Standard with unions on both sides | | | | |
| $\begin{array}{l} \mbox{High-pressure hose, 10 Metre, DN 6, 250 Bar,} \\ 2 \times \mbox{EASY!Lock} \end{array}$ | 11 | 6.110-034.0 | 10 m long high-pressure hose with EASY!Lock manual screw fitting on both sides. Nominal size DN 6, suitable up to 250 bar. | |
| High-pressure hose, 10 Metre, DN 6, 300 Bar, 2 × EASY!Lock | 12 | 6.110-056.0 | High-pressure hose (DN 6) equipped with ANTI!Twist and the new EASY!Lock manual screw fitting on both sides. For pressures up to 300 bar. 10 m long. | |
| High-pressure hose, 10 Metre, DN 8, 315 Bar, 2 × EASY!Lock | 13 | 6.110-031.0 | High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long. | |
| High-pressure hose, 15 Metre, DN 8, 315 Bar, 2 × EASY!Lock | 14 | 6.110-030.0 | 15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides. | |

 \blacksquare Included in delivery. \qed Available accessories.

HDS 6/12 C, 1.169-904.0, 2024-12-20

KÄRCHER

EQUIPMENT FOR HDS 6/12 C 1.169-904.0





























| | | | | \top |
|---|----|-------------|--|--------|
| | | | | |
| | | Order No. | Description | |
| HIGH-PRESSURE HOSES | | | | |
| Standard with unions on both sides | | | | |
| $\begin{array}{l} \mbox{High-pressure hose, 20 Metre, DN 8, 315 Bar,} \\ 2 \times \mbox{EASY!Lock} \end{array}$ | 15 | 6.110-032.0 | 20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar. | |
| Longlife 400 with unions on both sides | | | | |
| High-pressure hose Longlife, 10 Metre, DN 8, 400 Bar, 2 × EASY!Lock | 16 | 6.110-038.0 | Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure. | |
| High-pressure hose Longlife, 20 Metre, DN 8, 400 Bar, 2 × EASY!Lock | 17 | 6.110-027.0 | High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides. | |
| FLOOR AND HARD SURFACE CLEANER | | | | |
| Hard surface cleaner FR 30 ME | | | | |
| FR 30 ME surface cleaner | 18 | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | |
| Machine-specific nozzle kit for FR | | | | |
| Nozzle kit for FR, 500 Litres per hour - 650 Litres per hour | 19 | 2.640-401.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h). | |
| Machine-specific nozzle kits for FRV | · | | | |
| Nozzle kit for FRV, 045 | 20 | 2.642-432.0 | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. | |
| FRV 30 Me surface cleaner | | | | |
| FRV 30 ME | 21 | 2.111-012.0 | Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. | |
| FOAM SYSTEMS | • | | | |
| Cup foam lance | | | | |
| Cup foam lance DUO Advanced 1, 400 Litres per hour - 600 Litres per hour | 22 | 4.112-067.0 | DUO Advanced 1 cup foam lance with two-litre detergent tank and direct switching to high-pressure cleaning. Suitable for Kärcher pressure washers with a flow rate of 400 to 600 l/h. | |
| Cup foam lance Basic 1, 350 Litres per hour - 600 Litres per hour | 23 | 4.112-053.0 | For high-pressure cleaners with a flow rate of 350–600 l/h: new, robust and very high-quality Basic 1 cup foam lance with outstanding foam quality while consuming half as much cleaning agent | t. |
| 1-litre cleaning agent container for cup foam lance advanced | 24 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0). | |
| QUICK CONNECT | | | | |
| Quick-fitting pipe union coupler trapezo | 25 | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread. | |
| Quick-fitting pipe union plug nipple tra | 26 | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread. | |
| DRUM AND TANK CLEANING | | | | |
| Add-on kit mud sucker | 27 | 2.641-798.0 | For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps. | |
| FLUE PIPE | | | | |
| Flue gas adapter | 28 | 4.656-149.0 | Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system). | |
| | | | | |

EQUIPMENT FOR HDS 6/12 C 1.169-904.0






























| | | Order No. | Description | |
|--|-----|-------------|---|-----|
| COUPLING PARTS | | | | |
| Rotary coupling | | | | |
| Rotary coupling | 29 | 4.111-021.0 | Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection | |
| Connector | | | | |
| Short spray unit | 30 | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles. | t [|
| Adapter EASY!Lock | | | | |
| Adapter 1 M22AG-TR22AG | 31 | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose | |
| Adapter 2 M22IG-TR22AG | 32 | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose | [|
| Adapter 3 M22IG-TR22AG | 33 | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator | [|
| Adapter M22 - Swivel | 34 | 4.111-032.0 | M22 \times 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection. | 1 [|
| Adapter 5 TR22IG-M22AG | 35 | 4.111-033.0 | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance | [|
| Adapter 6 TR22IG-M22AG | 36 | 4.111-034.0 | Adapter 6 to connect the new device with the old hose and the old hose with the new gun | [|
| Adapter 7 M18IG-TR20AG | 37 | 4.111-035.0 | Adapter 7 to connect the old spray lance with the new nozzle | [|
| Adapter 8 TR20IG-M18AG | 38 | 4.111-036.0 | Adapter 8 to connect the new spray lance with the old nozzle | |
| Coupler -2xM22x1,5 | 39 | 4.111-037.0 | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x M 22 \times 1.5 m$. | [|
| ADAPTER for replacement TR22IG-M22AG Er | 40 | 4.111-046.0 | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection | [|
| HOSE REELS | | | | |
| Automatic, self-winding hose reel attachment | kit | | | |
| Attachment kit automatic hose reel HDS C | 41 | 2.110-012.0 | Complete automatic hose reel attachment kit for HDS compact class. Simple installation and all unit functions are accessible. Offers maximum convenience when winding and unwinding the HP hose. Contains: Automatic hose reel, HP hose and all connection parts. | . [|
| FACADE AND SOLAR PANEL CLEANING | | | | Ė |
| Brushes | | | | |
| Transmission brush complete | 42 | 4.762-584.0 | Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance. | |

[☐] Available accessories.

KÄRCHER

EQUIPMENT FOR HDS 6/12 C 1.169-904.0

























| | | | | _ |
|---------------------------------|----|-------------|---|-----|
| | | | | |
| | | Order No. | Description | |
| FACADE AND SOLAR PANEL CLEANING | | | | |
| Brushes | | | | |
| Splash guard complete | 43 | 4.762-621.0 | Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time. | |
| Roll soft | 44 | 4.762-623.0 | Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive. | |
| Roll middle | 45 | 4.762-624.0 | Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system. | |
| Roll hard | 46 | 4.762-625.0 | Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system. | |
| Brush rigid hard | 47 | 6.960-133.0 | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher. | |
| Brush rigid middle | 48 | 6.960-134.0 | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher. | |
| Brush rigid soft | 49 | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems. | |
| Teleskopstangen | | | | |
| Ball valve | 50 | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes. | |
| Telescope lance glass fibre 7 m | 51 | 4.762-609.0 | Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension. | |
| Telescope lance hybrid 7 m | 52 | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach. | . 🗆 |
| Telescope lance hybrid 10 m | 53 | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners. | |
| Telescope lance carbon 10 m | 54 | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels. | |
| Telescope lance carbon 14 m | 55 | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners. | |
| Pistol | 56 | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals. | |

[☐] Available accessories.



EQUIPMENT FOR HDS 6/12 C 1.169-904.0





| | | Order No. | Description | |
|---|----|-------------|--------------------|--|
| WATER CONNECTION | | | | |
| Geka coupling | | | | |
| Geka connector with hose barb, R 3/4" | 57 | 6.388-455.0 | with hose liner | |
| Geka connector with internal thread, R 1" | 58 | 6.388-458.0 | with female thread | |

☐ Available accessories.