### **HD 5/11 C EASY! \*AU**

Practical, mobile, versatile: the HD 5/11 C EASY! cold water high-pressure cleaner for vertical and horizontal operation. With accessory storage, brass cylinder head and automatic pressure relief.













Order No.

1.520-972.0

- Automatic pressure relief
- For horizontal and vertical operation
- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

Technical data		
EAN code		4054278296036
Type of current	Phases / Volt / Hertz	1 / 240 / 50
Flow rate	Litres per hour	500
Feed temperature	Celsius	up to 60
Operating pressure	Bar / Mega pascal	110 / 11
Max. pressure	Bar / Mega pascal	171 / 17.1
Power rating	Kilowatt	2.1
Power cord	Metre	5
Water feed		3/4"
Weight (with accessories)	Kilogram	24
Weight incl. packaging	Kilogram	26.4
Dimensions (L × W × H)	Millimetre	380 × 360 × 930

Equipment		
Trigger gun		EASY!Force
High-pressure hose	Metre	10 / DN 6, 250 bar
Spray lance	Millimetre	840
Triple nozzle (0°/25°/40°)		manual
Cleaning agent function		Suction
Pressure cut-off		
Included in delivery.		



### Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.

#### Portability

- The integrated carrying handle on the front of the machine enables easy loading and convenient transport.
- Push handle can be retracted at the push of a button.
- Compact package.

### Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on in horizontal operation. In this way,the machine offers maximum stability.
- Separate parking and transport position for the spray unit.

## **EQUIPMENT FOR HD 5/11 C EASY! \*AU** 1.520-972.0























				_
		Order No.	Description	
TRIGGER GUNS				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	•
Conversion kit 1 from high pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
Conversion kit 2 from device	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 840 mm, rotatable	4	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 600 mm, rotatable	5	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	7	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	8	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
HIGH-PRESSURE HOSES				Т
Standard with unions on both sides				
High-pressure hose, 10 m, DN 6, 250 bar, 2 × EASY!Lock	9	6.110-034.0	10 m long high-pressure hose with EASY!Lock manual screw fitting on both sides. Nominal size DN 6, suitable up to 250 bar.	
High-pressure hose, 10 m, DN 6, 300 bar, 2 × EASY!Lock	10	6.110-056.0	High-pressure hose (DN 6) equipped with ANT!!Twist and the new EASY!Lock manual screw fitting on both sides. For pressures up to 300 bar. 10 m long.	
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	11	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANT!Twist and 10 m long.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	12	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	Г
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	13	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	Г
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, DN 8, 400 bar, $2 \times EASY!Lock$	14	6.110-038.0	Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure.	

 $\blacksquare$  Included in delivery.  $\qed$  Available accessories.

# HD 5/11 C EASY! \*AU, 1.520-972.0, 2024-03-15































				T
		Order No.	Description	
HIGH-PRESSURE HOSES				Ť
Longlife 400 with unions on both sides				П
High-pressure hose Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$	15	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
ROTARY NOZZLES (DIRT BLASTERS)				Ť
Dirt Blaster, small				
Dirt blaster, small, 040	16	4.114-020.0	With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor.	
FLOOR AND HARD SURFACE CLEANER				
FR Classic surface cleaner				Ī
FR Classic surface cleaner	17	2.111-016.0	The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.	
Hard Surface Cleaner FRV 30				Ī
FRV 30	18	2.111-010.0	With the integrated, automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient and can be used in both inside and outside areas. There is no longer a need to rinse the surface after cleaning, since the dirty water can be discharged through the 5 m suction hose supplied. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1000 l/h / 60°C.	
Hard surface cleaner FR 30				
FR 30	19	2.111-011.0	Up to 10 times greater area performance compared with the conventional high-pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for optimal handling and integrated parking position. Machine-specific nozzle kit must be ordered separately. Max. 180 bar / 850 l/h / 60°C.	
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	20	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FR				Ī
Nozzle kit for FR, 450 l/h - 500 l/h	21	2.640-482.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	
Machine-specific nozzle kits for FRV				ľ
Nozzle kit for FRV, 035	22	2.642-430.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	1
Machine-specific nozzle kits for FR Classic		l .		
Nozzle kit for FR Classic, 034	23	2.885-313.0	Nozzle kit specifically for FR Classic surface cleaner.	1
FRV 30 Me surface cleaner		l		
FRV 30 ME	24	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
FOAM SYSTEMS				
Cup foam lance				Ī
Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h	25	4.112-067.0	DUO Advanced 1 cup foam lance with two-litre detergent tank and direct switching to high-pressure cleaning. Suitable for Kärcher pressure washers with a flow rate of 400 to 600 l/h.	
Cup foam lance Basic 1, 350 l/h - 600 l/h	26	4.112-053.0	For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality Basic 1 cup foam lance with outstanding foam quality while consuming half as much cleaning agent	t.
1-litre cleaning agent container for cup foam lance advanced	27	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
QUICK CONNECT				Ī
Quick-fitting pipe union coupler trapezo	28	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	





























				$\overline{}$
		Order No.	Description	
QUICK CONNECT				
Quick-fitting pipe union plug nipple tra	29	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 $ imes$ 1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	30	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	31	4.111-021.0	Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector				
Short spray unit	32	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	t
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	33	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	34	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	35	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	Г
Adapter M22 - Swivel	36	4.111-032.0	M22 $\times$ 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	1 [
Adapter 5 TR22IG-M22AG	37	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	38	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	39	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	40	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	T
Coupler -2xM22x1,5	41	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x M 22 \times 1.5 m$ .	
ADAPTER for replacement TR22IG-M22AG Er	42	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	

<sup>☐</sup> Available accessories.

























				$\top$
		Order No.	Description	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Transmission brush complete	43	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard complete	44	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roll soft	45	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roll middle	46	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roll hard	47	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush rigid hard	48	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush rigid middle	49	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush rigid soft	50	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
Teleskopstangen				
Ball valve	51	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescope lance glass fibre 7 m	52	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescope lance hybrid 7 m	53	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. 🗆
Telescope lance hybrid 10 m	54	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescope lance carbon 10 m	55	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescope lance carbon 14 m	56	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	

<sup>☐</sup> Available accessories.









	Order No.	Description	
57	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
58	6.388-455.0	with hose liner	
59	6.388-473.0	with female thread	
	58	57 4.775-154.0 58 6.388-455.0	57 4.775-154.0 TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.  58 6.388-455.0 with hose liner

<sup>☐</sup> Available accessories.