

SP 16.000 DIRT

Quickly pump out and transfer dirty water with a pumping capacity of up to 16,000 l/h: With the robust dirty water pump SP 16,000 Dirt incl. height-adjustable float switch for greater flexibility.



Order No. 1.645-835.0

- Extremely durable thanks to the ceramic slide ring sealing
- Height-adjustable float switch for greater flexibility

Technical data

EAN code		4066529018014
Max. motor rating	Watt	550
Max. flow rate	Litres per hour	< 16000
Delivery temperature	Celsius	Maximum 35
Delivery head	Metre	8
Pressure	Bar	Maximum 0.8
Grain size	Millimetre	Maximum 20
Depth of immersion	Metre	Maximum 7
Min. residual water, manual	Millimetre	25
Residual water height	Millimetre	25
Connecting thread		G1 1/2
Pressure-side connection thread		G1/2 internal thread
Power cord	Metre	10
Voltage	Volt	230 - 240
Frequency	Hertz	50
Colour		yellow
Weight without accessories	Kilogram	4.852
Weight incl. packaging	Kilogram	5.561
Dimensions (L × W × H)	Millimetre	229 × 238 × 303

Equipment


Comfortable carry handle	■
Connecting hose	G1, 1", 1 1/4", 1 1/2"
Easy hose connection thanks to Quick Connect	■
Switching between manual/automatic operation	Possibility of fixing the float switch
Flexible, height-adjustable float switch	■
In automatic operation (auto), the pump automatically switches with the water level	■
In manual operation, the pump runs continuously to ensure the minimum quantity of residual water	■
Ceramic face seal.	■

■ included in delivery.




Ceramic face seal.

- For an extra long lifetime.



Height-adjustable float switch

- Increases the flexibility when setting the switch-on and switch-off point of the pumps and prevents dry running.



Quick Connect

- Connection thread for quickly and simply connecting 1", 1 1/4" and 1 1/2" hoses or a G1 connection.

EQUIPMENT FOR SP 16.000 DIRT 1.645-835.0



		Order No.	Description	
FILTER				
Prefilter for submersible pumps, small	1	2.997-201.0	Protects the submersible pump and thereby improves its operational reliability: the robust and easy-to-fit prefilter for the SP 1 to SP 5 Flat/Dirt submersible pumps.	<input type="checkbox"/>
MISCELLANEOUS				
Flat Hose Set	2	2.997-100.0	Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	<input type="checkbox"/>

Available accessories.