

## SP 22.000 DIRT LEVEL SENSOR

With level sensor and integrated prefilter: For challenging drainage tasks the submersible dirty water pump SP 22,000 Dirt Level Sensor manages to pump out dirty water at a rate of up to 22,000 l/h.



Order No. 1.645-855.0

- Extremely durable thanks to the ceramic slide ring sealing
- Level sensor allows the switching level to be set to any level
- Integrated stainless steel prefilter


### Technical data

EAN code		4066529018038
Max. motor rating	Watt	750
Max. flow rate	Litres per hour	< 22000
Delivery temperature	Celsius	Maximum 35
Delivery head	Metre	8
Pressure	Bar	Maximum 0.8
Grain size	Millimetre	Maximum 30
Depth of immersion	Metre	Maximum 7
After-running time	Second	15
Min. residual water, manual	Millimetre	35
Residual water height	Millimetre	35
Connecting thread		G1 1/2
Pressure-side connection thread		G1/2 internal thread
Power cable	Metre	10
Voltage	Volt	230 – 240
Frequency	Hertz	50
Colour		yellow
Weight without accessories	Kilogram	6.668
Weight incl. packaging	Kilogram	7.565
Dimensions (L × W × H)	Millimetre	238 × 293 × 354

### Equipment

Comfortable carry handle	■
Connecting hose	1", 1 1/4", 1 1/2"
Easy hose connection thanks to Quick Connect	■
Switching between manual/automatic operation	Switch on the pump
Level sensor: Continuous switching level definition	■
Integrated stainless-steel prefilter	■
In automatic operation (auto), the pump automatically switches with the water level	■
In manual operation, the pump runs continuously to ensure the minimum quantity of residual water	■
Ceramic face seal.	■
Stainless steel housing	■

■ included in delivery.



## Ceramic face seal.

- For an extra long lifetime.



## Level Sensor


- For continuously variable definition of the switch-on and switch-off points of the pumps.



## Quick Connect

- Connection thread for quick and uncomplicated connection of 1", 1 1/4" and 1 1/2" hoses.

EQUIPMENT FOR SP 22.000 DIRT LEVEL SENSOR  
1.645-855.0



		Order No.	Description	
MISCELLANEOUS				
Flat Hose Set	1	2.997-100.0	Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	<input type="checkbox"/>
HOSES				
PrimoFlex 1" 1m	2	2.645-247.0		<input type="checkbox"/>
Hose PrimoFlex Plus 3/4" -25m	3	2.645-322.0		<input type="checkbox"/>
Hose PrimoFlex Plus 3/4" -50m	4	2.645-323.0		<input type="checkbox"/>
PrimoFlex® hose 3/4" - 25 m	5	2.645-142.0	PrimoFlex® quality garden hose (3/4") 25 m. Pressure-resistant, reinforced braided. Unharmful to health. Bursting pressure: 24 bar. Wide operating temperature range from -20 to 65 °C.	<input type="checkbox"/>

■ Included in delivery.    ☐ Available accessories.    ☐ Cleaning agents.