



HDS 6/12 C

Compact hot water high pressure cleaner with ecoefficiency mode and steam function



ecoefficiency



2-3 h



AVS




SERVO CONTROL



1



2



3



4

1 Efficiency

- ecoefficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

2 Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.

3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.

4 Mobility

- Jogger principle with large wheels and steering roller.
- Large integrated handles in the chassis.



HDS 6/12 C

■ Economical ecoefficiency mode

Technical data

| | | |
|-------------------------------|--------------------|------------------|
| Order Number | 1.169-219.0 | |
| EAN code | 4039784729490 | |
| Current type | Ph / V / Hz | 1 / 240 / 50 |
| Flow rate | l/h | 240-560 |
| Pressure | bar / MPa | 30-120 / 3-12 |
| Max. temperature | °C | 80 / 155 |
| Power rating | kW | 3 |
| Consumption fuel oil | kg/h | 3,5 |
| Fuel tank | l | 15 |
| Weight | kg | 93 |
| Dimensions (L x W x H) | mm | 1060 × 650 × 920 |

Equipment

| | | |
|---|------------------------|--------------------|
| Trigger gun | Easy-press trigger gun | |
| Trigger gun with soft grip | ■ | |
| High-pressure hose | m | 10 / ID 6, 250 bar |
| Spray lance | mm | 1050 |
| Power nozzle | ■ | |
| SDS system | ■ | |
| ANTI!Twist | - | |
| Pressure switch control | ■ | |
| Integral fuel and detergent tank | ■ | |
| Servo Control | ■ | |

■ Included in delivery.

HDS 6/12 C

1.169-219.0

KÄRCHER



| | | Order Number | ID | Max. working pressure | Length | Price | Description | |
|---|----|--------------|------|-----------------------|--------|-------|---|---|
| Standard with unions on both sides | | | | | | | | |
| High-pressure hose packaged | 1 | 6.391-342.0 | ID 8 | 315 bar | 10 m | | | ▲ |
| High-pressure hose, 30 m DN 8, including rotary coupling | 2 | 6.390-293.0 | ID 8 | 315 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| Longlife 400 with unions on both sides | | | | | | | | |
| High pressure hose DN 6, 10 m, drehbar,l | 3 | 6.391-883.0 | ID 6 | 400 bar | 10 m | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose packaged | 4 | 6.391-354.0 | ID 8 | 400 bar | 10 m | | | ▲ |
| High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling | 5 | 6.390-294.0 | ID 8 | 400 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose 1.5 m, DN 8, including connectors | 6 | 6.390-178.0 | ID 8 | 400 bar | 1.5 m | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). | □ |
| Longlife food industry version with unions on both sides | | | | | | | | |
| High pressure hose food DN 8 / 10 m | 7 | 6.391-864.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außendecke# animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5 | ▲ |
| High-pressure hose food industry 400 bar, 20 m, DN 8, including rotary coupling | 8 | 6.391-887.0 | ID 8 | 400 bar | 20 m | | | ▲ |
| Standard | | | | | | | | |
| High-pressure hose, 10 m DN 6, AVS trigger gun connector | 9 | 6.391-238.0 | ID 6 | 250 bar | 10 m | | 10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar. | ■ |
| High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connection | 10 | 6.391-875.0 | ID 6 | 300 bar | 10 m | | With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar | □ |
| High-pressure hose, 10 m DN 8, AVS trigger gun connector | 11 | 6.390-025.0 | ID 8 | 315 bar | 10 m | | 10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. | □ |
| High-pressure hose, 15 m DN 8, AVS trigger gun connector | 12 | 6.390-185.0 | ID 8 | 315 bar | 15 m | | 15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. | □ |
| High-pressure hose, 20 m DN 8, AVS trigger gun connector | 13 | 6.390-171.0 | ID 8 | 315 bar | 20 m | | 20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. | □ |
| Longlife 400 | | | | | | | | |
| High pressure hose DN 6, 10 m, Longlife | 14 | 6.391-882.0 | ID 6 | 400 bar | 10 m | | With patented AVS connection in the trigger gun (pivot-mounted). | □ |
| High-pressure hose packaged | 15 | 6.391-351.0 | ID 8 | 400 bar | 10 m | | | □ |
| High-pressure hose Longlife 400, 20 m DN 8, AVS trigger gun connector | 16 | 6.390-208.0 | ID 8 | 400 bar | 20 m | | 20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced. | □ |
| Food industry version | | | | | | | | |
| High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey | 17 | 6.391-654.0 | ID 6 | 250 bar | 15 m | | 15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar. | □ |
| High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food industry, grey | 18 | 6.390-704.0 | ID 8 | 250 bar | 10 m | | Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar | □ |
| High-pressure hose, 20 m ID 8, AVS trigger gun connector, suitable for food industry, grey | 19 | 6.390-705.0 | ID 8 | 250 bar | 20 m | | 20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar. | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0




| | | Order Number | ID | Max. working pressure | Length | | Price | Description |
|---|----|--------------|------|-----------------------|--------|--|-------|---|
| Longlife food industry version | | | | | | | | |
| High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection | 20 | 6.391-888.0 | ID 6 | 400 bar | 15 m | | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted) |
| High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection | 21 | 6.391-885.0 | ID 8 | 400 bar | 10 m | | | |
| High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection | 22 | 6.391-886.0 | ID 8 | 400 bar | 20 m | | | |

Included in delivery.
 Available accessories.
 Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Flow rate | | | | Price | Description | |
|---|---|--------------|-----------|--|--|--|-------|--|---|
| Easy Press high-pressure gun with holding power reduction (Kärcher patent) | | | | | | | | | |
| Easy press high-pressure trigger gun with softgrip | 1 | 4.775-463.0 | | | | | | Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter. | ■ |
| | 2 | 4.775-466.0 | | | | | | Easy press high-pressure trigger gun with integrated adapter for connecting to high-pressure hoses M 22 x 1.5. | □ |
| Servo Control | | | | | | | | | |
| Servo control | 3 | 4.775-526.0 | 0-750 l/h | | | | | Servo control for water flow and pressure control (< 750 l/h) on trigger gun. | ■ |
| Trigger guns | | | | | | | | | |
| High end high-pressure trigger gun | 4 | 4.775-823.0 | | | | | | | □ |
| Quick connect | | | | | | | | | |
| Quick coupling | 5 | 6.401-458.0 | | | | | | For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female. | □ |
| Plug nipple | 6 | 6.401-459.0 | | | | | | Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male. | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.



| | | Order Number | Max. working pressure | Length | | | Price | Description | |
|--|----|--------------|-----------------------|---------|--|--|-------|--|---|
| Rotating spray lances | | | | | | | | | |
| 1050 mm lance, rotatable, ergonomic | 1 | 4.760-660.0 | 300 bar | 1050 mm | | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ▲ |
| Rotatable lance, 600 mm, ergonomic | 2 | 4.760-664.0 | 300 bar | 600 mm | | | | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 850 mm, rotatable, ergonomic | 3 | 4.760-663.0 | 300 bar | 840 mm | | | | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 1550 mm, rotatable, ergonomic | 4 | 4.760-661.0 | 300 bar | 1550 mm | | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 2050 mm, rotatable, ergonomic | 5 | 4.760-662.0 | 300 bar | 2050 mm | | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Spray lance | | | | | | | | | |
| Lance 250 mm, non-rotatable | 6 | 4.760-667.0 | | 250 mm | | | | 250 mm stainless steel lance. With manual coupling. Non-rotatable. | □ |
| Anti-vibration lance | 7 | 6.415-951.0 | 250 bar | 950 mm | | | | The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster. | □ |
| Adapter for variable pressure spray lance | | | | | | | | | |
| Adapter for variable pressure lance | 8 | 4.762-075.0 | | | | | | For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5 | □ |
| Angular spray lance | | | | | | | | | |
| WC and gutter lance | 9 | 4.760-073.0 | | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | □ |
| Flexible spray lance | | | | | | | | | |
| Flexible lance 1050 mm | 10 | 6.394-654.0 | 210 bar | 1050 mm | | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | □ |
| Articulated joint M18x1,5 | 11 | 4.481-039.0 | 300 bar | | | | | | □ |
| Telescopic spray lance | | | | | | | | | |
| Telescopic jet pipe | 12 | 6.394-690.0 | 225 bar | 5400 mm | | | | | □ |
| Restraint belt for telescopic jet pipe | 13 | 6.373-987.0 | | | | | | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. | □ |
| Gutter cleaner | | | | | | | | | |
| Gutter cleaning lance | 14 | 2.642-305.0 | | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | □ |
| Undercarriage spray lance | | | | | | | | | |
| Underbody lance | 15 | 4.760-245.0 | | 700 mm | | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | □ |

▲ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



1



2

| | | Order Number | | | | | Price | Description | | |
|--|---|--------------|--|--|--|--|-------|-------------|--|--------------------------|
| Crane lifting kit | | | | | | | | | | |
| Add-on kit suspension crane HDS C | 1 | 2.642-638.0 | | | | | | | | <input type="checkbox"/> |
| Flame monitoring attachment kit | | | | | | | | | | |
| ABS flame monitor for HDS C | 2 | 2.642-711.0 | | | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0

KÄRCHER



| | | Order Number | Flow rate | Nozzle size | Diame- ter | Price | Description | |
|---|----|--------------|-------------|-------------|---------------|-------|---|--------------------------|
| Hard Surface Cleaner FRV 30 | | | | | | | | |
| FRV 30 | 1 | 2.642-999.0 | | | | | With the integrated and automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately. | <input type="checkbox"/> |
| Add-on kit rubber lip | 2 | 2.642-910.0 | | | | | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | <input type="checkbox"/> |
| Add-on kit hose attachment | 3 | 2.642-528.0 | | | | | | <input type="checkbox"/> |
| Add-on kit dirt trap | 4 | 2.642-532.0 | | | | | | <input type="checkbox"/> |
| Hard surface cleaner FR 30 | | | | | | | | |
| FR 30 | 5 | 2.642-997.0 | | | 300 mm | | Up to 10 times greater area coverage compared with the conventional high pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for ergonomic handling and integrated parking position. Machine specific nozzle kit must be ordered separately. | <input type="checkbox"/> |
| Hard surface cleaner FR 30 ME | | | | | | | | |
| FR 30 ME surface cleaner | 6 | 2.111-013.0 | | | 300 mm | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | <input type="checkbox"/> |
| | 7 | 2.640-355.0 | | | 300 mm | | | <input type="checkbox"/> |
| Machine-specific nozzle kit for FR | | | | | | | | |
| Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h | 8 | 2.640-401.0 | 500-650 l/h | | | | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h). | <input type="checkbox"/> |
| Machine-specific nozzle kits for FRV | | | | | | | | |
| Nozzle kit 035 for FRV 30 | 9 | 2.642-430.0 | | 35 | | | | <input type="checkbox"/> |
| Hard surface cleaner FRV 30 Me | | | | | | | | |
| FRV 30 ME | 10 | 2.642-911.0 | | | | | Surface cleaner with integrated waste water pick-up | <input type="checkbox"/> |
| Suction hose FRV 30 me | 11 | 4.441-040.0 | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



21



22-23

| | | Order Number | | | | | | Price | Description | |
|---|----|---------------------|--|--|--|--|--|--------------|---|--------------------------|
| Machine-specific nozzle kit with order no. 3.637-170.0 HD 500-700 l/h | 21 | 4.769-046.0 | | | | | | | For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union | <input type="checkbox"/> |
| Nozzle insert with order no. 3.637-001 | | | | | | | | | | |
| Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h. | 22 | 4.769-003.0 | | | | | | | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h. | <input type="checkbox"/> |
| Low pressure for units rated up to 1100 l/h | 23 | 4.769-001.0 | | | | | | | For low pressure with machines up to 1.100 l/h | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Nozzle size | | | | | Price | Description | |
|--------------------------------------|---|--------------|-------------|--|--|--|--|-------|---|--------------------------|
| HP nozzle spray angle 0° | | | | | | | | | | |
| High-pressure nozzle spray angle 0° | 1 | 2.884-533.0 | 40 | | | | | | High-pressure nozzle with powerful jet for extremely stubborn dirt. | <input type="checkbox"/> |
| Power nozzle spray angle 15° | | | | | | | | | | |
| Power nozzle 15036 - nur fuer Ersatz | 2 | 2.885-225.0 | 36 | | | | | | | <input type="checkbox"/> |
| Power nozzle spray angle 25° | | | | | | | | | | |
| | 3 | 2.884-521.0 | 250 | | | | | | | <input type="checkbox"/> |
| Power nozzle spray angle 40° | | | | | | | | | | |
| Power nozzle spray angle 40° | 4 | 2.884-522.0 | 40 | | | | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Nozzle size | | | | | Price | Description | |
|---|---|--------------|-------------|--|--|--|--|-------|--|--------------------------|
| Wet blasting attachment (without nozzle) | | | | | | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.762-010.0 | | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. | <input type="checkbox"/> |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.762-022.0 | | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. | <input type="checkbox"/> |
| Nozzle pack for wet blasting attachment | | | | | | | | | | |
| Nozzle kit for wet blasting attachment 040 | 3 | 2.637-900.0 | 40 | | | | | | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022. | <input type="checkbox"/> |
| Boron carbide nozzle | | | | | | | | | | |
| Boron carbide nozzle, for machines as of 1000 l/h | 4 | 6.415-084.0 | 6 mm | | | | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Max. working pressure | Nozzle size | Diame-ter | | Price | Description | |
|---|----|--------------|-----------------------|-------------|-----------|--|-------|--|---|
| Pipe cleaning hose, ID 6 | | | | | | | | | |
| Pipe cleaning hose | 1 | 6.390-028.0 | 120 bar | | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). <input type="checkbox"/> | |
| Pipe cleaning hose, DN 6, 30 m | 2 | 6.390-029.0 | 120 bar | | | | | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). <input type="checkbox"/> | |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 3 | 6.390-030.0 | 250 bar | | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). <input type="checkbox"/> | |
| Pipe cleaning nozzle | | | | | | | | | |
| Dirt blaster pipe cleaning D21/040 | 4 | 4.765-001.0 | | 40 | 21 mm | | | <input type="checkbox"/> | |
| Dirt blaster pipe cleaning D30/040 | 5 | 4.765-004.0 | | 40 | 30 mm | | | <input type="checkbox"/> | |
| Pipe cleaning nozzle | 6 | 5.763-015.0 | | 55 | 16 mm | | | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. <input type="checkbox"/> | |
| | 7 | 5.763-016.0 | | 60 | 16 mm | | | | <input type="checkbox"/> |
| | 8 | 5.763-017.0 | | 50 | 30 mm | | | | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. <input type="checkbox"/> |
| Rotating pipe cleaning nozzle | 9 | 6.415-428.0 | | 50 | 16 mm | | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. <input type="checkbox"/> | |
| Drain cleaning dirt blaster D 25/040 | 10 | 6.415-944.0 | | 40 | 25 mm | | | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. <input type="checkbox"/> | |
| Drain cleaning dirt blaster D 30/040 | 11 | 6.415-946.0 | | 40 | 30 mm | | | | <input type="checkbox"/> |
| Drain cleaning dirt blaster D 35/040 | 12 | 6.415-948.0 | | 40 | 35 mm | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Max. working pressure | Nozzle size | | | Price | Description | |
|----------------------------|---|--------------|-----------------------|-------------|--|--|-------|---|--------------------------|
| Dirt Blaster, small | | | | | | | | | |
| Dirt blaster | 1 | 4.767-023.0 | 180 bar | 40 | | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C. | <input type="checkbox"/> |
| Dirt blaster, large | | | | | | | | | |
| Dirt blaster 04 | 2 | 4.763-252.0 | 300 bar | 40 | | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Flow rate | | | | Price | Description | |
|---|---|--------------|-------------|--|--|--|-------|--|--------------------------|
| Cup foam lance | | | | | | | | | |
| Cup foam lance | 1 | 6.394-668.0 | 1200 l/h | | | | | Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design. | <input type="checkbox"/> |
| Tank 1L | 2 | 6.414-954.0 | | | | | | | <input type="checkbox"/> |
| Inno Foam Set | | | | | | | | | |
| Inno foam kit with detergent injector | 3 | 2.640-151.0 | | | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | <input type="checkbox"/> |
| Inno foam kit | 4 | 2.640-692.0 | | | | | | | <input type="checkbox"/> |
| Easy Foam Set | | | | | | | | | |
| Easy Foam Set with RM injector | 5 | 2.640-691.0 | | | | | | HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | <input type="checkbox"/> |
| Easy foam set | 6 | 2.640-693.0 | | | | | | | <input type="checkbox"/> |
| Nozzle kits for Inno/Easy Foam Set | | | | | | | | | |
| Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h | 7 | 2.640-870.0 | 500-600 l/h | | | | | Optimal adaptation to different machine outputs for economic use. | <input type="checkbox"/> |
| Foam nozzle mounting kit | | | | | | | | | |
| Foam nozzle kit | 8 | 2.637-926.0 | | | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Length | | | | Price | Description | |
|---|----|--------------|--------|--|--|--|-------|--|--------------------------|
| Hose reel add-on kit | | | | | | | | | |
| Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C | 1 | 2.642-756.0 | 20 m | | | | | | <input type="checkbox"/> |
| Automatic, self-winding hose reels | | | | | | | | | |
| Swivel holder | 2 | 2.639-931.0 | | | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel. | <input type="checkbox"/> |
| ABS wall fastening stainless steel | 3 | 2.641-867.0 | | | | | | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. | <input type="checkbox"/> |
| Add-on kit hose reel plastics | 4 | 6.392-975.0 | 20 m | | | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | <input type="checkbox"/> |
| Add-on kit hose reel | 5 | 6.392-965.0 | 20 m | | | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, painted | 6 | 2.639-919.0 | 20 m | | | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, stainless steel | 7 | 6.391-421.0 | 20 m | | | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| ABS hose reel stainless steel | 8 | 2.641-866.0 | 20 m | | | | | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple. | <input type="checkbox"/> |
| Anbausatz Schlauchtrommel automatik | | | | | | | | | |
| Add-on kit automatic hose reel HDS-C | 9 | 2.643-052.0 | | | | | | | <input type="checkbox"/> |
| Add-on kit hose reel | 10 | 2.643-181.0 | | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0

KÄRCHER



| | | Order Number | Length | Diameter | | Price | Description | |
|--------------------------------------|----|--------------|--------|----------|--|-------|--|--------------------------|
| Other HP Accessories | | | | | | | | |
| Starting current limiter | 1 | 2.637-495.0 | | | | | Reduces starting current in single-phase supply and protects line fuse. | <input type="checkbox"/> |
| Geka coupling | | | | | | | | |
| With hose nozzle, R 1/2" | 2 | 6.388-461.0 | | | | | with hose liner | <input type="checkbox"/> |
| With hose nozzle, R 3/4" | 3 | 6.388-455.0 | | | | | | <input type="checkbox"/> |
| With hose nozzle, R 1" | 4 | 6.388-465.0 | | | | | | <input type="checkbox"/> |
| Hose coupling | 5 | 6.388-458.0 | | | | | with female thread | <input type="checkbox"/> |
| Suction filter | | | | | | | | |
| Water filter | 6 | 6.414-956.0 | | | | | | <input type="checkbox"/> |
| Suction filter with check valve | 7 | 4.730-012.0 | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | <input type="checkbox"/> |
| Fine-mesh water filter | | | | | | | | |
| Fine-mesh water filter with adapter | 8 | 4.730-102.0 | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | <input type="checkbox"/> |
| Fine-mesh water filter, 100 µm, R 1" | 9 | 2.638-270.0 | | | | | Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1". | <input type="checkbox"/> |
| Water supply hose | | | | | | | | |
| Water supply hose | 10 | 4.440-038.0 | 7,5 m | | | | NW 13 R1" / R 3/4", up to 30 °C | <input type="checkbox"/> |
| | 11 | 4.440-207.0 | 7,5 m | | | | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | <input type="checkbox"/> |
| | 12 | 4.440-270.0 | 7,5 m | | | | NW 19 R1" / R1", up to 85 °C | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 6/12 C

1.169-219.0



| | | Order Number | Flow rate | | | | Price | Description | |
|--------------------------------|---|--------------|-------------|--|--|--|-------|---|--------------------------|
| Push-on washing brush | | | | | | | | | |
| Push-on wash brush, M 18 x 1.5 | 1 | 4.762-016.0 | | | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6. | <input type="checkbox"/> |
| Rotating washing brush | | | | | | | | | |
| | 2 | 4.762-561.0 | 500-800 l/h | | | | | | <input type="checkbox"/> |
| | 3 | 4.762-560.0 | 500-800 l/h | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.