### **HDS 6/12 C**

Compact hot water high pressure cleaner with ecolefficiency mode and steam function













#### Order no.

1.169-904.0

- Economical eco!efficiency mode
- Intuitive single-button selector switch
- Extensive range of standard equipment

| _                                       |             |                    |
|---|-------------|--------------------|
| Technical data                          |             |                    |
| EAN code                                |             | 4054278167206      |
| Current type                            | Ph / V / Hz | 1 / 240 / 50       |
| Flow Rate                               | l/h         | 240 - 560          |
| Operating pressure                      | bar / MPa   | 30 - 120 / 3 - 12  |
| Temperature (supply 12°C)               | °C          | min. 80 - max. 155 |
| Power rating                            | kW          | 3                  |
| Consumption fuel oil                    | kg/h        | 3.5                |
| Heating oil consumption, ecolefficiency | kg/h        | 2.8                |
| Power cable                             | m           | 5                  |
| Fuel tank                               | I           | 15                 |
| Weight (with accessories)               | kg          | 107.4              |
| Weight incl. packaging                  | kg          | 115.6              |
| Dimensions (L × W × H)                  | mm          | 1060 × 650 × 920   |

Users must receive training on this device.

| Equipment                        |    |                     |
|----------------------------------|----|---------------------|
| Trigger gun                      |    | EASY!Force Advanced |
| High-pressure hose length        | m  | 10                  |
| High-pressure hose specification |    | DN 6, 250 bar       |
| Spray lance                      | mm | 1050                |
| Power nozzle                     |    |                     |
| SDS system                       |    | •                   |
| Pressure switch control          |    | •                   |
| Integral fuel and detergent tank |    | •                   |
| Included in delivery.            |    |                     |





#### Efficiency

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.
- Precise detergent dosing unit with rinse function.



#### Ease of use

- Intuitive operation thanks to the large single-button selector switch.
- Large tank opening with filling chute.
- System care bottle can be changed conveniently from the outside.



#### Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cable and high-pressure hose
- Integrated lance holder for transport.



























| 14 |
|----|

|   |    | Order no.   | Description  |  |
|---|----|-------------|--|--|
| TRIGGER GUNS  |    |             |  |  |
| Trigger guns  |    |             |  |  |
| EASY!Force Advanced                                   | 1  | 4.118-005.0 | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.                                |  |
| EASY!Force conversion kit 1 - from high-pressure hose | 2  | 4.111-050.0 | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. |  |
| EASY!Force conversion kit 2 - from machine            | 3  | 4.111-051.0 | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.      |  |
| EASY!Force conversion kit 3 - high-pressure gun       | 4  | 4.111-052.0 | Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.          |  |
| Servo Control   |    |             |  |  |
| Servo Control, < 750 l/h                              | 5  | 4.118-007.0 | Servo control for water flow and pressure control (< 750 l/h) on trigger gun.  |  |
| SPRAY LANCES  |    | '           |  |  |
| Rotating spray lances                                 |    |             |  |  |
| Spray lance, 1050 mm, rotatable                       | 6  | 4.112-000.0 | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |  |
| LED nozzle light                                      | 7  | 2.680-002.0 | Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.                    |  |
| Spray lance, 250 mm, rotatable                        | 8  | 4.112-027.0 | Spray lance, 250 mm, rotatable, ergonomic  |  |
| Spray lance, 400 mm, rotatable                        | 9  | 4.112-024.0 | Spray lance, 400 mm, rotatable, ergonomic  |  |
| Spray lance, 600 mm, rotatable                        | 10 | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |  |
| Spray lance, 840 mm, rotatable                        | 11 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |  |
| Spray lance, 1550 mm, rotatable                       | 12 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |  |
| Spray lance, 2050 mm, rotatable                       | 13 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |  |
| Spray lance extender, 1000 mm                         | 14 | 4.112-048.0 | Spray lance extension with EASY!Lock connection. Length 1000 mm.   |  |

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.























|   |     | Order no.   | Description   | 1   |
|---|-----|-------------|---|-----|
| SPRAY LANCES  |     |             |   |     |
| Double lance  | 1 . | 1           |   | ۲.  |
| Double lance, 960 mm                                    | 15  | 2.112-016.0 | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).   | [   |
| Angular spray lance                                     |     |             |   | l,  |
| WC and gutter lance                                     | 16  | 4.112-029.0 | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.  | [   |
| Flexible spray lance                                    |     |             |   |     |
| Flexible lance, 1050 mm                                 | 17  | 4.112-035.0 | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.  | [   |
| High pressure articulated joint                         | 18  | 4.112-057.0 | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.   | [   |
| Gutter cleaner  |     |             |   |     |
| Gutter cleaning lance                                   | 19  | 2.112-015.0 | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.   | 1 [ |
| Undercarriage spray lance                               |     | •           |   | Ė   |
| Underbody lance   | 20  | 4.112-032.0 | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.   |     |
| Additional handle                                       |     |             |   |     |
| Additional handle for EASY!Lock spray lances            | 21  | 4.321-380.0 | Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. | [   |
| KÄRCHER POWER NOZZLE                                    |     |             |   | Ė   |
| Power nozzle spray angle 25°                            |     |             |   |     |
| Power nozzle , 042                                      | 22  | 2.113-007.0 | Fan jet nozzle for large-area coverage and stubborn dirt and stains.  | 1   |
| HP nozzle spray angle 0°                                | l   |             |   | Ė   |
| Power nozzle 0°, 045                                    | 23  | 2.113-033.0 | High-pressure nozzle with powerful jet for extremely stubborn dirt.   | [   |
| Power nozzle spray angle 15°                            |     | I.          |   | İ   |
| Power nozzle 15°, 045                                   | 24  | 2.113-046.0 | Fan jet nozzle with 15° spray angle suitable for stubborn dirt.   | [   |
| Power nozzle spray angle 40°                            |     | I.          |   | İ   |
| Power Nozzle 40°, 045                                   | 25  | 2.113-053.0 | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.   | [   |
| HIGH-PRESSURE HOSES                                     |     |             |   | Ė   |
| Standard with unions on both sides                      |     |             |   |     |
| High-pressure hose, 10 m, ID 6, 250 bar, 2 × EASY!Lock  | 26  | 6.110-035.0 | 10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $6/155^{\circ}$ C/250 bar.                                  |     |
| High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock | 27  | 6.110-041.0 |   | [   |
| High-pressure hose, 10 m, ID 6, 250 bar, 2 × EASY!Lock  | 28  | 6.110-034.0 | 10 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.  |     |

<sup>■</sup> Included in delivery. 

□ Available accessories.



















|   |    |             |   | _ |
|---|----|-------------|---|---|
|   |    |             |   |   |
|   |    | Order no.   | Description   |   |
| HIGH-PRESSURE HOSES   |    |             |   |   |
| Standard with unions on both sides  |    |             |   |   |
| High-pressure hose, 10 m, ID 6, 300 bar, 2 × EASY!Lock  | 29 | 6.110-056.0 | With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M $22 \times 1.5$ with anti-kink protection. NW $6/155^{\circ}$ C/300 bar                           |   |
| High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock  | 30 | 6.110-031.0 | 10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating TR22 trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.     |   |
| High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock  | 31 | 6.110-030.0 | 15 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.      |   |
| High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock  | 32 | 6.110-032.0 | 20 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.      |   |
| High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock  | 33 | 6.110-014.0 | With rotary coupling, 2 × M 22 × 1.5  |   |
| High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock   | 34 | 6.110-042.0 | 15 m high-pressure hose M 22 $\times$ 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155 $^{\circ}$ C/220 bar.  |   |
| High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock   | 35 | 6.110-043.0 | with union on both sides, M 22 $\times$ 1.5 with anti-kink protection. NW 10/155 $^{\circ}$ C/220 bar   |   |
| High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock   | 36 | 6.110-044.0 |   |   |
| High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock   | 37 | 6.110-045.0 |   |   |
| High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock   | 38 | 6.110-059.0 | High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. $2x M 22 \times 1.5$ with anti-kink protection.  |   |
| High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock   | 39 | 6.110-060.0 |   |   |
| Longlife 400 with unions on both sides  |    |             |   |   |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 $\times$ EASY!Lock                           | 40 | 6.110-024.0 | 1.5 m high-pressure hose (DN 8, M $22 \times 1.5$ ) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M $22 \times 1.5$ ).       |   |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, $1 \times EASY!Lock / 1 \times M22 \times 1.5$ | 41 | 6.110-069.0 | High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection. |   |
| High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock                                   | 42 | 6.110-038.0 | Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANT!!Twist. Approved for 400 bar pressure.              |   |

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.

























|   |        | Order no.   | Description  |   |
|---|--------|-------------|--|---|
| HIGH-PRESSURE HOSES   |        |             |  | ľ |
| Longlife 400 with unions on both sides  |        |             |  |   |
| High-pressure hose Longlife, 30 m, ID 8, 400<br>bar, 2 × EASY!Lock            | 43     | 6.110-023.0 | With rotary coupling, $2 \times M$ $22 \times 1.5$   |   |
| High-pressure hose Longlife, 20 m, ID 8, 400<br>bar, 2 × EASY!Lock            | 44     | 6.110-027.0 | with rotary coupling, 2 $\times$ M 22 $\times$ 1.5   |   |
| High-pressure hose Longlife, 15 m, ID 8, 400<br>bar, 2 × EASY!Lock            | 45     | 6.110-029.0 | With rotary coupling, 2 × M 22 × 1.5   |   |
| Food industry version with unions on both side                                | es     | <u> </u>    |  | Ī |
| High-pressure hose food grade, 15 m, ID 6,<br>250 bar, 2 × EASY!Lock          | 46     | 6.110-063.0 | 15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector.<br>Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.   |   |
| High-pressure hose food grade, 10 m, ID 8,<br>250 bar, 2 × EASY!Lock          | 47     | 6.110-051.0 | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M $22 \times 1.5$ with anti-kink sleeve.                           |   |
| High-pressure hose food grade, 20 m, ID 8,<br>250 bar, 2 × EASY!Lock          | 48     | 6.110-052.0 | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M $22 \times 1.5$ , with kink protection. NW $8/155^{\circ}$ C/250 bar. |   |
| Longlife food industry version with unions on                                 | both s | ides        |  |   |
| High-pressure hose food grade Longlife, 10 m,<br>ID 8, 400 bar, 2 × EASY!Lock | 49     | 6.110-053.0 | With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.                                       |   |
| High-pressure hose food grade Longlife, 20 m,<br>ID 8, 400 bar, 2 × EASY!Lock | 50     | 6.110-054.0 | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)                                    |   |
| WEED CONTROL  |        | '           |  | ľ |
| WR 50   | 51     | 2.114-013.0 | In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter                          |   |
| WR 20   | 52     | 2.114-014.0 | For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.   |   |
| WR 100  | 53     | 2.114-015.0 | Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.   |   |
| WR 10   | 54     | 2.114-016.0 | In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.  |   |
| QUICK CONNECT   |        |             |  | Ċ |
| Quick-fitting pipe union coupler trapezo                                      | 55     | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.                                    |   |
| Quick-fitting pipe union plug nipple tra                                      | 56     | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 × 1.5 external thread.  |   |

 $<sup>\</sup>hfill \square$  Available accessories.



















|  | 1     |             |   | _  |
|--|-------|-------------|---|----|
|  |       |             |   |    |
|  |       | Order no.   | Description   | _  |
| DRUM AND TANK CLEANING                   |       |             |   | 4  |
| Add-on kit mud sucker                    | 57    | 2.641-798.0 |   |    |
| OTHER HP ACCESSORIES                     |       |             |   | L  |
| Jet gun                                  | 58    | 2.869-067.0 | Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.                     | ı  |
| FLUE PIPE                                |       |             |   |    |
| Flue gas adapter                         | 59    | 4.656-149.0 | Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for  |    |
|  | 60    | 4.656-080.0 | connection to a stack system).  | Ī  |
| DICHTUNGEN FÜR TR-GEWINDE                |       |             |   | Ė  |
| Spare part set seals TR                  | 61    | 2.880-001.0 |   |    |
| ROTARY NOZZLES (DIRT BLASTERS)           |       |             |   | Ė  |
| Dirt blaster, large                      |       |             |   |    |
| Dirt blaster, large, 050                 | 62    | 4.114-027.0 | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzl and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.                  | le |
| MULTIPLE-JET NOZZLES                     |       |             |   |    |
| Angle vario nozzle 0°-90°                |       |             |   |    |
| Angled Vario nozzle, 050                 | 63    | 4.113-007.0 | Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.  | of |
| STEAM NOZZLE / NOZZLE PROTECTOR / ROLLO  | VER N | IOZZLE      |   |    |
| Steam nozzle                             |       |             |   |    |
| Steam jet nozzle 50°                     | 64    | 4.116-000.0 | Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.   |    |
| Steam jet nozzle 40°, 040                | 65    | 2.114-000.0 | Brass steam nozzle for operation of the HDS in steam stage.   | -  |
| Rollover nozzle holder                   |       |             |   |    |
| Ball Nozzle Holder                       | 66    | 4.764-012.0 | Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle). |    |
| NOZZLE UNION / SPACER                    |       |             |   |    |
| Nozzle union                             |       |             |   |    |
| Nozzle screws                            | 67    | 4.112-011.0 | Nozzle screws with protectors for high-pressure and power nozzles   | [  |
| PIPE CLEANING                            |       | <u> </u>    |   | Ť  |
| Pipe cleaning hose, ID 6                 |       |             |   |    |
| Hose assembly TR pipe cleaning DN6 max.2 | 68    | 6.110-046.0 | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  |    |
| Pipe cleaning hose, DN 6, 20 m, 220 bar  | 69    | 6.110-008.0 | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).  |    |
| Hose assembly TR pipe cleaning DN6 max.2 | 70    | 6.110-047.0 | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  | 1  |

<sup>☐</sup> Available accessories.



























|  |    |             |  | $\neg$ |
|--|----|-------------|--|--------|
|  |    |             |  |        |
|  |    | Order no.   | Description  |        |
| PIPE CLEANING                          |    |             |  |        |
| Pipe cleaning nozzle                   |    |             |  |        |
| Dirt blaster pipe cleaning D21/040     | 71 | 4.765-001.0 | 0,111  |        |
| Dirt blaster pipe cleaning D30/040     | 72 | 4.765-004.0 | jets ensure the necessary forward movement, as well as convenient handling.  |        |
| Nozzle pipe cleaning size 120          | 73 | 5.763-089.0 | Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.   |        |
| Pipe cleaning nozzle                   | 74 | 5.763-015.0 | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for  |        |
|  | 75 | 5.763-016.0 | environmentally-friendly cleaning of blocked drains and pipes.   |        |
|  | 76 | 5.763-017.0 | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.   |        |
| Rotating pipe cleaning nozzle          | 77 | 6.415-428.0 | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.   |        |
| FLOOR AND HARD SURFACE CLEANER         |    | <u>'</u>    |  |        |
| Hard Surface Cleaner FRV 30            |    |             |  |        |
| Add-on kit hose attachment             | 78 | 2.642-528.0 | Suction cup for fixing the suction hose to smooth surfaces.  |        |
| Add-on kit dirt trap                   | 79 | 2.642-532.0 | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.   |        |
| Hard surface cleaner FR 30 ME          | •  |             |  |        |
| FR 30 ME surface cleaner               | 80 | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.             |        |
| Machine-specific nozzle kit for FR     |    |             |  |        |
| Nozzle kit for FR, 500 l/h - 650 l/h   | 81 | 2.640-401.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).   |        |
| Machine-specific nozzle kits for FRV   |    |             |  |        |
| Nozzle kit for FRV, 045                | 82 | 2.642-432.0 | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.  |        |
| Hard surface cleaner FRV 30 Me         |    |             |  |        |
| FRV 30 Me Surface Cleaner              | 83 | 2.111-012.0 | Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. |        |
| Extension hose FRV 30 Me and FRV 50 Me | 84 | 4.441-040.0 | 5 m extension hose for FRV 30 Me. Includes connecting adapter.   |        |
| Available assessaries                  |    | 1           |  |        |

<sup>☐</sup> Available accessories.

# **EQUIPMENT FOR HDS 6/12 C** 1.169-904.0

























|  |    |             |   | _ |
|--|----|-------------|---|---|
|  |    |             |   |   |
|  |    | Order no.   | Description   |   |
| FOAM SYSTEMS   |    |             |   |   |
| Cup foam lance   |    |             |   |   |
| Cup foam lance Advanced 1, 400 l/h - 600 l/h                   | 85 | 4.112-063.0 |   |   |
| Cup foam lance Advanced 3, 900 l/h - 2500 l/h                  | 86 | 4.112-065.0 |   |   |
| Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h               | 87 | 4.112-067.0 |   |   |
| Cup foam lance DUO Advanced 3, 900<br>l/h - 2500 l/h           | 88 | 4.112-069.0 |   |   |
| Cup foam lance Basic 1, 350 l/h - 600 l/h                      | 89 | 4.112-053.0 | For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent. |   |
| 1-litre cleaning agent container for cup foam lance basic      | 90 | 5.071-414.0 |   |   |
| 1-litre cleaning agent container for cup foam lance advanced   | 91 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).   |   |
| Inno Foam Set  |    |             |   |   |
| Inno foam kit with detergent injector                          | 92 | 2.112-000.0 |   |   |
| Inno foam kit  | 93 | 2.112-008.0 | use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.  |   |
| Easy Foam Set  |    |             |   |   |
| Easy Foam Set with RM injector                                 | 94 | 2.112-010.0 | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for  |   |
| Easy foam set  | 95 | 2.112-011.0 | connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.  |   |
| Nozzle kits for Inno/Easy Foam Set                             |    |             |   |   |
| Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h                 | 96 | 2.111-018.0 | Optimal adaptation to different machine outputs for economic use.   |   |
| Foam nozzle mounting kit                                       |    |             |   |   |
| Foam nozzle kit  | 97 | 2.112-013.0 | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.  |   |
| MIXERS AND INJECTORS   |    |             |   |   |
| HP detergent injector  |    |             |   |   |
| Detergent injector for high and low pressure (without nozzles) | 98 | 4.637-032.0 | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.  |   |
|  |    |             | · · · · · · · · · · · · · · · · · · ·   |   |

☐ Available accessories.

### KÄRCHER



























|   |          | Order no.   | Description   |     |
|---|----------|-------------|---|-----|
| MIXERS AND INJECTORS  | <u> </u> |             |   | Ė   |
| HP detergent injector   |          |             |   | П   |
| Detergent injector for high pressure  | 99       | 4.637-033.0 | Cleaning agent dosage at high pressure 3 – 5 %  |     |
| Machine-specific nozzle kit with order no. 3.6                                    | 37-170   | )           |   | Ė   |
| Nozzle insert trapezoidal thread HDS-GER  | 100      | 4.769-009.0 | For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union  |     |
| Nozzle insert with order no. 3.637-001  |          |             |   | Ė   |
| Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h. | 101      | 4.769-003.0 | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.   |     |
| Low pressure for units rated up to 1100 l/h                                       | 102      | 4.769-001.0 | For low pressure with machines up to 1.100 l/h  |     |
| COUPLING PARTS  |          |             |   |     |
| Rotary coupling   |          |             |   |     |
| Rotary coupling   | 103      | 4.111-021.0 | Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use.<br>Connector Easy!Lock. With grip protection.   |     |
| Connector   |          |             |   |     |
| Nozzle connector/screw connector  | 104      | 4.111-022.0 | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1x M 22 \times 1.5$ and $1x M 18 \times 1.5$ . |     |
| Y distributor   | 105      | 4.111-024.0 | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.  |     |
| Short spray unit  | 106      | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.   | ( E |
| Adapter EASY!Lock   |          | •           |   |     |
| Adapter 1 M22AG-TR22AG  | 107      | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose   |     |
| Adapter 2 M22IG-TR22AG  | 108      | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose   | Г   |
| Adapter 3 M22IG-TR22AG  | 109      | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator   | Г   |
| Adapter M22 - Swivel  | 110      | 4.111-032.0 | M22 $	imes$ 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.                   |     |
| Adapter 5 TR22IG-M22AG  | 111      | 4.111-033.0 | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance  |     |
| Adapter 6 TR22IG-M22AG  | 112      | 4.111-034.0 | Adapter 6 to connect the new device with the old hose and the old hose with the new gun   | Е   |

<sup>☐</sup> Available accessories.

### **EQUIPMENT FOR HDS 6/12 C** 1.169-904.0



























|  |     | Order no.   | Description   |     |
|--|-----|-------------|---|-----|
| COUPLING PARTS   |     |             |   | Ť   |
| Adapter EASY!Lock  |     |             |   |     |
| Adapter 7 M18IG-TR20AG   | 113 | 4.111-035.0 | Adapter 7 to connect the old spray lance with the new nozzle  |     |
| Adapter 8 TR20IG-M18AG   | 114 | 4.111-036.0 | Adapter 8 to connect the new spray lance with the old nozzle  | [   |
| Coupler -2xM22x1,5   | 115 | 4.111-037.0 | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$ .  | [   |
| ADAPTER for replacement TR22IG-M22AG Er  | 116 | 4.111-046.0 | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection  | [   |
| HOSE REELS   |     |             |   |     |
| Hose reel add-on kit   |     |             |   |     |
| Hose reel attachment kit for HDS compact class, 20 m                               | 117 | 2.110-010.0 | Hose reel attachment kit for installation on the machine. For secure and space-saving storage of th high-pressure hoses (with a connection hose for the machine high-pressure outlet).  | e [ |
| Automatic, self-winding hose reels   |     |             |   |     |
| Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$ | 118 | 2.639-257.0 |   |     |
| Automatic hose reel, powder-coated steel / plastic, 20 m                           | 119 | 6.392-074.0 | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.   |     |
| Automatic stainless steel / synthetic material hose drum, 20 m                     | 120 | 6.392-083.0 | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.  |     |
| Automatic hose reel, coated, 20 m  | 121 | 6.392-106.0 | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.  | . [ |
| Hose reel, automatic, basalt grey-coated, 20 m                                     | 122 | 6.392-105.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.  |     |
| Automatic hose reel, stainless steel, includes swivel holder, 20 m                 | 123 | 6.392-076.0 | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.  |     |
| Automatic stainless steel hose reel, 40 m  | 124 | 6.392-442.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). |     |
| Powder-coated swivel holder  | 125 | 2.639-931.0 | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.   |     |
| Stainless steel swivel holder  | 126 | 2.641-867.0 | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility  | [   |

and convenience possible when working with the HP hose.

 $<sup>\</sup>hfill \square$  Available accessories.

### **KÄRCHER**



























|   |     | Order no.   | Description  |     |
|---|-----|-------------|--|-----|
| HOSE REELS                                      |     |             |  |     |
| Anbausatz Schlauchtrommel automatik             |     |             |  |     |
| Attachment kit automatic hose reel HDS C        | 127 | 2.110-012.0 | Complete automatic hose reel attachment kit for HDS compact class. Offers maximum convenience when winding and unwinding the HP hose. Contains: Automatic hose reel, HP hose and all connection parts. |     |
| Attachment kit automatic hose reel holder HDS C | 128 | 2.110-013.0 | Holder includes connection material for installing an automatic hose reel to machines from the HDS compact class.  | ; 🗆 |
| FACADE AND SOLAR PANEL CLEANING                 |     |             |  |     |
| Brushes   |     |             |  |     |
| Drive for roller brush 500                      | 129 | 4.762-584.0 | Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.          |     |
| Splash guard for roller brush 500               | 130 | 4.762-621.0 | Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.                                   |     |
| Roller brush 500 soft                           | 131 | 4.762-623.0 | Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.                        |     |
| Roller brush 500 medium                         | 132 | 4.762-624.0 | Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.   |     |
| Roller brush 500 hard                           | 133 | 4.762-625.0 | Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.   |     |
| Brush hard                                      | 134 | 6.960-133.0 | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.                    |     |
| Brush medium                                    | 135 | 6.960-134.0 | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.           |     |
| Brush soft                                      | 136 | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.                    |     |
| Telescopic                                      |     |             |  |     |
| TL low pressure adapter                         | 137 | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.   |     |
| Telescopic lance TL 7 F                         | 138 | 4.762-609.0 | Telescopic lance TL $7  \text{F}$ with up to $7  \text{m}$ reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.             |     |
| Telescopic lance TL 7 H                         | 139 | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.                                    | . 🗆 |
| Telescopic lance TL 10 H                        | 140 | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.          |     |

 $<sup>\</sup>hfill \square$  Available accessories.





















|   |     | Order no.   | Description   | L   |
|---|-----|-------------|---|-----|
| FACADE AND SOLAR PANEL CLEANING                                     |     |             |   |     |
| Telescopic  | ,   |             |   | Ļ   |
| Telescopic lance TL 10 C  | 141 | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.                                      |     |
| Telescopic lance TL 14 C  | 142 | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre.<br>Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.                    |     |
| TL high pressure adapter  | 143 | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.                        |     |
| WET BLASTING ATTACHMENT   |     |             |   |     |
| Wet blasting attachment (without nozzle)                            |     |             |   |     |
| Wet blasting attachment with flow control (without nozzles)         | 144 | 4.115-000.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.   |     |
| Wet blasting attachment without flow control (nozzles not included) | 145 | 4.115-006.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.                                     |     |
| Nozzle pack for wet blasting attachment                             |     | ,           |   |     |
| Nozzle pack TR wet jet set 0045                                     | 146 | 2.112-022.0 | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0   4.115-006.0. |     |
| Boron carbide nozzle  |     | '           |   |     |
| Boron carbide nozzle, for machines as of 100 $l/h$                  | 147 | 6.415-084.0 | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.   |     |
| DRUM AND TANK CLEANING  |     |             |   |     |
| Barrel and tank cleaning  |     |             |   |     |
| Barrel cleaner BC 14/12   | 148 | 2.112-020.0 | The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums – in particular oak barrels with a capacity between 225 and 600 liters.                                       |     |
| ADD-ON KITS   |     |             |   |     |
| Flame monitoring attachment kit                                     |     |             |   |     |
| ABS flame monitor for HDS C   | 149 | 2.642-711.0 | A light sensor monitors the burner flame. The fuel supply is shut off if the flame goes out.  |     |
| WATER CONNECTION  |     |             |   |     |
| Geka coupling   |     |             |   |     |
| With hose nozzle, R 1/2"  | 150 | 6.388-461.0 | with hose liner   |     |
| With hose nozzle, R 3/4"  | 151 | 6.388-455.0 |   |     |
| With hose nozzle, R 1"  | 152 | 6.388-465.0 | with hose barb  |     |
| Hose coupling   | 153 | 6.388-458.0 | with female thread  | [   |
| Suction filter  |     |             |   | _   |
| Water filter  | 154 | 6.414-956.0 | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh. R 3/4" and R 1" connection, without non-return valve  | ו ב |

<sup>☐</sup> Available accessories.



















|  | _   | 1           |   |     |
|--|-----|-------------|---|-----|
|  |     |             |   |     |
|  |     | Order no.   | Description   |     |
| WATER CONNECTION   |     |             |   |     |
| Suction filter   |     |             |   |     |
| Suction filter with check valve                              | 155 | 4.730-012.0 | Brass suction filter suitable for ponds, storage tanks, etc. With check valve.  |     |
| Fine-mesh water filter                                       |     | <b>'</b>    |   |     |
| Add-on kit water filter universal                            | 156 | 2.637-020.0 |   |     |
| Fine-mesh water filter with adapter                          | 157 | 4.730-102.0 | Fine-mesh water filter, 125 $\mu$ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 I/h. Connection 3/4", with adapter, 1".                             | ,   |
| Fine-mesh water filter, 100 $\mu$ m, R 1"                    | 158 | 2.638-270.0 | Fine-mesh water filter, $100 \mu m$ , max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$ . Connector 1". | 5 🗆 |
| Water supply hose  |     | •           |   |     |
| Water supply hose  | 159 | 4.440-038.0 | NW 13 R1" / R 3/4", up to 30 °C   |     |
|  | 160 | 4.440-207.0 | NW 19 R1" / R 3/4", up to 85 °C, for pick-up  |     |
| WASHING BRUSHES  |     |             |   |     |
| Push-on washing brush  |     |             |   |     |
| Push-on wash brush, M 18 × 1.5                               | 161 | 4.113-001.0 | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.   |     |
| Rotating washing brush                                       |     | '           |   |     |
| Rotating wash brush for < 800 l/h machines, nylon bristles   | 162 | 4.113-004.0 | The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to $60^{\circ}$ C. (M $18 \times 1.5$ , replaceable brush insert).  |     |
| Rotating wash brush for < 800 l/h machines, natural bristles | 163 | 4.113-003.0 | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).   |     |

<sup>☐</sup> Available accessories.