

HD 10/15-4 CAGE FOOD

Cold-water pressure washer designed for use in the food industry.













Order no.

1.353-908.0

- Grease-resistant high-pressure hose
- 2 cleaning agent tanks with rinse function
- High-pressure hose in food-industry qualitiy, grey non-marking wheels

2	Technical data		
	EAN code		4054278157924
	Current type	Ph / V / Hz	3 / 400 / 50
	Flow Rate	l/h	440 - 990
	Water feed temperature	°C	max. 85
	Operating pressure	bar / MPa	20 - 145 / 2 - 14.5
	Max. Pressure	bar / MPa	175 / 17.5
	Power rating	kW	6.4
	Weight (with accessories)	kg	78.4
	Weight incl. packaging	kg	86.8
	Dimensions (L × W × H)	mm	650 × 521 × 1100

Power nozzle Pressure switch control Enclosed tubular frame with attachment point for handling by crane	High-pressure hose	m	10 / Food industry version / DN 8,400 bar
Pressure switch control Enclosed tubular frame with attachment point for handling by Crane	Stainless steel spray lance	mm	1050
Pressure switch control Enclosed tubular frame with attachment point for handling by crane	Power nozzle		
attachment point for handling by	Pressure switch control		
Comerce Construct	attachment point for handling by		•
Servo Control	Servo Control		

This device does not require instruction.





Complies with the most rigorous hygiene requirements

- Non-corrosive stainless steel.
- All parts in contact with water are made from special food-grade brass.



Particularly effective cleaning

- Booster pump for feed temperature of up to 85°C.
- Approved for RM 734 chlorinated cleaning agent.



Hygiene requirements

- Non-marking and easy to manoeuvre.
- Food-grade, non-marking high-pressure hose.
- HD 10/15-4 Cage Food, 1.353-908.0, 2024-05-13

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



		Order no.	Description	
TRIGGER GUNS				
Trigger guns				
EASY!Force Food	1	4.118-015.0	Perfect for the food industry: the EASY!Force high-pressure gun with full ceramic valve enables fatigueless working due to virtually zero holding force for the operator.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kårcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo Control				
Servo Control, food, 750 l/h - 1100 l/h	5	4.118-016.0	Water flow and pressure control on the trigger gun. Food-grade, parts in contact with water are stainless steel.	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
LED nozzle light	7	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



				Т
		Order no.	Description	
SPRAY LANCES				
Double lance		1		
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance				
WC and gutter lance	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power Nozzle , 062	22	2.113-012.0	Fan jet nozzle for large-area coverage and stubborn dirt and stains.	
Power nozzle spray angle 15°	1			-
Power nozzle 15°, 070	23	2.113-049.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
HIGH-PRESSURE HOSES				
Longlife food industry version with unions on	both s	ides		
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	24	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	25	6.110-054.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 × EASY!Lock	26	6.110-024.0	1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).	
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	27	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22×1.5 , quick and convenient EASY!Lock hand screw connection.	
Food industry version with unions on both side	es	1	1	_
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock		6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 × 1.5 with anti-kink sleeve.	
			l	-

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0









42







		Order no.	Description			
HIGH-PRESSURE HOSES						
Food industry version with unions on both sid		1				
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	29	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 \times 1.5, with kink protection. NW 8/155°C/250 bar.			
ROTARY NOZZLES (DIRT BLASTERS)						
Dirt blaster, large						
Dirt blaster, large, 070/080	30	4.114-030.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzl and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	le 🗌		
NOZZLE UNION / SPACER						
Nozzle union						
Nozzle screws	31	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles			
PIPE CLEANING						
Pipe cleaning hose, ID 6						
Hose assembly TR pipe cleaning DN6 max.2	32	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).			
Pipe cleaning hose, DN 6, 20 m, 220 bar	33	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).			
Hose assembly TR pipe cleaning DN6 max.2	34	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).			
Pipe cleaning nozzle			·			
Pipe cleaning nozzle	35	5.763-019.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.			
Rotating pipe cleaning nozzle	36	6.415-440.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.			
FLOOR AND HARD SURFACE CLEANER						
Hard Surface Cleaner FRV 30						
FRV 30	37	2.111-010.0	Surface cleaner with integrated waste water pick-up			
Add-on kit rubber lip	38	2.642-910.0	For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.			
Extension hose 5 m	39	4.440-939.0	5m extension hose for FRV 30. Connection sleeve included.			
Add-on kit hose attachment	40	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.			
Add-on kit dirt trap	41	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.			
Hard surface cleaner FR 30 ME		1		_		
FR 30 ME surface cleaner	42	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.			

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



				_
		Order no.	Description	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FR 50				
FR 50 surface cleaner	43	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	g
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 850 l/h - 1100 l/h	44	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FRV	1			
Nozzle kit for FRV, 080	45	2.642-982.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me	1	1		
FRV 30 Me Surface Cleaner	46	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Extension hose FRV 30 Me and FRV 50 Me	47	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
Surface Cleaner FR 50 Me		1		
FRV 50 Me surface cleaner	48	2.111-024.0	Surface cleaning with automatic suction of the dirty water for very large surfaces. Hot water cleaning up to 85°C.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced 3, 900 l/h - 2500 l/h	49	4.112-065.0		
Cup foam lance DUO Advanced 3, 900 I/h - 2500 I/h	50	4.112-069.0		
Cup foam lance Basic 3, 900 l/h - 2500 l/h	51	4.112-055.0	For high-pressure cleaners with a flow rate of 900-2500 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	52	5.071-414.0		
1-litre cleaning agent container for cup foam lance	53	6.414-954.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 6.394-668)	
1-litre cleaning agent container for cup foam lance advanced	54	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Set			·	
Inno foam kit	55	2.112-008.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				
Easy foam set	56	2.112-011.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0

67



69

70

68

	1			—
		Order no.	Description	
FOAM SYSTEMS				
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 090 Inno/Easy kit 700 - 1000 l/h	57	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.	
Foam nozzle mounting kit				
Foam nozzle kit	58	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	59	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	60	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with order no. 3.63	37-170	5		-
Nozzle insert trapezoidal thread HDS-GER	61	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	62	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	63	4.769-001.0	For low pressure with machines up to 1.100 l/h	
QUICK CONNECT				
Quick-fitting pipe union coupler trapezo	64	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Quick-fitting pipe union plug nipple tra	65	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	66	2.641-798.0		
OTHER HP ACCESSORIES				
Add-on kit coin acceptor	67	2.644-029.0	Coin remote control with electronic coin acceptor for connecting a high-pressure cleaner as a pre-wash device. Please have the power outlet and cable provided on site.	
Jet gun	68	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	69	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	
Connector				
Nozzle connector/screw connector	70	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 × 1.5 and 1x M 18 × 1.5.	

□ Available accessories.

65

66

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



				-
		Order no.	Description	
COUPLING PARTS				
Connector				
Y distributor	71	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	72	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	t 🗆
Adapter EASY!Lock		•		
Adapter 1 M22AG-TR22AG	73	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	74	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	75	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 – Swivel	76	4.111-032.0	M22 × 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	ιC
Adapter 5 TR22IG-M22AG	77	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	78	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	79	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	80	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Coupler -2xM22x1,5	81	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2 \times M 22 \times 1.5$ m.	
ADAPTER for replacement TR22IG-M22AG Er	82	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 m	83	2.639-257.0		
Automatic hose reel, powder-coated steel / plastic, 20 m	84	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic stainless steel / synthetic material hose drum, 20 m	85	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	86	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	87	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	88	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	89	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	90	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	91	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	92	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	93	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	94	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	95	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	96	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	97	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	98	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0



		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING		order no.		┷╼┥
Brushes				
Brush soft	99	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
Telescopic				
TL low pressure adapter	100	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	101	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	102	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. 🗆
Telescopic lance TL 10 H	103	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	104	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	105	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	106	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	107	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	108	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0065	109	2.112-026.0	Consisting of wet jet nozzle and nozzle insert – only for use in combination with wet jet unit 4.115-000.0 4.115-006.0.	
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 l/h	110	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 3/4"	111	6.388-455.0	with hose liner	
Hose coupling	112	6.388-458.0	with female thread	

□ Available accessories.

HD 10/15-4 Cage Food, 1.353-908.0, 2024-05-13

EQUIPMENT FOR HD 10/15-4 CAGE FOOD 1.353-908.0









				-
		Order no.	Description	
WATER CONNECTION				
Suction filter				
Water filter	113	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μ m mesh, R 3/4" and R 1" connection, without non-return valve	
Suction filter with check valve	114	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.]
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush, M 18 × 1.5	115	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 \times 1.6.	
Rotating washing brush		1		
Rotating wash brush for > 800 l/h machines, nylon bristles	116	4.113-002.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 \times 1.5 (replaceable brush insert).	
Rotating wash brush for > 800 l/h machines, natural bristles	117	4.113-005.0		