

# HD 13/35-4 CAGE

This product uses up to 350 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.











#### Order no.

#### 1.367-154.0

Robust industrial gunLow-water cut-out (optional)

Technical data			
EAN code			4039784730984
Operating press	ure	bar / MPa	100 - max. 350 / 10 - max. 35
Flow Rate		l/h	500 - 1300
Water feed temp	perature	°C	max. 60
Fuel			Electric
Power Rating		kW	15
Current type		Ph / V / Hz	3 / 400 / 50
Pump Type			Maximum performance Kärcher crankshaft pump
Weight without	accessories	kg	160
Weight (with acc	cessories)	kg	195
Dimensions (L ×	W × H)	mm	930 × 800 × 920

1	Equipment		
	High-pressure hose	m	10 / Heavy duty
	Trigger gun		Industrial trigger gun
	Stainless steel spray lance	mm	700
	Flat jet nozzle		•
	Safety valve		
	Operating hour meter		•
	Included in delivery.		

#### Equipment

	5-09
	4-0
	202
	Ő
	154
	1
	1.36
	HD 13/35-4 Cage, 1.367-154.0, 2024-05-09
	4
	35
	13/
	ДH

This device does not require instruction.



#### High-performance crankshaft pump

• Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.



#### Safe storage


 Accessories and tools are stored in a protected compartment. This means that everything is always in its place.

# EQUIPMENT FOR HD 13/35-4 CAGE 1.367-154.0











				1
		Order no.	Description	
COLD WATER CAGE MACHINES				
High-pressure hoses				
Pressure hose, 10 m, 620 bar, M22 $\times$ 1.5	1	6.391-846.0	650 bar, M 22 × 1.5	
Pressure hose, 3 m, 640 bar, M22 × 1.5	2	6.391-856.0	650 bar, M 22 × 1.5.	
Pressure hose, 10 m, 640 bar, M22 × 1.5	3	6.391-848.0	640 bar, M 22 × 1,5	
Pressure hose, 20 m, 640 bar, M22 × 1.5	4	6.391-857.0	650 bar, M 22 × 1.5.	
Pressure hose, 20 m, 620 bar, M22 × 1.5	5	6.391-847.0		
Pressure hose, 30 m, 620 bar, M22 × 1.5	6	6.391-019.0	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 × 1.5. Suitable for up to 620 bar working pressure.	
Lances				
Kärcher industry gun	7	4.775-824.0	650 bar – industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 × 1.5.	
Jet tube				
Spray lance	8	4.760-679.0	With nozzle holder.	
	9	4.760-653.0		
Jet pipe complete 1550 mm 65 MPa	10	4.760-675.3		
Spray lance	11	4.760-677.0	With nozzle holder.	
Spray lance extension	12	4.760-699.0	Spray lance extension 800 mm, 65 MPa.	
Add on kits				
ABS protection against water shortage	13	2.641-922.0	For electric motors.	
	14	2.851-028.0	ABS steering rollers.	

■ Included in delivery. □ Available accessories.

# EQUIPMENT FOR HD 13/35-4 CAGE 1.367-154.0

26

27



28

		Order no.	Description	
COLD WATER CAGE MACHINES				
Couplings and connectors				
Coupling	15	4.403-004.0	For connecting and extending HP hoses. Connection $2 \times M22 \times 1.5$ . Brass with rubber protection.	
Grease for stainless steel threaded joints	16	6.280-180.0	Grease for stainless steel screw connections.	
Pipe cleaning				
Foot valve for pipe cleaning	17	6.470-223.0	Foot valve for convenient and safe use of accessories for effective pipe cleaning.	
Pipe cleaning nozzle standard 050 50MPa	18	4.765-012.0		
Pipe cleaning nozzle Four 050 50MPa	19	4.765-016.0		
Pipe cleaning nozzle, Rotor	20	5.763-092.0	For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x backward.	
Pipe cleaning hose	21	6.392-401.0	Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4 nozzle.	"
	22	6.392-402.0	Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	
	23	6.392-403.0	For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	
Surface Cleaner				
FRI 50 Me 50 MPa	24	2.643-577.0	Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	
Nozzle pack 025 FRI 50	25	6.415-045.0	Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 025.	
Abrasive blaster		1		
Required adapter for abrasive blasters	26	5.401-325.0	M 20 × 1 IG to 9/16" UNF AG.	
Abrasive blaster, incl. 3 × 0.7 nozzle	27	9.872-435.0	Abrasive spray head with nozzle size 3 × 0.7 mm for wet sand blasting. Only includes spray head. Without hose and lance.	
Replacement nozzle for abrasive blaster	28	6.025-346.0	Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	

■ Included in delivery. □ Available accessories.

25

# **EQUIPMENT FOR HD 13/35-4 CAGE** 1.367-154.0

29





40-42

31









		Order no.	Description	
COLD WATER CAGE MACHINES				
Abrasive blaster				
F98 nozzle kit, D 0.70 mm	29	9.886-551.0	For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	E
F98 nozzle for abrasive blaster	30	6.025-255.0	Nozzle (nozzle size 0.7 mm) for abrasive spray head for wet sand blasting.	
Suction lance	31	6.025-258.0	For the suction of spray agents.	
Abrasive material hose	32	6.025-308.0	Abrasive hose.	
Mounting tool for nozzle set	33	6.025-257.0	For F98 nozzles.	
Abrasive	34	6.025-309.0	25 kg, 0.5-1.00 mm, garnet sand.	
	35	6.025-310.0	25 kg, 0.7-1.40 mm, garnet sand.	
NOZZLES				
Power nozzles				
Flat jet nozzle, 15049	36	5.765-166.0	15°, 350 bar, 1,300 l/h (electr.)	
Point jet nozzle, 0049	37	5.765-162.0	350 bar, 1,300 l/h (electr.)	
Screw nozzle				
Dummy nozzle F21	38	6.025-237.0	F21 screw-on dummy nozzle for working pressures of up to 3000 bar.	
Round jet nozzle F21, Saphir, 0,9 mm	39	9.886-216.0	F21 screw-on sapphire round jet nozzle, 0.90 mm diameter, suitable for working pressures of up to 3000 bar.	эC
PROTECTIVE CLOTHING				
HD Overall size M	40	6.547-055.0		
HD Overall size L	41	6.547-056.0		
HD Overall size XL	42	6.547-057.0		

■ Included in delivery. □ Available accessories.

## KÄRCHER

# EQUIPMENT FOR HD 13/35-4 CAGE 1.367-154.0



				_
		Order no.	Description	
ROTARY NOZZLES				
Single-jet rotary nozzles				
Tool for changing rotor seat	43	6.025-233.0	For single-jet rotary nozzles.	
Rotary jet, 049, 1.35 mm	44	4.767-173.0	350 bar, 1.35 mm, 1,300 l/h, M 20 × 1, brass.	
Power rotary jet F7, 050, 1.35 mm	45	6.415-085.0		
Repair set Power Rotary Jet F9 050, 050, 1.35 mm	46	6.812-003.0		
Power rotary jet repair kit F7	47	6.025-436.0	Repair kit for power rotary jet for 350 bar working pressure and 1,300 l/h water flow rate, Order No. 6.415-914.0. Includes rotor, seat and O-ring (28 × 2).	
Multi-jet rotary nozzles				
Nozzle body	48	9.917-677.0		
Nozzle carrier head TD09	49	9.899-828.0	Nozzle holder for F21 nozzle. Suitable for working pressures of up to 3000 bar. 35° spray angle, includes guard and flow conditioner.	

■ Included in delivery. □ Available accessories.