

HD 9/50-4 CAGE

This product uses up to 500 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



Made in Germany



Order no.

1.367-156.0

- Robust industrial gun
- Low-water cut-out (optional)

Technical data


EAN code		4039784731011
Operating pressure	bar / MPa	150 - max. 500 / 15 - max. 50
Flow Rate	l/h	500 - 900
Water feed temperature	°C	max. 60
Fuel		Electric
Power Rating	kW	15
Current type	Ph / V / Hz	3 / 400 / 50
Pump Type		Maximum performance Kärcher crankshaft pump
Weight without accessories	kg	150
Weight (with accessories)	kg	195
Dimensions (L × W × H)	mm	930 × 800 × 920

This device does not require instruction.

Equipment

High-pressure hose	m	10 / Heavy duty
Trigger gun		Industrial trigger gun
Stainless steel spray lance	mm	700
Flat jet nozzle		■
Safety valve		■
Operating hour meter		■

■ Included in delivery.



High-performance crankshaft pump


- Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.



Safe storage

- Accessories and tools are stored in a protected compartment. This means that everything is always in its place.

EQUIPMENT FOR HD 9/50-4 CAGE 1.367-156.0



		Order no.	Description	
COLD WATER CAGE MACHINES				
High-pressure hoses				
Pressure hose, 10 m, 640 bar, M22 × 1.5	1	6.391-848.0	640 bar, M 22 × 1.5	■
Pressure hose, 3 m, 640 bar, M22 × 1.5	2	6.391-856.0	650 bar, M 22 × 1.5.	□
Pressure hose, 20 m, 640 bar, M22 × 1.5	3	6.391-857.0		□
Pressure hose, 30 m, 640 bar, M22 × 1.5	4	6.391-020.0	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 × 1.5. Suitable for up to 640 bar working pressure.	□
Pressure hose, 10 m, 620 bar, M22 × 1.5	5	6.391-846.0	650 bar, M 22 × 1.5	□
Pressure hose, 20 m, 620 bar, M22 × 1.5	6	6.391-847.0	650 bar, M 22 × 1.5.	□
Pressure hose, 30 m, 620 bar, M22 × 1.5	7	6.391-019.0	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 × 1.5. Suitable for up to 620 bar working pressure.	□
Lances				
Kärcher industry gun	8	4.775-824.0	650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 × 1.5.	■
Jet tube				
Spray lance	9	4.760-679.0	With nozzle holder.	■
	10	4.760-653.0		□
Jet pipe complete 1550 mm 65 MPa	11	4.760-675.3		□
Spray lance	12	4.760-677.0	With nozzle holder.	□
Spray lance extension	13	4.760-699.0	Spray lance extension 800 mm, 65 MPa.	□
Add on kits				
ABS protection against water shortage	14	2.641-922.0	For electric motors.	□

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 9/50-4 CAGE 1.367-156.0



		Order no.	Description	
COLD WATER CAGE MACHINES				
Add on kits				
ABS protection against water shortage	15	2.851-028.0	ABS steering rollers.	<input type="checkbox"/>
Couplings and connectors				
Coupling	16	4.403-004.0	For connecting and extending HP hoses. Connection 2 × M22 × 1.5. Brass with rubber protection.	<input type="checkbox"/>
Grease for stainless steel threaded joints	17	6.280-180.0	Grease for stainless steel screw connections.	<input type="checkbox"/>
Pipe cleaning				
Foot valve for pipe cleaning	18	6.470-223.0	Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle standard 030 50MPa	19	4.765-013.0		<input type="checkbox"/>
Pipe cleaning nozzle Four 030 50MPa	20	4.765-019.0		<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	21	5.763-095.0	Rotor pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning hose	22	6.392-401.0	Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	23	6.392-402.0	Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	24	6.392-403.0	For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
Surface Cleaner				
FRI 50 Me 50 MPa	25	2.643-577.0	Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle pack 015 FRI 50	26	6.415-044.0	Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 015.	<input type="checkbox"/>
Abrasive blaster				
Required adapter for abrasive blasters	27	5.401-325.0	M 20 × 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	28	6.025-346.0	Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.




EQUIPMENT FOR HD 9/50-4 CAGE 1.367-156.0



	Order no.	Description	
COLD WATER CAGE MACHINES			
Abrasive blaster			
F98 nozzle set, 0.60 mm	29	9.886-550.0	<input type="checkbox"/>
F98 nozzle for abrasive blasters	30	6.025-256.0	0.6 mm <input type="checkbox"/>
Suction lance	31	6.025-258.0	For the suction of spray agents. <input type="checkbox"/>
Abrasive material hose	32	6.025-308.0	Abrasive hose. <input type="checkbox"/>
Mounting tool for nozzle set	33	6.025-257.0	For F98 nozzles. <input type="checkbox"/>
Abrasive	34	6.025-309.0	25 kg, 0.5-1.00 mm, garnet sand. <input type="checkbox"/>
	35	6.025-310.0	25 kg, 0.7-1.40 mm, garnet sand. <input type="checkbox"/>
NOZZLES			
Power nozzles			
Flat jet nozzle, 15030	36	5.765-164.0	15°, 500 bar, 900 l/h (electr.) <input checked="" type="checkbox"/>
Point jet nozzle, 0030	37	5.765-159.0	500 bar, 900 l/h (electr.) <input type="checkbox"/>
Screw nozzle			
Dummy nozzle F21	38	6.025-237.0	F21 screw-on dummy nozzle for working pressures of up to 3000 bar. <input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,7 mm	39	6.025-222.0	F21 screw-on sapphire round jet nozzle, 0.70 mm diameter, suitable for working pressures of up to 3000 bar. <input type="checkbox"/>
PROTECTIVE CLOTHING			
HD Overall size M	40	6.547-055.0	<input type="checkbox"/>
HD Overall size L	41	6.547-056.0	<input type="checkbox"/>
HD Overall size XL	42	6.547-057.0	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HD 9/50-4 CAGE 1.367-156.0



		Order no.	Description	
ROTARY NOZZLES				
Single-jet rotary nozzles				
Tool for changing rotor seat	43	6.025-233.0	For single-jet rotary nozzles.	<input type="checkbox"/>
Power Rotary Jet F8 030, 030, 1.05 mm	44	6.415-069.0		<input type="checkbox"/>
Repair set Power Rotary Jet F8 030, 030, 1.05 mm	45	6.812-000.0		<input type="checkbox"/>
Power rotary jet repair kit F8	46	6.025-437.0	Repair kit for power rotary Jet, Order No. 6.415-915.0. Suitable for 500 bar pressure and 900 l/h water flow. Includes rotor, seat and O-ring (28 x 2).	<input type="checkbox"/>
Multi-jet rotary nozzles				
Nozzle body	47	9.917-677.0		<input type="checkbox"/>
Nozzle carrier head TD09	48	9.899-828.0	Nozzle holder for F21 nozzle. Suitable for working pressures of up to 3000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

Available accessories.