### NT 70/3

High capacity powerful wet/dry vacuum cleaner with three suction motors for heavy-duty use





1.667-270.0

- Robust bumper, large wheelsErgonomic Push Handle
- Optional wet filter available

| Technical data             |             |                         |
|----------------------------|-------------|-------------------------|
| EAN code                   |             | 4039784725386           |
| Current type               | Ph / V / Hz | 1 / 220 - 240 / 50 - 60 |
| Air flow                   | I/s         | 3 × 74                  |
| Vacuum                     | mbar / kPa  | 254 / 25.4              |
| Container content          | 1           | 70                      |
| Container material         |             | Plastic                 |
| Rated input power          | W           | max. 3600               |
| Standard nominal width     |             | ID 40                   |
| Cable length               | m           | 10                      |
| Sound pressure level       | dB(A)       | 83                      |
| Colour                     |             | anthracite              |
| Weight without accessories | kg          | 27.6                    |
| Dimensions (L × W × H)     | mm          | 720 × 510 × 975         |

| Equipment                  |          |                 |
|----------------------------|----------|-----------------|
| Suction hose length        | m        | 4               |
| Bend                       |          | Plastic         |
| Quantity of suction tubes  | Piece(s) | 2               |
| Suction tubes length       | mm       | 550             |
| Suction tubes material     |          | Stainless steel |
| Wet/dry floor nozzle width | mm       | 360             |
| Crevice nozzle             |          |                 |
| Cartridge filter           |          | Paper           |
| Drain hose                 |          | •               |
| Sturdy bumper              |          |                 |
| Push handle                |          |                 |
| Safety class               |          | II              |
|                            |          |                 |

Included in delivery.



#### Integrated accessory storage

■ Large bumper with accessory storage.



#### **Ergonomic Push Handle**

■ The NT 70 has an ergonomic push handle for greater manoeuvrability.

#### Integrated drain hose

■ The container is easy to empty via the drain hose. Extremely practical due to the very large 70 litre container capacity.

### **KÄRCHER**

















|   |        |             |   | $\top$ |  |
|---|--------|-------------|---|--------|--|
|   |        |             |   |        |  |
|   |        | Order no.   | Description   |        |  |
| CARTRIDGE FILTER, STANDARD, BIA C OR UP | TO DUS | T CLASS M   |   |        |  |
| Cartridge filter paper                  |        |             |   |        |  |
| Cartridge filter, paper                 | 1      | 6.907-038.0 | Paper cartridge filter (M BIA-C dust class M), suitable as a main filter for dry and wet pick up.   | ı      |  |
| BENDS                                   |        |             |   | Ť      |  |
| Plastic bend                            |        |             |   |        |  |
| Elbow packaged NW40 1K                  | 2      | 2.889-171.0 | Bend for the new clip system in nominal size DN 40.   | ı      |  |
| Plastic bend                            | 3      | 5.031-718.0 | Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).   |        |  |
|   | 4      | 5.031-939.0 | Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.  |        |  |
|   | 5      | 5.032-427.0 | Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.  | [      |  |
| Bend metal                              |        |             |   | Ť      |  |
| Bend, DN 35, metal                      | 6      | 6.900-519.0 | Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el.).   | [      |  |
| Bend, stainless steel ID 35             | 7      | 6.903-141.0 | Stainless steel and crooked, ID 35  |        |  |
| Bend, DN 40, metal                      | 8      | 6.900-276.0 | Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0, C 40-DN 40, plastic, el.).   |        |  |
| Bend, stainless steel ID 40             | 9      | 6.902-079.0 | Stainless steel and crooked, ID 40  |        |  |
| SUCTION NOZZLES                         |        |             |   | Ť      |  |
| All-purpose nozzles (wet/dry)           |        |             |   |        |  |
| Floor tool packaged NW40 360mm          | 10     | 2.889-153.0 |   | I      |  |
| Floor tool DN40-370                     | 11     | 6.903-018.0 | All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.         |        |  |
| Floor tool neutrally DN40               | 12     | 6.906-383.0 | All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners. |        |  |
| Floor tool neutrally DN35               | 13     | 6.906-384.0 | All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners. |        |  |
| Wet and dry floor nozzle                | 14     | 2.889-117.0 | The wet and dry floor nozzle (DN 40) allows quick changing of the squeegees/brush and is ideal for wet vacuum cleaning of large areas.  | r [    |  |

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.

























|                                 |    | Order no.   | Description   |   |
|---------------------------------|----|-------------|---|---|
| SUCTION NOZZLES                 |    |             |   |   |
| Crevice nozzles                 |    |             |   |   |
| Crevice nozzle DN 40 300mm 1:50 | 15 | 5.130-655.0 |   |   |
| Crevice nozzle packaged NW35    | 16 | 2.889-130.0 | Plastic crevice nozzle.   |   |
| Crevice nozzle                  | 17 | 6.900-922.0 | Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.                                       |   |
| Crevice nozzle DN40             | 18 | 6.905-817.0 | Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.   | T |
| All-purpose brushes             |    |             |   |   |
| All-purpose brush               | 19 | 6.903-863.0 | Natural bristles (ox hair), bristle element 120 × 45 mm.  |   |
| Car cleaning nozzles            |    |             |   |   |
| Car nozzle, ID 40, 90 mm        | 20 | 6.900-952.0 | Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.                     |   |
|                                 | 21 | 2.840-095.0 |   | - |
| Gangway nozzles                 |    |             |   |   |
| Gangway nozzle                  | 22 | 4.130-432.0 | Vacuuming larger Areas in connection with NT 70/1, NT 70/2 or NT 70/3 versions only.                                      | 1 |
| Rubber suction tools, nose 45°  |    |             |   |   |
| Rubber suction tools, nose 45°  | 23 | 6.902-104.0 | $45^\circ$ rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners. |   |
|                                 | 24 | 6.902-105.0 | $45^\circ$ rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners. |   |
| Pipe dusting nozzles            |    |             |   |   |
| BRUSH                           | 25 | 6.903-035.0 | Plastic, pipe diameter 100 mm   | 1 |
|                                 | 26 | 6.903-036.0 | Plastic, pipe diameter 200 mm   |   |
| Suction brushes                 |    |             |   |   |
| Suction brush DN35              | 27 | 6.903-862.0 | Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.  |   |
| Suction brush DN32              | 28 | 6.903-887.0 | Rotatable suction brush (DN 32 plastic) with PA bristles, 70x45 mm. Only for BV and T vacuum cleaners.                    |   |

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.



























|  |        | Order no.     | Description  |   |
|--|--------|---------------|--|---|
| SUCTION TUBES                                  |        |               |  |   |
| Suction tubes stainless steel                  |        |               |  |   |
| Set suction tube stainless steel NW40 55       | 29     | 2.889-194.0   | Stainless steel suction tube set (2 × 0.55 m)  |   |
| Suction tube, DN 35                            | 30     | 6.902-154.0   | 0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components. |   |
| Suction tube, ID 40                            | 31     | 6.902-081.0   | Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.  |   |
| Suction tube                                   | 32     | 6.906-531.0   | Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.  |   |
| Suction tubes metal                            |        |               |  |   |
| Suction tube DN35                              | 33     | 6.900-514.0   | Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.  |   |
| SUCTION HOSES                                  | •      |               |  |   |
| Suction hoses with clip system 2.0 (compatible | e with | vacuum cleane | rs from model year 2017 on)  |   |
| Suction hose                                   | 34     | 2.889-138.0   | 4 m suction hose with new bayonet and clip fastener.   |   |
| Electrically conductive suction hose           | 35     | 2.889-137.0   | 4 m suction hose with new bayonet and clip fastener. Electrically conductive.  |   |
| Suction hose                                   | 36     | 2.889-139.0   | Suction hose with new bayonet and clip fastener. Length: 2.5 m.  |   |
| Suction hose, oil-resistant                    | 37     | 2.889-140.0   | Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.  |   |
| Electrically conductive suction hose           | 38     | 2.889-141.0   | 4 m, electrically conductive suction hose with new bayonet and clip fastener.  |   |
|  | 39     | 2.889-142.0   | Suction hose, electrically conductive, with new bayonet and clip fastener. 2.5 m long.   |   |
| Extension hose packaged NW40 2.5m              | 40     | 2.889-146.0   | Extension hose for new clip system ID 40. Length: 2.5 m.   |   |
| Repair set NW40                                | 41     | 2.889-150.0   | Repair kit ID 40 for the new clip system.  |   |
| Hose connection                                | -      |               |  | _ |
| Adapter, DN 32/35, with internal thread        | 42     | 6.902-077.0   | Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.                            |   |

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.

























|   |      | Order no.     | Description  |   |
|---|------|---------------|--|---|
| SUCTION HOSES                                     |      |               |  | _ |
| Hose connection                                   |      |               |  |   |
| Adapter, DN 40 with internal thread               | 43   | 6.900-286.0   | Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.   |   |
| Suction hoses with clip system 1.0 (compatible    | with | vacuum cleane | ers up to model year 2016)   |   |
| Repair set, C 40                                  | 44   | 2.639-873.0   | Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system. |   |
| Extension hose, C 40                              | 45   | 6.906-344.0   | 2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.                                 |   |
| Suction hose                                      | 46   | 4.440-784.0   | 16 m suction hose (C-DN 40) with bayonet and straight adapter.   |   |
| Suction hose (clip system), C 40, 10 m            | 47   | 6.906-279.0   | 10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.     |   |
| Suction hose                                      | 48   | 6.906-321.0   | 4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.  |   |
| Suction hose (Clip-system), C 40, 16 m            | 49   | 6.906-635.0   | With bayonet and clip connection.  |   |
| Suction hose (clip system), C 40, 10 m, el.       | 50   | 6.906-877.0   | Suction hose with bayonet coupling, electrically conductive.   |   |
| Suction hoses with cone connection                |      |               |  |   |
| Suction hose, complete                            | 51   | 4.440-263.0   | Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.            |   |
| Suction hose complete, ID 40, 4 m, oil-resistant, | 52   | 4.440-303.0   | Oil-resistant.   |   |
| Suction hose, complete                            | 53   | 4.440-463.0   | Electrically non-conductive 10.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.           |   |
| Suction hose complete                             | 54   | 4.440-466.0   | Electrically conductive, 10.0m, ID 40  |   |
| Suction hose complete, ID 40, 10 m, oil-resistant | 55   | 4.440-612.0   | Oil-resistant.   |   |
| Suction hose, complete                            | 56   | 4.440-264.0   | 4 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.                                    |   |

 $<sup>\</sup>hfill \square$  Available accessories.

### **EQUIPMENT FOR NT 70/3**

### 1.667-270.0





























|   |       |             |   | Т   |
|---|-------|-------------|---|-----|
|   |       | Order no.   | Description   |     |
| SUCTION HOSES   |       | order no.   | DESCRIPTION .   | _   |
| Suction hoses with cone connection  |       |             |   | _   |
| Suction hose complete, ID 61, smooth inside   | 57    | 4.440-328.0 | Industrial hose, PVC/elastomer with steel spiral, smooth inside.  |     |
| Suction hose, complete, DN 61, 10 m   | 58    | 4.440-467.0 | 10 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.  | . [ |
| Suction hose complete, ID 61, 4 m, oil-resistant  | 59    | 4.440-613.0 | Oil-resistant.  |     |
| Suction hose complete, ID 61, 4 m, el.  | 60    | 4.440-616.0 | Electrically conductive.  |     |
| FILTER BAGS   |       |             |   |     |
| Fleece filter bags (3 ply)  |       |             |   |     |
| Fleece filter bags, 5 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 90   | 61    | 2.885-753.0 |   |     |
| Paper filter bags   |       |             |   |     |
| Paper filter bags, 5 Piece(s), NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC                          | 62    | 6.904-285.0 | 5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco - Me and NT 72/2 Eco Tc models.  | + [ |
| FILTER T/ NT  |       |             |   |     |
| Coarse filter for wet pickup  |       |             |   |     |
| Foam filter   | 63    | 2.889-083.0 | Not suitable for dry vacuuming.   |     |
| Special filter bags, wet filter bags  |       |             |   |     |
| Special filter bags, wet filter bags  | 64    | 6.904-252.0 | Approved for dust class L, general cleaning, wet and dry, tear-resistant.   |     |
| Plastic sacks for dust-free disposal  |       |             |   |     |
| Plastic bag for dust-free disposal, 10 Piece(s),<br>NT 65, NT 70, NT 72, NT 75, NT 602, NT 700,<br>NT 702 | 65    | 6.900-698.0 | PE plastic sack.  |     |
| Membrane filter / fabric filter   |       | '           |   |     |
| Membrane filter, NT 65, NT 70, NT 72, NT 75,<br>NT 551, NT 602, NT 700, NT 702, NT 802, NT<br>993         | 66    | 6.904-282.0 | Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners. |     |
| CONNECTING SLEEVES  |       |             |   | Ė   |
| Y-adapter kit   |       |             |   |     |
| Y-adapter kit   | 67    | 2.637-217.0 | Plastic distributor - suitable for NT vacuum cleaners.  |     |
| Connecting sleeve C-DN (clip on taper), EL (elec  | troco | nductive)   |   | _   |
| Connection cone NW35  | 68    | 5.407-005.0 |   | [   |
| Connection cone NW40  | 69    | 5.407-006.0 |   | Ε   |
| C-ID 35 adapter   | 70    | 5.407-112.0 | Connects C 35 hose for ID 35, electrically conductive.  |     |
| ☐ Available accessories.  |       | II.         |   |     |





















|  |           |             |   | _ |
|--|-----------|-------------|---|---|
|  |           |             |   |   |
|  |           | Order no.   | Description   |   |
| CONNECTING SLEEVES                     | '         |             |   |   |
| Reducing sleeves                       |           |             |   |   |
| Reducer                                | 71        | 5.407-108.0 | Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.   |   |
|  | 72        | 6.902-017.0 | Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.   |   |
| Sleeve C40 / C35                       | 73        | 5.407-113.0 | Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.   |   |
| Reducer from ID 35 to 32               | 74        | 6.902-072.0 | Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.                                      |   |
| TARGET GROUP SPECIFIC VACUUM CLEANE    | R ACCESSO | ORY SETS    |   |   |
| Professional cleaning kit ID 40        | 75        | 2.637-353.0 | Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube $2\times0.5$ m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0). |   |
| Car cleaning kit                       | 76        | 2.862-166.0 | Contains: - Car cleaning nozzle ID 35 - Upholstery/crevice tool ID 35 - Suction brush ID 35 - Connecting sleeve C 35/ ID 35   |   |
| Chip cleaning kit                      | 77        | 2.640-760.0 | Individual parts: suction hose 4 m, oil-proof (4.440-613.0), crevice tool (6.900-222.0), rubber suction nozzle angled at $45^{\circ}$ (6.902-106.0).  |   |
| OTHER ACCESSORIES FOR T AND NT         |           |             |   |   |
| CS 40 Me                               | 78        | 2.863-026.0 | The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.   |   |
| Adapter connection old elektr. leitend | 79        | 5.031-436.0 |   |   |

 $<sup>\</sup>hfill \square$  Available accessories.