

NT 75/2 TACT² ME TC

High capacity, high filtration professional multi-purpose vacuum cleaner with twin motors and Tact² automatic filter clean system for heavy duty dust extraction.



Order no.

1.667-289.0

- Automatic Filter Cleaning System Tact²
- Push handle and drain hose
- Moisture-proof PES filter

Technical data

EAN code		4039784727274
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 × 74
Vacuum	mbar / kPa	254 / 25.4
Container content	l	75
Container material		Stainless steel
Rated input power	W	max. 2760
Standard nominal size		ID 40
Cable length	m	10
Sound pressure level	dB(A)	73
Weight without accessories	kg	29
Weight incl. packaging	kg	36.6
Dimensions (L × W × H)	mm	685 × 560 × 920

Equipment

Suction hose	m	4 / with bend
Suction Tube	Piece(s) × mm	2 × 550 / Stainless steel
Filter bag	Piece(s)	1 / Paper
Wet and dry floor tool	mm	360
Crevice nozzle		■
Drain hose (oil-resistant)		■
Auto shutdown when max. level is reached		■
Antistatic system		■
Stainless steel container		■
Flat pleated filter		PES
Tilting chassis		■
Filter cleaning		Automatic Filter Cleaning System Tact ²
Sturdy bumper		■
Push handle		■
Safety class		II
Caster with brake		■

■ included in delivery.



Tilting chassis with container lock

- to keep the container securely attached to the chassis.



Drain hose for emptying liquids.

- Cover remains tightly closed until the contents are drained.



Suction pipes and floor nozzles can be stored in any direction in the accessory holders

- For easy access from all sides.
- Ample storage for a 4 m hose and rubber power cord (10 m).

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0




		Order no.	Description	
FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M				
Flat pleated filter (PES)				
Flat pleated filter (PES)	1	6.907-277.0	Flat pleated filter dust class M, rotproof PES fleece. Suitable for frequent wet pick up.	■
Flat pleated filter (paper)				
Flat pleated filter (paper)	2	6.907-276.0	Flat pleated filter dust class M, nano-coated paper. Suitable for fine dust and dry dirt pick up.	□
Flachfaltenfilter (PTFE)				
Flat pleated filter, PTFE	3	6.907-449.0	Polyester fleece with PTFE coating, dust class M, for Tact ² vacuum cleaners. Particularly suitable for very adhesive materials.	□
BENDS				
Plastic bend				
Elbow electrically conducting packaged N	4	2.889-172.0	Bend for the new clip system in nominal size DN 40. Electrically conductive design. Particularly suited to high concentrations of fine dust.	■
Plastic bend	5	5.031-718.0	Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	□
	6	5.031-939.0	Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
	7	5.032-427.0	Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Bend metal				
Bend, DN 35, metal	8	6.900-519.0	Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el.).	□
Bend, stainless steel ID 35	9	6.903-141.0	Stainless steel and crooked, ID 35	□
Bend, DN 40, metal	10	6.900-276.0	Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0, C 40-DN 40, plastic, el.).	□
Bend, stainless steel ID 40	11	6.902-079.0	Stainless steel and crooked, ID 40	□
SUCTION NOZZLES				
All-purpose nozzles (wet/dry)				
Floor tool packaged NW40 360mm	12	2.889-153.0		■
Floor tool anthracite packaged NW35	13	2.889-173.0	300 millimetre width, anthracite coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Incl. brush strips and squeegees.	□
Floor tool anthracite packaged NW40	14	2.889-174.0	Standard floor nozzle, anthracite, in nominal diameter 40, with brush strips and squeegees. Suitable for all wet and dry applications.	□

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



		Order no.	Description	
SUCTION NOZZLES				
All-purpose nozzles (wet/dry)				
Floor tool DN40-370	15	6.903-018.0	All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	<input type="checkbox"/>
Floor tool neutrally DN40	16	6.906-383.0	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	<input type="checkbox"/>
Floor tool neutrally DN35	17	6.906-384.0	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	<input type="checkbox"/>
Wet and dry floor nozzle	18	2.889-117.0	The wet and dry floor nozzle (DN 40) allows quick changing of the squeegees/brush and is ideal for wet vacuum cleaning of large areas.	<input type="checkbox"/>
Crevice nozzles				
Crevice nozzle DN 40 300mm 1:50	19	5.130-655.0		<input checked="" type="checkbox"/>
Crevice nozzle packaged NW35	20	2.889-130.0	Plastic crevice nozzle.	<input type="checkbox"/>
Crevice nozzle	21	6.900-922.0	Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	<input type="checkbox"/>
Crevice nozzle DN40	22	6.905-817.0	Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	<input type="checkbox"/>
All-purpose brushes				
All-purpose brush	23	6.903-863.0	Natural bristles (ox hair), bristle element 120 x 45 mm.	<input type="checkbox"/>
Car cleaning nozzles				
Car nozzle, DN 40, 90 mm	24	6.900-952.0	Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	<input type="checkbox"/>
	25	2.840-095.0		<input type="checkbox"/>
Gangway nozzles				
Wide nozzle	26	4.130-400.0	Wide metal nozzle, height adjustable with brush strip. Only suitable for Tc models.	<input type="checkbox"/>
Rubber suction tools, nose 45°				
Rubber suction tools, nose 45°	27	6.902-104.0	45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	<input type="checkbox"/>
	28	6.902-105.0	45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



	Order no.	Description	
SUCTION NOZZLES			
Pipe dusting nozzles			
BRUSH	29	6.903-035.0 Plastic, pipe diameter 100 mm	<input type="checkbox"/>
	30	6.903-036.0 Plastic, pipe diameter 200 mm	<input type="checkbox"/>
SUCTION TUBES			
Suction tubes stainless steel			
Set suction tube stainless steel NW40 55	31	2.889-194.0 Stainless steel suction tube set (2 × 0.55 m)	<input checked="" type="checkbox"/>
Suction tube, DN 35	32	6.902-154.0 0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components.	<input type="checkbox"/>
Suction tube, ID 40	33	6.902-081.0 Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	<input type="checkbox"/>
Suction tube	34	6.906-531.0 Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	<input type="checkbox"/>
Suction tubes metal			
Set suction tube chromed NW35 550mm	35	2.889-191.0 Suction tube set, metal-chrome-plated, NW 35, 2-part, each 0.55 millimetres.	<input type="checkbox"/>
Suction tube DN35	36	6.900-514.0 Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	<input type="checkbox"/>
SUCTION HOSES			
Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)			
Electrically conductive suction hose	37	2.889-141.0 4 m, electrically conductive suction hose with new bayonet and clip fastener.	<input checked="" type="checkbox"/>
	38	2.889-137.0 4 m suction hose with new bayonet and clip fastener. Electrically conductive.	<input type="checkbox"/>
Suction hose	39	2.889-138.0 4 m suction hose with new bayonet and clip fastener.	<input type="checkbox"/>
	40	2.889-139.0 Suction hose with new bayonet and clip fastener. Length: 2.5 m.	<input type="checkbox"/>
Suction hose, oil-resistant	41	2.889-140.0 Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	<input type="checkbox"/>
Electrically conductive suction hose	42	2.889-142.0 Suction hose, electrically conductive, with new bayonet and clip fastener. 2.5 m long.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



		Order no.	Description	
SUCTION HOSES				
Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)				
Extension hose packaged NW40 2.5m	43	2.889-146.0	Extension hose for new clip system ID 40. Length: 2.5 m.	<input type="checkbox"/>
Repair set NW40	44	2.889-150.0	Repair kit ID 40 for the new clip system.	<input type="checkbox"/>
Hose connection				
Adapter, DN 32/35, with internal thread	45	6.902-077.0	Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	<input type="checkbox"/>
Adapter, DN 40 with internal thread	46	6.900-286.0	Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	<input type="checkbox"/>
Suction hoses with clip system 1.0 (compatible with vacuum cleaners up to model year 2016)				
Repair set, C 40	47	2.639-873.0	Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	<input type="checkbox"/>
Extension hose, C 40	48	6.906-344.0	2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	<input type="checkbox"/>
Suction hose	49	4.440-678.0	4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accessory end. Without module.	<input type="checkbox"/>
Suction hose (clip system), C 40, 10 m	50	6.906-279.0	10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	<input type="checkbox"/>
Suction hose	51	6.906-321.0	4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	<input type="checkbox"/>
	52	6.906-714.0	With bayonet and clip connection.	<input type="checkbox"/>
Suction hose complete (Clip-system), C ID 40, 4 m, el.	53	4.440-728.0	With bend and module (4.060-533.0), electrically conductive.	<input type="checkbox"/>
Suction hose (Clip-system), C 40, 16 m	54	6.906-635.0	With bayonet and clip connection.	<input type="checkbox"/>
Suction hose (clip system), C 40, 10 m, el.	55	6.906-877.0	Suction hose with bayonet coupling, electrically conductive.	<input type="checkbox"/>
Suction hoses with cone connection				
Suction hose, complete	56	4.440-263.0	Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



	Order no.	Description	
SUCTION HOSES			
Suction hoses with cone connection			
Suction hose complete, ID 40, 4 m, oil-resistant.	57 4.440-303.0	Oil-resistant.	<input type="checkbox"/>
Suction hose, complete	58 4.440-463.0	Electrically non-conductive 10.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	<input type="checkbox"/>
Suction hose complete	59 4.440-466.0	Electrically conductive, 10.0m, ID 40	<input type="checkbox"/>
Suction hose complete, ID 40, 10 m, oil-resistant	60 4.440-612.0	Oil-resistant.	<input type="checkbox"/>
Suction hose, complete	61 4.440-264.0	4 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.	<input type="checkbox"/>
Suction hose complete, ID 61, smooth inside	62 4.440-328.0	Industrial hose, PVC/elastomer with steel spiral, smooth inside.	<input type="checkbox"/>
Suction hose, complete, DN 61, 10 m	63 4.440-467.0	10 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.	<input type="checkbox"/>
Suction hose complete, ID 61, 4 m, oil-resistant	64 4.440-613.0	Oil-resistant.	<input type="checkbox"/>
Suction hose complete, ID 61, 4 m, el.	65 4.440-616.0	Electrically conductive.	<input type="checkbox"/>
FILTER BAGS			
Fleece filter bags (3 ply)			
Fleece filter bags, 5 × , NT 65, NT 70, NT 72, NT 75	66 2.885-753.0		<input type="checkbox"/>
Paper filter bags			
Paper filter bags, 5 × , NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC	67 6.904-285.0	5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	<input type="checkbox"/>
FILTER T/ NT			
Flat pleated filter HEPA, dust class H			
HEPA surface filter	68 6.904-364.0	HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	<input type="checkbox"/>
Special filter bags, wet filter bags			
Special filter bags, wet filter bags	69 6.904-252.0	Approved for dust class L, general cleaning, wet and dry, tear-resistant.	<input type="checkbox"/>
Plastic sacks for dust-free disposal			
Plastic bag for dust-free disposal, 10 × , NT 65, NT 70, NT 72, NT 75, NT 602, NT 700, NT 702	70 6.900-698.0	PE plastic sack.	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



		Order no.	Description	
FILTER T/ NT				
Membrane filter / fabric filter				
Candle Filter - Wood, NT 65/2, NT 75/2	71	2.414-003.0		<input type="checkbox"/>
Membrane filter, NT 65, NT 70, NT 72, NT 75, NT 551, NT 602, NT 700, NT 702, NT 802, NT 993	72	6.904-282.0	Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	<input type="checkbox"/>
CONNECTING SLEEVES				
Y-adapter kit				
Y-adapter kit	73	2.637-217.0	Plastic distributor - suitable for NT vacuum cleaners.	<input type="checkbox"/>
Connecting sleeve C-DN (clip on taper), EL (electroconductive)				
Connection cone NW35	74	5.407-005.0		<input type="checkbox"/>
Connection cone NW40	75	5.407-006.0		<input type="checkbox"/>
C-ID 35 adapter	76	5.407-112.0	Connects C 35 hose for ID 35, electrically conductive.	<input type="checkbox"/>
C 40 adapter	77	5.407-109.0	Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
C-DN 40 adapter	78	5.407-111.0	Connects C 40 hose for ID 40, electrically conductive.	<input type="checkbox"/>
Adapter for electric power tools, clip on, el.				
Sleeve for tool C35EL	79	5.453-042.0	3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
Adapter for electric power tools, C 35, el.	80	5.453-048.0	Inner Ø 25.4 mm, outer Ø 34.6 mm/ 38 mm, el. Only NT-vacuums.	<input type="checkbox"/>
	81	5.453-050.0	Inner Ø 27 mm, outer Ø 36.5 mm/ 38.8 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Adapter for electric power tools, screwable				
Power tool adapter, threaded, DN 35	82	5.453-016.0	3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	<input type="checkbox"/>
Adapter for electric power tools, screwable, ID 35	83	5.453-026.0	Inner Ø 28.6 mm, outer Ø 37.3/38.8 mm.	<input type="checkbox"/>
Power tool adapter, threaded, DN 35	84	6.902-059.0	Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	<input type="checkbox"/>

Available accessories.

EQUIPMENT FOR NT 75/2 TACT² ME TC

1.667-289.0



	Order no.	Description		
CONNECTING SLEEVES				
Adapter for electric power tools, screwable				
Power tool adapter, threaded, DN 35	85	6.902-095.0	2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	<input type="checkbox"/>
Reducing sleeves				
Reducer	86	5.407-108.0	Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
	87	6.902-017.0	Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	<input type="checkbox"/>
Sleeve C40 / C35	88	5.407-113.0	Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	<input type="checkbox"/>
Reducer from ID 35 to 32	89	6.902-072.0	Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	<input type="checkbox"/>
Set reducing / extension sleeves				
Set reducing / extension sleeves	90	2.860-117.0	ID 40/35, ID 35/32 (tube -> nozzle), plastic.	<input type="checkbox"/>
TARGET GROUP SPECIFIC VACUUM CLEANER ACCESSORY SETS				
Professional cleaning kit ID 40	91	2.637-353.0	Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	<input type="checkbox"/>
Chip cleaning kit	92	2.640-760.0	Individual parts: suction hose 4 m, oil-proof (4.440-613.0), crevice tool (6.900-222.0), rubber suction nozzle angled at 45° (6.902-106.0).	<input type="checkbox"/>
OTHER ACCESSORIES FOR T AND NT				
CS 40 Me	93	2.863-026.0	The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	<input type="checkbox"/>
Adapter connection old elektr. leitend	94	5.031-436.0		<input type="checkbox"/>
UBS NON-CONDUCTIVE MEDIA				
Add-on kit nonconducting media NT Tact ²	95	2.642-602.0	For switching off when vacuuming non-conductive fluids such as oils and greases	<input type="checkbox"/>
EMPTYING SUPPORTS				
Shaving baskets				
Chip sieve	96	5.731-645.0	Plastic, perforates with internal thread. Protection of the drain hose from rough splinters, chips etc.	<input type="checkbox"/>

Available accessories.