



HD 5/12 C

Convenient, mobile, versatile: the HD 5/12 C cold water high-pressure cleaner for vertical and horizontal operation. With accessory storage, brass cylinder head and automatic pressure relief.









1 Mobility

- The integrated carrying handle on the front of the machine enables easy loading and convenient transport.
- Push handle can be retracted at the push of a button.

2 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on during horizontal operation. As such, the machine offers maximum stability.





- Screw connections (M 18 \times 1.5) for storing surface cleaner directly on the machine.
- Practical nozzle compartments for triple nozzle and rotary nozzle.

Quality 4

- The automatic pressure relief protects the components and extends the service life of the machine.
- High-quality brass cylinder head.

TECHNICAL DATA AND EQUIPMENT



HD 5/12 C

Automatic pressure relief

- For horizontal and vertical operation
- Save time and effort: EASY!Force high-pressure gun and EASY!Lock
- quick-release couplings.

Technical data		
Order no.		1.520-120.0
EAN code		4039784607446
Current type	Ph / V / Hz	1 / 230 / 50
Flow rate	l/h	500
Working pressure	bar / MPa	120 / 12
Max. pressure	bar / MPa	175 / 17.5
Max. inlet temperature	°C	up to 60
Connection load	kW	2.5
Weight	kg	23.7
Dimensions (L × W × H)	mm	380 × 360 × 930
Equipment		
Equipment Spray gun		Easy Press trigger gun
		Easy Press trigger gun
Spray gun	m	Easy Press trigger gun I 10 / DN 6, 250 bar
Spray gun Spray gun with soft grip	m mm	8
Spray gun Spray gun with soft grip High-pressure hose		■ 10 / DN 6, 250 bar
Spray gun Spray gun with soft grip High-pressure hose Spray lance		 10 / DN 6, 250 bar 850
Spray gun Spray gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°)		 10 / DN 6, 250 bar 850 Manual
Spray gun Spray gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°) ANTI!Twist		10 / DN 6, 250 bar 850 Manual -

KARCHER

1













10-11

12	13



Т

		Order no.	ID	Max. working pressure	Length	Price	Description
Standard with unions on both side	s						
High-pressure hose, 10 m, ID 8, 315 bar, extension	1	6.391-342.0	ID 8	315 bar	10 m		To extend the operating radius with the high-pressure clean- er. Connection on both sides M22 x 1.5.
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling		6.390-010.0	ID 8	315 bar	15 m		With screw connections on both sides, M 22 x 1.5 with bend protection.
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	3	6.390-031.0	ID 8	315 bar	20 m		Screw connections at both ends, M 22 x 1.5, with kink pro- tection.
High-pressure hose, 30 m, ID 8, incl. rotary coupling	4	6.390-293.0	ID 8	315 bar	30 m		To extend the operating radius with the high-pressure clean- er. Connection on both sides M22 x 1.5.
Longlife 400 with unions on both s	ides						
High pressure hose ID 6, 10 m, including rotary coupling	5	6.391-883.0	ID 6	400 bar	10 m		With rotary coupling, 2 x M 22 x 1,5
High-pressure hose Longlife 400, 10 m, ID 8, extension	6	6.391-354.0	ID 8	400 bar	10 m		To extend the operating radius with the high-pressure clean- er. Connection on both sides M22 x 1.5.
High-pressure hose Longlife 400, 15 m, ID 8, including rotary cou- pling	7	6.389-709.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 30 m, ID 8, including rotary cou- pling	8	6.390-294.0	ID 8	400 bar	30 m		
High-pressure hose 1.5 m, ID 8, including connectors	9	6.390-178.0	ID 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).
Food industry version with unions	on bot	h sides					
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	10	6.389-479.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.
High-pressure hose, 20 m, ID 8, suitable for food industry, exten- sion piece	11	6.389-581.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.
Longlife food design with screw co	nnecti	ons at both ends					
High pressure hose food ID 8, 10 m	12	6.391-864.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate-
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	13	6.391-887.0	ID 8	400 bar	20 m		rial. With rotary coupling, 2 x M 22 x 1,5
Standard							
High-pressure hose, 10 m, ID 6, AVS trigger gun connector	14	6.391-238.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 6/155°C/250 bar.
High-pressure hose, 15 m, ID 6, AVS gun connection	15	6.391-394.0	ID 6	250 bar	15 m		With patented AVS trigger gun connection (rotatable) and hand screw connection, M 22 x 1.5 with kink protection.
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connec- tion	16	6.391-875.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (piv- ot-mounted) and hand screw union. M 22 x 1.5 with an- ti-kink protection. NW 6/155°C/300 bar
High-pressure hose, 10 m, ID 8, AVS trigger gun connector	17	6.390-025.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 15 m, ID 8, AVS trigger gun connector	18	6.390-185.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

KARCHER

HD 5/12 C 1.520-120.0



		Order no.	ID	Max. working pressure	Length	Price	Description
High-pressure hose, 20 m, ID 8, AVS trigger gun connector	19	6.390-171.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.
Longlife 400							
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	20	6.391-882.0	ID 6	400 bar	10 m		With patented AVS connection in the trigger gun (piv- ot-mounted).
High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun con- nection	21	6.391-351.0	ID 8	400 bar	10 m		With patented AVS connection in the trigger gun (rotatable) and hand screw connection, M 22 x 1.5 with kink protection With double steel reinforcement.
High-pressure hose Longlife 400, 20 m, DN 8, AVS trigger gun con- nector	22	6.390-208.0	ID 8	400 bar	20 m		20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.
Food industry version							
High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food, grey	23	6.390-704.0	ID 8	250 bar	10 m		Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar
High-pressure hose, 20 m, ID 8, AVS trigger gun connector, suitable for food industry, grey	24	6.390-705.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar.
Longlife food design							
HIgh-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun con- nection	25	6.391-885.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate- rial. With patented AVS connection in the pistol (pivot
HIgh-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun con- nection	26	6.391-886.0	ID 8	400 bar	20 m		mounted)
Special hoses							
High-pressure hose, 1.5 m, ID 8, incl. connection parts, curved outflow	27	6.388-886.0	ID 8	400 bar	1.5 m		Connection hose in longlife quality with 2x M22 x 1.5, with angled connection on one side.

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



		Order no.	Flow rate			Price	Description	
Easy Press high-pressure trigger g	un with	holding force re	duction (Kärcher	patent)				
Easy Press HP trigger gun with soft grip	1	4.775-463.0					Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.	-
Trigger guns								
High-end HP trigger gun	2	4.775-823.0					High-end spray guns with optimised flow. Small pressure losses also with water volumes up to 2500 l/h. Robustness and durability for professional use. Food-safe and saltwa- ter-resistant materials offer the best conditions for use in the food sector and in industry. Connector for HP hoses M 22 × 1.5.	
Quick connect			·					
Quick coupling	3	6.401-458.0					For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.	
Male coupling	4	6.401-459.0					Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread.	

KARCHER

1 2		3		4	5	
8 9		10				
		Order no.	Max. working pressure	Length	Price	Description
Rotating spray lances Spray lance, 840 mm, rotatable	1	4,760-663.0	300 bar	840 mm		850 mm stainless steel lance (manual coupling) with ergo-
Spray lance, 640 mm, rotatable	T	4.700-003.0	500 bai	840 11111		nomic handle for ease of use and protection. Rotatable 360°
600 mm spray pipe, rotatable	2	4.760-664.0	300 bar	600 mm		600 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
1050 mm spray pipe, rotatable	3	4.760-660.0	300 bar	1050 mm		1050 nm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
1550 mm spray pipe, rotatable	4	4.760-661.0	300 bar	1550 mm		1550 nm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
2050 mm spray pipe, rotatable	5	4.760-662.0	300 bar	2050 mm		2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
Spray lance	_	4769 667 9	1	250		
250 mm lance, non-rotatable	6	4.760-667.0		250 mm		250 mm stainless steel lance. With manual coupling. Non-ro- tatable.
Angular spray lance Spray lance for toilets and rain gutters	7	4.760-073.0				Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance High-pressure M18x1.5 articulated joint	8	4.481-039.0	300 bar			High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.
Gutter cleaner Gutter cleaning lance	9	2.642-305.0				The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.
Undercarriage spray lance		l	I	l		can be created without removing the cover plates.
Underbody lance	10	4.760-245.0		700 mm		Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.

Included in the scope of supply. \Box Available accessories. \blacktriangle Extension hose.



Triple permise		Order no.	Max. working pressure	Nozzle size		Price	Description
Triple nozzles				0.5		1	
Triple nozzle 035	1	4.767-212.0	300 bar	35			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5.
Dirt Blaster, small							
Dirt blaster - more Performance	2	4.767-230.0	180 bar	35			The new performance dirt blaster (nozzle size 035) with rotating point jet makes a big difference: up to 50% higher cleaning and area performance than its predecessor.
Dirt blaster, large							
Dirt blaster	3	4.763-931.0	300 bar	35			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



	Order no.	Nozzle size				Price	Description
1	2.885-225.0	36					Flat stream for stubborn contaminations.
2	2.885-255.0	35					Flat stream for large area performance and stubborn dirt.
3	2.884-521.0	250					Brass power nozzle for low pressure operation and cleaning agent suction.
	-	1 2.885-225.0 2 2.885-255.0	1 2.885-225.0 36 2 2.885-255.0 35	1 2.885-225.0 36 2 2.885-255.0 35	1 2.885-225.0 36 2 2.885-255.0 35	1 2.885-225.0 36 2 2.885-255.0 35	1 2.885-225.0 36 2 2.885-255.0 35

KARCHER

HD 5/12 C 1.520-120.0



		Order no.	Max. working pressure	Nozzle size	Diame- ter	Price	Description
Pipe cleaning hose, ID 6							· · · · · · · · · · · · · · · · · · ·
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	1	6.390-028.0	120 bar				The 20 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	2	6.390-029.0	120 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	3	6.390-030.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).
Pipe cleaning nozzle							
Pipe cleaning dirt blaster D21/040	4	4.765-001.0		40	21 mm		The forward-tilted rotating pencil jet removes the most
Pipe cleaning dirt blaster D30/040	5	4.765-004.0		40	30 mm		stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient han- dling.
Pipe cleaning nozzle	6	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.
-	7	5.763-017.0		50	30 mm		Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" □ connection, 3 x 30° backwards, diameter 30 mm.)
Rotating pipe cleaning nozzle	8	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.

KARCHER



		Order no.	Flow rate	Nozzle size	Diame- ter	Price	Description	
FR Classic surface cleaner								
FR Classic surface cleaner	1	2.643-476.0					The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.	
Hard Surface Cleaner FRV 30								
FRV 30 surface cleaner	2	2.642-999.0					With the integrated and automatic suction of the dirty wa- ter, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately.	
Hard surface cleaner FR 30								
Surface Cleaner FR 30	3	2.642-997.0			300 mm		Up to 10 times greater area coverage compared with the conventional high pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for ergonomic handling and integrated parking position. Machine specific nozzle kit must be ordered separately.	
FR 30 Me surface cleaner								
Hard surface cleaner FR 30 Me	4	2.640-355.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kits for FR	1							
Nozzle kit for surface cleaners	5	2.640-401.0	500 - 650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	
Machine-specific nozzle kits for FR	Classi	c						
Nozzle kit for FR Classic 034	6	2.885-313.0		34			Nozzle kit specifically for FR Classic surface cleaner.	
FRV 30 Me surface cleaner								
FRV 30 Me	7	2.642-911.0					Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	

Included in the scope of supply. \Box Available accessories. \blacktriangle Extension hose.



		Order no.	Flow rate			Price	Description
Cup foam lance		I		1	 		
Cup foam lance Advanced 042	1	6.394-969.0					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its com- pact design.
Inno Foam Kit							
Inno Foam Set with detergent injector	2	2.640-151.0					High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set							
Easy Foam Set with RM injector	3	2.640-691.0					HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set							
Nozzle kit 055 for Inno / Easy Set 500-600 l/h	4	2.640-870.0	500 - 600 l/h				Optimal adaptation to different machine outputs for eco- nomic use.
Foam nozzle mounting kit							
Foam nozzle attachment kit	5	2.637-926.0					Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

KARCHER

			?	4	5		
		Order no.			Price	Description	
Coupling		4.403-002.0				For every dispetto dispertice betting cell for electric sector	
Coupler -2 × M22 × 1,5	1	4.405-002.0				For overriding the dismantled heating coil for cleaningalter- native:4.111-029.0 adapter 1 - hose old / hose new	
Connector	1 -		1				
Nozzle screws / screw socket	2	4.402-022.0				Nozzle connector/screw connector for connecting high-pres- sure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
Adapters		· · · ·					
Sealing cone complete	3	4.424-004.0				In order to install high-pressure hose with male coupling on thread with M22 x 1.5 Alternative:4.111-032.0 Adapter 4 - Device new / Hose old Swivel	
EASY!Lock adapter							
Adapter 1 M22AG-TR22AG	4					Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	5	4.111-030.0				Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	6	4.111-031.0				Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 4 TR22IG-D11	7	4.111-032.0					
Adapter 5 TR22IG-M22AG	8	4.111-033.0				Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	9	4.111-034.0				Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	10	4.111-035.0				Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	11	4.111-036.0				Adapter 8 to connect the new spray lance with the old	



		Order no.	Length		Price	Description
Automatic, self-winding hose reels	for wa	all mounting				
Powder-coated swivel holder	1	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.



		Order no.	Nozzle size		Price	Description	
Wet blasting attachment (without n	ozzle)						
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. Without flow control.	
Nozzle kits for wet jet unit							
Nozzle kit for wet jet unit 035	3	2.638-526.0	30			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment per- formance. Only in combination with wet blasting attachmen 4.762-010/-022.	

		Order no.			Price	De- scrip- tion	
Geka coupling	L	I	1		1		
Geka connector with hose barb, R 3/4"	1	6.388-455.0				with hose liner	
Geka connector with inner thread, R 3/4"	2	6.388-473.0				with female thread	
Suction filter		1		1			
Suction filter with check valve	3	4.730-012.0				Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter		4 700 400 0	1	1	1	e:	
Water fine filter, with adapter	4	4.730-102.0				Fine- mesh water filter, 125 µm, max. temper- ature 50°C. Protects the	
Water supply hose		1	1				
Water supply hose	5	4.440-038.0				NW 13 R1" / R 3/4", up to 30 °C	
Backflow check valve			1	1	1		
Backflow preventer	6	2.641-374.0				To pre- vent deter- gent getting into the drinking water cycle in case of inlet at	







		Order no.		Price	De- scrip- tion	
Other HP Accessories						
Starting current limiter	7	2.637-495.0			Reduces starting current in sin- gle- phase supply and protects line fuse.	
Coin remote control	8	2.644-029.0			Coin remote control with electron- ic coin acceptor for connect- ing a	

HD 5/12 C, 1.520-120.0, 2020-07-24



		Order no.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.762-497.0				The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.
Rotating washing brush						· · · · · · · · · · · · · · · · · · ·
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.762-561.0	500 - 800 l/h			The rotating wash brush gently removes fine dust and traf- fic film from all surfaces. Temperature resistant up to 60° C. (M 18 x 1.5, replaceable brush insert).
Rotating wash brush for < 800 l/h machines, natural bristles	3	4.762-560.0	500 - 800 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18 x 1.5 (replaceable brush insert).