

PGG 3/1

Reliable PGG 3/1 synchronous petrol-powered generator with 2.8 kW output, puncture-proof wheels and 15 l tank. For use on the go for up to 12 hours of operation without external power sources.



Order no. 1.042-207.0

- Convenient electric start function with key switch
- Foldable push handle and puncture-proof tyres
- Robust cage frame

Technical data

EAN code		4054278547923
Supply voltage	Ph / V	1 / 230
Sound pressure level	dB(A)	74
Rated performance	kW	2.8
Power	kW	3
Drive type		Petrol
Cubic capacity	cm³	208
Engine rating	kW / hp	4 / 5.4
Fuel consumption	l/h	2.3
Tank capacity	l	15
Runtime at 50% output	h	12
Runtime at 100% output	h	6.5
Weight incl. packaging	kg	56.1
Weight without accessories	kg	51.7
Dimensions (L × W × H)	mm	645 × 622 × 549

Equipment

Operating state display	■
DC output (12 V)	■
Protection class IP 23	■
Low oil and overload protection	■
Fuel gauge	■
Single phase socket type F (Schuko)	■
Automatic Voltage Regulation (AVR)	■
■ Included in the scope of supply.	



Extraordinary ease of use

- High mobility thanks to the foldable push handle and puncture-proof wheels.
- Electro start function for the convenient and quick start of the petrol engine.



Ultimate reliability and safety

- With overload and oil shortage protection as well as tubular steel frame for maximum safety.
- With automatic voltage regulator (AVR) for the operation of sensitive electronic devices.



Operation of Kärcher high-pressure cleaners

- Enables the use of high-pressure cleaners in areas without external power supply.
- Suitable for selected single-phase high-pressure cleaners.