

PGG 6/1

With a power rating of 5 kW, the petrol-operated synchronous generator PGG 6/1 impresses with up to 10 hours of independent power supply in many commercial and municipal applications.



V
Stage V



Order no. 1.042-208.0

- Convenient electric start function with key switch
- Robust cage frame

Technical data

EAN code		4054278547930
Power supply	Ph / V	1 / 230
Sound pressure level	dB(A)	75
Nominal power	kW	5
Power	kW	5.5
Drive type		Petrol
Displacement	cm ³	390
Motor rating	kW / hp	8.5 / 11.6
Fuel consumption	l/h	3.8
Tank capacity	l	25
Runtime at 50% output	h	10
Runtime at 100% output	h	6.5
Weight incl. packaging	kg	92.4
Weight without accessories	kg	84.7
Dimensions (L × W × H)	mm	743 × 713 × 670

Equipment

Operating state display	■
DC output (12 V)	■
Protection class IP 23	■
Low oil and overload protection	■
Fuel gauge	■
2 single phase sockets type F (Schuko)	■
Single phase CEE socket (32 A)	■
Automatic Voltage Regulation (AVR)	■

■ included in the scope of supply.



Extraordinary ease of use

- Puncture-proof wheels guarantee permanently high mobility.
- Electro start function for the convenient and quick start of the petrol engine.



Ultimate reliability and safety

- With automatic voltage regulator (AVR), which supplies a largely constant voltage.



Very powerful

- 230 V synchronous generator reliably provides continuous power of 5.5 kW.
- Powerful petrol engine for applications of min. 6.5 hours per tank filling.