# HDS 10/20-4 M

HDS 10/20-4 M - the most powerful 3-phase hot water high-pressure cleaner in the Kärcher middle class. With 4-pole, water-cooled electric motor, 2 cleaning agent tanks, service electronics.













Order no.


1.071-900.0

- Economical eco!efficiency mode
- 2 cleaning agent tanks
- Three-phase motor: water-cooled

_		
Technical data		
EAN code		4054278134925
Supply voltage	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	500 - 1000
Working pressure	bar / MPa	30 - 200 / 3 - 20
Temperature (for supply 12 °C)	°C	min. 80 - max. 155
Connected load	kW	7.8
Consumption of heating oil or gas at full load	kg/h	6.4
Consumption of heating oil in eco!efficiency mode	kg/h	5.1
Power cable	m	5
Fuel tank	1	25
Weight (with accessories)	kg	168
Weight incl. packaging	kg	180
Dimensions (L × W × H)	mm	1330 × 750 × 1060

Equipment		
Cleaning agent function		20 + 10 l tank
Spray gun		EASY!Force Advanced
High-pressure hose length	m	10
High-pressure hose type		Longlife
Spray lance	mm	1050
Power nozzle		
ANTI!Twist		
Tanks for cleaning agents, calcification protection and fuel that can be filled from the outside		•
Control bar with display light		
Pressure switch-off		
Pole reverse plug (3~)		
Service electronics with LED display		
Servo control		•
2 cleaning agent tanks		
Dry-running protection		

■ Included in the scope of supply.






#### **Economic efficiency**

- In eco!efficiency mode, the machine operates in the most economical temperature range (60 °C) – with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full load operation.



#### Maximum efficiency

- Proven and highly efficient burner technology.
- 4-pole electric motor with 3-piston axial pump.
- Water-cooled motor for a high performance and long service life.



#### **Operational safety**

- The large, integrated water fine filter reliably protects the high-pressure pump against small dirt particles.
- The integrated exhaust gas thermostat switches off the drive motor if the emission temperature exceeds 300 °C.
- The Soft Damping System (SDS) compensates for vibration and pressure peaks in the high-pressure system.



























14

				Т
		Order no.	Description	
TRIGGER GUNS				
Spray guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo control		'		
Servo Control, 750 l/h - 1100 l/h	5	4.118-008.0	Water quantity and pressure regulated directly from the hand spray gun.	-
SPRAY LANCES	1			
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
LED nozzle light	7	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	Г

lacksquare Included in the scope of supply.  $\qed$  Available accessories.























				Т
		Order no.	Description	
SPRAY LANCES				Ė
Double lance				
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance				
Spray lance for toilets and rain gutters	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from $20^\circ$ to $140^\circ$ , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	1 [
Undercarriage spray lance				
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power nozzle 25°, 052	22	2.113-024.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	•
HP nozzle spray angle 0°				
Power nozzle 0°, 055	23	2.113-035.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°		'		
Power nozzle 15°, 055	24	2.113-047.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 40°	-			Ť
Power nozzle 40°, 055	25	2.113-055.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				Т
High-pressure hose Longlife, 10 m, ID 8, 400 bar, $2 \times EASY!Lock$	26	6.110-038.0	Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure.	ľ
High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock	27	6.110-024.0	1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure.	
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock	28	6.110-023.0	Robust high-pressure hose with double steel core, ANT!!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.

















		Order no.	Description	
HIGH-PRESSURE HOSES		<u> </u>		
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock	29	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock	30	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	
Standard with unions on both sides	-	<b>'</b>		
High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock	31	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock	32	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANT!!Twist and 10 m long.	
High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock	33	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock	34	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock	35	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	
High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock	36	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10).	: [
High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock	37	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock	38	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock	39	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	
High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock	40	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock	41	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	
Food industry version with unions on both side	es	•		
High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock	42	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends.	

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.

























		Order no.	Description	
HIGH-PRESSURE HOSES				
Food industry version with unions on both side		1		Ļ
High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock	43	6.110-052.0	Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections.	
Longlife food design with screw connections at	both	ends		
High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	44	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTIITwist and EASY!Lock hand screw connection at both ends.	[
Special hoses				
High-pressure hose curved, 1.5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	45	6.110-068.0	For connection to hose reels: high-pressure hose, with M $22 \times 1.5$ connection and curved EASY!Lock hand screw connection. $1.5$ m long, suitable for up to 400 bar working pressure.	K [
WEED CONTROL				
WR 50	46	2.114-013.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	47	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	[
WR 100	48	2.114-015.0	Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	[
WR 10	49	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	[
QUICK CONNECT				Ť
Quick coupling	50	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M $22 \times 1.5$ internal thread.	[
Male coupling	51	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M $22 \times 1.5$ external thread.	[
DRUM AND TANK CLEANING				
Add-on kit mud sucker	52	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	[
OTHER HP ACCESSORIES				
Jet gun	53	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	[
FLUE PIPE				Ė
Flue gas adapter	54	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for	[
	55	4.656-080.0	connection to a stack system).	I
DICHTUNGEN FÜR TR-GEWINDE				t
Gasket set with 9x O-rings for TR thread	56	2.880-001.0		Ti

 $<sup>\</sup>hfill \square$  Available accessories.

























		Order no.	Description	
ROTARY NOZZLES (DIRT BLASTERS)				Ė
Dirt blaster, large				
Dirt blaster, large, 055/060	57	4.114-036.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzli and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e [
MULTIPLE-JET NOZZLES				
Angled vario nozzle 0-90°				
Angled Vario nozzle, 055	58	4.113-008.0	Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.	f
STEAM JET NOZZLE / NOZZLE PROTECTOR / RO	DLLOV	ER NOZZLE		
Steam jet nozzles				
Steam jet nozzle 50°	59	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
Steam jet nozzle 40°, 080	60	2.114-008.0	Brass steam nozzle for operation of the HDS in steam stage.	
Rollover nozzle holder		<u> </u>		
Owner of jets double brass	61	4.764-012.0	Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).	: [
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	62	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	63	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	64	6.110-008.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	65	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle		I.		Ė
Pipe cleaning dirt blaster D21/060	66	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Pipe cleaning dirt blaster D30/060	67	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.	
Pipe cleaning nozzle 120	68	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	69	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	70	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	

 $<sup>\ \</sup>square$  Available accessories.





























		Order no.	Description	
PIPE CLEANING	<u>'</u>			T
Pipe cleaning nozzle				
Pipe cleaning nozzle	71	5.763-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	72	6.415-440.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Hose fastening attachment kit	73	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Dirt trap attachment kit	74	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
FR 30 Me surface cleaner				Ť
Hard Surface Cleaner FR 30 Me	75	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50				
Surface Cleaner FR 50 Me	76	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kits for FR		·		
Nozzle kit for FR, 850 l/h - 1100 l/h	77	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FRV		I.		
Nozzle kit for FRV, 080	78	2.642-982.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
FRV 30 Me surface cleaner		I.		
FRV 30 Me Surface Cleaner	79	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Extension hose FRV 30 Me and FRV 50 Me	80	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
Surface Cleaner FR 50 Me				
FRV 50 Me surface cleaner	81	2.111-024.0	Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C.	
FOAM SYSTEMS Cup foam lance				
Cup foam lance Advanced 3, 900 l/h - 2500 l/h	82	4.112-065.0	Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher.	
Cup foam lance DUO Advanced 3, 900 l/h - 2500 l/h	83	4.112-069.0	DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank.	
Cup foam lance Basic 3, 900 l/h - 2500 l/h	84	4.112-055.0	High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality.	



























		01	Bernitation	
FOAM SYSTEMS		Order no.	Description	J
FOAM SYSTEMS				_
Cup foam lance	1	1	I=	1
1-litre cleaning agent container for cup foam lance basic	85	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	
1-litre cleaning agent container for cup foam lance advanced	86	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Kit				İ
Inno Foam Set with detergent injector	87	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or	
Inno Foam Set	88	2.112-008.0	disinfection.	
Easy Foam Set				Ī
Easy Foam Set with RM injector	89	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine	
Easy Foam Set	90	2.112-011.0	onlinection to lance and he chemical injector with precision 6-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set		<b>'</b>		ľ
Nozzle kit 110 for Inno / Easy Set 1,000-1,300 l/h	91	2.111-020.0	Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.	
Foam nozzle mounting kit				Ť
Foam nozzle attachment kit	92	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
Cleaning agent injector				Ī
Cleaning agent injector for high and low pressure (without nozzles)	93	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Cleaning agent injector for high pressure (without nozzle)	94	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Stainless steel injector kit for HDS 10/20-4M	95	6.645-762.0	Developed for the HD 10/20-4 M High-pressure cleaner, the stainless steel injector ensures optima cleaning agent dosage. Supplied with suction hose and filter.	I
Machine-specific nozzle kit with order no. 4.63	7-033	3.0		1
Nozzle kit 1000-1200 l/h	96	4.769-013.0	For HD/HDS 1000 – 1200 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 4.637-032.0				Ī
Nozzle insert up to 1,100 l/h - high pressure	97	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low pressure	98	4.769-001.0	For low pressure with machines up to 1.100 l/h	-

<sup>☐</sup> Available accessories.































		Order no.	Description	
COUPLING PARTS		Graci iio.	Securitaria	+
Rotary coupling				
Rotary coupling	99	4.111-021.0	Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector				
Screw socket for surface cleaners and Servo Control controllers	100	4.111-022.0	For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) – $1 \times$ M $22 \times 1.5/1 \times$ M $18 \times 1.5$ .	
Y distributor	101	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	102	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	ot 🗆
EASY!Lock adapter		<b>'</b>		
Adapter 1 M22AG-TR22AG	103	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	104	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	105	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 4 TR22IG-D11	106	4.111-032.0	Adapter 4 to connect the new gun with the old swivel hose	
Adapter 5 TR22IG-M22AG	107	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	108	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	109	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	110	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Adapter hose extension 9 TR	111	4.111-037.0	Adapter 9 to connect the new hose with the new hose	
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 × 1.8 AG	112	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	

<sup>☐</sup> Available accessories.





























				_
		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels for wall mo	untin	3		
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	113	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	: 🗆
Automatic hose reel, powder-coated steel / plastic, 20 m	114	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	115	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	116	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	117	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	118	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	119	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Zinc-coated swivel holder	120	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	121	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Automatic, self-winding hose reel attachment l	kit			
Attachment kit automatic hose reel HDS M/S	122	2.110-011.0	Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	
Attachment kit automatic hose reel holder HDS M/S	123	2.110-020.0	Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	124	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	125	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	126	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0), Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	

 $<sup>\</sup>hfill\square$  Available accessories.

























				$\overline{}$
		Order no.	Description	
FACADE AND SOLAR PANEL CLEANIN	G			
Brushes				
Roller brush 500 medium	127	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	128	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	129	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	130	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	131	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
iSolar 800 Advanced	132	6.368-094.0	isolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	, [
iSolar 400 Advanced	133	6.368-092.0	isolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.	
Telescopic lances				
TL low pressure adapter	134	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	135	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	136	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. [
Telescopic lance TL 10 H	137	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	138	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	139	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	140	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	

 $<sup>\</sup>hfill \square$  Available accessories.





















		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Water softening				
WS 50	141	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS 100	142	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS Regenerator	143	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening unit WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s [
Hoses				
iSolar HP hose 7	144	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 10	145	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 14	146	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters				
iSolar fall protection	147	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	148	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	149	4.115-006.0	Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling.  Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation	
Nozzle kits for wet jet unit		•		
Nozzle kit for wet jet unit 055	150	2.112-024.0	Consisting of wet jet nozzle and nozzle insert – only for use in combination with wet jet unit 4.115-000.0   4.115-006.0.	
Boron carbide nozzle				
Boron carbide nozzle, for machines up to 1,000 l/h	151	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Barrel cleaner BC 14/12	152	2.112-020.0	The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres.	
Spray head HKF 30/14-E	153	6.751-061.0	Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor.	
Nozzle kit for spray head HKF 50 (3.631-009.0	/ 3.6	31-039.0)		
Nozzle 045 for 2-nozzle operation HKF 50	4 = 4	6.415-446.0	Nozzle for dual-nozzle operation	

<sup>☐</sup> Available accessories.

























				Т
		Order no.	Description	
DRUM AND TANK CLEANING		010011101		_
Nozzle kit for spray head HKF 50 (3.631-009.0	/ 3.63	31-039.0)		Т
High-pressure full jet nozzle 090 for interior cleaning heads	155	6.415-447.0	High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread.	
Double grip for precise control of spray head	156	2.863-036.0	Double handle. Precise control of the spray head	
1/8" screw plug for interior cleaning heads	157	5.411-061.0	Screw plug for high-pressure interior cleaning heads with 1/8-inch thread.	T
ADD ON KITS				Ė
Attachment kit for transport				
Transport eyelet attachment kit	158	2.644-053.0	Robust transport eyelet attachment kit for the secure fixing of HDS Medium and Super Class pressure washers during transport.	
Flame monitoring attachment kit				
Flame monitoring attachment kit for HDS Middle and Super Class	159	2.641-796.0	More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	
Accumulator kits				
Pressure tank attachment kit for HDS Middle and Super Class	160	2.641-803.0	The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system.	
Remote control set	,			Ī
Remote control attachment kit for HDS Middle and Super Class	161	2.642-157.0	Remote control for the machines of the HDS Middle and Super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting to a wall.	
Coin-op remote control	•	•		Ī
Coin remote control attachment kit for HDS Middle and Super Class	162	2.642-158.0	Retrofittable coin acceptor for machines in the HDS Middle and Super class for self-service operation. For installation on the machine.	
WATER CONNECTION				
Geka coupling				
Geka connector with hose barb, R 3/4"	163	6.388-455.0	with hose liner	
Geka connector with hose barb, R 1"	164	6.388-465.0	with hose barb	
Geka connector with internal thread, R 1"	165	6.388-458.0	with female thread	
Suction filter				İ
Water suction filter	166	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 $\mu$ m mesh, R 3/4" and R 1" connection, without non-return valve	n
Suction filter with check valve	167	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter				Ť
Universal water fine filter, 25 µm	168	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	

 $<sup>\ \</sup>square$  Available accessories.















		Order no.	Description	
WATER CONNECTION				
Water fine filter				
Water fine filter, with adapter	169	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Water fine filter, 100 μm, R 1"	170	2.638-270.0	Fine-mesh water filter, $100 \mu m$ , max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$ . Connector 1".	
Water supply hose				
Water supply hose	171	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	172	4.440-270.0	NW 19 R1" / R1", up to 85 °C	
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush	173	4.113-001.0	For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection	
Rotating washing brush				
Rotating wash brush for > 1000 l/h machines, nylon bristles	174	4.113-002.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).	
Rotating wash brush for > 800 l/h machines, natural bristles	175	4.113-005.0		

 $<sup>\</sup>hfill \square$  Available accessories.