

## IVC 60/24-2 TACT<sup>2</sup> M

Compact, manoeuvrable industrial vacuum cleaner with Tact<sup>2</sup> automatic filter cleaning system. Ideal for cleaning production machines and areas subject to health-endangering dusts, dust class M.



**Order no.** 1.576-105.0

- Antistatic equipment
- Certified for dust class M
- Integrated cyclone for pre-separation system

### Technical data

<b>EAN code</b>		4039784463745
<b>Power supply</b>	<b>Ph / V / Hz</b>	1 / 220 - 240 / 50 - 60
<b>Air flow</b>	<b>l/s / m³/h</b>	148 / 532
<b>Vacuum</b>	<b>mbar / kPa</b>	254 / 25.4
<b>Container capacity</b>	<b>l</b>	60
<b>Container material</b>		Stainless steel
<b>Rated input power</b>	<b>kW</b>	2.4
<b>Vacuuming type</b>		Electric
<b>Connection nominal diameter</b>		DN 70
<b>Accessory nominal diameter</b>		DN 50 / DN 40
<b>Sound pressure level</b>	<b>dB(A)</b>	73
<b>Main filter dust class</b>		M
<b>Filter area for main filter</b>	<b>m²</b>	0.95
<b>Weight without accessories</b>	<b>kg</b>	60
<b>Dimensions (L × W × H)</b>	<b>mm</b>	970 × 690 × 995

This machine requires instruction.

### Equipment

<b>Main filter</b>	Flat pleated filter
<b>Accessories included in the scope of delivery</b>	no
<b>Container emptying</b>	Set-down trolley

■ Included in the scope of supply.



## Dust class M

- Complete device certified according to DIN EN 60335-2-69 for dust class M.



## Fitted with two blower motors

- For powerful suction power and optimum cleaning performance.
- Electronic control of the drive to avoid high inrush currents.



## Automatic filter cleaning system Tact²

- Automatic cleaning of the filters by means of targeted and powerful air blasts.
- Despite filter cleaning, the suction power remains constantly high.
- Long life of the filter reduces maintenance costs.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M</b>				
<b>Flat pleated filter, PTFE</b>				
Flat pleated filter, PTFE	1	6.907-449.0	Polyester fleece with PTFE coating, dust class M, for Tact <sup>2</sup> vacuum cleaners. Particularly suitable for very adhesive materials.	<input type="checkbox"/>
<b>FILTER T/ NT</b>				
<b>Fabric filter</b>				
Candle filter Wood, NT 65/2, NT 75/2	2	2.414-003.0	Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums.	<input type="checkbox"/>
<b>ACCESSORY SETS</b>				
<b>Accessory kit for solids/dust</b>				
Oven cleaning accessory kit Expert DN 50	3	9.989-938.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-979.0), handle (9.989-899.0), suction tube (9.989-929.0), floor nozzle (9.989-935.0), reducer (9.989-712.0), adapter (9.993-011.0).	<input type="checkbox"/>
Oven cleaning accessory kit Expert DN 40	4	9.989-939.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-976.0), handle (9.989-898.0), suction tube (9.989-928.0), floor nozzle (9.989-934.0), reducer (9.989-713.0), adapter (9.993-012.0).	<input type="checkbox"/>
Food accessory kit Expert DN 40	5	9.989-940.0	Food accessory kit DN 40: PU hose 3 m (9.989-970.0), handle (9.989-898.0), standard nozzle (9.989-838.0), brush (9.989-879.0), reducer (9.989-713.0), adapter (9.993-012.0).	<input type="checkbox"/>
Food accessory kit Expert DN 50	6	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	<input type="checkbox"/>
Accessory kit for overhead cleaning Expert DN 40	7	9.989-942.0	Accessory kit DN 40 for overhead cleaning: suction tubes (9.989-920.0/9.993-008.0), handles (9.989-916.0/9.989-918.0), standard nozzle (9.989-838.0), brush (9.989-879.0), adapter (9.993-012.0).	<input type="checkbox"/>
Accessory kit for overhead cleaning DN 50 Expert	8	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	<input type="checkbox"/>
Professional dry floor cleaning set DN40	9	9.990-877.0	Professional dry floor cleaning set: adapter (9.990-874.0), hose (2.889-141.0), bend (2.889-172.0), 2 × suction tube (2.889-194.0), 3 × nozzles (6.906-958.0, 6.903-033.0, 6.902-105.0).	<input type="checkbox"/>
Advanced dry floor cleaning set DN40	10	9.990-893.0	Advanced dry floor cleaning set: EVA hose (9.990-923.0), handle (9.990-929.0), 2 × suction tube (9.990-933.0), floor nozzle (9.990-935.0), standard nozzle (9.980-773.0).	<input type="checkbox"/>
Advanced dry floor cleaning set DN50	11	9.990-894.0	Advanced dry floor cleaning set: EVA hose (9.990-924.0), handle (9.990-930.0), 2 × suction tube (9.990-934.0), floor nozzle (9.990-936.0), standard nozzle (9.980-761.0).	<input type="checkbox"/>
<b>NOZZLES</b>				
<b>Standard nozzles</b>				
Standard nozzle silicone FDA blue DN-F40	12	9.989-835.0		<input type="checkbox"/>
Standard nozzle silicone FDA green DN-F40	13	9.989-836.0		<input type="checkbox"/>
Standard nozzle silicone FDA red DN-F40	14	9.989-837.0		<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M  
1.576-105.0



		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA transparent DN-F40	15	9.989-838.0		<input type="checkbox"/>
Standard nozzle silicone FDA white DN-F40	16	9.989-839.0		<input type="checkbox"/>
Standard nozzle silicone FDA yellow DN-F40	17	9.989-840.0		<input type="checkbox"/>
Standard nozzle silicone FDA blue DN-F50	18	9.989-841.0		<input type="checkbox"/>
Standard nozzle silicone FDA green DN-F50	19	9.989-842.0		<input type="checkbox"/>
Standard nozzle silicone FDA red DN-F50	20	9.989-843.0		<input type="checkbox"/>
Standard nozzle silicone FDA transparent DN-F50	21	9.989-844.0		<input type="checkbox"/>
Standard nozzle silicone FDA white DN-F50	22	9.989-845.0		<input type="checkbox"/>
Standard nozzle silicone FDA yellow DN-F50	23	9.989-846.0		<input type="checkbox"/>
Standard PVC nozzle DN40	24	9.989-674.0	Electroconductive standard PVC nozzle. DN 40.	<input type="checkbox"/>
Standard PVC nozzle DN50	25	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	<input type="checkbox"/>
Standard nozzle silicone DN40	26	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	<input type="checkbox"/>
Standard nozzle silicone DN50	27	9.988-402.0		<input type="checkbox"/>
Standard nozzle cuttable rubber DN40	28	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	<input type="checkbox"/>

■ Included in the scope of supply.    □ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>NOZZLES</b>				
<b>Standard nozzles</b>				
Standard nozzle cuttable rubber DN50	29	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	<input type="checkbox"/>
Standard aluminium nozzle DN40	30	9.980-748.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 40.	<input type="checkbox"/>
Standard aluminium nozzle DN50	31	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	<input type="checkbox"/>
<b>Flexible standard nozzles</b>				
Standard nozzle flexible PVC DN40	32	9.981-420.0	Electroconductive, flexible round nozzle made from galvanised steel, with rubber mouthpiece DN 30.	<input type="checkbox"/>
Standard nozzle flexible PVC DN50	33	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	<input type="checkbox"/>
Standard nozzle, flexible, angled 90° PP DN40	34	9.981-429.0	Flexible, electroconductive angled nozzle, DN 40, length: 800 mm.	<input type="checkbox"/>
Standard nozzle, flexible, angled 90° PP DN50	35	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	<input type="checkbox"/>
<b>Floor nozzles</b>				
Floor nozzle stainless steel AISI 304 DN-F40 blue	36	9.989-861.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50 blue	37	9.989-862.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40 green	38	9.989-863.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50 green	39	9.989-864.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40 red	40	9.989-865.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50 red	41	9.989-866.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40 transparent	42	9.989-867.0		<input type="checkbox"/>

■ Included in the scope of supply.    □ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M  
1.576-105.0



		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F50 transparent	43	9.989-868.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40 white	44	9.989-869.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50 white	45	9.989-870.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40 yellow	46	9.989-871.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50 yellow	47	9.989-872.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F40	48	9.989-914.0		<input type="checkbox"/>
Floor nozzle stainless steel AISI 316L DN-F50	49	9.989-915.0		<input type="checkbox"/>
Floor nozzle stainless steel 400 mm DN-F40	50	9.989-934.0		<input type="checkbox"/>
Floor nozzle stainless steel 400 mm DN-F50	51	9.989-935.0		<input type="checkbox"/>
Floor nozzle aluminium 400 mm DN-F40	52	9.989-936.0		<input type="checkbox"/>
Floor nozzle aluminium 400 mm DN-F50	53	9.989-937.0		<input type="checkbox"/>
Aluminium floor nozzle 370 mm DN40	54	9.989-683.0	Floor nozzle, 370 mm, made from aluminium. DN 40.	<input type="checkbox"/>
Aluminium floor nozzle, el, 370 mm, DN40	55	9.989-682.0	Floor nozzle, 370 mm, made from aluminium. Electroconductive. DN 40.	<input type="checkbox"/>
Aluminium floor nozzle 200 mm DN50	56	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	<input type="checkbox"/>

☐ Available accessories.



## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>NOZZLES</b>				
<b>Floor nozzles</b>				
Aluminium floor nozzle 370 mm DN50	57	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. Electroconductive. DN 50.	<input type="checkbox"/>
Aluminium floor nozzle, el, 370 mm, DN50	58	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	<input type="checkbox"/>
Aluminium floor nozzle 500 mm DN50	59	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	<input type="checkbox"/>
Aluminium floor nozzle, el, 500 mm, DN50	60	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	<input type="checkbox"/>
Stainless steel floor nozzle el 370 mm DN40	61	9.989-558.0	Multi-purpose floor nozzle (370 mm), electroconductive, DN 40.	<input type="checkbox"/>
Stainless steel floor nozzle el 370 mm DN50	62	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	<input type="checkbox"/>
Floor nozzle rubber strip oil-resistant. 220 mm	63	9.981-923.0	Squeegee with plastic strip for floor nozzle, 220 mm wide.	<input type="checkbox"/>
Floor nozzle rubber strip 370 mm	64	9.981-914.0	Squeegee with profiled strip for floor nozzle, 370 mm wide.	<input type="checkbox"/>
Floor nozzle rubber strip 500 mm	65	9.981-915.0	Oil-resistant squeegee with profiled strip for floor nozzle, 500 mm wide.	<input type="checkbox"/>
Floor nozzle brush strip el. 370 mm	66	9.984-939.0	Electroconductive squeegee for floor nozzle, 370 mm wide.	<input type="checkbox"/>
Floor nozzle brush strip 500 mm	67	9.980-764.0	Brush strip set for floor nozzle 500 mm, with profiled strip.	<input type="checkbox"/>
<b>Crevice nozzles</b>				
Crevice nozzle PP 15 mm × 145 mm DN50	68	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	<input type="checkbox"/>
Crevice nozzle PU 22 mm × 175 mm DN50	69	9.981-482.0	Crevice nozzle made from PU, DN 50.	<input type="checkbox"/>
Crevice nozzle 18 mm × 120 mm DN50	70	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>NOZZLES</b>				
<b>Crevice nozzles</b>				
Crevice nozzle 25 mm × 120 mm DN50	71	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	<input type="checkbox"/>
<b>Flexible crevice nozzles</b>				
Crevice nozzle flexible silicone FDA DN-F50 transparent	72	9.989-847.0		<input type="checkbox"/>
Crevice nozzle flexible silicone FDA DN-F40 transparent	73	9.989-848.0		<input type="checkbox"/>
Flexible crevice nozzle silicone 65 mm DN50	74	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	<input type="checkbox"/>
Flexible crevice nozzle 11 mm × 58 mm DN40	75	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	<input type="checkbox"/>
Flexible crevice nozzle 20 mm × 45 mm DN40	76	9.981-423.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 40.	<input type="checkbox"/>
Flexible crevice nozzle 12 mm × 45 mm DN50	77	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	<input type="checkbox"/>
Flexible crevice nozzle 20 mm × 45 mm DN50	78	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	<input type="checkbox"/>
<b>Surface nozzles</b>				
Silicone surface nozzle FDA blue DN-F40	79	9.989-849.0		<input type="checkbox"/>
Silicone surface nozzle FDA blue DN-F50	80	9.989-850.0		<input type="checkbox"/>
Silicone surface nozzle FDA green DN-F40	81	9.989-851.0		<input type="checkbox"/>
Silicone surface nozzle FDA green DN-F50	82	9.989-852.0		<input type="checkbox"/>
Silicone surface nozzle FDA red DN-F40	83	9.989-853.0		<input type="checkbox"/>
Silicone surface nozzle FDA red DN-F50	84	9.989-854.0		<input type="checkbox"/>

☐ Available accessories.



## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>NOZZLES</b>				
<b>Surface nozzles</b>				
Silicone surface nozzle FDA transparent DN-F40	85	9.989-855.0		<input type="checkbox"/>
Silicone surface nozzle FDA transparent DN-F50	86	9.989-856.0		<input type="checkbox"/>
Silicone surface nozzle FDA white DN-F40	87	9.989-857.0		<input type="checkbox"/>
Silicone surface nozzle FDA white DN-F50	88	9.989-858.0		<input type="checkbox"/>
Silicone surface nozzle FDA yellow DN-F40	89	9.989-859.0		<input type="checkbox"/>
Silicone surface nozzle FDA yellow DN-F50	90	9.989-860.0		<input type="checkbox"/>
Silicone surface nozzle 120 mm DN40	91	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	<input type="checkbox"/>
Silicone surface nozzle 120 mm DN50	92	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	<input type="checkbox"/>
Aluminium surface nozzle, 150 mm, DN 40	93	9.989-666.0	Surface nozzle, 150 mm, made from aluminium. DN 40.	<input type="checkbox"/>
Aluminium surface nozzle 150 mm DN50	94	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	<input type="checkbox"/>
<b>Liquid nozzles</b>				
Liquid nozzle 900 mm DN50	95	9.981-427.0	Bypass nozzle, DN 50, overall length: 1000 mm.	<input type="checkbox"/>
<b>Borehole nozzles</b>				
Blind hole nozzle DN40	96	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	<input type="checkbox"/>
Blind hose nozzle angled 60° DN40	97	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	<input type="checkbox"/>
Blind hose nozzle angled 90° DN40	98	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>NOZZLES</b>				
<b>Borehole nozzles</b>				
Blind hose nozzle angled 90° 200 mm extension DN40	99	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	<input type="checkbox"/>
<b>BRUSHES</b>				
<b>Standard brushes</b>				
Standard brush 40 mm DN40	100	9.981-431.0	Flat brush nozzle DN 40.	<input type="checkbox"/>
Standard brush 40 mm DN50	101	9.981-432.0	Flat brush nozzle DN 50.	<input type="checkbox"/>
<b>End brushes</b>				
Brush FDA blue ø 75 mm DN-F40	102	9.989-873.0		<input type="checkbox"/>
Brush FDA blue ø 75 mm DN-F50	103	9.989-874.0		<input type="checkbox"/>
Brush FDA green ø 75 mm DN-F40	104	9.989-875.0		<input type="checkbox"/>
Brush FDA green ø 75 mm DN-F50	105	9.989-876.0		<input type="checkbox"/>
Brush FDA red ø 75 mm DN-F40	106	9.989-877.0		<input type="checkbox"/>
Brush FDA red ø 75 mm DN-F50	107	9.989-878.0		<input type="checkbox"/>
Brush FDA white ø 75 mm DN-F40	108	9.989-879.0		<input type="checkbox"/>
Brush FDA white ø 75 mm DN-F50	109	9.989-880.0		<input type="checkbox"/>
Brush FDA yellow ø 75 mm DN-F40	110	9.989-881.0		<input type="checkbox"/>
Brush FDA yellow ø 75 mm DN-F50	111	9.989-882.0		<input type="checkbox"/>
End brush Ø 82 mm DN40	112	9.989-609.0	Electroconductive end brush with 82 mm diameter. DN 40.	<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
BRUSHES				
End brushes				
End brush Ø 82 mm DN50	113	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	<input type="checkbox"/>
Surface brushes				
Surface brush PP 24 mm DN40	114	9.989-610.0	Electroconductive surface brush. DN 40.	<input type="checkbox"/>
Surface brush 300 mm DN40	115	9.981-911.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	<input type="checkbox"/>
Surface brush 300 mm DN50	116	9.981-912.0		<input type="checkbox"/>
Cylinder brushes				
Cylinder brush ø 100 mm DN-F40	117	9.989-922.0		<input type="checkbox"/>
Cylinder brush ø 200 mm DN-F40	118	9.989-923.0		<input type="checkbox"/>
Cylinder brush ø 100 mm DN-F50	119	9.989-925.0		<input type="checkbox"/>
Cylinder brush ø 200 mm DN-F50	120	9.989-926.0		<input type="checkbox"/>
HOSES				
ME-Schläuche				
Hose ME DN40 3 m	121	9.989-976.0		<input type="checkbox"/>
Hose ME DN40 5 m	122	9.989-977.0		<input type="checkbox"/>
Hose without connection ME DN40 15 m	123	9.989-978.0		<input type="checkbox"/>
Hose ME DN50 3 m	124	9.989-979.0		<input type="checkbox"/>
Hose ME DN50 5 m	125	9.989-980.0		<input type="checkbox"/>
PVC				
Hose PVC DN40 1 m	126	9.989-626.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 1 m.	<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



127-130



131-132, 134-135



133, 136



137-138, 140



139

		Order no.	Description	
<b>HOSES</b>				
<b>PVC</b>				
Hose PVC DN40 3 m	127	9.989-962.0		<input type="checkbox"/>
Hose PVC DN40 5 m	128	9.989-963.0		<input type="checkbox"/>
Hose PVC DN50 3 m	129	9.989-964.0		<input type="checkbox"/>
Hose PVC DN50 5 m	130	9.989-965.0		<input type="checkbox"/>
Hose PVC DN40 3 m	131	9.989-647.0	PVC hose, DN 40. Temperature-resistant up to 85 °C and electrically conductive. Length: 3 m.	<input type="checkbox"/>
Hose PVC DN40 5 m	132	9.989-614.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 5 m.	<input type="checkbox"/>
PVC hose DN40 15 m without connectors	133	9.989-633.0	PVC hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	<input type="checkbox"/>
Hose PVC DN50 3 m	134	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	<input type="checkbox"/>
Hose PVC DN50 5 m	135	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	<input type="checkbox"/>
PVC hose DN50 15 m without connectors	136	9.989-634.0	PVC hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	<input type="checkbox"/>
<b>EVA hoses</b>				
Hose EVA DN40 3 m	137	9.989-982.0		<input type="checkbox"/>
Hose EVA DN40 5 m	138	9.989-983.0		<input type="checkbox"/>
Hose EVA DN50 3 m	139	9.989-984.0		<input type="checkbox"/>
Hose EVA DN50 5 m	140	9.989-985.0		<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



141-142, 144



143, 146



145



147-148



149-150



151-154

		Order no.	Description	
<b>HOSES</b>				
<b>EVA hoses</b>				
Hose EVA NW40 3 m	141	9.988-088.0	Electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 3 m.	<input type="checkbox"/>
Hose EVA NW40 5 m	142	9.988-089.0	Five-metre-long, electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 5 m.	<input type="checkbox"/>
EVA hose DN40 15 m without connectors	143	9.989-630.0	EVA hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	<input type="checkbox"/>
Hose EVA NW50 3 m	144	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	<input type="checkbox"/>
Hose EVA NW50 5 m	145	9.988-091.0		<input type="checkbox"/>
EVA hose DN50 15 m without connectors	146	9.989-631.0	EVA hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	<input type="checkbox"/>
<b>Hose installation sets</b>				
Hose installation kit DN40	147	9.989-627.0	Multipiece hose connection set, DN 40.	<input type="checkbox"/>
Hose installation kit DN50	148	9.989-628.0	Multipiece hose connection kit, DN 50.	<input type="checkbox"/>
Hose connection kit, stainless steel AISI 304 DN40	149	9.989-986.0	Hose connection kit in nominal width DN 40, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	<input type="checkbox"/>
Hose connection kit, stainless steel AISI 304 DN50	150	9.989-987.0	Hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	<input type="checkbox"/>
<b>PU hoses</b>				
Hose PU DN40 3 m	151	9.989-966.0		<input type="checkbox"/>
Hose PU DN40 5 m	152	9.989-967.0		<input type="checkbox"/>
Hose PU DN50 3 m	153	9.989-968.0		<input type="checkbox"/>
Hose PU DN50 5 m	154	9.989-969.0		<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>HOSES</b>				
<b>PU hoses</b>				
Hose PU FDA DN40 3 m	155	9.989-970.0		<input type="checkbox"/>
Hose PU FDA DN40 5 m	156	9.989-971.0		<input type="checkbox"/>
Hose PU FDA DN40 15 m	157	9.989-972.0		<input type="checkbox"/>
Hose PU FDA DN50 3 m	158	9.989-973.0		<input type="checkbox"/>
Hose PU FDA DN50 5 m	159	9.989-974.0		<input type="checkbox"/>
Hose PU FDA DN50 15 m	160	9.989-975.0		<input type="checkbox"/>
Hose PU DN40 3 m	161	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	<input type="checkbox"/>
Hose PU DN40 5 m	162	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	<input type="checkbox"/>
PU hose DN40 15 m without connectors	163	9.989-637.0	PU hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	<input type="checkbox"/>
Hose PU DN50 3 m	164	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	<input type="checkbox"/>
Hose PU DN50 5 m	165	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	<input type="checkbox"/>
PU hose DN50 15 m without connectors	166	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	<input type="checkbox"/>
<b>ME-PU-hoses</b>				
Hose without connection ME DN50 15 m	167	9.989-981.0		<input type="checkbox"/>
Hose ME-PU DN40 3 m	168	9.989-621.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	<input type="checkbox"/>

☐ Available accessories.



## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>HOSES</b>				
<b>ME-PU-hoses</b>				
ME-PU hose, DN 40, 5 m	169	9.989-622.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	<input type="checkbox"/>
ME-PU hose DN40 15 m without connectors	170	9.989-640.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	<input type="checkbox"/>
Hose ME-PU DN50 3 m	171	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	<input type="checkbox"/>
Hose ME-PU DN50 5 m	172	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	<input type="checkbox"/>
ME-PU hose DN50 15 m without connectors	173	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	<input type="checkbox"/>
<b>HANDLES</b>				
Elbow aluminium 45° DN40	174	9.989-544.0	45° curved handle made from aluminium, DN 40.	<input type="checkbox"/>
Elbow aluminium 45° DN50	175	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	<input type="checkbox"/>
Handle stainless steel AISI 304 DN40	176	9.989-896.0		<input type="checkbox"/>
Handle stainless steel AISI 304 DN50	177	9.989-897.0		<input type="checkbox"/>
Handle straight stainless steel AISI 304 DN40	178	9.989-898.0		<input type="checkbox"/>
Handle straight stainless steel AISI 304 DN50	179	9.989-899.0		<input type="checkbox"/>
Handle carbon 45° DN-F40	180	9.989-916.0		<input type="checkbox"/>
Handle carbon 45° DN-F50	181	9.989-917.0		<input type="checkbox"/>
Handle carbon 110° DN-F40	182	9.989-918.0		<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



182-183



184




185




186-187



188-189



190-191



192-193




194-199

		Order no.	Description	
<b>HANDLES</b>				
Handle carbon 110° DN-F50	183	9.989-919.0		<input type="checkbox"/>
Handle DN 40	184	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	<input type="checkbox"/>
Handle DN50, curved	185	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	<input type="checkbox"/>
Stainless steel handle NW40	186	9.989-036.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 40.	<input type="checkbox"/>
Stainless steel handle NW50	187	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	<input type="checkbox"/>
<b>SUCTION TUBES</b>				
Carbon suction tube 1500 mm DN40	188	9.989-552.0	Very light carbon extension tube, electroconductive, DN 40. Length: 1500 mm.	<input type="checkbox"/>
Carbon suction tube 1500 mm DN50	189	9.989-553.0	Electroconductive, very light carbon extension tube. Inner cone DN 50, 1500 mm long.	<input type="checkbox"/>
Suction tube stainless steel AISI 304 DN40	190	9.989-912.0		<input type="checkbox"/>
Suction tube stainless steel AISI 304 DN50	191	9.989-913.0		<input type="checkbox"/>
Suction tube carbon 1500 mm DN-F40 conical	192	9.989-920.0		<input type="checkbox"/>
Suction tube carbon 1500 mm DN-F50 conical	193	9.989-921.0		<input type="checkbox"/>
Suction tube aluminium high temperature 1000 mm DN-F40	194	9.989-928.0		<input type="checkbox"/>
Suction tube aluminium high temperature 1000 mm DN-F50	195	9.989-929.0		<input type="checkbox"/>
Suction tube aluminium high temperature 2000 mm DN-F40	196	9.989-930.0		<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
<b>SUCTION TUBES</b>				
Suction tube aluminium high temperature 2000 mm DN-F50	197	9.989-931.0		<input type="checkbox"/>
Suction tube aluminium high temperature 3000 mm DN-F40	198	9.989-932.0		<input type="checkbox"/>
Suction tube aluminium high temperature 3000 mm DN-F50	199	9.989-933.0		<input type="checkbox"/>
Suction tube 850 mm DN 40	200	9.977-525.0	Steel extension tube, electroconductive, DN 40. Length: 850 mm.	<input type="checkbox"/>
Suction tube 850 mm DN 50	201	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	<input type="checkbox"/>
Aluminium suction tube 1500 mm NW40	202	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	<input type="checkbox"/>
Aluminium suction tube 1500 mm NW50	203	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	<input type="checkbox"/>
Stainless steel suction tube 850 mm NW40	204	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	<input type="checkbox"/>
Stainless steel suction tube 850 mm NW50	205	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	<input type="checkbox"/>
<b>OTHER ACCESSORIES</b>				
Universal accessories holder	206	9.989-789.0	Universal accessories holder for simple storage of suction tubes directly on industrial vacuums from the IVC, IVM and IVS product lines from Kärcher.	<input type="checkbox"/>
<b>ADAPTERS / REDUCERS / DISTRIBUTORS</b>				
<b>Accessories adapter</b>				
Adapter DN70 auf Bajonett 2.0 elektr. leitend	207	9.990-874.0		<input type="checkbox"/>
Adapter accessories DN 50 to DN 51	208	9.989-603.0	Steel adapter for connection of DN 50 to DN 51. Electroconductive.	<input type="checkbox"/>
Adapter accessories DN 51 to DN 50	209	9.989-601.0	Steel adapter for connection of DN 51 to DN 50. Electroconductive.	<input type="checkbox"/>
Adapter accessories DN50 to DN61	210	9.989-602.0	Steel adapter for connection of DN 50 to DN 61. Electroconductive.	<input type="checkbox"/>

☐ Available accessories.

## ACCESSORIES FOR IVC 60/24-2 TACT<sup>2</sup> M

### 1.576-105.0



		Order no.	Description	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter accessories DN 61 to DN 50	211	9.989-604.0	Steel adapter for connection of DN 61 to DN 50. Electroconductive.	<input type="checkbox"/>
Reducers/expanders				
Reducer in AISI 304 stainless steel DN50 to DN40	212	9.989-893.0		<input type="checkbox"/>
Reducer DN 70 to DN 50	213	9.977-772.0		<input type="checkbox"/>
Reduction DN70 to DN40	214	9.989-690.0	Electroconductive steel reducer for reduction from DN 70 to DN 40.	<input type="checkbox"/>
Reduction DN50 to DN40	215	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	<input type="checkbox"/>
Stainless steel reducer DN 70 to DN 50	216	9.989-712.0		<input type="checkbox"/>
Stainless steel reducer DN 70 to DN 40	217	9.989-713.0		<input type="checkbox"/>
Expander				
Expansion DN50 to DN70	218	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.	<input type="checkbox"/>
Distributor				
AISI 304 stainless steel manifold DN70 to DN50	219	9.989-894.0		<input type="checkbox"/>
AISI 304 stainless steel manifold DN70 to DN40	220	9.989-895.0		<input type="checkbox"/>
Y distributor DN 70 to DN 50	221	9.989-611.0	Electroconductive steel fitting, DN 70/DN 50 / DN 50.	<input type="checkbox"/>
EMPTYING SUPPORTS				
Emptying bags				
Disposal bag PE Ø 540 mm 100 l	222	9.989-607.0	For dust-free emptying: 5 PE emptying bags with 100 l volume. Diameter: 540 mm.	<input type="checkbox"/>
Strainer baskets				
Sieve basket IVC	223	5.731-645.0	Plastic swarf sieve, perforated, with internal thread. For protecting the drain hose against very abrasive suction material such as coarse shavings.	<input type="checkbox"/>
PRE-SEPARATORS				
Pre-separator				
Pre-separator Tc Op liquids 125 l DN70	224	9.989-686.0	125 litre pre-separator, DN 70.	<input type="checkbox"/>

☐ Available accessories.