

SP 22.000 DIRT LEVEL SENSOR

With level sensor and integrated prefilter: For challenging drainage tasks the submersible dirty water pump SP 22,000 Dirt Level Sensor manages to pump out dirty water at a rate of up to 22,000 l/h.



Order no.

1.645-851.0

- Extremely durable thanks to the ceramic slide ring sealing
- Level sensor allows the switching level to be set to any level
- Integrated stainless steel prefilter


Technical data

EAN code		4054278952031
Max. motor rating	W	750
Max. flow rate	l/h	< 22000
Delivery temperature	°C	max. 35
Delivery head	m	8
Pressure	bar	max. 0.8
Grain size	mm	max. 30
Immersion depth	m	max. 7
After-running time	s	15
Min. residual water, manual	mm	35
Residual water height	mm	35
Connection thread		G1 1/2
Pressure-side connection thread		G1/2 internal thread
Power cable	m	10
Voltage	V	230 – 240
Frequency	Hz	50
Colour		Yellow
Weight without accessories	kg	6.7
Weight incl. packaging	kg	7.7
Dimensions (L × W × H)	mm	238 × 293 × 354

Equipment

Comfortable carrying handle	■
Hose connection piece	1", 1 1/4", 1 1/2"
Easy hose connection thanks to Quick Connect	■
Switching between manual/automatic operation	Switch on the pump
Level sensor: Continuous switching level definition	■
Integrated stainless steel pre-filter	■
In automatic operation (auto), the pump automatically switches with the water level	■
In manual operation, the pump runs continuously to ensure the minimum quantity of residual water	■
Ceramic face seal.	■
Stainless steel housing	■

■ included in the scope of supply.



Ceramic face seal.

- For an extra long lifetime.



Level Sensor


- For continuously variable definition of the switch-on and switch-off points of the pumps.



Quick Connect

- Connection thread for quick and uncomplicated connection of 1", 1 1/4" and 1 1/2" hoses.

ACCESSORIES FOR SP 22.000 DIRT LEVEL SENSOR
1.645-851.0



		Order no.	Description	
MISCELLANEOUS				
Fabric hose set	1	2.997-100.0	Space-saving hose set with a flexible fabric hose, including stainless steel hose clamp for connecting to submersible pumps. Ideal as a feed hose for water removal in the event of flooding.	<input type="checkbox"/>
HOSES				
PrimoFlex® hose 1" 1 m	2	2.645-247.0	The PrimoFlex® 1" quality garden hose is available by the metre, meaning it can be ordered in exactly the length you require (max. 50 m). With pressure-resistant reinforcement mesh. Contains no substances that are harmful to health.	<input type="checkbox"/>
Hose Performance Plus 3/4" -25m	3	2.645-322.0	Easy-to-handle, long-lasting and weather-resistant: the 25-metre long Performance Plus 3/4" garden hose. Flexible, ultra-robust and extremely resistant to kinks - for constant water flow.	<input type="checkbox"/>
Hose Performance Plus 3/4" -50m	4	2.645-323.0	Ultra-robust, extremely resistant to kinks and free from potentially harmful substances: the 50-metre long Performance Plus 3/4" garden hose. Made from high-quality multi-layered woven material - for constant water flow.	<input type="checkbox"/>
PrimoFlex® hose 3/4" - 25 m	5	2.645-142.0	PrimoFlex® quality garden hose (3/4"). 25 m long. With pressure-resistant woven reinforcement. Contains no substances that are harmful to health. Bursting pressure: 24 bar. High temperature resistance from 0 to +40 °C.	<input type="checkbox"/>

■ Included in the scope of supply. ☐ Available accessories. ○ Detergents.