

NT 75/1 ME EC H Z22

The TÜV tested NT 75/1 Me Ec H Z22 safety vacuum cleaner is a powerful, single motor wet and dry vacuum cleaner for explosive dust (hazard class zone 22) with continuous antistatic system.



Order no.

- Brushless EC motor (5000 hrs)
- Anti-static systemSuitable for asbestos

.

	4039784538115
V / Hz	220 - 240 / 50 - 60
l/s	61
mbar / kPa	220 / 22
I	75
w	max. 1000
	ID 40
dB(A)	76
kg	27.8
kg	33.2
mm	640 × 540 × 925
	l/s mbar / kPa l W dB(A) kg kg

Equipment		
Safety filter bag	piece(s)	1
Suction hose	m	4 / with bend (electrically conductive)
Suction tube	piece(s) × m	1 × 1 / Metal
Filter bag		Fleece
Wet/dry floor nozzle	mm	360
Crevice nozzle		-
Anti-static system		
Stainless steel container		-
Flat pleated filter		Fibreglass
Metal bend		-
Push handle		
Protection class		T
Stop swivel castor		
Dust class		Н
Container material		Stainless steel

Included in the scope of supply.

Users must receive training on this device.

KARCHER



Zone 22 + dust class H

For combustible dusts in dust explosion classes,
 Zone 22 and health-endangering dusts, dust class H.

Anti-static system

 All Kärcher safety vacuum cleaners feature a continuous antistatic system with conductive accessories.



Brushless EC motor

• The brushless EC motor has a service life of 5000 hours - ideal for continuous use.

KARCHER

ACCESSORIES FOR NT 75/1 ME EC H Z22 1.667-239.0

	3		$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array}\\ 4 \end{array} \end{array} $
		0	
FILTER T/ NT		Order no.	Description
Flat pleated filter HEPA, dust class H			
HEPA-14 flat pleated filter	1	6.904-364.0	For Kärcher wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter. Suitable for vacuuming hazardous dusts, coarse dirt and liquids.
Safety filter sets/bags			
Safety filter bag, 5 × , NT 75/1	2	6.904-420.0	For dust-free/low-dust emptying in conjunction with the 4.070-930.0 container, with dust disposal bag, electrically conductive. Checked and approved for dust class H.
BENDS			
Bend, other			
Unique bend, NT safety vacuum cleaner, DN 40, chrome-plated metal, threaded ring at hose end, union nut at accessory end	3	4.036-032.0	Unique DN 40 chrome-plated metal bend for NT safety vacuum cleaner. Equipped with a threaded ring at the hose end and a union nut at the accessory end.
SUCTION NOZZLES			
Floor nozzles			
Wet/dry floor nozzle, standard plastic, DN 40	4	4.763-244.0	All-purpose plastic nozzle (DN 40) with 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). Only for NT-80/1 B1 M + MS.
Wet/dry floor nozzle, aluminium, DN 40	5	4.130-399.0	Aluminium floor nozzle, earthed, non-interchangeable, 450 mm, height adjustable. As a standard

	4	4.705-244.0	(6.905-878.0) and squeegees (6.905-877.0). Only for NT-80/1 B1 M + MS.	
Wet/dry floor nozzle, aluminium, DN 40	5	4.130-399.0	Aluminium floor nozzle, earthed, non-interchangeable, 450 mm, height adjustable. As a standard accessory for NT 80/1 B1 Ms and optional for NT 75/1 Me Ec H Z22.	
Crevice nozzles				
Crevice nozzle, NT, unique Z22 connection, DN 40, plastic, 290 mm	6	4.763-243.0	Plastic crevice tool (DN 35) with non-interchangeable screw connection for vacuuming in crevices and corners. Length: 290 mm.	
All-purpose brushes				
Multi-purpose brush, non-interchangeable	7	4.763-242.0	All-purpose brush with natural bristles (cow hair) Bristles: 120 \times 45 mm. Only for NT 801 B1 M, B1 MS and NT 80/1 B1 M & B1 MS.	
SUCTION TUBES				
Suction tubes, metal				
Suction tube, non-interchangeable	8	4.025-372.0	Non-interchangeable suction tube ID 40, 1.0 m, metal chromed, with special fixation on both sides.	
SUCTION HOSES				
Suction hoses zone 22				
Suction hose, NT, DN 40, length 4 m, electrically conductive, with unique connection zone 22, bayonet		4.440-991.0	The electrically conductive suction hose in nominal width DN 40 and with 4 m length is suitable for use with zone 22 explosion-proof wet and dry vacuum cleaners from Kärcher.	
Suction hose, NT, DN 40, length 8 m, electrically conductive, with unique connection zone 22, bayonet	10	4.440-013.0	The electrically conductive suction hose in nominal width DN 40 and with 8 m length is suitable for use with zone 22 explosion-proof wet and dry vacuum cleaners from Kärcher.	

■ Included in the scope of supply. □ Available accessories.