

HD 9/100-4 CAGE ADV

Removes even extremely stubborn dirt: the versatile HD 9/100-4 Cage Adv ultra high-pressure cleaner with UHP trigger gun, 1000 bar working pressure and a low water consumption of 900 l/h.



Order no. 1.812-002.0

- Pressure relief valve that makes it easy and comfortable to use
- Pressure relief valve that makes it easy and comfortable to use
- Water shortage protection as standard

Technical data


EAN code		4054278303154
Working pressure	bar / MPa	1000 / 100
Flow rate	l/h	978
Inlet temperature	°C	45
Fuel		Electric
Motor rating	kW	30
Power supply	Ph / V / Hz	3 / 380 / 415 / 50
Pump type		Crankshaft
Weight without accessories	kg	385
Weight (with accessories)	kg	376.5
Weight incl. packaging	kg	380
Dimensions (L × W × H)		1385 × 790 × 1090

This machine requires instruction.

Equipment

High-pressure hose length	m	20
Spray gun		UHP trigger gun (Dry Shut)
Stainless steel spray lance	mm	750
Flat jet nozzle		■
Safety valve		■
Elapsed time counter		■

■ Included in the scope of supply.



Powerful industrial high-pressure pump

- Plunger made from carbide for a long service life.
- Maintenance-friendly design that makes replacing wear parts such as valves, seals and plungers easy.
- Central valve design for high volumetric effectiveness.



Ergonomic blasting gun

- Ergonomic handle and lightweight design for ease of operation.
- Reduced trigger forces for effortless working.




Pressure relief valve

- The pressure relief valve reduces the pressure in the hose, so it remains flexible when the trigger gun is closed.
- Prevents any sudden recoil for the user, as the pressure is built up slowly when pulling the trigger gun.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0



		Order no.	Description	
ULTRA-HIGH-PRESSURE CLEANERS				
Attachment kits				
Filter fleece filter housing 100 µm	1	6.414-074.0	5 pc. fleece filter bags, 100 µm for filter casing.	■
Attachment kit for advance pressure pump	2	2.637-017.0	Booster pump attachment kit for reliable high-pressure pump water supply. The advance pressure pump is installed in the machine.	□
Filter fleece, filter casing	3	6.414-073.0	Filter fleece, 50 µm for filter casing. Contents: Pack of 5.	□
Splash guard	4	9.871-040.0	Splash guard for pushing onto the spray lance.	□
High-pressure hoses				
Pressure hose, 20 m, 1100 bar, M24 × 1.5	5	9.919-791.0	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 24 × 1.5. Suitable for up to 1100 bar working pressure.	■
Pressure hose, 40 m, 1100 bar, M24 × 1.5	6	9.919-912.0	Abrasion-resistant, flexible and thanks to multilayer steel casing also very durable hose with 40 m length. Suitable for up to 1100 bar working pressure. Connection size M 24 × 1.5.	□
Pressure hose, 10 m, 1250 bar, M24 × 1.5	7	9.887-894.0	The 10 m long high-pressure hose is more abrasion-resistant and long-lasting than the standard hose. Suitable for up to 1250 bar working pressure and the connection size M 24 × 1.5.	□
Pressure hose, 20 m, 1250 bar, M24 × 1.5	8	9.887-895.0	Abrasion-resistant and extremely long-lasting: The 20 m long high-pressure hose is suitable for up to 1250 bar working pressure and the connection size M 24 × 1.5.	□
Metal safety sling	9	9.887-583.0	Hose sling for securing high-pressure hose at machine. Prevents uncontrolled lashing in the event of malfunctions, thus minimising the risk of injury for the operator.	□
Textile safety sling	10	9.920-368.0		□
Mounting rope, 0.5 m	11	6.025-311.0	Fastening rope	□
Shackles	12	6.025-195.0	Sturdy shackles for fastening slings for high-pressure hoses at machine.	□
Trigger guns				
UHP trigger gun - Dry Shut	13	9.920-787.0	The UHP trigger gun is suitable for working pressures of up to 1000 bar. The water is recycled into the circulation system when the trigger gun is closed. Connection for high-pressure hose, M24 × 1.5.	■
Spray lances				
Spray lance	14	9.891-183.0	Spray lance with connection size 9/16" UNF. Suitable for up to 1,500 bar working pressure.	■

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0




		Order no.	Description	
ULTRA-HIGH-PRESSURE CLEANERS				
Spray lances				
Spray lance handle	15	6.025-300.0	Spray lance handle.	■
Nozzle pipe	16	9.891-182.0	Spray lance with connection size 9/16" UNF. Suitable for up to 1500 bar working pressure.	□
Spray lance	17	9.891-184.0	Spray lance with connection size 9/16" UNF. Suitable for up to 1,500 bar working pressure.	□
	18	9.891-207.0		□
	19	9.891-185.0	Spray lance with connection size 9/16" UNF. Suitable for working pressures of up to 1500 bar .	□
Spray lance handle, 90°	20	9.871-675.0	Side handle for spray lance. 90° angle to spray lance axis. Flexible and individually adjustable.	□
Couplings and connectors				
Hose connector	21	9.877-911.0	For connecting and extending high-pressure hoses with connection M 24 × 1.5.	□
Pressure screw	22	9.883-492.0	Thrust screw with connection size M26 × 1.5.	□
Pressure ring	23	9.883-570.0	Thrust collar with connection size 9/16" UNF.	□
Pressure screw	24	9.883-669.0	Pressure screw, connection size 1 1/8" UNF.	□
Pressure ring	25	9.883-670.0	Pressure ring, connection size 9/16" UNF.	□
Grease for stainless steel threaded joints	26	6.280-180.0	Grease for stainless steel screw connections.	□
Abrasive blaster				
Replacement nozzle for abrasive blaster	27	6.025-346.0	Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	□
F98 nozzle set, 0.60 mm	28	9.886-550.0		□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0




		Order no.	Description	
ULTRA-HIGH-PRESSURE CLEANERS				
Abrasive blaster				
Nozzle F98 for abrasive blaster	29	6.025-256.0	0.6 mm	<input type="checkbox"/>
Suction lance	30	6.025-258.0	For the suction of spray agents.	<input type="checkbox"/>
Mounting tool for nozzle set	31	6.025-257.0	For F98 nozzles.	<input type="checkbox"/>
Abrasive	32	6.025-309.0	25 kg, 0.5–1.00 mm, garnet sand.	<input type="checkbox"/>
	33	6.025-310.0	25 kg, 0.7–1.40 mm, garnet sand.	<input type="checkbox"/>
Abrasive sprayer	34	9.872-250.0	Abrasive spray head for wet sand blasting. Nozzle size: 3 × 0.6. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Abrasive material hose	35	6.025-308.0	Abrasive hose.	<input type="checkbox"/>
NOZZLES				
Plug-in nozzles F4/F19				
Nozzle carrier F4/F19	36	9.872-008.0	Nozzle carrier for nozzle F4 / F19. Suitable for working pressures of up to 1,500 bar.	■
O-ring	37	6.025-168.0	For nozzle carrier F4/F19.	■
Flat jet nozzle F19, 1,1 mm, 20 °	38	6.025-466.0	Plug-in flat jet nozzle F19 with a diameter of 1.10 mm and 20°. Suitable for working pressures of up to 1,500 bar.	■
Round jet nozzle F4, 0,9 mm	39	6.025-470.0	Plug-in round jet nozzle F4 with a diameter of 0.90 mm. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Round jet nozzle F4, 1 mm	40	6.025-198.0	Plug-in round jet nozzle F4 with a diameter of 1.00 mm. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Round jet nozzle F4, 1,1 mm	41	9.885-951.0	Plug-in round jet nozzle F4 with a diameter of 1.10 mm. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Round jet nozzle F4, 1,2 mm	42	6.025-199.0	Plug-in round jet nozzle F4 with a diameter of 1.20 mm. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0




		Order no.	Description	
NOZZLES				
Plug-in nozzles F4/F19				
Round jet nozzle F4, 1,3 mm	43	6.025-196.0	Plug-in round jet nozzle F4 with a diameter of 1.30 mm. Suitable for working pressures of up to 250 bar with water flow rate of 900 l/h.	<input type="checkbox"/>
Flat jet nozzle F19, 1,2 mm, 20 °	44	6.025-207.0	Plug-in flat jet nozzle F19 with a diameter of 1.20 mm and 20°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,4 mm, 20 °	45	6.025-211.0	Plug-in flat jet nozzle F19 with a diameter of 1.40 mm and 20°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,5 mm, 20 °	46	6.025-203.0	Plug-in flat jet nozzle F19 with a diameter of 1.50 mm and 20°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,1 mm, 30 °	47	6.025-467.0	Plug-in flat jet nozzle F19 with a diameter of 1.10 mm and 30°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,2 mm, 30 °	48	6.025-208.0	Plug-in flat jet nozzle F19 with a diameter of 1.20 mm and 30°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,3 mm, 30 °	49	6.025-469.0	Plug-in flat jet nozzle F19 with a diameter of 1.30 mm and 30°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,4 mm, 30 °	50	6.025-212.0	Plug-in flat jet nozzle F19 with a diameter of 1.40 mm and 30°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Flat jet nozzle F19, 1,5 mm, 30 °	51	6.025-204.0	Plug-in flat jet nozzle F19 with a diameter of 1.50 mm and 30°. Suitable for working pressures of up to 1,500 bar.	<input type="checkbox"/>
Screw nozzles F21				
Nozzle carrier F21	52	9.878-291.0	Nozzle carrier for sapphire nozzle F21. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Dummy nozzle F21	53	6.025-237.0	F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,35 mm	54	9.886-208.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.35 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,4 mm	55	9.886-209.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.40 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,45 mm	56	6.025-220.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.45 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0



		Order no.	Description	
NOZZLES				
Screw nozzles F21				
Round jet nozzle F21, Saphir, 0,55 mm	57	9.886-211.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.55 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,6 mm	58	9.886-212.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.60 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,65 mm	59	6.025-221.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.65 mm. Suitable for working pressures of up to 2,500 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,7 mm	60	6.025-222.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.70 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,75 mm	61	9.886-213.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.75 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,8 mm	62	9.886-214.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.80 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,85 mm	63	9.886-215.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.85 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,9 mm	64	9.886-216.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,95 mm	65	9.886-217.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.95 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 1 mm	66	9.886-218.0	Screw-on F21 sapphire round jet nozzle with a diameter of 1.00 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 1,1 mm	67	9.886-219.0	Screw-on F21 sapphire round jet nozzle with a diameter of 1.10 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,3 mm	68	9.886-207.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.30 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
Round jet nozzle F21, Saphir, 0,5 mm	69	9.886-210.0	Screw-on F21 sapphire round jet nozzle with a diameter of 0.50 mm. Suitable for working pressures of up to 3,000 bar.	<input type="checkbox"/>
PROTECTIVE CLOTHING				
HD Overall size M	70	6.547-055.0	High-pressure protective suit for safe working with high-pressure water jets of up to 1000 bar. Particularly lightweight design which feels comfortable to wear and provides excellent freedom of movement.	<input type="checkbox"/>

☐ Available accessories.

ACCESSORIES FOR HD 9/100-4 CAGE ADV

1.812-002.0



		Order no.	Description	
PROTECTIVE CLOTHING				
High-pressure protective suit, size L	71	6.547-056.0	High-pressure protective suit for safe working with high-pressure water jets of up to 1000 bar. Particularly lightweight design which feels comfortable to wear and provides excellent freedom of movement.	<input type="checkbox"/>
HD Overall size XL	72	6.547-057.0		<input type="checkbox"/>
ROTARY NOZZLES				
Single-jet rotary nozzles				
Orbimaster, 1 mm	73	9.886-666.0	High area performance due to orbital movement of the water stream. Rotor and seat made of hard metal, casing made of high-strength stainless steel. Easy rotor replacement. Suitable for hot water operation up to 100°C. Self-propelling. Low weight.	<input type="checkbox"/>
Repair kit Orbimaster, 1 mm	74	9.884-069.0	Repair kit Orbimaster, comprising rotor, fitting and O-ring. Suitable for our single rotary nozzle (Order No. 9.886-666.0). Can be used up to 1,500 bar water pressure.	<input type="checkbox"/>
Multi-jet rotary nozzles				
Nozzle carrier head TD06	75	9.886-875.0	6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 30° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>
Nozzle carrier head TD08	76	9.886-879.0	6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 25° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>
Nozzle carrier head TD10	77	9.918-067.0	4-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3000 bar. 45° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>
Nozzle body	78	9.917-677.0	Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	<input type="checkbox"/>
Nozzle carrier head TD09	79	9.899-828.0	6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

☐ Available accessories.