KÄRCHE

IVR-L 100/24-2 TC DP

IVR-L 100/24-2 Tc Dp mobile liquid and swarf vacuum. AC-powered, suitable for oils, coolant emulsions or fine, light metal shavings in medium quantities, for example.









Order no.

9.989-400.0

- Tilting chassis
- Drum pump function
- Visual filling level indicator

	4054278695136
Ph / V / Hz	1 / 220 - 240 / 50 - 60
l/s / m³/h	148 / 532
mbar / kPa	230 / 23
I	100
kW	2.4
	Electric
	DN 50
	DN 50 / DN 40
	L
m²	0.45
kg	57
kg	57
kg	57
mm	840 × 660 × 1320
	l/s / m³/h mbar / kPa l kW

This machine requires instruction.

Equipment	
Drum pump function	
Container emptying	Tilting chassis
Included in the scope of supply.	

KARCHER





Ergonomic tilting chassis

- Sophisticated system for safe, manual, effortless emptying.
- Chassis system enables ergonomic tilted emptying using the roll-off mechanism.
- Quick and easy emptying of the container: just tip backwards and you are done!



High robustness, flexibility and modularity

- Machine and chassis very robust and equipped with high wall thicknesses.
- Rotatable hose connection with up to 360° rotatable pipe bend.
- Optionally available with overfill protection, strainer or accessories holder.

Drum pump function

- An autonomous barrel pump significantly increases the ability for vacuumed matter to be returned.
- Transparent hose for checking the amount of fluid absorbed.





















	1			
		Order no.	Description	
OTHER ACCESSORIES				
Baffle plate Ø 517 mm	1	9.980-857.0	Baffle plate made from plastic with 517 mm diameter for containers and tanks.	
HANDLES				
Elbow aluminium 45° DN40	2	9.989-544.0	45° curved handle made from aluminium, DN 40.	
Elbow aluminium 45° DN50	3	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	
Handle DN 40	4	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	
Handle DN50, curved	5	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	
Stainless steel handle NW40	6	9.989-036.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 40.	
Stainless steel handle NW50	7	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	
SUCTION TUBES				
Carbon suction tube 1500 mm DN40	8	9.989-552.0	Very light carbon extension tube, electroconductive, DN 40. Length: 1500 mm.	
Carbon suction tube 1500 mm DN50	9	9.989-553.0	Electroconductive, very light carbon extension tube. Inner cone DN 50, 1500 mm long.	
Suction tube 850 mm DN 40	10	9.977-525.0	Steel extension tube, electroconductive, DN 40. Length: 850 mm.	
Suction tube 850 mm DN 50	11	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	
Aluminium suction tube 1500 mm NW40	12	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	
Aluminium suction tube 1500 mm NW50	13	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	
Stainless steel suction tube 850 mm NW40	14	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.























		Order no.	Description	
SUCTION TUBES				
Stainless steel suction tube 850 mm NW50	15	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	
ACCESORY SETS				
Accessory kit for liquids				
Liquid/solid accessory kit Expert DN40	16	9.990-878.0	Accessory kit DN40 for liquid vacuums: PU hose 3 m (9.989-617.0), handle (9.977-679.0), standard nozzle (9.988-401.0), reducer (9.981-231.0), surface nozzle 120 mm (9.988-118.0).	
Liquid/solid accessory kit Expert DN50	17	9.990-879.0	Accessory kit DN50 for liquid vacuums: PU hose 3 m (9.989-619.0), handle (9.977-678.0), standard nozzle (9.988-402.0), surface nozzle 120 mm (9.988-119.0).	
Accessory kit for liquids/chips		•		
Oil/swarf accessory kit DN40 Expert	18	9.990-880.0	Accessory kit DN40 for liquid vacuum and swarf vacuum: 3 m ME-PU hose (9.989-621.0), handle (9.977-679.0), standard nozzle (9.989-674.0), reducer (9.981-231.0), surface nozzle (9.988-118.0).	
Oil/swarf accessory kit DN50 Expert	19	9.990-881.0	Accessory kit DN50 for liquid and swarf vacuum: ME-PU hose 3 m (9.989-623.0), handle (9.977-678.0), standard nozzle (9.989-673.0), surface nozzle (9.988-119.0).	
Advanced liquid floor cleaning set DN40	20	9.990-895.0	Advanced liquid floor cleaning set: EVA hose (9.990-925.0), handle (9.990-927.0), 2×10^{-2} suction tube (9.990-931.0), floor nozzle (9.990-937.0), standard nozzle (9.980-773.0).	
Advanced liquid floor cleaning set DN50	21	9.990-896.0	Advanced liquid floor cleaning set: EVA hose (9.990-926.0), handle (9.990-928.0), 2×10^{-2} suction tube (9.990-932.0), floor nozzle (9.990-938.0), standard nozzle (9.980-761.0).	
NOZZLES				
Standard nozzles				
Standard PVC nozzle DN40	22	9.989-674.0	Electroconductive standard PVC nozzle. DN 40.	
Standard PVC nozzle DN50	23	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	
Standard nozzle silicone DN40	24	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	
Standard nozzle silicone DN50	25	9.988-402.0		
Standard nozzle cuttable rubber DN40	26	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	
Standard nozzle cuttable rubber DN50	27	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	
Standard aluminium nozzle DN40	28	9.980-748.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 40.	

 $[\]blacksquare$ Included in the scope of supply. $\hfill\Box$ Available accessories.























		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard aluminium nozzle DN50	29	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	
Flexible standard nozzles		•		
Standard nozzle flexible PVC DN40	30	9.981-420.0	Electroconductive, flexible round nozzle made from galvanised steel, with rubber mouthpiece DN 30.	
Standard nozzle flexible PVC DN50	31	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	
Standard nozzle, flexible, angled 90° PP DN40	32	9.981-429.0	Flexible, electroconductive angled nozzle, DN 40, length: 800 mm.	
Standard nozzle, flexible, angled 90° PP DN50	33	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	
Floor nozzles				
Aluminium floor nozzle 370 mm DN40	34	9.989-683.0	Floor nozzle, 370 mm, made from aluminium. DN 40.	
Aluminium floor nozzle, el, 370 mm, DN40	35	9.989-682.0	Floor nozzle, 370 mm, made from aluminium. Electroconductive. DN 40.	T
Aluminium floor nozzle 200 mm DN50	36	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	
Aluminium floor nozzle 370 mm DN50	37	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. Electroconductive. DN 50.	
Aluminium floor nozzle, el, 370 mm, DN50	38	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	
Aluminium floor nozzle 500 mm DN50	39	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	
Aluminium floor nozzle, el, 500 mm, DN50	40	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	
Stainless steel floor nozzle el 370 mm DN40	41	9.989-558.0	Multi-purpose floor nozzle (370 mm), electroconductive, DN 40.	T
Stainless steel floor nozzle el 370 mm DN50	42	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	

[☐] Available accessories.





















		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle rubber strip oil-resistant. 220 mm	43	9.981-923.0	Squeegee with plastic strip for floor nozzle, 220 mm wide.	
Floor nozzle rubber strip 370 mm	44	9.981-914.0	Squeegee with profiled strip for floor nozzle, 370 mm wide.	
Floor nozzle rubber strip 500 mm	45	9.981-915.0	Oil-resistant squeegee with profiled strip for floor nozzle, 500 mm wide.	
Floor nozzle brush strip el. 370 mm	46	9.984-939.0	Electroconductive squeegee for floor nozzle, 370 mm wide.	
Floor nozzle brush strip 500 mm	47	9.980-764.0	Brush strip set for floor nozzle 500 mm, with profiled strip.	
Crevice nozzles				
Crevice nozzle PP 15 mm × 145 mm DN50	48	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	
Crevice nozzle PU 22 mm × 175 mm DN50	49	9.981-482.0	Crevice nozzle made from PU, DN 50.	
Crevice nozzle 18 mm × 120 mm DN50	50	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	
Crevice nozzle 25 mm × 120 mm DN50	51	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	
Flexible crevice nozzles		L		
Flexible crevice nozzle silicone 65 mm DN50	52	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	
Flexible crevice nozzle 11 mm × 58 mm DN40	53	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	
Flexible crevice nozzle 20 mm × 45 mm DN40	54	9.981-423.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 40.	
Flexible crevice nozzle 12 mm × 45 mm DN50	55	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	
Flexible crevice nozzle 20 mm × 45 mm DN50	56	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	

[☐] Available accessories.

























	_			
		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle 120 mm DN40	57	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	
Silicone surface nozzle 120 mm DN50	58	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	
Aluminium surface nozzle, 150 mm, DN 40	59	9.989-666.0	Surface nozzle, 150 mm, made from aluminium. DN 40.	
Aluminium surface nozzle 150 mm DN50	60	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	
Liquid nozzles		•		
Liquid nozzle 900 mm DN50	61	9.981-427.0	Bypass nozzle, DN 50, overall length: 1000 mm.	
Borehole nozzles		•		
Blind hole nozzle DN40	62	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	
Blind hose nozzle angled 60° DN40	63	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	
Blind hose nozzle angled 90° DN40	64	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	
Blind hose nozzle angled 90° 200 mm extension DN40	65	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	
BRUSHES				
Standard brushes				
Standard brush 40 mm DN40	66	9.981-431.0	Flat brush nozzle DN 40.	
Standard brush 40 mm DN50	67	9.981-432.0	Flat brush nozzle DN 50.	
End brushes		'		,
End brush Ø 82 mm DN40	68	9.989-609.0	Electroconductive end brush with 82 mm diameter. DN 40.	
End brush Ø 82 mm DN50	69	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	
Surface brushes				
Surface brush PP 24 mm DN40	70	9.989-610.0	Electroconductive surface brush. DN 40.	

 $[\]hfill\square$ Available accessories.















				\neg
		Order no.	Description	\perp
BRUSHES				
Surface brushes	1 .	1		
Surface brush 300 mm DN40	71	9.981-911.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	L
Surface brush 300 mm DN50	72	9.981-912.0		
HOSES				
Hose installation sets				
Hose installation kit DN40	73	9.989-627.0	Multipiece hose connection set, DN 40.	
Hose installation kit DN50	74	9.989-628.0	Multipiece hose connection kit, DN 50.	
PU hoses	•			
Hose PU DN40 3 m	75	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	
Hose PU DN40 5 m	76	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	
PU hose DN40 15 m without connectors	77	9.989-637.0	PU hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 80 $^{\circ}$ C. Length: 15 m.	
Hose PU DN50 3 m	78	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	
Hose PU DN50 5 m	79	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	
PU hose DN50 15 m without connectors	80	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 $^{\circ}$ C. Length: 15 m.	
ME-PU-hoses				
Hose ME-PU DN40 3 m	81	9.989-621.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	
ME-PU hose, DN 40, 5 m	82	9.989-622.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	
ME-PU hose DN40 15 m without connectors	83	9.989-640.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	
Hose ME-PU DN50 3 m	84	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	

[☐] Available accessories.































		Order no.	Description
HOSES			
ME-PU-hoses			
Hose ME-PU DN50 5 m	85	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 $^{\circ}$ C. Length: 5 m.
ME-PU hose DN50 15 m without connectors	86	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.
ADAPTERS / REDUCERS / DISTRIBUTORS			
Accessories adapter			
Adapter accessories DN 50 to DN 51	87	9.989-603.0	Steel adapter for connection of DN 50 to DN 51. Electroconductive.
Adapter accessories DN 51 to DN 50	88	9.989-601.0	Steel adapter for connection of DN 51 to DN 50. Electroconductive.
Adapter accessories DN50 to DN61	89	9.989-602.0	Steel adapter for connection of DN 50 to DN 61. Electroconductive.
Adapter accessories DN 61 to DN 50	90	9.989-604.0	Steel adapter for connection of DN 61 to DN 50. Electroconductive.
Reducers/expanders		1	
Reduction DN50 to DN40	91	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.
Expander			
Expansion DN50 to DN70	92	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.
Distributor			
Y-piece fitting DN50 to DN40	93	9.981-149.0	Manifold, electroconductive, steel, DN 50/40/40.
FILTERS			
Surface filter			
Surface filter PE L 0.45 m²	94	9.988-256.0	
EMPTYING SUPPORTS			
Strainer baskets			
Filter basket, stainless steel, Ø 495 mm, 40 l	95	9.980-849.0	Filter basket, stainless steel, 40 l, hole diameter 1.5 mm. For the efficient separation of liquids and shavings.
Other emptying aids			
Overfill protection dia. 540 mm	96	9.982-117.0	Float insert, stainless steel, for overfill prevention with ball float, central suction.
PRE-SEPARATORS			
Pre-separator			
Pre-separator Tc Op liquids 125 DN70	97	9.989-686.0	125 litre pre-separator, DN 70.
Pre-separator drum 200 l	98		Standard drum which complies with the ISO 15750-2 standard.

[☐] Available accessories.





		Order no.	Description	
PRE-SEPARATORS				
Pre-separator lid				
Pre-separator cover Op liquids ø 517 mm DN70	99	9.981-666.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	
Pre-separator cover Op liquids ø 575 mm DN70	100	9.981-662.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	
Pre-separator cover solid materials ø 517 mm DN70	101	9.981-665.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	
Pre-separator cover solid materials ø 575 mm DN70	102	9.981-661.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	

[☐] Available accessories.