PGG 3/1

Petrol-powered, with 2.8 kW power, puncture-proof wheels and 15 litre tank: Synchronous generator PGG 3/1 for up to 12 hours independent of external power sources in many different areas of use.



Stage V

6–12 h

Order no.	1.042-207.0

- Foldable push handle and puncture-proof tyres with robust cage frame
- Convenient electric start function with key switch

Technical data		
EAN code		4054278547923
Number of current phases	Ph	1
Voltage	V	230
Sound pressure level	dB(A)	74
Nominal power	kW	2.8
Power	kW	3
Drive type		Petrol
Displacement	cm^3	208
Motor rating	kW / hp	4 / 5.4
Fuel consumption	l/h	2.3
Tank capacity	l	15
Runtime at 50% output	h	12
Runtime at 100% output	h	6.5
Weight incl. packaging	kg	56.1
Weight without accessories	kg	51.7
Dimensions (L × W × H)	mm	645 × 622 × 549

Scope of supply
Operating state display
DC output (12 V)
Protection class IP 23
Low oil and overload protection
Fuel gauge
Single phase socket type F (Schuko)
Automatic Voltage Regulation (AVR)

PGG 3/1, 1.042-207.0, 2026-04-12









Extraordinary ease of use

- High mobility thanks to the foldable push handle and puncture-proof wheels.
- Electro start function for the convenient and quick start of the petrol engine.

Ultimate reliability and safety

- With overload and oil shortage protection as well as tubular steel frame for maximum safety.
- With automatic voltage regulator (AVR) for the operation of sensitive electronic devices.

Operation of Kärcher high-pressure cleaners

- Enables the use of high-pressure cleaners in areas without external power supply.
- Suitable for selected single-phase high-pressure cleaners.

PGG 3/1, 1.042-207.0, 2026-04-12