PGG 6/1

With a power rating of 5 kW, the petrol-operated synchronous generator PGG 6/1 impresses with up to 10 hours of independent power supply in many commercial and municipal applications.



Stage V

6-10 h

Order no.	1.042-208.0

- Foldable push handle and puncture-proof tyres with robust cage frame
- Convenient electric start function with key switch

Technical data		
EAN code		4054278547930
Number of current phases	Ph	1
Voltage	V	230
Sound pressure level	dB(A)	75
Nominal power	kW	5
Power	kW	5.5
Drive type		Petrol
Displacement	cm^3	390
Motor rating	kW / hp	8.5 / 11.6
Fuel consumption	l/h	3.8
Tank capacity	l	25
Runtime at 50% output	h	10
Runtime at 100% output	h	6.5
Weight incl. packaging	kg	92.4
Weight without accessories	kg	84.7
Dimensions (L × W × H)	mm	743 × 713 × 670

Scope of supply
Operating state display
DC output (12 V)
Protection class IP 23
Low oil and overload protection
Fuel gauge
2 single phase sockets type F (Schuko)
Single phase CEE socket (32 A)
Automatic Voltage Regulation (AVR)

PGG 6/1, 1.042-208.0, 2026-04-12









Extraordinary ease of use

- Puncture-proof wheels guarantee permanently high mobility.
- Electro start function for the convenient and quick start of the petrol engine.

Ultimate reliability and safety

- With automatic voltage regulator (AVR), which supplies a largely constant voltage.

Very powerful

- 230 V synchronous generator reliably provides continuous power of 5.5 kW.
- Powerful petrol engine for applications of min. 6.5 hours per tank filling.

PGG 6/1, 1.042-208.0, 2026-04-12