

IVM 60/36 -3

3-motor, mobile and robust middle-class industrial vacuum cleaner IVM 60/36-3 for universal use in industry for fine and coarse solid materials. With star filter in dust class M.



Order no. 1.573-320.0

- Antistatic equipment
- Extra-large filter area
- Robust wheels and castors

Technical data		
EAN code		4054278325668
Power supply	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s / m³/h	221 / 799
Vacuum	mbar / kPa	254 / 25.4
Container capacity	l	60
Rated input power	kW	3.6
Vacuuming type		Electric
Connection nominal diameter		DN 70
Accessory nominal diameter		DN 70 / DN 50 / DN 40
Sound pressure level	dB(A)	79
Main filter dust class		M
Filter area for main filter	m²	2.2
Weight without accessories	kg	68
Weight incl. packaging	kg	71.8
Dimensions (L × W × H)	mm	1020 × 680 × 1490

This machine requires instruction.

Equipment	
Main filter	Star filter
Accessories included in the scope of delivery	no
Container emptying	Set-down trolley
■ Included in the scope of supply.	



Fitted with three blower motors

- Three powerful fans for impressive cleaning performance.
- Fans can be switched on separately for individual suction power as required.



Manual IVM filter cleaning

- Effortless operation by means of an ergonomically placed lever if required.
- Extends the life of the filter and thus reduces the maintenance effort.
- Identical cleaning results, regardless of the amount of force used.



Equipped with extra-large star filter

- For safely vacuuming solids and dusts up to dust class M.
- Also suitable for large quantities of dust.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
ACCESSORY SETS				
Accessory kit for solids/dust				
Oven cleaning accessory kit Expert DN 50	1	9.989-938.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-979.0), handle (9.989-899.0), suction tube (9.989-929.0), floor nozzle (9.989-935.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Oven cleaning accessory kit Expert DN 40	2	9.989-939.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-976.0), handle (9.989-898.0), suction tube (9.989-928.0), floor nozzle (9.989-934.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit Expert DN 40	3	9.989-940.0	Food accessory kit DN 40: PU hose 3 m (9.989-970.0), handle (9.989-898.0), standard nozzle (9.989-838.0), brush (9.989-879.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit Expert DN 50	4	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Accessory kit for overhead cleaning Expert DN 40	5	9.989-942.0	Accessory kit DN 40 for overhead cleaning: suction tubes (9.989-920.0/9.993-008.0), handles (9.989-916.0/9.989-918.0), standard nozzle (9.989-838.0), brush (9.989-879.0), adapter (9.993-012.0).	☐
Accessory kit for overhead cleaning DN 50 Expert	6	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	☐
Advanced dry floor cleaning set DN50	7	9.990-894.0	Advanced dry floor cleaning set: EVA hose (9.990-924.0), handle (9.990-930.0), 2 × suction tube (9.990-934.0), floor nozzle (9.990-936.0), standard nozzle (9.980-761.0).	☐
Accessory kit for solids/dust DN 50 Expert	8	9.989-662.0	Accessory kit DN 50 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-090.0), handle (9.977-678.0), standard nozzle (9.988-402.0), reducer (9.977-772.0).	☐
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F40	9	9.989-835.0		☐
Standard nozzle silicone FDA green DN-F40	10	9.989-836.0		☐
Standard nozzle silicone FDA red DN-F40	11	9.989-837.0		☐
Standard nozzle silicone FDA transparent DN-F40	12	9.989-838.0		☐
Standard nozzle silicone FDA white DN-F40	13	9.989-839.0		☐
Standard nozzle silicone FDA yellow DN-F40	14	9.989-840.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 60/36 -3
1.573-320.0




		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F50	15	9.989-841.0		☐
Standard nozzle silicone FDA green DN-F50	16	9.989-842.0		☐
Standard nozzle silicone FDA red DN-F50	17	9.989-843.0		☐
Standard nozzle silicone FDA transparent DN-F50	18	9.989-844.0		☐
Standard nozzle silicone FDA white DN-F50	19	9.989-845.0		☐
Standard nozzle silicone FDA yellow DN-F50	20	9.989-846.0		☐
Standard PVC nozzle DN40	21	9.989-674.0	Electroconductive standard PVC nozzle. DN 40.	☐
Standard PVC nozzle DN50	22	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	☐
Standard PVC nozzle DN70	23	9.989-676.0	Electroconductive standard PVC nozzle. DN 70.	☐
Standard nozzle silicone DN40	24	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	☐
Standard nozzle silicone DN50	25	9.988-402.0		☐
Standard silicone nozzle DN70	26	9.989-672.0	Electroconductive standard silicone nozzle. DN 70.	☐
Standard nozzle cuttable rubber DN40	27	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	☐
Standard nozzle cuttable rubber DN50	28	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 60/36 -3


1.573-320.0



29-31




32




33



34



35-36



37-38



39-40



41-42

		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard aluminium nozzle DN40	29	9.980-748.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 40.	☐
Standard aluminium nozzle DN50	30	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	☐
Standard aluminium nozzle DN70	31	9.989-663.0	Standard nozzle made from aluminium. Electroconductive. DN 70.	☐
Flexible standard nozzles				
Standard nozzle flexible PVC DN40	32	9.981-420.0	Electroconductive, flexible round nozzle made from galvanised steel, with rubber mouthpiece DN 30.	☐
Standard nozzle flexible PVC DN50	33	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	☐
Standard nozzle flexible PVC DN70	34	9.981-422.0	Flexible, electroconductive standard nozzle, DN 70, with rubber mouthpiece.	☐
Standard nozzle, flexible, angled 90° PP DN40	35	9.981-429.0	Flexible, electroconductive angled nozzle, DN 40, length: 800 mm.	☐
Standard nozzle, flexible, angled 90° PP DN50	36	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 304 DN-F40 blue	37	9.989-861.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 blue	38	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 green	39	9.989-863.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	40	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 red	41	9.989-865.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	42	9.989-866.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 60/36 -3
1.573-320.0



		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F40 transparent	43	9.989-867.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 transparent	44	9.989-868.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 white	45	9.989-869.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 white	46	9.989-870.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 yellow	47	9.989-871.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 yellow	48	9.989-872.0		☐
Floor nozzle stainless steel AISI 316L DN-F40	49	9.989-914.0		☐
Floor nozzle stainless steel AISI 316L DN-F50	50	9.989-915.0		☐
Floor nozzle stainless steel 400 mm DN-F40	51	9.989-934.0		☐
Floor nozzle stainless steel 400 mm DN-F50	52	9.989-935.0		☐
Floor nozzle aluminium 400 mm DN-F40	53	9.989-936.0		☐
Floor nozzle aluminium 400 mm DN-F50	54	9.989-937.0		☐
Aluminium floor nozzle 370 mm DN40	55	9.989-683.0	Floor nozzle, 370 mm, made from aluminium. DN 40.	☐
Aluminium floor nozzle, el, 370 mm, DN40	56	9.989-682.0	Floor nozzle, 370 mm, made from aluminium. Electroconductive. DN 40.	☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



57




58-59



60-61




62-63



64



65-66



67-68



69

		Order no.	Description	
NOZZLES				
Floor nozzles				
Aluminium floor nozzle 200 mm DN50	57	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	☐
Aluminium floor nozzle 370 mm DN50	58	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 370 mm, DN50	59	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	☐
Aluminium floor nozzle 500 mm DN50	60	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 500 mm, DN50	61	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	☐
Stainless steel floor nozzle el 370 mm DN40	62	9.989-558.0	Multi-purpose floor nozzle (370 mm), electroconductive, DN 40.	☐
Stainless steel floor nozzle el 370 mm DN50	63	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	☐
Floor nozzle rubber strip oil-resistant. 220 mm	64	9.981-923.0	Squeegee with plastic strip for floor nozzle, 220 mm wide.	☐
Floor nozzle rubber strip 370 mm	65	9.981-914.0	Squeegee with profiled strip for floor nozzle, 370 mm wide.	☐
Floor nozzle rubber strip 500 mm	66	9.981-915.0	Oil-resistant squeegee with profiled strip for floor nozzle, 500 mm wide.	☐
Floor nozzle brush strip el. 370 mm	67	9.984-939.0	Electroconductive squeegee for floor nozzle, 370 mm wide.	☐
Floor nozzle brush strip 500 mm	68	9.980-764.0	Brush strip set for floor nozzle 500 mm, with profiled strip.	☐
Crevice nozzles				
Crevice nozzle PP 15 mm × 145 mm DN40	69	9.988-116.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 42.	☐
Crevice nozzle PP 15 mm × 145 mm DN50	70	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3

1.573-320.0



		Order no.	Description	
NOZZLES				
Crevice nozzles				
Crevice nozzle PU 19 mm × 160 mm DN40	71	9.981-483.0	Crevice nozzle made from PU, DN 40.	☐
Crevice nozzle PU 22 mm × 175 mm DN50	72	9.981-482.0	Crevice nozzle made from PU, DN 50.	☐
Crevice nozzle 17 mm × 120 mm DN40	73	9.989-680.0	Electroconductive crevice nozzle, 17 × 120 mm. DN 40.	☐
Crevice nozzle 25 mm × 120 mm DN40	74	9.989-678.0	Electroconductive crevice nozzle, 25 × 120 mm. DN 40.	☐
Crevice nozzle 18 mm × 120 mm DN50	75	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	☐
Crevice nozzle 25 mm × 120 mm DN50	76	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Crevice nozzle 28 mm × 120 mm DN70	77	9.981-444.0	Electroconductive crevice nozzle made from sheet steel, DN 70, with 30 mm slot width.	☐
Stainless steel crevice nozzle 17 mm × 120 mm DN40	78	9.989-193.0	Crevice nozzle made from stainless steel, DN 50.	☐
Stainless steel crevice nozzle 22 mm × 220 mm DN50	79	9.988-123.0	Stainless steel crevice nozzle, DN 42, suitable for use with foods.	☐
Flexible crevice nozzles				
Crevice nozzle flexible silicone FDA DN-F50 transparent	80	9.989-847.0		☐
Crevice nozzle flexible silicone FDA DN-F40 transparent	81	9.989-848.0		☐
Flexible crevice nozzle silicone 65 mm DN50	82	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	☐
Flexible crevice nozzle 11 mm × 58 mm DN40	83	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	☐
Flexible crevice nozzle 20 mm × 45 mm DN40	84	9.981-423.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 40.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
NOZZLES				
Flexible crevice nozzles				
Flexible crevice nozzle 12 mm × 45 mm DN50	85	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	86	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F40	87	9.989-849.0		☐
Silicone surface nozzle FDA blue DN-F50	88	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F40	89	9.989-851.0		☐
Silicone surface nozzle FDA green DN-F50	90	9.989-852.0		☐
Silicone surface nozzle FDA red DN-F40	91	9.989-853.0		☐
Silicone surface nozzle FDA red DN-F50	92	9.989-854.0		☐
Silicone surface nozzle FDA transparent DN-F40	93	9.989-855.0		☐
Silicone surface nozzle FDA transparent DN-F50	94	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F40	95	9.989-857.0		☐
Silicone surface nozzle FDA white DN-F50	96	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F40	97	9.989-859.0		☐
Silicone surface nozzle FDA yellow DN-F50	98	9.989-860.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3

1.573-320.0



		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle 120 mm DN40	99	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	☐
Silicone surface nozzle 120 mm DN50	100	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
Aluminium surface nozzle, 150 mm, DN 40	101	9.989-666.0	Surface nozzle, 150 mm, made from aluminium. DN 40.	☐
Aluminium surface nozzle 150 mm DN50	102	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	☐
Borehole nozzles				
Blind hole nozzle DN40	103	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	☐
Blind hose nozzle angled 60° DN40	104	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐
Blind hole nozzle angled 90° DN40	105	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	☐
Blind hose nozzle angled 90° 200 mm extension DN40	106	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN40	107	9.981-431.0	Flat brush nozzle DN 40.	☐
Standard brush 40 mm DN50	108	9.981-432.0	Flat brush nozzle DN 50.	☐
End brushes				
Brush FDA blue ø 75 mm DN-F40	109	9.989-873.0		☐
Brush FDA blue ø 75 mm DN-F50	110	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F40	111	9.989-875.0		☐
Brush FDA green ø 75 mm DN-F50	112	9.989-876.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
BRUSHES				
End brushes				
Brush FDA red ø 75 mm DN-F40	113	9.989-877.0		☐
Brush FDA red ø 75 mm DN-F50	114	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F40	115	9.989-879.0		☐
Brush FDA white ø 75 mm DN-F50	116	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F40	117	9.989-881.0		☐
Brush FDA yellow ø 75 mm DN-F50	118	9.989-882.0		☐
End brush Ø 82 mm DN40	119	9.989-609.0	Electroconductive end brush with 82 mm diameter. DN 40.	☐
End brush Ø 82 mm DN50	120	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	☐
Surface brushes				
Surface brush PP 24 mm DN40	121	9.989-610.0	Electroconductive surface brush. DN 40.	☐
Surface brush 300 mm DN40	122	9.981-911.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	☐
Surface brush 300 mm DN50	123	9.981-912.0		☐
Cylinder brushes				
Cylinder brush ø 100 mm DN-F40	124	9.989-922.0		☐
Cylinder brush ø 200 mm DN-F40	125	9.989-923.0		☐
Cylinder brush ø 100 mm DN-F50	126	9.989-925.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
BRUSHES				
Cylinder brushes				
Cylinder brush ø 200 mm DN-F50	127	9.989-926.0		☐
HOSES				
ME-Schläuche				
Hose ME DN40 3 m	128	9.989-976.0		☐
Hose ME DN40 5 m	129	9.989-977.0		☐
Hose without connection ME DN40 15 m	130	9.989-978.0		☐
Hose ME DN50 3 m	131	9.989-979.0		☐
Hose ME DN50 5 m	132	9.989-980.0		☐
PVC				
Hose PVC DN40 1 m	133	9.989-626.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 1 m.	☐
Hose PVC DN40 3 m	134	9.989-962.0		☐
Hose PVC DN40 5 m	135	9.989-963.0		☐
Hose PVC DN50 3 m	136	9.989-964.0		☐
Hose PVC DN50 5 m	137	9.989-965.0		☐
Hose PVC DN40 3 m	138	9.989-647.0	PVC hose, DN 40. Temperature-resistant up to 85 °C and electrically conductive. Length: 3 m.	☐
Hose PVC DN40 5 m	139	9.989-614.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 5 m.	☐
PVC hose DN40 15 m without connectors	140	9.989-633.0	PVC hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3

1.573-320.0



		Order no.	Description	
HOSES				
PVC				
Hose PVC DN50 3 m	141	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN50 5 m	142	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	☐
PVC hose DN50 15 m without connectors	143	9.989-634.0	PVC hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
Hose PVC DN70 3 m	144	9.989-635.0	Electroconductive PVC hose, DN 70. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN70 5 m	145	9.989-643.0	PVC hose, DN 70. Temperature-resistant up to 85 °C and electroconductive. Length: 5 m.	☐
PVC hose DN70 15 m without connectors	146	9.989-636.0	PVC hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
EVA hoses				
Hose EVA DN40 3 m	147	9.989-982.0		☐
Hose EVA DN40 5 m	148	9.989-983.0		☐
Hose EVA DN50 3 m	149	9.989-984.0		☐
Hose EVA DN50 5 m	150	9.989-985.0		☐
Hose EVA NW40 3 m	151	9.988-088.0	Electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW40 5 m	152	9.988-089.0	Five-metre-long, electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 5 m.	☐
EVA hose DN40 15 m without connectors	153	9.989-630.0	EVA hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose EVA NW50 3 m	154	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0




155



153, 156, 159



151-152, 154,
157-158



160-162



163-164



165-168

		Order no.	Description	
HOSES				
EVA hoses				
Hose EVA NW50 5 m	155	9.988-091.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐
EVA hose DN50 15 m without connectors	156	9.989-631.0	EVA hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose EVA DN70 3 m	157	9.989-613.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 3 m.	☐
Hose EVA DN70 5 m	158	9.989-624.0	Electroconductive EVA hose, DN 70. Temperature-resistant up to 65 °C. Length: 5 m.	☐
EVA hose DN70 15 m without connectors	159	9.989-632.0	EVA hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose installation sets				
Hose installation kit DN40	160	9.989-627.0	Multipiece hose connection set, DN 40.	☐
Hose installation kit DN50	161	9.989-628.0	Multipiece hose connection kit, DN 50.	☐
Hose installation kit DN70	162	9.989-629.0	Multipiece hose connection kit, DN 70.	☐
Hose connection kit, stainless steel AISI 304 DN40	163	9.989-986.0	Hose connection kit in nominal width DN 40, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
Hose connection kit, stainless steel AISI 304 DN50	164	9.989-987.0	Hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
PU hoses				
Hose PU DN40 3 m	165	9.989-966.0		☐
Hose PU DN40 5 m	166	9.989-967.0		☐
Hose PU DN50 3 m	167	9.989-968.0		☐
Hose PU DN50 5 m	168	9.989-969.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3

1.573-320.0



169-173



174



175-176, 178-179,
181-182



177, 180, 183

		Order no.	Description	
HOSES				
PU hoses				
Hose PU FDA DN40 3 m	169	9.989-970.0		☐
Hose PU FDA DN40 5 m	170	9.989-971.0		☐
Hose PU FDA DN40 15 m	171	9.989-972.0		☐
Hose PU FDA DN50 3 m	172	9.989-973.0		☐
Hose PU FDA DN50 5 m	173	9.989-974.0		☐
Hose PU FDA DN50 15 m	174	9.989-975.0		☐
Hose PU DN40 3 m	175	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN40 5 m	176	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN40 15 m without connectors	177	9.989-637.0	PU hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
Hose PU DN50 3 m	178	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	179	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN50 15 m without connectors	180	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
Hose PU DN70 3 m	181	9.989-644.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 3 m.	☐
Hose PU DN70 5 m	182	9.989-645.0	Oil-resistant, electroconductive PU hose, DN 70. Temperature-resistant up to 80 °C, suitable for abrasive suction media. Length: 5 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



177, 180, 183



185-186



187-188



189-190



191-192



193-194



195






196

		Order no.	Description	
HOSES				
PU hoses				
PU hose DN70 15 m without connectors	183	9.989-639.0	PU hose without tap adapter, DN 70. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
ME-PU-hoses				
Hose without connection ME DN50 15 m	184	9.989-981.0		☐
HANDLES				
Elbow aluminium 45° DN40	185	9.989-544.0	45° curved handle made from aluminium, DN 40.	☐
Elbow aluminium 45° DN50	186	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	☐
Handle stainless steel AISI 304 DN40	187	9.989-896.0		☐
Handle stainless steel AISI 304 DN50	188	9.989-897.0		☐
Handle straight stainless steel AISI 304 DN40	189	9.989-898.0		☐
Handle straight stainless steel AISI 304 DN50	190	9.989-899.0		☐
Handle carbon 45° DN-F40	191	9.989-916.0		☐
Handle carbon 45° DN-F50	192	9.989-917.0		☐
Handle carbon 110° DN-F40	193	9.989-918.0		☐
Handle carbon 110° DN-F50	194	9.989-919.0		☐
Handle DN 40	195	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	☐
Handle DN50, curved	196	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
HANDLES				
Handle DN 70	197	9.977-677.0		☐
Stainless steel handle NW40	198	9.989-036.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 40.	☐
Stainless steel handle NW50	199	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	☐
SUCTION TUBES				
Carbon suction tube 1500 mm DN40	200	9.989-552.0	Very light carbon extension tube, electroconductive, DN 40. Length: 1500 mm.	☐
Carbon suction tube 1500 mm DN50	201	9.989-553.0	Electroconductive, very light carbon extension tube. Inner cone DN 50, 1500 mm long.	☐
Suction tube stainless steel AISI 304 DN40	202	9.989-912.0		☐
Suction tube stainless steel AISI 304 DN50	203	9.989-913.0		☐
Suction tube carbon 1500 mm DN-F40 conical	204	9.989-920.0		☐
Suction tube carbon 1500 mm DN-F50 conical	205	9.989-921.0		☐
Suction tube aluminium high temperature 1000 mm DN-F40	206	9.989-928.0		☐
Suction tube aluminium high temperature 1000 mm DN-F50	207	9.989-929.0		☐
Suction tube aluminium high temperature 2000 mm DN-F40	208	9.989-930.0		☐
Suction tube aluminium high temperature 2000 mm DN-F50	209	9.989-931.0		☐
Suction tube aluminium high temperature 3000 mm DN-F40	210	9.989-932.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3 1.573-320.0



		Order no.	Description	
SUCTION TUBES				
Suction tube aluminium high temperature 3000 mm DN-F50	211	9.989-933.0		☐
Suction tube 850 mm DN 40	212	9.977-525.0	Steel extension tube, electroconductive, DN 40. Length: 850 mm.	☐
Suction tube 850 mm DN 50	213	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	☐
Suction tube 850 mm DN 70	214	9.981-910.0	Electroconductive extension tube, internal cone DN 70, 850 mm total length.	☐
Aluminium suction tube 1500 mm NW40	215	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	☐
Aluminium suction tube 1500 mm NW50	216	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	☐
Stainless steel suction tube 850 mm NW40	217	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	☐
Stainless steel suction tube 850 mm NW50	218	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter DN70 auf Bajonett 2.0 elektr. leitend	219	9.990-874.0		☐
Adapter accessories DN 50 to DN 51	220	9.989-603.0	Steel adapter for connection of DN 50 to DN 51. Electroconductive.	☐
Adapter accessories DN 51 to DN 50	221	9.989-601.0	Steel adapter for connection of DN 51 to DN 50. Electroconductive.	☐
Adapter accessories DN50 to DN61	222	9.989-602.0	Steel adapter for connection of DN 50 to DN 61. Electroconductive.	☐
Adapter accessories DN 61 to DN 50	223	9.989-604.0	Steel adapter for connection of DN 61 to DN 50. Electroconductive.	☐
Reducers/expanders				
Reducer in AISI 304 stainless steel DN50 to DN40	224	9.989-893.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 60/36 -3

1.573-320.0



225-226



227



224, 228-229



230



231-232



233



234

		Order no.	Description	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Reducers/expanders				
Reducer DN 70 to DN 50	225	9.977-772.0		☐
Reduction DN70 to DN40	226	9.989-690.0	Electroconductive steel reducer for reduction from DN 70 to DN 40.	☐
Reduction DN50 to DN40	227	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	☐
Stainless steel reducer DN 70 to DN 50	228	9.989-712.0		☐
Stainless steel reducer DN 70 to DN 40	229	9.989-713.0		☐
Expander				
Expansion DN50 to DN70	230	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.	☐
Distributor				
AISI 304 stainless steel manifold DN70 to DN50	231	9.989-894.0		☐
AISI 304 stainless steel manifold DN70 to DN40	232	9.989-895.0		☐
Y distributor DN 70 to DN 50	233	9.989-611.0	Electroconductive steel fitting, DN 70/DN 50 / DN 50.	☐
FILTERS				
Bag/star filter				
Star filter PE/PTFE M 2.2 m²	234	6.907-651.0		☐

☐ Available accessories.