

IVC 60/24-2 TACT²

Compact industrial vacuum with large wheels and brake rollers for maximum portability. With automatic TACT² filter cleaning for a long operating time without interruptions.



Order no. 1.576-100.0

- Antistatic equipment
- Liquid cut-off
- Integrated cyclone for pre-separation system

Technical data

EAN code		4039784463691
Power supply	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s / m³/h	148 / 532
Vacuum	mbar / kPa	254 / 25.4
Container capacity	l	60
Container material		Stainless steel
Rated input power	kW	2.4
Vacuuming type		Electric
Connection nominal diameter		DN 70
Accessory nominal diameter		DN 50 / DN 40
Sound pressure level	dB(A)	73
Main filter dust class		M
Filter area for main filter	m²	0.95
Weight incl. packaging	kg	68.2
Dimensions (L × W × H)	mm	970 × 690 × 995

This machine requires instruction.

Equipment

Main filter	Flat pleated filter
Accessories included in the scope of delivery	no
Automatic filling level shut-off	■
Container emptying	Set-down trolley

■ Included in the scope of supply.



Fitted with two blower motors

- For powerful suction power and optimum cleaning performance.
- Electronic control of the drive to avoid high inrush currents.



Automatic Filter Cleaning System Tact²

- Automatic cleaning of the filters by means of targeted and powerful air blasts.
- Despite filter cleaning, the suction power remains constantly high.
- Long life of the filter reduces maintenance costs.



Equipped with compact flat pleated filter

- Clear compact design of the filter.
- Suitable for picking up free-flowing, dry dusts up to dust class M.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M				
Flat pleated filter, paper				
Dry flat pleated filter, green label, suitable for NT 55/2 Tact ² , NT 65/2 Tact ² , NT 75/2 Tact ² Me	1	6.907-276.0	Dry flat pleated filter made from cellulose fibre material with green label for vacuuming fine dust and coarse dirt of dust classes L and M for: NT 55/2 Tact ² , NT 65/2 Tact ² and NT 75/2 Tact ² Me.	☐
Flat pleated filter, PTFE				
Flat pleated filter, PTFE	2	6.907-449.0	Polyester fleece with PTFE coating, dust class M, for Tact ² vacuum cleaners. Particularly suitable for very adhesive materials.	☐
FILTER T/ NT				
Fabric filter				
Candle filter Wood, NT 65/2, NT 75/2	3	2.414-003.0	Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact ² vacuums.	☐
ACCESSORY SETS				
Accessory kit for solids/dust				
Oven cleaning accessory kit Expert DN 50	4	9.989-938.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-979.0), handle (9.989-899.0), suction tube (9.989-929.0), floor nozzle (9.989-935.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Oven cleaning accessory kit Expert DN 40	5	9.989-939.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-976.0), handle (9.989-898.0), suction tube (9.989-928.0), floor nozzle (9.989-934.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit Expert DN 40	6	9.989-940.0	Food accessory kit DN 40: PU hose 3 m (9.989-970.0), handle (9.989-898.0), standard nozzle (9.989-838.0), brush (9.989-879.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit Expert DN 50	7	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Accessory kit for overhead cleaning Expert DN 40	8	9.989-942.0	Accessory kit DN 40 for overhead cleaning: suction tubes (9.989-920.0/9.993-008.0), handles (9.989-916.0/9.989-918.0), standard nozzle (9.989-838.0), brush (9.989-879.0), adapter (9.993-012.0).	☐
Accessory kit for overhead cleaning DN 50 Expert	9	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	☐
Professional dry floor cleaning set DN40	10	9.990-877.0	Professional dry floor cleaning set: adapter (9.990-874.0), hose (2.889-141.0), bend (2.889-172.0), 2 × suction tube (2.889-194.0), 3 × nozzles (6.906-958.0, 6.903-033.0, 6.902-105.0).	☐
Advanced dry floor cleaning set DN40	11	9.990-893.0	Advanced dry floor cleaning set: EVA hose (9.990-923.0), handle (9.990-929.0), 2 × suction tube (9.990-933.0), floor nozzle (9.990-935.0), standard nozzle (9.980-773.0).	☐
Advanced dry floor cleaning set DN50	12	9.990-894.0	Advanced dry floor cleaning set: EVA hose (9.990-924.0), handle (9.990-930.0), 2 × suction tube (9.990-934.0), floor nozzle (9.990-936.0), standard nozzle (9.980-761.0).	☐
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F40	13	9.989-835.0		☐
Standard nozzle silicone FDA green DN-F40	14	9.989-836.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA red DN-F40	15	9.989-837.0		☐
Standard nozzle silicone FDA transparent DN-F40	16	9.989-838.0		☐
Standard nozzle silicone FDA white DN-F40	17	9.989-839.0		☐
Standard nozzle silicone FDA yellow DN-F40	18	9.989-840.0		☐
Standard nozzle silicone FDA blue DN-F50	19	9.989-841.0		☐
Standard nozzle silicone FDA green DN-F50	20	9.989-842.0		☐
Standard nozzle silicone FDA red DN-F50	21	9.989-843.0		☐
Standard nozzle silicone FDA transparent DN-F50	22	9.989-844.0		☐
Standard nozzle silicone FDA white DN-F50	23	9.989-845.0		☐
Standard nozzle silicone FDA yellow DN-F50	24	9.989-846.0		☐
Standard PVC nozzle DN40	25	9.989-674.0	Electroconductive standard PVC nozzle. DN 40.	☐
Standard PVC nozzle DN50	26	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	☐
Standard nozzle silicone DN40	27	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	☐
Standard nozzle silicone DN50	28	9.988-402.0		☐


■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²


1.576-100.0




29-30




31-32




33



34



35-36



37-38



39-40



41-42

		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle cuttable rubber DN40	29	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	☐
Standard nozzle cuttable rubber DN50	30	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐
Standard aluminium nozzle DN40	31	9.980-748.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 40.	☐
Standard aluminium nozzle DN50	32	9.980-749.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 50.	☐
Flexible standard nozzles				
Standard nozzle flexible PVC DN40	33	9.981-420.0	Electroconductive, flexible round nozzle made from galvanised steel, with rubber mouthpiece DN 30.	☐
Standard nozzle flexible PVC DN50	34	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	☐
Standard nozzle, flexible, angled 90° PP DN40	35	9.981-429.0	Flexible, electroconductive angled nozzle, DN 40, length: 800 mm.	☐
Standard nozzle, flexible, angled 90° PP DN50	36	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 304 DN-F40 blue	37	9.989-861.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 blue	38	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 green	39	9.989-863.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	40	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 red	41	9.989-865.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	42	9.989-866.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²
1.576-100.0



		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F40 transparent	43	9.989-867.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 transparent	44	9.989-868.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 white	45	9.989-869.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 white	46	9.989-870.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 yellow	47	9.989-871.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 yellow	48	9.989-872.0		☐
Floor nozzle stainless steel AISI 316L DN-F40	49	9.989-914.0		☐
Floor nozzle stainless steel AISI 316L DN-F50	50	9.989-915.0		☐
Floor nozzle stainless steel 400 mm DN-F40	51	9.989-934.0		☐
Floor nozzle stainless steel 400 mm DN-F50	52	9.989-935.0		☐
Floor nozzle aluminium 400 mm DN-F40	53	9.989-936.0		☐
Floor nozzle aluminium 400 mm DN-F50	54	9.989-937.0		☐
Aluminium floor nozzle 370 mm DN40	55	9.989-683.0	Floor nozzle, 370 mm, made from aluminium. DN 40.	☐
Aluminium floor nozzle, el, 370 mm, DN40	56	9.989-682.0	Floor nozzle, 370 mm, made from aluminium. Electroconductive. DN 40.	☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



57




58-59



60-61




62-63



64



65-66



67-68



70

		Order no.	Description	
NOZZLES				
Floor nozzles				
Aluminium floor nozzle 200 mm DN50	57	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	☐
Aluminium floor nozzle 370 mm DN50	58	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 370 mm, DN50	59	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	☐
Aluminium floor nozzle 500 mm DN50	60	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 500 mm, DN50	61	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	☐
Stainless steel floor nozzle el 370 mm DN40	62	9.989-558.0	Multi-purpose floor nozzle (370 mm), electroconductive, DN 40.	☐
Stainless steel floor nozzle el 370 mm DN50	63	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	☐
Floor nozzle rubber strip oil-resistant. 220 mm	64	9.981-923.0	Squeegee with plastic strip for floor nozzle, 220 mm wide.	☐
Floor nozzle rubber strip 370 mm	65	9.981-914.0	Squeegee with profiled strip for floor nozzle, 370 mm wide.	☐
Floor nozzle rubber strip 500 mm	66	9.981-915.0	Oil-resistant squeegee with profiled strip for floor nozzle, 500 mm wide.	☐
Floor nozzle brush strip el. 370 mm	67	9.984-939.0	Electroconductive squeegee for floor nozzle, 370 mm wide.	☐
Floor nozzle brush strip 500 mm	68	9.980-764.0	Brush strip set for floor nozzle 500 mm, with profiled strip.	☐
Crevice nozzles				
Crevice nozzle PP 15 mm × 145 mm DN50	69	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	☐
Crevice nozzle PU 22 mm × 175 mm DN50	70	9.981-482.0	Crevice nozzle made from PU, DN 50.	☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
NOZZLES				
Crevice nozzles				
Crevice nozzle 18 mm × 120 mm DN50	71	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	☐
Crevice nozzle 25 mm × 120 mm DN50	72	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Flexible crevice nozzles				
Crevice nozzle flexible silicone FDA DN-F50 transparent	73	9.989-847.0		☐
Crevice nozzle flexible silicone FDA DN-F40 transparent	74	9.989-848.0		☐
Flexible crevice nozzle silicone 65 mm DN50	75	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	☐
Flexible crevice nozzle 11 mm × 58 mm DN40	76	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	☐
Flexible crevice nozzle 20 mm × 45 mm DN40	77	9.981-423.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 40.	☐
Flexible crevice nozzle 12 mm × 45 mm DN50	78	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	79	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F40	80	9.989-849.0		☐
Silicone surface nozzle FDA blue DN-F50	81	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F40	82	9.989-851.0		☐
Silicone surface nozzle FDA green DN-F50	83	9.989-852.0		☐
Silicone surface nozzle FDA red DN-F40	84	9.989-853.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle FDA red DN-F50	85	9.989-854.0		☐
Silicone surface nozzle FDA transparent DN-F40	86	9.989-855.0		☐
Silicone surface nozzle FDA transparent DN-F50	87	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F40	88	9.989-857.0		☐
Silicone surface nozzle FDA white DN-F50	89	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F40	90	9.989-859.0		☐
Silicone surface nozzle FDA yellow DN-F50	91	9.989-860.0		☐
Silicone surface nozzle 120 mm DN40	92	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	☐
Silicone surface nozzle 120 mm DN50	93	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
Aluminium surface nozzle, 150 mm, DN 40	94	9.989-666.0	Surface nozzle, 150 mm, made from aluminium. DN 40.	☐
Aluminium surface nozzle 150 mm DN50	95	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	☐
Liquid nozzles				
Liquid nozzle 900 mm DN50	96	9.981-427.0	Bypass nozzle, DN 50, overall length: 1000 mm.	☐
Borehole nozzles				
Blind hole nozzle DN40	97	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	☐
Blind hose nozzle angled 60° DN40	98	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
NOZZLES				
Borehole nozzles				
Blind hole nozzle angled 90° DN40	99	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	☐
Blind hose nozzle angled 90° 200 mm extension DN40	100	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN40	101	9.981-431.0	Flat brush nozzle DN 40.	☐
Standard brush 40 mm DN50	102	9.981-432.0	Flat brush nozzle DN 50.	☐
End brushes				
Brush FDA blue ø 75 mm DN-F40	103	9.989-873.0		☐
Brush FDA blue ø 75 mm DN-F50	104	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F40	105	9.989-875.0		☐
Brush FDA green ø 75 mm DN-F50	106	9.989-876.0		☐
Brush FDA red ø 75 mm DN-F40	107	9.989-877.0		☐
Brush FDA red ø 75 mm DN-F50	108	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F40	109	9.989-879.0		☐
Brush FDA white ø 75 mm DN-F50	110	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F40	111	9.989-881.0		☐
Brush FDA yellow ø 75 mm DN-F50	112	9.989-882.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
BRUSHES				
End brushes				
End brush Ø 82 mm DN40	113	9.989-609.0	Electroconductive end brush with 82 mm diameter. DN 40.	☐
End brush Ø 82 mm DN50	114	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	☐
Surface brushes				
Surface brush PP 24 mm DN40	115	9.989-610.0	Electroconductive surface brush. DN 40.	☐
Surface brush 300 mm DN40	116	9.981-911.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	☐
Surface brush 300 mm DN50	117	9.981-912.0		☐
Cylinder brushes				
Cylinder brush ø 100 mm DN-F40	118	9.989-922.0		☐
Cylinder brush ø 200 mm DN-F40	119	9.989-923.0		☐
Cylinder brush ø 100 mm DN-F50	120	9.989-925.0		☐
Cylinder brush ø 200 mm DN-F50	121	9.989-926.0		☐
HOSES				
ME-Schläuche				
Hose ME DN40 3 m	122	9.989-976.0		☐
Hose ME DN40 5 m	123	9.989-977.0		☐
Hose without connection ME DN40 15 m	124	9.989-978.0		☐
Hose ME DN50 3 m	125	9.989-979.0		☐
Hose ME DN50 5 m	126	9.989-980.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²
1.576-100.0



		Order no.	Description	
HOSES				
PVC				
Hose PVC DN40 1 m	127	9.989-626.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 1 m.	☐
Hose PVC DN40 3 m	128	9.989-962.0		☐
Hose PVC DN40 5 m	129	9.989-963.0		☐
Hose PVC DN50 3 m	130	9.989-964.0		☐
Hose PVC DN50 5 m	131	9.989-965.0		☐
Hose PVC DN40 3 m	132	9.989-647.0	PVC hose, DN 40. Temperature-resistant up to 85 °C and electrically conductive. Length: 3 m.	☐
Hose PVC DN40 5 m	133	9.989-614.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 5 m.	☐
PVC hose DN40 15 m without connectors	134	9.989-633.0	PVC hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
Hose PVC DN50 3 m	135	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN50 5 m	136	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	☐
PVC hose DN50 15 m without connectors	137	9.989-634.0	PVC hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
EVA hoses				
Hose EVA DN40 3 m	138	9.989-982.0		☐
Hose EVA DN40 5 m	139	9.989-983.0		☐
Hose EVA DN50 3 m	140	9.989-984.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
HOSES				
EVA hoses				
Hose EVA DN50 5 m	141	9.989-985.0		☐
Hose EVA NW40 3 m	142	9.988-088.0	Electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW40 5 m	143	9.988-089.0	Five-metre-long, electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 5 m.	☐
EVA hose DN40 15 m without connectors	144	9.989-630.0	EVA hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose EVA NW50 3 m	145	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW50 5 m	146	9.988-091.0		☐
EVA hose DN50 15 m without connectors	147	9.989-631.0	EVA hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose installation sets				
Hose installation kit DN40	148	9.989-627.0	Multipiece hose connection set, DN 40.	☐
Hose installation kit DN50	149	9.989-628.0	Multipiece hose connection kit, DN 50.	☐
Hose connection kit, stainless steel AISI 304 DN40	150	9.989-986.0	Hose connection kit in nominal width DN 40, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
Hose connection kit, stainless steel AISI 304 DN50	151	9.989-987.0	Hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
PU hoses				
Hose PU DN40 3 m	152	9.989-966.0		☐
Hose PU DN40 5 m	153	9.989-967.0		☐
Hose PU DN50 3 m	154	9.989-968.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
HOSES				
PU hoses				
Hose PU DN50 5 m	155	9.989-969.0		☐
Hose PU FDA DN40 3 m	156	9.989-970.0		☐
Hose PU FDA DN40 5 m	157	9.989-971.0		☐
Hose PU FDA DN40 15 m	158	9.989-972.0		☐
Hose PU FDA DN50 3 m	159	9.989-973.0		☐
Hose PU FDA DN50 5 m	160	9.989-974.0		☐
Hose PU FDA DN50 15 m	161	9.989-975.0		☐
Hose PU DN40 3 m	162	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN40 5 m	163	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN40 15 m without connectors	164	9.989-637.0	PU hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
Hose PU DN50 3 m	165	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	166	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN50 15 m without connectors	167	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
ME-PU-hoses				
Hose without connection ME DN50 15 m	168	9.989-981.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
HOSES				
ME-PU-hoses				
Hose ME-PU DN40 3 m	169	9.989-621.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
ME-PU hose, DN 40, 5 m	170	9.989-622.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐
ME-PU hose DN40 15 m without connectors	171	9.989-640.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	☐
Hose ME-PU DN50 3 m	172	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
Hose ME-PU DN50 5 m	173	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐
ME-PU hose DN50 15 m without connectors	174	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	☐
HANDLES				
Elbow aluminium 45° DN40	175	9.989-544.0	45° curved handle made from aluminium, DN 40.	☐
Elbow aluminium 45° DN50	176	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	☐
Handle stainless steel AISI 304 DN40	177	9.989-896.0		☐
Handle stainless steel AISI 304 DN50	178	9.989-897.0		☐
Handle straight stainless steel AISI 304 DN40	179	9.989-898.0		☐
Handle straight stainless steel AISI 304 DN50	180	9.989-899.0		☐
Handle carbon 45° DN-F40	181	9.989-916.0		☐
Handle carbon 45° DN-F50	182	9.989-917.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



183-184



185




186




187-188



189-190



191-192



193-194






195-200

		Order no.	Description	
HANDLES				
Handle carbon 110° DN-F40	183	9.989-918.0		☐
Handle carbon 110° DN-F50	184	9.989-919.0		☐
Handle DN 40	185	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	☐
Handle DN50, curved	186	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	☐
Stainless steel handle NW40	187	9.989-036.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 40.	☐
Stainless steel handle NW50	188	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	☐
SUCTION TUBES				
Carbon suction tube 1500 mm DN40	189	9.989-552.0	Very light carbon extension tube, electroconductive, DN 40. Length: 1500 mm.	☐
Carbon suction tube 1500 mm DN50	190	9.989-553.0	Electroconductive, very light carbon extension tube. Inner cone DN 50, 1500 mm long.	☐
Suction tube stainless steel AISI 304 DN40	191	9.989-912.0		☐
Suction tube stainless steel AISI 304 DN50	192	9.989-913.0		☐
Suction tube carbon 1500 mm DN-F40 conical	193	9.989-920.0		☐
Suction tube carbon 1500 mm DN-F50 conical	194	9.989-921.0		☐
Suction tube aluminium high temperature 1000 mm DN-F40	195	9.989-928.0		☐
Suction tube aluminium high temperature 1000 mm DN-F50	196	9.989-929.0		☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
SUCTION TUBES				
Suction tube aluminium high temperature 2000 mm DN-F40	197	9.989-930.0		☐
Suction tube aluminium high temperature 2000 mm DN-F50	198	9.989-931.0		☐
Suction tube aluminium high temperature 3000 mm DN-F40	199	9.989-932.0		☐
Suction tube aluminium high temperature 3000 mm DN-F50	200	9.989-933.0		☐
Suction tube 850 mm DN 40	201	9.977-525.0	Steel extension tube, electroconductive, DN 40. Length: 850 mm.	☐
Suction tube 850 mm DN 50	202	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	☐
Aluminium suction tube 1500 mm NW40	203	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	☐
Aluminium suction tube 1500 mm NW50	204	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	☐
Stainless steel suction tube 850 mm NW40	205	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	☐
Stainless steel suction tube 850 mm NW50	206	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	☐
OTHER ACCESSORIES				
Universal accessories holder	207	9.989-789.0	Universal accessories holder for simple storage of suction tubes directly on industrial vacuums from the IVC, IVM and IVS product lines from Kärcher.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter DN70 auf Bajonett 2.0 elektr. leitend	208	9.990-874.0		☐
Adapter accessories DN 50 to DN 51	209	9.989-603.0	Steel adapter for connection of DN 50 to DN 51. Electroconductive.	☐
Adapter accessories DN 51 to DN 50	210	9.989-601.0	Steel adapter for connection of DN 51 to DN 50. Electroconductive.	☐

☐ Available accessories.

ACCESSORIES FOR IVC 60/24-2 TACT²

1.576-100.0



		Order no.	Description	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter accessories DN50 to DN61	211	9.989-602.0	Steel adapter for connection of DN 50 to DN 61. Electroconductive.	☐
Adapter accessories DN 61 to DN 50	212	9.989-604.0	Steel adapter for connection of DN 61 to DN 50. Electroconductive.	☐
Reducers/expanders				
Reducer in AISI 304 stainless steel DN50 to DN40	213	9.989-893.0		☐
Reducer DN 70 to DN 50	214	9.977-772.0		☐
Reduction DN70 to DN40	215	9.989-690.0	Electroconductive steel reducer for reduction from DN 70 to DN 40.	☐
Reduction DN50 to DN40	216	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	☐
Stainless steel reducer DN 70 to DN 50	217	9.989-712.0		☐
Stainless steel reducer DN 70 to DN 40	218	9.989-713.0		☐
Expander				
Expansion DN50 to DN70	219	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.	☐
Distributor				
AISI 304 stainless steel manifold DN70 to DN50	220	9.989-894.0		☐
AISI 304 stainless steel manifold DN70 to DN40	221	9.989-895.0		☐
Y distributor DN 70 to DN 50	222	9.989-611.0	Electroconductive steel fitting, DN 70/DN 50 / DN 50.	☐
PRE-SEPARATORS				
Pre-separator				
Pre-separator Tc Op liquids 125 l DN70	223	9.989-686.0	125 litre pre-separator, DN 70.	☐

☐ Available accessories.