

# KÄRCHER

makes a difference



## MOBILE CLEANING ANYWHERE, ANYTIME.

A compact, towable and maneuverable hot water pressure washer.

PROFESSIONAL | TULE SERIES HDS 3.5/40 GE MT

# TULE SERIES HDS 3.5/40 GE MT




Shown with optional hose reel

## Towable and maneuverable hot water pressure washer.

Ready to pick up and go at a moments notice, Kärcher's Tule Series HDS 3.5/40 Ge MT hot water pressure washer trailer provides the necessary cleaning power on virtually any job site which has a water source. Simply unhitch the Tule Series HDS 3.5/40 Ge MT and take the cleaning power where you need it most. The Tule Series trailer features a reliable Honda engine, 8 gallon diesel fuel tank, electric start with manual start backup and much more.

U.S. Design Patent No. 9,724,734 B2



### 1 Smart design

- Reliable Honda GX engine
- 8-gallon diesel fuel tank
- Manual parking brake
- Adjustable bracket and multiple hitch configurations for various vehicle heights
- Adjustable thermostat for regulating water temperature
- 2-inch Ball Coupler for quick and easy hook up of trailer
- EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

### 2 Ease of use

- Electric start with manual start backup
- Controls are located on the curb side of the trailer
- Easy to use - only 2 switches to operate the entire unit
- 12V Battery included for hot water operation

### 3 Mobile

- Highway rated 16" pneumatic tires
- Compact design and easy towing for on-site applications, easy to maneuver and store
- Lift handle and swing away tongue for easier hook up of the trailer and storage

# Technical data and equipment

## TECHNICAL DATA

Model	Part No.	GPM	PSI	Drive	Engine	Start	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) Inches
HDS 3.5/40 Ge MT	1.103-844.0	3.5	4000	Direct	Honda GX390	Electric*	Kärcher KS	790	100 x 45 x 75

## ACCESSORIES

Order No.	Description
■ 8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
■ 8.756-797.0	3-5 GPM Chemical Injector Kit
■ 8.754-990.0	12V Battery (required for hot water operation)
■ 8.711-293.0	Zinc plated variable pressure lance

## OPTIONS (FACTORY INSTALLED)

Order No.	Description
<input type="checkbox"/> 8.924-367.0	2-5/16" Ball Coupler
<input type="checkbox"/> 8.924-667.0	Lifting Kit
<input type="checkbox"/> 8.924-370.0	LED Lights
<input type="checkbox"/> 8.924-700.0	2-inch Collar Lock Coupler

## OPTIONS (FIELD INSTALLED)

Order No.	Description
<input type="checkbox"/> 8.750-682.0	Hose Reel Fixed 100', 5000 PSI, 325° F, equipped for 3/8" hose
<input type="checkbox"/> 8.925-255.0	Hose Reel Bracket (Mount Kit)

Please contact us for  
more information:

**Kärcher North America**

4555 Airport Way  
Denver, CO 80239  
U.S.A.

Tel. 888-805-9852  
Fax 800-248-8409

[www.karcher.com/us](http://www.karcher.com/us)

**Kärcher Canada**

275 Pendant Drive  
Mississauga, ON L5T 2W9  
Canada

Tel. 905-672-8233  
Fax 905-672-3155

[www.karcher.ca](http://www.karcher.ca)