

KÄRCHER

makes a difference



RUGGED AND POWERFUL CLEANING POWER.

Roll cage, gas/diesel-powered, cold water pressure washers.

PROFESSIONAL | HD PB/PEB/D CAGE

HD PB/PEB/D CAGE



Extra rugged and powerful.

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by either a rugged powder coated roll cage built of 1-1/4" steel or a corrosion-resistant stainless steel cage, these units feature powerful Vanguard, Honda or Kohler engines, tri-plunger oil bath Kärcher pumps, flat-free tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys.



Diesel model HD 3.4/30 D Cage with optional hose reel

1 Powerful and durable

- Safety thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Rugged roll cage and chassis made of 1 1/4-inch steel and powder coated with an epoxy finish for all-weather protection for PB and PEB models.
- Corrosion-resistant stainless steel frame for D cage model only.
- Reliable Honda, Vanguard or new Kohler engine - model HD 3.4/30 D Cage (shown above)
- Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons; backed by 7-year warranty.
- Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life.
- 50' durable wire-braid hose rated for 4000 or 6000 PSI; with hose guard for burst protection
- Inlet strainer protects pump from debris in the water source.

2 Smart features

- Five conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

3 Outstanding mobility

- Heavy-duty lifting beam for ease in loading and transporting.
- Flat-free tires on all models for easy maneuvering on any surface, especially surfaces with nails and sharp debris.

Technical data and equipment.

TECHNICAL DATA

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) Inches
HD 3.7/35 PB Cage	1.575-205.0	3.7	3500	Belt	389	Honda GX390	Gas	Kärcher KM	350	42 x 26 x 30
HD 4.0/40 PB Cage	1.575-207.0	4.0	4000	Belt	479	Vanguard 16	Gas	Kärcher KT	470	42 x 26 x 30
HD 4.0/50 PeB Cage*	1.575-200.0	4.0	5000	Belt	688	Honda GX630	Gas	Kärcher KX	495	42 x 26 x 30
HD 4.5/50 PeB Cage*	1.575-201.0	4.5	5000	Belt	688	Honda GX690	Gas	Kärcher KX	500	42 x 26 x 30
HD 3.4/30 D Cage	1.107-373.0	3.4	3000	Belt	442	Kohler KD440	Diesel	LM3540R.3	195	50 x 40 x 50

OPTIONS (FIELD INSTALLED)

Order No.	Description
<input type="checkbox"/> 9.801-028.0	100' EZEE Hose Reel kit, single axle (hose not Included)
<input type="checkbox"/> 9.801-029.0	100' Hose Reel kit, 5000 psi, double axle (hose not Included)
<input type="checkbox"/> 8.750-682.0	100' capacity Hose Reel fixed base (for HD 3.4/30 D Cage model only)
<input type="checkbox"/> 8.929-070.0	Skid feet (for HD 3.4/30 D Cage model only)

Included
 Optional

Please contact us for more information:

Kärcher U.S.A.

6398 N. Kärcher Way
Aurora, CO 80019
U.S.A.

Phone 888-805-9852
Fax 800-248-8409

www.karcher.com/us