HDS 12/18-4 S CLASSIC

The powerful HDS 12/18-4 S hot water high-pressure cleaner offers a high flow rate and optimised burner engineering for economical operation.













Order no.

1.071-923.0

- Dual spray lance operation possible
- 2 Detergent tanks
- Economical eco!efficiency mode

Technical data		
EAN code		4054278140438
Power supply	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	600 - 1200
Working pressure	bar / MPa	30 - 180 / 3 - 18
Temperature (for supply 12 °C)	°C	min. 80 - max. 155
Consumption of heating oil or gas at full load	kg/h	7.7
Consumption of heating oil in ecolefficiency mode	kg/h	6.2
Connected load	kW	8.4
Power cable	m	5
Fuel tank	1	25
Weight (with accessories)	kg	179.9
Weight incl. packaging	kg	191.9
Dimensions (L × W × H)	mm	1330 × 750 × 1060

This machine requires instruction.

Spray gun High-pressure hose length High-pressure hose type Spray lance Power nozzle Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection Included in the scope of supply.	Faultanest		
High-pressure hose length m 10 High-pressure hose type Longlife Spray lance mm 1050 Power nozzle Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	Equipment		
High-pressure hose type Spray lance Power nozzle Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	Spray gun		EASY!Force Advanced
Spray lance mm 1050 Power nozzle Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	High-pressure hose length	m	10
Power nozzle Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	High-pressure hose type		Longlife
Pressure cut-off Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	Spray lance	mm	1050
Option for the 2 spray lance operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	Power nozzle		
operation Soft Damping System (SDS) Service electronics with LED display 2 Detergent tanks Dry-running protection	Pressure cut-off		
Service electronics with LED display 2 Detergent tanks Dry-running protection			•
display 2 Detergent tanks Dry-running protection	Soft Damping System (SDS)		
Dry-running protection			•
	2 Detergent tanks		
■ Included in the scope of supply.	Dry-running protection		
	■ Included in the scope of supply.		

HDS 12/18-4 S Classic, 1.071-923.0, 2025-06-29





High efficiency

- In eco!efficiency mode, the machine operates in the most economical temperature range (60 °C) with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full load operation.



Maximum efficiency

- Proven and highly efficient burner technology.
- 4-pole electric motor with 3-piston axial pump.
- Water-cooled motor for a high performance and long service life.



Storage

- Spacious storage compartment, e.g. for detergents, gloves or tools.
- Within easy reach for left-handed/right-handed operators and ideal for two-spray lance operation.



























14

				\top
		Order no.	Description	
TRIGGER GUNS				
Spray guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	-
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	t [
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo control				
Servo Control, 1100 l/h -	5	4.118-009.0	Water quantity and pressure regulated directly from the hand spray gun.	
SPRAY LANCES		<u> </u>		
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	-
LED nozzle light	7	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

lacksquare Included in the scope of supply. \qed Available accessories.























CDD AV LANCES		Order no.	Description	L
SPRAY LANCES Double lance				_
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable	
Angular envay lance			for agricultural use (e.g. stable cleaning).	L
Angular spray lance Spray lance for toilets and rain gutters	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance	-	l		Ė
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power nozzle 25°, 068	22	2.113-027.0	Fan jet nozzle for large-area coverage and stubborn dirt and stains.	
HP nozzle spray angle 0°				
Power nozzle 0°, 075	23	2.113-037.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				
Power nozzle 15°, 070	24	2.113-049.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 40°	1			
Power nozzle 40°, 075	25	2.113-056.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HIGH-PRESSURE HOSES		<u> </u>		Ė
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	26	6.110-038.0	Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure.	•
High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock	27	6.110-024.0	1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure.	
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock	28	6.110-023.0	Robust high-pressure hose with double steel core, ANTIITwist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	

















		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 \times EASY!Lock	29	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock	30	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	
Standard with unions on both sides				
High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock	31	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock	32	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long.	
High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock	33	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock	34	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock	35	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	
High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock	36	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10).	
High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock	37	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock	38	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock	39	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	
High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock	40	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock	41	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	
Food industry version with unions on both sid	es	•		
High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock	42	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends.	

 $[\]blacksquare$ Included in the scope of supply. $\hfill\Box$ Available accessories.

























		0	Beautistics	
HIGH PRESSURE HOSES	<u> </u>	Order no.	Description	L
HIGH-PRESSURE HOSES	05			
Food industry version with unions on both sid High-pressure hose food grade, 20 m, ID 8,		6.110-052.0		
250 bar, 2 × EASY!Lock	4 6 4 6	anda	covering, ANTI!Twist and EASY!Lock hand screw connections.	L
Longlife food design with screw connections a High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	44	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	
Special hoses			of the contract of the contrac	+
High-pressure hose curved, 1.5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	45	6.110-068.0	For connection to hose reels: high-pressure hose, with M 22×1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure.	⟨ [
WEED CONTROL		<u> </u>		T
WR 50	46	2.114-013.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	47	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	
WR 100	48	2.114-015.0	Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	
WR 10	49	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	
QUICK CONNECT				
Quick coupling	50	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Male coupling	51	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	52	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
OTHER HP ACCESSORIES				
Jet gun	53	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
FLUE PIPE				
Exhaust gas nozzle	54	4.656-079.0	Exhaust gas nozzle (oval connection, diameter 157 mm) for connection to the hot water high-pressure cleaner. With draught diverter for flue tube connection. For flue tube diameter up to 200 mm.	
SEALS FOR TRAPEZOIDAL THREAD				
Gasket set with 9x O-rings for TR thread	55	2.880-001.0		
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt blaster, large, 070/080	56	4.114-030.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	= [

[☐] Available accessories.























				_
		Order no.	Description	
MULTIPLE-JET NOZZLES				
Angled vario nozzle 0-90°				
Angled Vario nozzle, 055	57	4.113-008.0	Variable angle nozzle for spray angle adjustment from 0° to 90° . For easy adjustment to all kinds o soiling and surfaces.	f 🗆
STEAM JET NOZZLE / NOZZLE PROTECTOR / RO	LLOV	ER NOZZLE		
Steam jet nozzles				
Steam jet nozzle 50°	58	4.116-001.0	50° flat jet for cleaning and thawing operations in steam mode, e.g. thawing sand and gravel, de-icing formwork, dewaxing vehicles.	
Steam jet nozzle 40°, 085	59	2.114-009.0	Brass steam nozzle for operation of the HDS in steam stage.	
Rollover nozzle holder	,			
Owner of jets double brass	60	4.764-012.0	Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).	: 🗆
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	61	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	62	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	63	6.110-008.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	64	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle		'		
Pipe cleaning dirt blaster D21/090	65	4.765-003.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Pipe cleaning dirt blaster D30/090	66	4.765-010.0	jets ensure the necessary forward movement, as well as convenient handling.	
Pipe cleaning nozzle 100	67	5.763-088.0	Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	68	5.763-019.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	69	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	70	5.763-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	

[☐] Available accessories.





























Orient trap attachment kit 72 2.642-532.0 Galivanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [Fix 80 Me surface Cleaner FR 30 Me 73 2.111-013.0 Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. 74 2.111-023.0 Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. 75 2.639-188.0 Nozzle kit for FR. 1100 I/h = 1300 I/h 76 2.642-982.0 Machine-specific nozzle kits for FRV 77 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner 78 3.0 Me Surface Cleaner 79 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface cleaning up to 85°C. 80 Extension hose FRV 30 Me and FRV 50 Me 81 4.441-040.0 5 m extension hose for FRV 30 Me. Includes connecting adapter. 80 Surface Cleaner 80 Surface Cleaner 80 Surface Cleaner 81 Surface Cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. 80 Surface Cleaner 80 Surface Cleaner 81 Surface Cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. 80 Surface Cleaner FR 50 Me 81 Surface Cleaning with automatic suction of the dirty water for very large surfaces—this means the [FRV 50 Me. Hot water cleaning with automatic suction of the dirty water for very large surfaces—this means the [FRV 50 Me. Hot water cleaning with automatic suction of the dirty water for very large surfaces—this means the [FRV 50 Me. Hot water cleaning with automatic suction of the dirty water for very large surfaces—this means the [FRV 50 Me. Hot water cleaning supplied water for very large surfaces—this means the [FRV 50 Me. Hot water cleaning supplied water for very large surfaces—this means the [FRV 50 Me. Hot wa					Т
Aard Surface Cleaner FRV 30 To 2 2642-532.0 Suction cup for fixing the suction hose to smooth surfaces. TR 30 Me surface Cleaner FR 30 Me To 2 2642-532.0 Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. TR 30 Me surface Cleaner FR 30 Me To 2 2111-013.0 Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection, ideal for indoor cleaning, e.g. food industry. The surface Cleaner FR 50 Me To 2 2111-023.0 Hot water resistant stainless steel surface cleaner with 500 mm working width, ideal for large areas With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. Watchine-specific nozzle kits for FR Watchine-specific nozzle kits for FRV Wozzle kit for FR, 1100 l/h - 1300 l/h To 2 639-188.0 Nozzle kit includes power nozzles and unions. For Karcher surface cleaners (1100 to 1300 l/h). To 3 Assistant for FRV 30 Me surface Cleaner FRV 50 Me surface Cleaner FRV					
Hose fastening attachment kit 71			Order no.	Description	L
First part of the surface deamer 72 2.642-528.0 Suction cup for fixing the suction hose to smooth surfaces. [73 2.642-53.0 Calvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [78 2.642-53.0 Calvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [78 2.642-53.0 Calvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [78 2.642-53.0 Calvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [78 2.111-013.0 Calvanised steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. [78 2.111-013.0 Calvanised steel surface cleaner with 500 mm working width ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. [78 2.639-188.0 Nozzle kit for FR 100 l/h - 1300 l/h 1300 l/h 1300 l/h 1400 learned steel surface cleaner [78 2.639-188.0 Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h) [78 2.639-188.0 Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h) [78 2.441-040.0 Surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. To FR 100 l/h 1300 l/h					
Contract trap attachment kit 72 2.642-532.0 Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. [In R 30 Me surface Cleaner FR 30 Me 73 2.111-013.0] Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection, ideal for indoor cleaning, e.g. food industry. **Aard Surface Cleaner FR 50 Me 74 2.111-023.0] Hot water resistant stainless steel surface cleaner with 500 mm working width, ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. **Wachine-specific nozzie kits for FR** **Wozzie kit for FR**, 1100 l/h - 1300 l/h 75 2.639-188.0] Nozzie kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h). [In Machine-specific nozzie kits for FR**) **Wozzie kit for FR**, 1000 l/h - 2642-982.0] Machine-specific nozzie kit with Kärcher power nozzles and jet nozzie for FR** 30. [In R 2.111-012.0] Thanks to automatic suction of the dirty water, the stainless steel FR** 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. **Extension hose FR** 30 Me and FR** 50 Me **R** 50 Me surface cleaner		1			
Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. Machine-specific nozzle kits for FR Nozzle kit for FR, 1100 l/h - 1300 l/h - 75 2.639-188.0 Nozzle kit includes power nozzles and unions. For Karcher surface cleaners (1100 to 1300 l/h). [Includes that for FR, 1800 l/h - 1300 l/	Hose fastening attachment kit	71	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Hard Surface Cleaner FR 30 Me	Dirt trap attachment kit	72	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. Hard Surface Cleaner FR 50 Burface Cleaner FR 50 Me 74	FR 30 Me surface cleaner				
Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. Wachine-specific nozzle kits for FR Nozzle kit for FR, 1:100 //h = 1300 //h = 75 2639-188.0 Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1:100 to 1:300 //h). [If Nozzle kits for FRV Nozzle kit for FRV, 080 76 2.642-982.0 Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. [If Nozzle kits for FRV 30 Me surface cleaner FRV 30 Me surface Cleaner 77 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface PRV 30 Me surface cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 //h 85°C. Dur foam lance Advanced 3, 900 //h - 2500 //h 8112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3, 900 //h - 2500 //h 8112-055.0 High-pressure cleaners from Kärcher. DuO Advanced 3. 900 //h - 2500 //h 82 4.112-055.0 High-pressure cleaners from Kärcher. DuO Advanced 3. 900 //h - 2500 //h 82 4.112-055.0 High-quality, simple and durable. Basic 3. cup foam lance for high-pressure cleaners with a flow rate of 900-2500 //h 1.112-055.0 High-quality simple and durable. Basic 3. cup foam lance for high-pressure cleaners with a flow rate of 900-2500 //h 1.112-055.0 High-quality cleaning agent container for cup foam lance (2.112-055.0). High-quality agent container for durk replacement of the cleaning agent container for basic foam lance (2.112-055.0). Additional 1-litre cleaning agent container for fl	Hard Surface Cleaner FR 30 Me	73	2.111-013.0		
wachine-specific nozzle kits for FR Nozzle kit for FR, 1100 l/h - 1300 l/h Nozzle kit for FR, 1100 l/h - 1300 l/h Nozzle kit for FR, 1100 l/h - 1300 l/h Nozzle kit for FRV Nozzle kit for FRV, 080 76 2.639-188.0 Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h). Nozzle kit for FRV, 080 76 2.642-982.0 Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. FRV 30 Me surface cleaner RRV	Hard Surface Cleaner FR 50				
Nozzle kit for FR, 1100 l/h - 1300 l/h Wachine-specific nozzle kits for FRV Nozzle kit for FR, 100 l/h - 1300 l/h Wachine-specific nozzle kits for FRV Nozzle kit for FRV, 080 76 2.642-982.0 Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. FRV 30 Me surface cleaner FRV 30 Me Surface Cleaner 77 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. Extension hose FRV 30 Me and FRV 50 Me RRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me surface cleaner RRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Addinal quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS FOAM SYSTEMS FOUR foam lance DUO Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. FOAM SYSTEMS	Surface Cleaner FR 50 Me	74	2.111-023.0	areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing	g
Machine-specific nozzle kits for FRV Nozzle kit for FRV, 080 76 2.642-982.0 Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. FRV 30 Me surface Cleaner 77 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. Extension hose FRV 30 Me and FRV 50 Me 78 4.441-040.0 5 m extension hose for FRV 30 Me. Includes connecting adapter. FRV 50 Me surface Cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS TOP foam lance Cup foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Cup foam lance Basic 3, 900 l/h - 2500 l/h 81 4.112-065.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow switching to high-pressure cleaners with a flow quality. 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow quality. 83 5.071-414.0 For the quick change of the cleaning agent container for durable: Basic 3 cup foam lance for high-pressure cleaners with a flow quality. 84 6.414-050.0 Additional 1-litre cleaning agent container for quick replacement of the cleaning agent container for durable: Basic 3 cup foam container for quick replacement of the cleaning agent container for durable: Basic 3 cup foam lance for high-pressure cleaners with a flow quality. 85 6.414-050.0 Additional 1-lit	Machine-specific nozzle kits for FR				
Nozzle kit for FRV, 080 76 2.642-982.0 Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. RRV 30 Me Surface Cleaner 77 2.111-012.0 Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. Extension hose FRV 30 Me and FRV 50 Me 78 4.441-040.0 5 m extension hose for FRV 30 Me. Includes connecting adapter. Surface Cleaner FR 50 Me RRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS TOP foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Tup foam lance DUO Advanced 3, 900 l/h - 2500 l/h 80 4.112-065.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litte tank. Tup foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-055.0 High-quality, simple and durable. Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). II-litre cleaning agent container for cup foam 84 6.414-050.0 Additional 1-litre cleaning agent container for felicenent of the cleaning agent (for foam lance).	Nozzle kit for FR, 1100 l/h - 1300 l/h	75	2.639-188.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h).	
FRV 30 Me Surface Cleaner FRV 30 Me Surface Cleaner 77	Machine-specific nozzle kits for FRV		-		
Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. Extension hose FRV 30 Me and FRV 50 Me 78 4.441-040.0 5 m extension hose for FRV 30 Me. Includes connecting adapter. 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceraning. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS Exp foam lance Advanced 3, 900 l/h – 2500	Nozzle kit for FRV, 080	76	2.642-982.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. Extension hose FRV 30 Me and FRV 50 Me 84.441-040.0 5 m extension hose for FRV 30 Me. Includes connecting adapter. Curface Cleaner FR 50 Me FRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS Eup foam lance Advanced 3, 900 l/h - 2500	FRV 30 Me surface cleaner				Ť
Surface Cleaner FR 50 Me FRV 50 Me surface cleaner 79 2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS Cup foam lance Cup foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Cup foam lance DUO Advanced 3, 900 l/h - 2500 l/h Cup foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-069.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Cup foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam 84 5.071-414.0 For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for the cleaning agent (for foam Element of the cleaning agent (for foam	FRV 30 Me Surface Cleaner	77	2.111-012.0	makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to	
2.111-024.0 Surface cleaning with automatic suction of the dirty water for very large surfaces – this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS Tup foam lance Tup foam lance Advanced 3, 900 l/h – 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Tup foam lance DUO Advanced 3, 900 l/h – 2500 l/h Tup foam lance Basic 3, 900 l/h – 2500 l/h 82 4.112-069.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Tup foam lance Basic 3, 900 l/h – 2500 l/h 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam 83 5.071-414.0 For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for cup foam 84 6.414-050.0 Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam 1.1).	Extension hose FRV 30 Me and FRV 50 Me	78	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. FOAM SYSTEMS Exp foam lance Exp foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Exp foam lance DUO Advanced 3, 900 81 4.112-069.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Exp foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam 83 5.071-414.0 For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam Element Element	Surface Cleaner FR 50 Me				
Cup foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Cup foam lance DUO Advanced 3, 900 81 4.112-069.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Cup foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam ance basic 84 6.414-050.0 Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam Litre cleaning agent).	FRV 50 Me surface cleaner	79	2.111-024.0	FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar /	
Eup foam lance Advanced 3, 900 l/h - 2500 80 4.112-065.0 Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Eup foam lance DUO Advanced 3, 900 81 4.112-069.0 DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Eup foam lance Basic 3, 900 l/h - 2500 l/h 82 4.112-055.0 High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam 83 5.071-414.0 For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance)	FOAM SYSTEMS				
3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. Dup foam lance DUO Advanced 3, 900 Author 2500 I/h Duo Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. Dup foam lance Basic 3, 900 I/h - 2500 I/h Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 I/h. Halves the cleaning agent consumption while maintaining optimum foam quality. Inlitre cleaning agent container for cup foam ance basic Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 I/h. Halves the cleaning agent consumption while maintaining optimum foam quality. For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). Inlitre cleaning agent container for cup foam agent container for quick replacement of the cleaning agent (for foam lance (2.112-053.0).	Cup foam lance				
/h - 2500 l/h Lup foam lance Basic 3, 900 l/h - 2500 l/h Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for cup foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	Cup foam lance Advanced 3, 900 l/h - 2500 l/h	80	4.112-065.0		
rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. 1-litre cleaning agent container for cup foam ance basic 83 5.071-414.0 For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for cup foam 84 6.414-050.0 Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam agent container for quick replacement)	Cup foam lance DUO Advanced 3, 900 l/h - 2500 l/h	81	4.112-069.0		
ance basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). 1-litre cleaning agent container for cup foam 84 6.414-050.0 Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam Description of t	Cup foam lance Basic 3, 900 l/h – 2500 l/h	82	4.112-055.0	rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam	
	1-litre cleaning agent container for cup foam lance basic	83	5.071-414.0		
	1-litre cleaning agent container for cup foam lance advanced	84	6.414-050.0		



























				Т
		Order no.	Description	
FOAM SYSTEMS		order no.	DESCRIPTION .	+
Inno Foam Kit				
Inno Foam Set with detergent injector	85	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For	[
Inno Foam Set	86	2.112-008.0	use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	l
Easy Foam Set				_
Easy Foam Set with RM injector	87	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for	[
Easy Foam Set	88	2.112-011.0	connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	İ
Nozzle kits for Inno/Easy Foam Set				Ť
Nozzle kit 110 for Inno / Easy Set 1,000-1,300 l/h	89	2.111-020.0	Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.	I
Foam nozzle mounting kit				+
Foam nozzle attachment kit	90	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS			7	_
Cleaning agent injector				
Cleaning agent injector for high and low pressure (without nozzles)	91	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	I
Cleaning agent injector for high pressure (without nozzle)	92	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	ı
Stainless steel injector kit for HDS 12/18-4S	93	6.645-763.0	The stainless steel injector is supplied as a kit with a suction hose and vacuum filter for the HDS 12/18-4 S High-pressure cleaner – fits on the high-pressure outlet of the machine.	
Machine-specific nozzle kit with order no. 4.6	37-03	3.0		Ť
Nozzle kit 1000-1200 l/h	94	4.769-013.0	For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HP power nozzle + union	[
Nozzle insert with order no. 4.637-032.0	•			
Nozzle insert from 1,100 l/h - HD	95	4.769-002.0	For high pressure with machines above 1.100 l/h	
Nozzle insert from 1,100 l/h - ND	96	4.769-006.0	For low pressure with machines above 1.100 l/h	[
COUPLING PARTS				
Rotary coupling				
Rotary coupling	97	4.111-021.0	Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector				
Screw socket for surface cleaners and Servo Control controllers	98	4.111-022.0	For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) – $1 \times$ M $22 \times 1.5/1 \times$ M 18×1.5 .	[
□ Available accessories				

[☐] Available accessories.































				Т
		Order no.	Description	
COUPLING PARTS				
Connector				
Y distributor	99	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	100	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	
EASY!Lock adapter				
Adapter 1 M22AG-TR22AG	101	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	102	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	103	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 4 TR22IG-D11	104	4.111-032.0	Adapter 4 to connect the new gun with the old swivel hose	
Adapter 5 TR22IG-M22AG	105	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	106	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	107	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	108	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Adapter hose extension 9 TR	109	4.111-037.0	Adapter 9 to connect the new hose with the new hose	
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 × 1.8 AG	110	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels for wall mo	untin	g		
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	111	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	
Automatic hose reel, powder-coated steel / plastic, 20 m	112	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	

[☐] Available accessories.



























				Т
HOSE PERIS		Order no.	Description	
HOSE REELS	untin	~		
Automatic, self-winding hose reels for wall mo			Let 11 10 20 11 11 11 11 11 11 11 11 11 11 11 11 11	1-
Automatic stainless steel / synthetic material hose drum, 20 m	113	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	114	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	. [
Hose reel, automatic, basalt grey-coated, 20 m	115	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	116	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	117	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Zinc-coated swivel holder	118	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	119	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Automatic, self-winding hose reel attachment	kit	<u>'</u>		
Attachment kit automatic hose reel HDS M/S	120	2.110-011.0	Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	
Attachment kit automatic hose reel holder HDS M/S	121	2.110-020.0	Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Brush hard	122	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	123	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	124	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
iSolar 800 Advanced (1100-1300 l/h)	125	6.368-095.0	For water flow rates of 1,100-1,300 l/h: The 800-mm iSolar water-driven brush head with two contra-rotating disc brushes and flexible angle joint ensures that photovoltaic systems are given at even clean.	n
iSolar 400 Advanced	126	6.368-093.0	The iSolar 400 water-driven disc brush (working width 400 mm) is designed for water flow rates o 1,100-1,300 l/h. For small to medium-sized photovoltaic systems (including elevated systems).	of [

 $[\]hfill \square$ Available accessories.





















		Order no.	Description	
FACADE AND SOLAR PANEL CLEANII	NG			
Telescopic lances				
TL low pressure adapter	127	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	128	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	129	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. [
Telescopic lance TL 10 H	130	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	131	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	132	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	133	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
Water softening				
WS 50	134	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS 100	135	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water.	
WS Regenerator	136	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	5 🗆
Hoses	<u>'</u>			
iSolar HP hose 7	137	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 10	138	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 14	139	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters				
iSolar fall protection	140	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	

[☐] Available accessories.



























	1	1		_
	<u> </u>	Order no.	Description	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle) Wet blasting attachment with flow control	141	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for	
(without nozzles) Wet blasting attachment without flow control (sozzles act included)	142	4.115-006.0	adding blasting abrasive to the high-pressure jet. Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling.	
(nozzles not included) Nozzle kits for wet jet unit			Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation	_
Nozzle kit for wet jet unit 070	143	2.112-027.0	Consisting of wet jet nozzle and nozzle insert – only for use in combination with wet jet unit 4.115-000.0 4.115-006.0.	[
Boron carbide nozzle				+
Boron carbide, for machines from 1,000 l/h	144	6.415-083.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING				Ť
Barrel and tank cleaning				
Barrel cleaner BC 14/12	145	2.112-020.0	The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres.	
Spray head HKF 30/14-E	146	6.751-061.0	Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor.	
Nozzle kit for spray head HKF 50 (3.631-009.0	/ 3.63	31-039.0)		
High-pressure full jet nozzle 090 for interior cleaning heads	147	6.415-447.0	High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread.	
Double grip for precise control of spray head	148	2.863-036.0	Double handle. Precise control of the spray head	
1/8" screw plug for interior cleaning heads	149	5.411-061.0	Screw plug for high-pressure interior cleaning heads with 1/8-inch thread.	
ADD ON KITS				亡
Attachment kit for transport				
Transport eyelet attachment kit	150	2.644-053.0	Robust transport eyelet attachment kit for the secure fixing of HDS Medium and Super Class pressure washers during transport.	
Flame monitoring attachment kit				
Flame monitoring attachment kit for HDS Middle and Super Class	151	2.641-796.0	More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	
Accumulator kits				
Pressure tank attachment kit for HDS Middle and Super Class	152	2.641-803.0	The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system.	
Remote control set		•		
Remote control attachment kit for HDS Middle and Super Class	153	2.642-157.0	Remote control for the machines of the HDS Middle and Super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting to a wall.	
Coin-op remote control				
Coin remote control attachment kit for HDS Middle and Super Class	154	2.642-158.0	Retrofittable coin acceptor for machines in the HDS Middle and Super class for self-service operation. For installation on the machine.	























		Order no.	Description	\perp
WATER CONNECTION				
Geka coupling				
Geka connector with hose barb, R 3/4"	155	6.388-455.0	with hose liner	[
Geka connector with hose barb, R 1"	156	6.388-465.0	with hose barb	
Geka connector with internal thread, R 1"	157	6.388-458.0	with female thread	[
Suction filter				
Water suction filter	158	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μm mesh, R 3/4" and R 1" connection, without non-return valve	n [
Suction filter with check valve	159	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	[
Water fine filter				
Universal water fine filter, 25 µm	160	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	
Water fine filter, with adapter	161	4.730-102.0	Fine-mesh water filter, $125 \mu m$, max. temperature 50° C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$. Connection $3/4^{\circ}$, with adapter 1° .	r,
Water fine filter, 100 μm, R 1"	162	2.638-270.0	Fine-mesh water filter, $100 \mu m$, max. temperature 60° C. Connects to high-pressure cleaner. Protect the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$. Connector $1''$.	:s [
Water supply hose				
Water supply hose	163	4.440-207.0	NW 19 R1" / R 3/4", up to 85 $^{\circ}$ C, for pick-up	
	164	4.440-270.0	NW 19 R1" / R1", up to 85 °C	Ε
WASHING BRUSHES				Ė
Push-on washing brush				
Push-on wash brush	165	4.113-001.0	For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection	
Rotating washing brush				Ť
Rotating wash brush for > 1000 l/h machines, nylon bristles	166	4.113-002.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18×1.5 (replaceable brush insert).	[
Rotating wash brush for > 800 l/h machines, natural bristles	167	4.113-005.0		[
☐ Available accessories.				