

# NT 65/2 AP

The NT 65/2 Ap is a powerful, 2-motor wet and dry vac for professional applications. The suction power remains nearly constant due to the efficient cleaning of the flat pleated filter by blasts of air.



#### Order no.

#### 1.667-291.0

- Semi-automatic filter cleaningFlat pleated filter (dust class M)
- Drain hose and push handle

#### Technical data

EAN code		4039784727281
Power supply	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 × 74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	I	65
Container material		Plastic
Rated input power	W	max. 2760
Standard nominal width		ID 40
Cable length	m	10
Sound pressure level	dB(A)	73
Colour		anthracite
Weight without accessories	kg	20
Dimensions (L × W × H)	mm	600 × 480 × 920

_		
Equipment		
Suction hose length	m	4
Bend		Plastic
Quantity of suction tubes	Piece(s)	2
Suction tubes length	mm	550
Suction tubes material		Stainless steel
Quantity of filter bags	Piece(s)	1
Filter bag material		Paper
Wet/dry floor nozzle width	mm	360
Crevice nozzle		
Drain hose (oil-resistant)		
Automatic cut-out features at ma filling quality	х.	•
Flat pleated filter		Cellulose fibre material
Filter cleaning		Semi-automatic filter cleaning
Sturdy bumper		•
Push handle		
Protection class		П
Stop swivel castor		

Included in the scope of supply.







#### **On-board storage**

- Large, practical storage area on the casing head.
- Tools and accessories are always to hand.



#### Semi-automatic filter cleaning

- Optimum filter cleaning efficiency at the push of a button.
- Enables consistently high filter performance and suction power.
- Time-saving design and longer filter service life.

#### Integrated drain hose (oil-resistant)

- The drain hose is easily and quickly accessible.
- Liquids can be disposed of easily and cleanly.

# ACCESSORIES FOR NT 65/2 AP

13

14-16



10-12



				$\square$
		Order no.	Description	
FLAT PLEATED FILTER, STANDARD, BIA C OR UF	о то р			
Flat pleated filter, paper				
Dry flat pleated filter, green label, suitable for NT 65/2 Ap	1	6.904-283.0	Dry flat pleated filter made from cellulose fibre material with a green label. Suitable for NT 65/2 Ap variants for vacuuming fine dust and coarse dirt of dust classes L and M.	
Flat pleated filter, PTFE				
Flat pleated filter, PTFE	2	6.907-449.0	Polyester fleece with PTFE coating, dust class M, for Tact <sup>2</sup> vacuum cleaners. Particularly suitable for very adhesive materials.	
Wet & Dry flat pleated filter, PES fibre material with PTFE coating, suitable for NT 65/2 Eco, NT 75/2 Ap Me Tc	3	6.904-284.0	Wet & Dry flat pleated filter made from PES fibre material with PTFE coating with a blue label. Suitable for vacuuming liquids, fine dust and coarse dirt from the M and L dust classes.	
BENDS				
Bend, plastic				
Bend, NT, DN 40, plastic, clip 2.0 at hose end, cone at accessory end	4	2.889-171.0	DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end.	
Bend with air-flow regulator, T, DN 35, plastic, antistatic, clip 2.0 at hose end, cone at accessory end	5	2.889-148.0	Antistatic, ergonomic bends with air-flow regulator in size DN 35 for dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end.	
Bend, NT, DN 35, plastic, clip 1.0 at hose end, cone at accessory end	6	5.031-718.0	DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	
Bend, NT, DN 35, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end	7	5.031-939.0	Electrically conductive DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	
Bend, NT, DN 40, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end	8	5.032-427.0	Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	
Bend, other				
Bend, NT, DN 35, chrome-plated metal, cone at hose end, cone at accessory end	9	6.900-519.0	DN 35 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	
Bend, NT, DN 35, stainless steel, cone at hose end, cone at accessory end	10	6.903-141.0	Robust DN 35 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	
Bend, NT, DN 40, chrome-plated metal, cone at hose end, cone at accessory end	11	6.900-276.0	DN 40 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The robust bend has a cone connection at both the hose end and the accessory end.	
Bend, NT, DN 40, stainless steel, cone at hose end, cone at accessory end	12	6.902-079.0	Robust DN 40 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	
SUCTION NOZZLES				
Floor nozzles				
Wet/dry floor nozzle, Adv, DN 40, width 360 mm	13	2.889-153.0	Plastic Adv floor nozzle with width of 360 mm and nominal size of DN 40 for wet and dry vacuum cleaners from Kärcher. Features brush strips and squeegees that are easy to change.	
Wet/dry floor nozzle, aluminium, DN 40, width 370 mm	14	6.903-018.0	Aluminium floor nozzle with rollers, width of 370 mm and nominal size of DN 40 for wet and dry vacuum cleaners from Kärcher. Includes easy-to-replace brush strips and squeegees.	

■ Included in the scope of supply. □ Available accessories.

# ACCESSORIES FOR NT 65/2 AP 1.667-291.0



		Order no.	Description	
SUCTION NOZZLES				
Floor nozzles				
Wet/dry floor nozzle, aluminium, DN 40, width 450 mm	15	6.906-383.0	Aluminium floor nozzle with rollers, width of 450 mm and nominal size of DN 40 for wet and dry vacuum cleaning. The brush strips and squeegees that are included are easy to change.	
Wet/dry floor nozzle, aluminium, DN 35, width 370 mm	16	6.906-384.0	For wet and dry vacuum cleaners from Kärcher: aluminium floor nozzle (DN 35) with a width of 370 mm, including brush strips and squeegees that are easy to change.	
Wet/dry floor nozzle, Adv, DN 40, width 400 mm	17	2.889-117.0	For wet and dry vacuum cleaners from Kärcher: plastic Adv floor nozzle with width of 400 mm and nominal size of DN 40. Includes easy-to-replace brush strips and squeegees.	
Crevice nozzles				
Crevice nozzle, NT, DN 40, plastic, 300 mm	18	5.130-655.0	Plastic crevice nozzle in nominal width DN 40 for Kärcher wet and dry vacuum cleaners. Especially suitable for vacuuming out areas that are difficult to reach, such as joints, crevices and corners.	
Crevice nozzle, DN 35, plastic, length 210 mm	19	2.889-130.0	With the DN 35 plastic crevice nozzle, corners and crevices can be vacuumed quickly and thoroughly. Length: 210 mm.	
Crevice nozzle, NT, DN 35, metal, 500 mm long	20	6.900-922.0	The metal crevice nozzle (DN 35) enables vacuuming in crevices and corners. Length: 500 mm.	
Crevice nozzle, NT, DN 40, metal, 400 mm	21	6.905-817.0	Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	
All-purpose brushes				
All-purpose brush	22	6.903-863.0	Natural bristles (ox hair), bristle element 120 × 45 mm.	
Car cleaning nozzles				
Car nozzle, ID 40, 90 mm	23	6.900-952.0	For retrofitting older Kärcher wet and dry vacuum cleaner models with bends in DN 40: Flat angled, convenient, plastic car cleaning nozzle with a working width of approx. 90 mm.	
	24	2.840-095.0	Flat angled, convenient, plastic, DN 40 car cleaning nozzle specially designed for new Kärcher wet and dry vacuum cleaners with a clip system at the suction hose. Working width: Approx. 90 mm.	
Rubber suction tools, nose 45°				
Rubber suction tool, nose 45°	25	6.902-104.0	45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	
NT rubber suction nozzle, bevelled at 45°, DN 40	26	6.902-105.0	45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	
Pipe dusting nozzles				
Pipe brush 35/100	27	6.903-035.0	Plastic, pipe diameter 100 mm	
Pipe brush 35/200	28	6.903-036.0	Plastic, pipe diameter 200 mm	

Included in the scope of supply.  $\Box$  Available accessories.

# ACCESSORIES FOR NT 65/2 AP 1.667-291.0



		Order no.	Description	
SUCTION TUBES				
Suction tubes, stainless steel				
Suction tube, 2 x, NT, DN 40, 550 mm long, stainless steel, suitable for: NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 75/2	29	2.889-194.0	The suction tube set consists of 2 suction tubes made of high-quality stainless steel (DN 40 and 550 mm long each). For Kärcher wet and dry vacuum cleaners.	
Suction tube, DN 35, 505 mm, stainless steel	30	6.902-154.0	Suction tube made of high-quality stainless steel in DN 35 and 505 mm long for wet and dry vacuum cleaners from Kårcher.	
Suction tube, NT, DN 40, 550 mm long, stainless steel, suitable for: AP 100/50, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV	31	6.902-081.0	Suction tube made of high-quality stainless steel in nominal width DN 40 and 550 mm long for wet and dry vacuum cleaners from Kärcher.	t 🗆
Suction tube, NT, DN 40, 1000 mm long, stainless steel, suitable for: NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV	32	6.906-531.0	The suction tube made of high-quality stainless steel (DN 40 and 1000 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.	t 🗆
Suction tubes, metal				
Suction tube, NT, DN 35, 505 mm long, chrome-plated steel, suitable for: NT 25/1, NT 27/1, NT 30/1, NT 35/1, NT 40/1, NT 48/1, NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/1, NT 75/2, NT 611, NT 802 IV	33	6.900-514.0	The suction tube made of chrome-plated steel (DN 35, 505 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.	
SUCTION HOSES				
Suction hoses with clip system 2.0 (compatible	with	vacuum cleane	rs from model year 2017 on)	
Suction hose, NT, DN 40, length 4 m, clip 2.0, bayonet 2.0	34	2.889-138.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
Suction hose, NT, DN 35, length 4 m, electrically conductive, clip 2.0, bayonet 2.0	35	2.889-137.0	The electrically conductive suction hose in nominal width DN 35 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	r 🗆
Suction hose, NT, DN 40, length 2.5 m, clip 2.0, bayonet 2.0	36	2.889-139.0	The suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	
Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 2.0, bayonet 2.0	37	2.889-140.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	
Suction hose, NT, DN 40, length 4 m, electrically conductive, clip 2.0, bayonet 2.0	38	2.889-141.0	The electrically conductive suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	r 🗆
Suction hose, NT, DN 40, length 2.5 m, electrically conductive, clip 2.0, bayonet 2.0	39	2.889-142.0	The electrically conductive suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.	
Extension hose, NT, DN 40, length 2.5 m, clip 2.0, connecting adapter	40	2.889-146.0	The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	
Repair kit for suction hoses DN 40, Clip 2.0	41	2.889-150.0	Repair kit ID 40 for the new clip system.	
Hose connection				-
Adapter, ID 32/35, with internal thread	42	6.902-077.0	Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	

 $\blacksquare$  Included in the scope of supply.  $\Box$  Available accessories.

## ACCESSORIES FOR NT 65/2 AP 1.667-291.0

43 44	4	5	
50 50 50 51-52	5	3, 55-56	54
		Order no.	Description
SUCTION HOSES Hose connection			
Connecting adapter, ID 40, with internal thread	43	6.900-286.0	Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.
Suction hoses with clip system 1.0 (compatib	le with	vacuum cleane	rs up to model year 2016)
Repair kit for suction hoses DN 40 Clip 1.0	44	2.639-873.0	Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT

e with	vacuum cleane	rs up to model year 2016)	
44	2.639-873.0	Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	
45	6.906-344.0	The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.	
46	4.440-678.0	The suction hose with bend in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
47	6.906-279.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	′
48	6.906-321.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
49	6.906-714.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
50	4.440-728.0	The electrically conductive suction hose with bend and PFC module in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
51	6.906-635.0	The suction hose in nominal width DN 40 and with 16 m length is suitable for use with wet and dry vacuum cleaners.	'
52	6.906-877.0	The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	
53	4.440-263.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
54	4.440-303.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
55	4.440-463.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	′ 🗆
56	4.440-466.0	The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	
	44 45 46 47 48 49 50 51 51 52 53 53 54 55	44         2.639-873.0           45         6.906-344.0           46         4.440-678.0           47         6.906-279.0           48         6.906-321.0           49         6.906-714.0           50         4.440-728.0           51         6.906-635.0           52         6.906-877.0           53         4.440-263.0           54         4.440-303.0           55         4.440-463.0	<ul> <li>vacuum cleaners with clip system.</li> <li>6.906-344.0 The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>4.440-678.0 The suction hose with bend in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-279.0 The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-279.0 The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-321.0 The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-714.0 The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-635.0 The electrically conductive suction hose with bend and PFC module in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-635.0 The suction hose in nominal width DN 40 and with 16 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-637.0 The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>6.906-837.0 The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>53 4.440-263.0 The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>54 4.440-463.0 The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>55 4.440-463.0 The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>55 4.440-463.0 The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.</li> <li>56 4.440-</li></ul>

# ACCESSORIES FOR NT 65/2 AP 1.667-291.0

$   \begin{bmatrix}     \hline      \hline     \hline     \hline      \hline      \hline    $		9 9 6	$\left  \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
		Order no.	Description	
SUCTION HOSES				
Suction hoses with cone connection				
Suction hose, NT, DN 40, length 10 m, oil-resistant, cone, bayonet 1.0	57	4.440-612.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	′ 🗆
Suction hose, NT, DN 50, length 4 m, cone, bayonet 1.0	58	4.440-264.0	The suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
Suction hose, NT, DN 50, length 3 m, cone, bayonet 1.0	59	4.440-328.0	The suction hose in nominal width DN 50 and with 3 m length is suitable for use with wet and dry vacuum cleaners.	
Suction hose, NT, DN 50, length 10 m, cone, bayonet 1.0	60	4.440-467.0	The suction hose in nominal width DN 50 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	′ 🗆
Suction hose, NT, DN 50, length 4 m, oil-resistant, cone, bayonet 1.0	61	4.440-613.0	The oil-resistant suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
Suction hose, NT, DN 50, length 4 m, electrically conductive, cone, bayonet 1.0	62	4.440-616.0	The electrically conductive suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	
FILTER BAGS				
Fleece filter bags Fleece filter bags, 5 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 90	63	2.885-753.0	Tear-resistant fleece filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack.	
Paper filter bags Paper filter bags, 5 Piece(s), NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC	64	6.904-285.0	Premium 3-layer paper filter bags of dust class M, suitable for Kårcher wet and dry vacuum cleaners. Contents: 5-pack.	
FILTER T/NT				
Flat pleated filter HEPA, dust class H				
HEPA-14 (H14) flat pleated filter, dust class H, made of glass fibre material	65	6.904-364.0	For wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter made of high-quality glass fibre material. Suitable for vacuuming hazardous dusts, coarse dirt and liquids.	
Wet filter bag				
Wet filter bag	66	6.904-252.0	Approved for dust class L, general cleaning, wet and dry, tear-resistant.	
Plastic sacks for dust-free disposal				
Plastic bag for dust-free disposal, 10 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 602, NT 700, NT 702	67	6.900-698.0	PE plastic sack.	
Fabric filter				
Candle filter Wood, NT 65/2, NT 75/2	68	2.414-003.0	Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums.	
Membrane filter, NT 65, NT 70, NT 72, NT 75, NT 551, NT 602, NT 700, NT 702, NT 802, NT 993	69	6.904-282.0	Polyester needle fleece membrane/fabric filter – BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	
CONNECTING SLEEVES				
Y-adapter kit				
Y-adapter kit	70	2.637-217.0	Plastic distributor – suitable for NT vacuum cleaners.	
Available accessories.		1	I	

# ACCESSORIES FOR NT 65/2 AP 1.667-291.0



		Order no.	Description		
CONNECTING SLEEVES					
Connection adapter C ID (clip to cone)					
Adapter clip DN 35 on cone DN 35	71	5.407-005.0	Adapter clip system DN 35 for connecting suction tubes and small nozzles to cone DN 35. Perfect for vehicle interior cleaning, even without the connection of other nozzles.		
Adapter clip DN 40 to cone DN 40	72	5.407-006.0	For connecting small nozzles and suction tubes with cone DN 40: Adapter clip system DN 40. Ideal for vehicle interior cleaning tasks, with no need to connect additional nozzles.		
Connection adapter C DN 35	73	5.407-112.0	C 35 hose connector for DN 35 accessory, electrically conductive.		
Electrically conductive DN 40 connection adapter for DN 35 accessories	74	5.407-109.0	Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.		
Connection adapter C DN 40	75	5.407-111.0	C 40 hose connector for DN 40 accessory, electrically conductive.		
Connection adapter for power tools, clip conne	ction				
Power tool connection adapter, DN 26-36, electrically conductive	76	5.453-042.0	3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.		
Connection adapter for power tools, C 35,	77	5.453-048.0	Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.		
electrically conductive	78	5.453-050.0	Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.		
Adapter for electric power tools, screwable					
Adapter for electric power tools, screwable, ID 35	79	5.453-016.0	3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.		
	80	5.453-026.0	Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.		
	81	6.902-059.0	Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.		
	82	6.902-095.0	2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.		
Reducing sleeves					
NT reducer from DN 40 to DN 35, electrically conductive	83	5.407-108.0	Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.		
Reducer adapter from DN 40 to DN 35	84	6.902-017.0	Reducer, enabling accessories (upholstery nozzle, crevice nozzle, etc.) with a DN 35 connection adapter to be connected to accessory parts (bend or suction tube) that have a DN 40 connection adapter.		

## ACCESSORIES FOR NT 65/2 AP 1.667-291.0



85	Order no.	Description	
85			╘
85			
85			-
	5.407-113.0	Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	
86	6.902-072.0	Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	
87	2.860-117.0	DN 40/35, DN 35/32 (tube -> nozzle), plastic.	
VAC	UUM CLEANERS		
88	2.637-353.0	Single parts: 4 m suction hose (4.440-263.0), metal bend (6.900-276.0), 2x 0.5 m metal suction tubes (6.900-275.0), crevice nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	
89	2.862-166.0	Vehicle interior cleaning accessory kit in nominal width DN 35 for Kärcher wet and dry vacuum cleaners. The kit comprises various nozzles and adapter pieces in nominal widths DN 35 and DN 40.	
90	2.640-760.0	Target group-specific robust connection set in DN 61 for cleaning work in combination with oil-resistant suction hose and rubber nozzle.	
91	2.863-026.0	The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	
92	5.031-436.0	Electroconductive adapter for connecting NT hoses with bayonet 1.0 connection of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher.	
93	2.642-602.0	For switching off when vacuuming non-conductive fluids such as oils and greases	
94	6.647-022.0	Extension cable, 20 m, 3x1.5 mm <sup>2</sup> . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	
	90 91 92 93	VACUUM CLEANERS           88         2.637-353.0           89         2.862-166.0           90         2.640-760.0           91         2.863-026.0           92         5.031-436.0           93         2.642-602.0	<ul> <li>VACUUM CLEANERS</li> <li>88 2.637-353.0 Single parts: 4 m suction hose (4.440-263.0), metal bend (6.900-276.0), 2x 0.5 m metal suction tubes (6.900-275.0), crevice nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).</li> <li>89 2.862-166.0 Vehicle interior cleaning accessory kit in nominal width DN 35 for Kärcher wet and dry vacuum cleaners. The kit comprises various nozzles and adapter pieces in nominal widths DN 35 and DN 40.</li> <li>90 2.640-760.0 Target group-specific robust connection set in DN 61 for cleaning work in combination with oil-resistant suction hose and rubber nozzle.</li> <li>91 2.863-026.0 The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.</li> <li>92 5.031-436.0 Electroconductive adapter for connecting NT hoses with bayonet 1.0 connection of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher.</li> <li>93 2.642-602.0 For switching off when vacuuming non-conductive fluids such as oils and greases</li> <li>94 6.647-022.0 Extension cable, 20 m, 3x1.5 mm<sup>2</sup>. With splash-proof earthing pin plug, strain relief and anti-kink</li> </ul>