



NT 25/1 Ap

Kätevän kokoinen, helposti liikuteltava ammattitason märkä-kuivaimuri rakennus- ja remontti-työmaille.

1 ApClean - puoliautomaattinen suodattimen puhdistus

- Puoliautomaattinen suodattimenpuhdistus ehkäisee tukkeutumisen ja ylläpitää imutehon.

3 Käytännöllinen säilytyspaikka virtajohdolle

- Säilytyskoukku virtajohdon turvalliseen säilytykseen

2 Helposti liikuteltava ja suorituskykyinen

- Kätevän kokoinen imuri liikkuu helposti mukana.
- Kompakti koko ja ammattikäyttöön mitoitettu teho.

4 Virtajohdon säilytys

- Säilytyskoukku virtajohdon turvalliseen säilytykseen
- Virtajohdon säilytyspaikka helpottaa kuljetusta.



NT 25/1 Ap

■ Puoliautomaattinen suodattimen puhdistus

Tekniset tiedot

Tuotenumero		1.184-503.0
EAN koodi		4039784718289
Ilman läpivirtaus	l/s	74
Alipaine	mbar / kPa	254 / 25,4
Säiliötilavuus	l	25
Maks. ottoteho	W	1380
Varusteiden halkaisija ID 51/61		ID 35
Virtajohdon pituus	m	7,5
Äänenvoimakkuus	dB(A)	70
Säiliön materiaali		muovi
Mootoreiden lukumäärä		1
Taajuus	Hz	50-60
Jännite	V	220-240
Paino	kg	11
Mitat (p x l x k)	mm	510 x 370 x 480

Laite

Imuletku	m	2,5	Huoltovapaat imumootorit	kpl	1
Imuputki	kpl / m	2 x 0,5 / Metalli			
Pölypussi		fleece			
Lattiasuulake markä- ja kuivaimurointiin	mm	300			
Rakosuulake	■				
Automaattinen pinnanvartija säiliön täyttyessä	■				
Eco-suodatinjärjestelmä	■				
Laakasuodatin		Paperi			
Imukahva	■				
Suodattimen puhdistus		ApClean - puoliautomaattinen suodattimen puhdistus			
Turvallisuusluokitus		II			

■ Toimituksen mukana.

NT 25/1 AP 1.184-503.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Laakasuodatin (paperi)								
Laakasuodatin, paperi	1	6.904-367.0	1 kpl				Paperinen laakasuodatin pölyluokka M.	■
Taivutettu imutanko, muovia								
Taivutettu tanko DN 35, muovi	2	5.031-718.0	1 kpl	ID 35			Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	■
Taivutettu tanko DN 35, muovi, sähköä johtava	3	5.031-939.0	1 kpl	ID 35			Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
Taivutettu tanko DN 40, muovi, sähköä johtava	4	5.032-427.0	1 kpl	ID 40			Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Taivutettu tanko DN 40, muovi	5	5.031-904.0	1 kpl	ID 40			Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.	□
Rakosuulakkeet								
RAKOSUUTIN, NW 35	6	6.900-385.0	1 kpl	ID 35	210 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	■
RAKOSUUTIN METALLISTA	7	6.900-922.0	1 kpl	ID 35	500 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
RAKOSUUTIN NW 40	8	6.903-033.0	1 kpl	ID 40	290 mm		Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	□
RAKOSUUTIN	9	6.905-817.0	1 kpl	ID 40	400 mm		Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Crevice nozzle DN35	10	6.906-240.0	1 kpl	ID 35	250 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 250 mm.	□
Imutangot metallia								
IMUPUTKI NW 35, 0,5	11	6.900-514.0	1 kpl	ID 35	0,5 m		Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	■
Imutanko, 0,5m, metallia/ ID 40	12	6.900-275.0	1 kpl	ID 40	0,55 m		Chromium-plated metal suction tube (DN 40, 1x0.5 m), standard for virtually all two-motor industrial vacuum cleaners. Optional for industrial single-motor NT vacuum cleaners with DN 40 suction hose.	□
Imuletkut täydellinen (Clip-system)								
IMULETKU+TAIVUTETTU IMUTANKO	13	4.440-626.0	1 kpl	ID 35	2,5 m		2.5 m standard suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without PDFC module. Standard for NT 27/1/Me Advance und NT 48/1.	■
Imuletku 2,5 m, (Clip-system), sähköä johtava	14	4.440-653.0	1 kpl	ID 35	2,5 m		2.5 m electrically conductive suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without module.	□
Sovitin sähkötyökaluille, clip-kiinnitys, antistaattinen								
SÄHKÖTYÖKALUADAPTERI	15	5.453-042.0	1 kpl	ID 35			3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	■
Liitoscappale, sähkötyökalulle	16	5.453-048.0	1 kpl	ID 35			Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	□
	17	5.453-049.0	1 kpl	ID 35				□
	18	5.453-050.0	1 kpl	ID 35			Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	□
	19	5.453-051.0	1 kpl	ID 35				□
	20	5.453-052.0	1 kpl	ID 35				□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 25/1 AP 1.184-503.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Fleece-pölypussit (3-kerroksiset)								
Set filter bags-fleece 25L	21	6.907-478.0	5 kpl					■
Fleece pölypussit NT 361, 5 kpl	22	6.904-351.0	5 kpl				3-ply tear-resistant fleece filter bags (dust class M). For dry pick up, suitable for the following models: NT 361 Eco, Eco TE, TE-A and NT 361 Eco M, NT 35/1 Eco, Eco Te, Eco M. Contents: x5	□
Mikrosuihkusetit								
SUUTINSARJA NW35	23	2.860-116.0	1 kpl	ID 35			Nozzle kit for all NT vacuum cleaners with DN 35 accessories includes crevice tool, upholstery tool, round brush (x3)	□
Laakasuoatin (PES)								
Laakasuoatin, (PES)	24	6.904-360.0	1 kpl				Flat pleated filter (PES) – BIA-C dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 35/1 Eco BS and NT 55/1 Eco BS.	□
Karkeanliansuoatin veden imurointiin								
Karkeanliansuoatin NT 361, 561,611	25	6.904-287.0	1 kpl				Coarse dirt filter with perforated metal plate and foam seal suitable for wet pick up - NT 611 Eco K & KF models.	□
Kangassuoatin								
Membraansuoatin	26	6.904-212.0	1 kpl				Polyester needle fleece membrane/fabric filter, washable up to 40°C, suitable for all NT 361 Eco to NT 611 Eco versions as an alternative to a filter bag.	□
HEPA-suoatin, pölyluokka H								
Laakasuoatin HEPA (luokka H) NT 361, 561,611,	27	6.904-242.0	1 kpl				HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	□
Paperinen pölypussi (kaksinkertainen)								
Paperinen pölypussi NT 361, 5 kpl	28	6.904-259.0	5 kpl				5 paper filter bags (BIA-C dust class M) with reinforced outer ply (e.g. cement dust). For all NT 361 Eco models (except Eco H).	□
Muovisäkit								
Muovisäkki NT 35/1	29	6.596-886.0	10 kpl				PE plastic sack.	□
Erikoispölypussi, märkäimurointi								
Pölypussit märkä-kuivaimurointiin NT 361, 5 kpl	30	6.904-171.0	5 kpl				Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Taivutetut imutangot, rosteria								
Taivutettu tanko DN 35, RST	31	6.903-141.0	1 kpl	ID 35			Stainless steel and crooked, ID 35	□
Taivutettu tanko DN 40, RST	32	6.902-079.0	1 kpl	ID 40			Stainless steel and crooked, ID 40	□
Taivutetut imutangot, metallia								
Taivutettu tanko, metallia ID 35	33	6.900-519.0	1 kpl	ID 35			Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	□
Taivutettu tanko, metallia ID 40	34	6.900-276.0	1 kpl	ID 40			Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el.).	□
Lattiasuulakkeet								
LATTIASUULAKE DN35	35	6.906-512.0	1 kpl	ID 35		300 mm	All-purpose plastic nozzle (DN 35) with 300 mm working width. With side rollers, brush strips (6.903-278.0) and squeegees (6.903-277.0). Only for NT vacuum cleaners.	□
LAITOSSUUTIN GRD 370	36	6.903-018.0	1 kpl	ID 40		370 mm	All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 25/1 AP 1.184-503.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus		
LATTIASUULAKE DN40	37	6.906-383.0	1 kpl	ID 40		450 mm	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	☐	
LATTIASUULAKE DN 35	38	6.906-384.0	1 kpl	ID 35		370 mm	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	☐	
Floor tool packaged basalt grey DN40	39	6.907-408.0	1 kpl	ID 40		360 mm		☐	
Imusuulake, kumikärki 45°									
Kumisuulake, DN 35 45° kärki	40	6.902-104.0	1 kpl	ID 35	220 mm		45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐	
Kumisuulake, DN 40, 45° kärki	41	6.902-105.0	1 kpl	ID 40	220 mm		45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐	
Lattiasuulakkeet, kuivaimurointi									
Yhdistelmäsuulake (kuiva) ID 35, 270 mm	42	6.906-511.0	1 kpl	ID 35		270 mm	Combination floor tool with changeover function, plastic (272 mm). With stainless steel base plate, thread catcher 6.905-417.0 and DN 35 connection.	☐	
Putkisuulakkeet									
PUTKISUUTIN 100 MM	43	6.903-035.0	1 kpl	ID 35			Plastic, pipe diameter 100 mm	☐	
PUTKISUUTIN 200 MM	44	6.903-036.0	1 kpl	ID 35			Plastic, pipe diameter 200 mm	☐	
Harjasuulakkeet									
HARJASUUTIN NIVELÖITY 35mm	45	6.903-862.0	1 kpl	ID 35		70 mm	Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.	☐	
Turbosuulakkeet									
TURBOSUUTIN/HUONEKALU	46	2.860-113.0	1 kpl	ID 32		160 mm	Plastic turbo upholstery nozzle (DN 35/32, 160 mm) with reduction sleeve.	☐	
TURBOSUUTIN/LATTIA	47	2.860-114.0	1 kpl	ID 32		270 mm	Plastic turbo floor nozzle (DN 35/32, 270 mm) with reduction sleeve.	☐	
Imutangot, ruostumaton teräs									
Imutanko, 0,5 m RST DN 40	48	6.902-081.0	1 kpl	ID 40	0,5 m		Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	☐	
Imutanko, 1 m RST DN 40	49	6.906-531.0	1 kpl	ID 40	1 m		Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	☐	
Imutangot muovi									
Imutanko, 0,5 m, muovia/ ID 35	50	6.900-384.0	1 kpl	ID 35	0,5 m		Plastic suction tube (DN 35, 1x0.5 m) only suitable for BV and T vacuum cleaners.	☐	
Korjaussarjat									
Korjaussetti	51	2.639-682.0	1 kpl	ID 35			Repair set (C35) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	☐	
Imuletkut (Clip-system)									
Imuletku 4 m clip-system	52	6.906-241.0	1 kpl	35	4 m		4 m suction hose without bend and adapter. With bayonet at vacuum end and C 35 clip connection at accessory end.	☐	
Imuletku 2,5 m clip-system	53	6.906-275.0	1 kpl	35	2,5 m		2.5 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.	☐	

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 25/1 AP 1.184-503.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Imuletku 4 m clip-system	54	6.906-500.0	1 kpl	35	4 m		4 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.	☐
	55	6.906-321.0	1 kpl	40	4 m		4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	☐
Imuletku 4 m, öljyn kestävä, clip-system	56	6.906-714.0	1 kpl	40	4 m		With bayonet and clip connection.	☐
Imuletku 4 m, clip-system, sähköä johtava	57	6.906-546.0	1 kpl	40	4 m		Sähköä johtava, 4 m imuletku bajonet-liitännällä ja C 40 clip-system pikakiinnityksellä. Mutka ja adapteri eivät sisälly toimitukseen. Huom! Ilman erillistä sovitinta, imuletku ei ole yhteensopiva 1-moottoristen imureiden vakiovarusteiden kanssa.	☐
Imuletku 4 m, clip-system, sähköä johtava	58	6.906-877.0	1 kpl	40	10 m		Suction hose with bayonet coupling, electrically conductive.	☐
Imuletku 10 m clip-system	59	6.906-242.0	1 kpl	35	10 m		Electrically conductive, 10 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	☐
Imuletkut täydellinen								
Imuletku 7 m, liitin sähkötyökalulle, sähköä johtava	60	4.440-461.0	1 kpl	ID 27	7 m		Electrically non-conductive suction hose (7 m) with DN 27 power tool adapter at accessory end and DN 27 bayonet at vacuum end. Connectors available on request.	☐
Sovitin kappaleet								
Letkujen liitoskappale	61	6.902-077.0	1 kpl	ID 32			Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	☐
	62	6.900-286.0	1 kpl	ID 40			Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	☐
	63	6.902-078.0	1 kpl	ID 61				☐
Y-liitinsetti								
Y-kappalesetti, muovia	64	2.637-217.0	1 kpl	ID 35			Plastic distributor - suitable for NT vacuum cleaners.	☐
Sovitin C ID, antistaattinen								
Liitoskappale C-DN35 (sähköä johtava)	65	5.407-112.0	1 kpl	ID 35			C 35 hose connector for DN 35 accessory, electrically conductive.	☐
Liitoskappale C40-DN35	66	5.407-109.0	1 kpl	ID 40			Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	☐
Liitoskappale C-DN40	67	5.407-111.0	1 kpl	ID 40			C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Sovitin sähkötyökaluille, kierteellä								
Adapteri sähkötyökalulle	68	5.453-016.0	1 kpl	ID 35			3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	☐
	69	5.453-026.0	1 kpl	ID 35			Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	☐
	70	6.902-059.0	1 kpl	ID 35			Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm. External diameter: 39 mm.	☐
	71	6.902-095.0	1 kpl	ID 35			2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mm. Suitable for NT vacuum cleaners.	☐
Sovitin (putkisuutin)								
Sovitin DN 35- 40	72	6.902-084.0	1 kpl	ID 35			From DN 35 to DN 40: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 25/1 AP

1.184-503.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus	
Supistin									
Supistin C40	73	5.407-108.0	1 kpl	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	☐
Supistin (putki - suutin)									
Supistin DN40 - DN35	74	6.902-017.0	1 kpl	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	☐
Supistin DN35 - DN32	75	6.902-072.0	1 kpl	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐
Supistin ja jatko-osasetti									
Supistin/sovitinsetti ID40/35, 35/32 muovia	76	2.860-117.0	1 kpl					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	☐
Varusteet imureihin									
Ammatti- ja laitossetti ID 35	77	2.637-595.0		ID 35				Accessory kit for industrial and commercial use.	☐
Lämmityskattilasetti ID 35 NT 351,361	78	2.638-852.0		ID 35				Accessory kit for vacuuming and cleaning boilers, oil stoves, etc.	☐
Rakentajasetti ID 40	79	2.637-352.0		ID 40				Building and ancillary trade accessory kit.	☐
Profi-setti ID 40	80	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	☐
Hevossetti ID 35	81	2.637-248.0		ID 40				Target group-specific accessory kit for horse and pony breeders or owners	☐
Märkä/kuivaimurointiseti (sähköä johtava) ID 40	82	2.638-147.0		ID 40				Wet and dry vacuum cleaner kit, electrically conductive, DN 40.	☐
Laakasuodatin (PTFE)									
Flat-pleated filter packaged PTFE	83	6.907-455.0	1 kpl						☐
Autonimurointisuulakkeet									
AUTOSUUTIN NW35	84	6.906-108.0	1 kpl	ID 35		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	☐
muut									
Drilling dust tool	85	2.679-000.0	1 kpl						☐
CS 40 Me	86	2.863-026.0	1 kpl						☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 25/1 AP
1.184-503.0



		Tuotenumero	Pituus		Määrä		Kuvaus	
Sekalaiset								
Jatkojohto	1	6.647-022.0	20 m		1 kpl		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

■ Toimituksen mukana. ☐ Saatavilla olevat varusteet.