



ШЛАНГ PRIMOFLEX 5/8 – 50M

Высококачественный садовый шланг PrimoFlex® (5/8") длиной 50 м. Армирован устойчивой к давлению тканью. Безопасен для здоровья. Давление разрыва 24 бар. Высокая термостойкость: от 0 до +40 °C.



Артикул	2.645-141.0
---------	-------------

Технические характеристики

Штрих-код (EAN)	4039784447615
Диаметр	5/8"
Длина шланга	м50
Цвет	Желтый
Вес	кг7,37
Вес (с упаковкой)	кг7,415
Размеры (Д×Ш×В)	мм370 × 370 × 195

Гарантия 12 лет

- Гарантированная стойкость

3 слоя

- Устойчив к перегибам

Выдерживает давление до 24 бар

- Гарантированная надежность

СОВМЕСТИМАЯ ТЕХНИКА

- K 2 Battery
- K 2 Car
- K 2 Classic Car
- K 2 Compact Car
- K 2 Power Control
- K 2 Universal Edition
- K 2 Universal Edition Car
- K 3
- K 3 Car & Home
- K 3 Power Control
- K 4 Classic Car
- K 4 Compact Car
- K 4 Power Control Flex Car & Home
- K 4 Power Control Flex Car & Stairs
- K 5 Basic
- K 5 Power Control Flex
- K 5 Power Control Flex Home&Brush Anniversary Edition
- K 5 WCM
- K 6 Special
- K 7 Compact
- K 7 Premium Power Flex Home
- K 7 Premium Power Home
- K 7 WCM
- K 7 WCM FJ Home
- K Mini
- K Silent Anniversary Edition
- KHB 6 Battery