

Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: VehiclePro Spray Wax RM 821 Classic
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.
- · Application of the substance / the mixture Drying aid for vehicle washing plants
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

Kärcher (UK) Ltd.

Kärcher House Brookhill Way Banbury Oxon OX16 3ED Great Britain

Tel.: +44-1295-752-000

Internet: www.karcher.com

· Further information obtainable from:

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com

1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms Void
- · Signal word Void

(Contd. on page 2)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 1)

· Hazard statements

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 1335202-95-3 EC number: 931-216-1 Reg.nr.: 01-2119472309-33	Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me sulfate-quaternized ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 28 % Eye Irrit. 2; H319: C ≥ 28 %	1-5%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43-0000	decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	≥1-≤5%
CAS: 5131-66-8 EINECS: 225-878-4 Index number: 603-052-00-8 Reg.nr.: 01-2119475527-28-XXXX	propylene glycol monobutyl ether Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	1-5%
CAS: 5989-27-5 EINECS: 227-813-5 Index number: 601-096-00-2 Reg.nr.: 01-2119529223-47	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥0.25-<19
CAS: 68424-85-1 EINECS: 270-325-2 Reg.nr.: 01-2119965180-41	Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16)) Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302	≥0.1-<0.25

·SVHC

541-02-6 decamethylcyclopentasiloxane

Additional information For the wording of the listed hazard phrases refer to section 16.

— GB



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Rinse with warm water.
- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Keep away from food, beverages and feed.
- Further information about storage conditions: Protect from frost.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1 Control parameters					
Ingredients with limit values that require monitoring at the workplace:					
67-63-0 propan	67-63-0 propan-2-ol				
	WEL Short-term value: 1250 mg/m³, 500 ppm				
Long-term	ı value:	999 mg/m³, 400 ppm			
· DNELs					
67-63-0 propan	-2-ol				
Oral	DNEL	26 mg/kg×d (consumer)			
Dermal	DNEL	888 mg/kg×d (employee)			
		319 mg/kg×d (consumer)			
Inhalative	DNEL	500 mg/m3 (employee)			
		89 mg/m3 (consumer)			
68424-85-1 Alky	yl (C12	-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))			
Dermal	DNEL	5.7 mg/kg×d (employee)			
Inhalative	DNEL	3.96 mg/m3 (employee)			
		1.64 mg/m3 (consumer)			
Irritation of skin	DNEL	3.4 mg/cm2 (consumer)			
· PNECs					
541-02-6 decan	nethylc	yclopentasiloxane			
PNEC	10 mg	g/l (STP) (Assessment factor: 100)			
PNEC sediment	PNEC sediment 11 mg/kg (freshwater) (Assessment factor: 10)				
	1.1 m	g/kg (marine water) (Assessment factor: 100)			
PNEC soil	2.54 n	ng/kg (Assessment factor: 50)			
	•	(Contd. on page 5)			

(Contd. on page 5)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

		Contd. of page 4
PNEC aqua	0.0012 mg/l (freshwater) (Assessment factor: 10)	Conta. or page +
•	0.00012 mg/l (marine water) (Assessment factor: 100)	
67-63-0 propan-		
PNEC	140.9 mg/l (freshwater)	
	140.9 mg/l (marine water)	
	140.9 mg/l (STP)	
	2251 mg/l (STP)	
PNEC sediment	552 mg/kg (freshwater)	
	552 mg/kg (marine water)	
PNEC soil	28 mg/kg (soil)	
5989-27-5 (R)-p-	-mentha-1,8-diene	
PNEC	1.8 mg/l (STP) (Assessment factor: 10)	
PNEC sediment	PNEC sediment 3.85 mg/kg (freshwater) (sediment dw)	
	0.385 mg/kg (marine water) (sediment dw)	
PNEC soil	0.763 mg/kg (soil dw)	
PNEC aqua	0.014 mg/l (freshwater) (Assessment factor: 10)	
	0.0014 mg/l (marine water) (Assessment factor: 100)	
68424-85-1 Alky	/I (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))	
PNEC	0.001 mg/l (freshwater)	
	0.001 mg/l (marine water)	
	0.4 mg/l (STP)	
PNEC sediment	12.27 mg/kg (freshwater)	
	13.09 mg/kg (marine water)	
PNEC soil	7 mg/kg (soil)	

- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection
- * chemical resistant protective gloves (EN 374)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- For the permanent contact gloves made of the following materials are suitable:
- * butyl rubber 0,7 mm, 480 min (EN 374)
- As protection from splashes gloves made of the following materials are suitable:
- * nitril rubber 0,4 mm, 30 min (EN 374)

(Contd. on page 6)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

· Eye/face protection Goggles recommended during refilling.

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateColour:Odour:FluidBluefresh

· Odour threshold: Not determined.

Melting point/freezing point:
 Boiling point or initial boiling point and boiling range
 100 °C

Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable
 Auto-ignition temperature: not applicable
 Decomposition temperature: Not determined.

pH at 20 °C 4 pH-value 1 %: 6-8

· Viscosity:

· Kinematic viscosity Not determined.

· dynamic at 20 °C: 3 mPas

Solubility

Water: Fully miscible
 Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C:

Relative density

Vapour density

Relative gas density

O.994 g/cm³

Not determined.

Not determined.

Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 5.1 %

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 7)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

		(Contd. of page
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammab	le gases	
in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- 10.1 Reactivity corresponds to 10.3
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
541-02-6 decamethylcyclopentasiloxane				
LD50	>15000 mg/kg (Rat)			
LC50	>5000 mg/kg (Rat)			
5131-66-8 propylene glycol monobutyl ether				
LD50	3300 mg/kg (Rat)			
	lecam LD50 LC50 propy			

(Contd. on page 8)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

		(Contd. of page 7)			
67-63-0 pi	67-63-0 propan-2-ol				
Oral	LD50	5840 mg/kg (Rat) (OECD 401)			
Dermal	LD50	13900 mg/kg (Rabbit) (OECD 402)			
68424-85-	68424-85-1 Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))				
Oral	LD50	344 mg/kg (Rat)			
Dermal	LD50	3340 mg/kg (Rabbit)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- * STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

· Endocrine disrupting properties			
541-02-6	decamethylcyclopentasiloxane	List II	
540-97-6	Dodecamethylcyclohexasiloxane	List II	
118-58-1	benzyl salicylate	List II	
556-67-2	octamethylcyclotetrasiloxane	List II; III	

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic tox	· Aquatic toxicity:			
5131-66-8 pro	5131-66-8 propylene glycol monobutyl ether			
LC50/96 h	_C50/96 h 560-1000 mg/l (fish)			
67-63-0 propa	67-63-0 propan-2-ol			
LC50/96 h	9640 mg/l (Pimephales promelas)			
EC50/48 h	13299 mg/l (Daphnia magna)			
EC50/72 h	>1000 mg/l (Desmodesmus subspicatus)			
EC10/18 h	>1000 mg/l (Pseudomonas putida) (DIN 38412)			
5989-27-5 (R)	5989-27-5 (R)-p-mentha-1,8-diene			
LC50/96 h	0.72 mg/l (Pimephales promelas)			
EC50/48 h	0.307 mg/l (Daphnia magna)			
	0.25 mg/l (Pseudokirchneriella subcapitata)			
EC50/72 h	0/72 h 0.32 mg/l (Pseudokirchneriella subcapitata)			
EC10/72 h	10/72 h 0.174 mg/l (Pseudokirchneriella subcapitata)			
EC10/21 d	0.153 mg/l (Daphnia magna)			

(Contd. on page 9)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

(Conte	d. of page 8)
0.37-0.67 mg/l (Pimephales promelas)	
209 mg/l (activated sludge) (OECD 209)	
Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))	
0.28 mg/l (Pimephales promelas) (US-EPA)	
0.515 mg/l (Lepomis macrochirus)	
0.03 mg/l (Algae)	
0.016 mg/l (Daphnia magna)	
11 mg/l (activated sludge) (OECD 209)	
0.049 mg/l (Pseudokirchneriella subcapitata)	
0.032 mg/l (Pimephales promelas)	
0.0042 mg/l (Daphnia magna)	
0.456 mg/l (Lepomis macrochirus)	
	0.37-0.67 mg/l (Pimephales promelas) 209 mg/l (activated sludge) (OECD 209) Ikyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16)) 0.28 mg/l (Pimephales promelas) (US-EPA) 0.515 mg/l (Lepomis macrochirus) 0.03 mg/l (Algae) 0.016 mg/l (Daphnia magna) 11 mg/l (activated sludge) (OECD 209) 0.049 mg/l (Pseudokirchneriella subcapitata) 0.032 mg/l (Pimephales promelas) 0.0042 mg/l (Daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

Degree of elimination:		
1335202-95-	3 Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me sulfate-quaternized	
OECD 301B	>60 % (28 d)	
541-02-6 ded	camethylcyclopentasiloxane	
OECD 310	0.14 % (28 d)	
5131-66-8 pr	opylene glycol monobutyl ether	
OECD 301E	90 % (28 d)	
5989-27-5 (R)-p-mentha-1,8-diene	
OECD 301B	71.4 % (28 d)	
68424-85-1 A	Alkyl (C12-16) dimethylbenzyl ammonium chloride (ADBAC/BKC (C12-C16))	
OECD 301D	63 % (28 d)	

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

· PBT:	
541-02-6	decamethylcyclopentasiloxane
· vPvB:	
541-02-6	decamethylcyclopentasiloxane

- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · COD-value: 219000 mg/l

(Contd. on page 10)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 9)

· General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The product does not contain organic complexing agents.

The product does not contain organically bounded halogens (AOX-free). Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

20 01 29* detergents containing hazardous substances

- Uncleaned packaging:
- · Recommendation:

Packaging may be reused or recycled after cleaning.

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information 14.1 UN number or ID number ADR, ADN, IMDG, IATA Void 14.2 UN proper shipping name ADR, ADN, IMDG, IATA Void 14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class Void 14.4 Packing group ADR, IMDG, IATA Void

(Contd. on page 11)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

		(Contd. of page 10)
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

A product information sheet can be provided if requested.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

(Contd. on page 12)



Printing date 22.03.2024 Version number 7 (replaces version 6) Revision: 09.08.2021

Trade name: VehiclePro Spray Wax RM 821 Classic

(Contd. of page 11)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

· 0·011-776·0 RM 821/11 2·051

GB