Revision: 17.03.2022



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.03.2023

Version number 8 (replaces version 7)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: VehiclePro Hot Wax RM 820 Classic
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.
- · Application of the substance / the mixture Drying aid for vehicle washing plants
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

#### Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

#### Kärcher (UK) Ltd.

Kärcher House **Brookhill Way** Banbury Oxon OX16 3ED Great Britain Tel.: +44-1295-752-000

Internet: www.karcher.com

· Further information obtainable from:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management@de.kaercher.com

· 1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void

(Contd. on page 2)



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 1)

Revision: 17.03.2022

· Additional information:

Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT:

541-02-6 decamethylcyclopentasiloxane

· vPvB:

541-02-6 decamethylcyclopentasiloxane

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 1335202-95-3 EC number: 931-216-1 Reg.nr.: 01-2119472309-33	Fatty acids, C18 unsatd., reaction productswith triethanolamine, di-Me sulfate-quaternized  ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319  Specific concentration limits: Skin Irrit. 2; H315: C ≥ 28 %  Eye Irrit. 2; H319: C ≥ 28 %	1-5%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43-0000	decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	≥1-≤5%
CAS: 5131-66-8 EINECS: 225-878-4 Index number: 603-052-00-8 Reg.nr.: 01-2119475527-28-XXXX	propylene glycol monobutyl ether  Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	1-5%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol  Eye Irrit. 2, H319	1-5%

·SVHC

541-02-6 decamethylcyclopentasiloxane

· Additional information For the wording of the listed hazard phrases refer to section 16.

— GE

(Contd. on page 3)



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 2)

Revision: 17.03.2022

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Rinse with warm water.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

See Section 13 for disposal information.

(Contd. of page 3)

Revision: 17.03.2022

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Keep away from food, beverages and feed.
- · Further information about storage conditions: Protect from frost.
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

Ingredier	nts wit	th limit values that require monitoring at the workplace:
67-63-0 pı	opan-2	2-ol
		value: 1250 mg/m³, 500 ppm
Lon	g-term	value: 999 mg/m³, 400 ppm
112-34-5 2	2-(2-bu	toxyethoxy)ethanol
		value: 101.2 mg/m³, 15 ppm
Lon	g-term	value: 67.5 mg/m³, 10 ppm
DNELs		
67-63-0 pı	opan-	2-ol
Oral	DNEL	26 mg/kg*d (consumer)
Dermal	DNEL	888 mg/kg*d (employee)
		319 mg/kg*d (consumer)
Inhalative	DNEL	500 mg/m3 (employee)
		89 mg/m3 (consumer)
PNECs		
67-63-0 pı	opan-	2-ol
PNEC		140.9 mg/l (freshwater)
		140.9 mg/l (marine water)
		140.9 mg/l (STP)
		2251 mg/l (STP)
PNEC sediment		552 mg/kg (freshwater)
		552 mg/kg (marine water)
PNEC soil	- 1	28 mg/kg (soil)



Printing date 04.03.2023 Version number 8 (replaces version 7) Revision: 17.03.2022

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 4)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection
  - \* chemical resistant protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material Not required.
- · For the permanent contact gloves made of the following materials are suitable:
- \* butyl rubber 0,7 mm, 480 min (EN 374)
- · As protection from splashes gloves made of the following materials are suitable:
- \* nitril rubber 0,4 mm, 30 min (EN 374)
- · Eye/face protection Goggles recommended during refilling.

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical stateColour:Odour:Pine

· Odour threshold: Not determined.

 $\cdot$  Melting point/freezing point: 0 °C

· Boiling point or initial boiling point and boiling range

range 100 °C • Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable
Ignition temperature: not applicable
Decomposition temperature: Not determined.

• pH at 20 °C 3.5 • pH-value 1 %: 6-7

· Viscosity:

· Kinematic viscosity Not determined.

· dynamic at 20 °C: 4 mPas

(Contd. on page 6)



Printing date 04.03.2023 Version number 8 (replaces version 7) Revision: 17.03.2022

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 5) · Solubility · Water: Fully miscible · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined. · Density and/or relative density · Density at 20 °C: 0.992 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined. · Relative gas density Not determined. · Particle characteristics Not applicable. · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product does not present an explosion hazard. · Solvent content: · Solids content: 6.8 % · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 6)

Revision: 17.03.2022

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity corresponds to 10.3
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ecame	ethylcyclopentasiloxane	
LD50	>15000 mg/kg (Rat)	
LC50	>5000 mg/kg (Rat)	
propy	lene glycol monobutyl ether	
LD50	3300 mg/kg (Rat)	
opan-	2-ol	
LD50	5840 mg/kg (Rat) (OECD 401)	
LD50	13900 mg/kg (Rabbit) (OECD 402)	
-(2-bu	toxyethoxy)ethanol	
LD50	2410 mg/kg (mouse) (OECD 401)	
LD50	2764 mg/kg (Rabbit)	
	LD50 LC50 propy LD50 ppan-2 LD50 LD50 -(2-bu	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Revision: 17.03.2022



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

· 11.2 Info	(Contd. of page 7)  1.2 Information on other hazards				
· Endocri	ne disrupting properties				
541-02-6	decamethylcyclopentasiloxane	List II			
540-97-6	Dodecamethylcyclohexasiloxane	List II			
556-67-2	octamethylcyclotetrasiloxane	List II, III			

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic to	exicity:
5131-66-8	propylene glycol monobutyl ether
LC50/96 h	560-1000 mg/l (fish)
67-63-0 pro	ppan-2-ol
LC50/96 h	9640 mg/l (Pimephales promelas)
EC50/48 h	13299 mg/l (Daphnia magna)
EC50/72 h	>1000 mg/l (Desmodesmus subspicatus)
EC10/18 h	>1000 mg/l (Pseudomonas putida) (DIN 38412)
112-34-5 2-	(2-butoxyethoxy)ethanol
LC50/96 h	1300 mg/l (Lepomis macrochirus)
EC10/16 h	1170 mg/l (Pseudomonas putida)
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)
NOEC	>100 mg/l (Desmodesmus subspicatus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT:

541-02-6 decamethylcyclopentasiloxane

· vPvB:

541-02-6 decamethylcyclopentasiloxane

- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · COD-value: 322000 mg/l
- · General notes:

The product does not contain organic complexing agents.

(Contd. on page 9)



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 8)

Revision: 17.03.2022

The product does not contain organically bounded halogens (AOX-free).

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· European waste catalogue

20 01 30 detergents other than those mentioned in 20 01 29

- Uncleaned packaging:
- · Recommendation:

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information	1	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according IMO instruments	ing to  Not applicable.	
· UN "Model Regulation":	Void	



Printing date 04.03.2023

Version number 8 (replaces version 7)

Trade name: VehiclePro Hot Wax RM 820 Classic

(Contd. of page 9)

Revision: 17.03.2022

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. A product information sheet can be provided if requested.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Contact:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management@de.kaercher.com

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

0.011-775.0

RM 820 Classic/2

2.574

GB