

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

Version number 9 (replaces version 8)

Revision: 21.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

[•] Trade name: VehiclePro High-Pressure Wash RM 806

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Restricted to professional users.
- · Application of the substance / the mixture High pressure cleaner

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

Kärcher (UK) Ltd. Kärcher House Brookhill Way Banbury Oxon OX16 3ED Great Britain Tel.: +44-1295-752-000

Internet: www.karcher.com

[•] Further information obtainable from:

Regulatory Affairs Tel.: +49-7195-14-0 productsafety.management.de@karcher.com

1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

[·] 2.1 Classification of the substance or mixture [·] Classification according to Regulation (EC) No 1272/2008	
Met. Corr.1 H290 May be corrosive to metals.	
Skin Corr. 1B H314 Causes severe skin burns and eye damage.	
Eye Dam. 1 H318 Causes serious eye damage.	
 [•] 2.2 Label elements [•] Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2) 	

according to Regulation (EC) No 1907/2006, Article 31


Printing date 03.05.2024

KARCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806



SECTION 3: Composition/information on ingredients

[•] 3.2 Mixtures

· Description: Cleaning agent

[•] Dangerous components:		
CAS: 15763-76-5 EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	sodium p-cumenesulphonate	_ 1-5%
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6 Reg.nr.: 01-2119457892-27-xxxx	sodium hydroxide	_ ≥2-<5%
CAS: 78330-20-8	fatty alcohol ethoxylate	_ ≥1-<3%
CAS: 69011-36-5	isotridecanolethoxylate + 8 EO ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	_ ≥1-<3%
• Additional information For th	e wording of the listed hazard phrases refer to section 16.	

(Contd. on page 3)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

KÄRCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 2)

SECTION 4: First aid measures

[•] 4.1 Description of first aid measures

- [·] General information
- Involve doctor immediately.

Immediately remove any clothing soiled by the product.

[•] After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact Immediately wash with water and soap and rinse thoroughly.
- * After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

* 4.2 Most important symptoms and effects, both acute and delayed Corneal damage

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- [·] 5.1 Extinguishing media
- [•] Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- [•] 5.3 Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Use neutralising agent. Dispose contaminated material as waste according to section 13.

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 3)

Ensure adequate ventilation.

[•] 6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with eyes and skin.

· Information about fire - and explosion protection: No special measures required.

[•]7.2 Conditions for safe storage, including any incompatibilities

- [·] Storage
- Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: aluminium. Store only in the original receptacle.
- Information about storage in one common storage facility: Do not store together with acids.
 Keep away from food, beverages and feed.
- · Further information about storage conditions: Keep receptacle tightly sealed.

*7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Ingredients with limit values that require monitoring at the workplace:

1310-73-2 sodium hydroxide

WEL Short-term value: 2 mg/m³

· DNELs

15763-76-	⋅5 sodiı	um p-cumenesulphonate
Oral	DNEL	3.8 mg/kg×d (consumer)
Dermal	DNEL	136.25 mg/kg×d (employee)
		68.1 mg/kg×d (consumer)
Inhalative	DNEL	26.9 mg/m3 (employee)
		6.6 mg/m3 (consumer)
1310-73-2	sodiu	m hydroxide
Inhalative	DNEL	1 mg/m3 (employee)
		1 mg/m3 (consumer)
		(Contd. on page



according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

KARCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd.	of page 4)
(00////0.	or page i)

· PNECs	
15763-76-5 sodi	um p-cumenesulphonate
PNEC	0.23 mg/l (freshwater)
	0.023 mg/l (marine water)
	100 mg/l (STP)
PNEC sediment	0.862 mg/kg (freshwater)
	0.086 mg/kg (marine water)
PNEC soil	0.037 mg/kg (soil)

[•] 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

Filter A/P2.

· Hand protection



Protective gloves.

- · Material of gloves Butyl rubber, BR
- Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
- * butyl rubber 0,7 mm, 480 min (EN 374)
- As protection from splashes gloves made of the following materials are suitable: * nitril rubber 0,4 mm, 30 min (EN 374)
- Eye/face protection



Tightly sealed goggles (EN 166)

• **Body protection:** Protective work clothing. Boots

(Contd. on page 6)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

Version number 9 (replaces version 8)

Revision: 21.10.2021

(Contd. of page 5)

Trade name: VehiclePro High-Pressure Wash RM 806

SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties [•] General Information · Physical state Fluid · Colour: Yellow · Odour: citrus-like · Odour threshold: Not determined. · Melting point/freezing point: -7.5 °C Boiling point or initial boiling point and boiling range 100 °C · Flammability Not applicable. · Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable · Auto-ignition temperature: not applicable · Decomposition temperature: Not determined. · pH at 20 °C 13.1 · pH-value 1 %: 11-12 · Viscosity: Kinematic viscosity Not determined. · dynamic at 20 °C: 6 mPas · Solubility · Water: Fully miscible · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined. · Density and/or relative density · Density at 20 °C: 1.134 g/cm³ Relative density Not determined. · Vapour density Not determined. · Relative gas density Not determined. Particle characteristics Not applicable. 9.2 Other information Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Solvent content: · Solids content: 27.0 % [·] Change in condition · Evaporation rate Not determined. Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void (Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

KARCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

	(Contd. of page 6)
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases	
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	May be corrosive to metals.
Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity corresponds to 10.3

[•] 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Strong exothermic reaction with acids Reacts with light alloys to form hydrogen Corrodes aluminium

• 10.4 Conditions to avoid No further relevant information available.

* 10.5 Incompatible materials: Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.

• **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

15763-76-5 sodium p-cumenesulphonate

Oral LD50 >5000 mg/kg (Rat) (OECD 401)

Dermal LD50 >2000 mg/kg (Rabbit)

78330-20-8 fatty alcohol ethoxylate

Oral ATE 500 mg/kg (Rat)

(Contd. on page 8)

— GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

KARCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 7)

69011-36-5 isotridecanolethoxylate + 8 EO

Oral ATE 500 mg/kg (Rat)

• Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• **STOT-single exposure** Based on available data, the classification criteria are not met.

• **STOT-repeated exposure** Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity	:
15763-76-5 sodiu	m p-cumenesulphonate
LC50/96 h (static)	>100 mg/l (Oncorhynchus mykiss)
EC50/48 h (static)	>100 mg/l (Daphnia magna)
EC50/96 h (static)	>100 mg/l (Pseudokirchneriella subcapitata)
1310-73-2 sodium	h hydroxide
LC50/96 h	125 mg/l (Gambusia affinis)
EC50/48 h	76 mg/l (Daphnia magna)
	40.4 mg/l (Ceriodaphnia dubia)
EC50/15 min	22 mg/l (Photobacterium phosphoreum)
78330-20-8 fatty a	licohol ethoxylate
LC50/96 h	>10-100 mg/l (Leuciscus idus)
EC50/48 h	>10-<100 mg/l (Aquatic invertebrates)
EC50/72 h >10-<100 mg/l (Aquatic plants)	
69011-36-5 isotric	decanolethoxylate + 8 EO
LC50/96 h	>1-10 mg/l (Leuciscus idus)
EC50/48 h >1-10 mg/l (Aquatic invertebrates)	
EC50/72 h >1-10 mg/l (Aquatic plants)	
NOEC	>1 mg/l /(21 d)

• **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 9)

GB -

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

KARCHER

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 8)

69011-36-5 isotridecanolethoxylate + 8 EO

OECD 301B >60 % (28 d) OECD 301E ≥90 % (28 d)

Degree of elimination:

- * **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- * 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

¹12.7 Other adverse effects

- [•] Additional ecological information:
- · COD-value: 230000 mg/l

· General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Direction on liqid waste.

The product does not contain organically bounded halogens (AOX-free).

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

[•] 13.1 Waste treatment methods

[•] Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

[·] European waste catalogue

20 01 29* detergents containing hazardous substances

(Contd. on page 10)



according to Regulation (EC) No 1907/2006, Article 31

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 9)

[·] Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

• Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information	
 14.1 UN number or ID number ADR, IMDG, IATA 	UN1824
 14.2 UN proper shipping name ADR IMDG, IATA 	1824 SODIUM HYDROXIDE SOLUTION SODIUM HYDROXIDE SOLUTION
[•] 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	8 (C5) Corrosive substances. 8
· IMDG, IATA	
Class	8 Corrosive substances.
·Label	8
· 14.4 Packing group · ADR, IMDG, IATA	III
 14.5 Environmental hazards: Marine pollutant: 	Νο
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Segregation Code 	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
	(Contd. on page 1



Printing date 03.05.2024



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
ΙΑΤΑ	
Remarks:	Product ist corrosive to aluminium

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- [•] National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- * 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. A product information sheet can be provided if requested.

· Relevant phrases

H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 12)

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.05.2024

Version number 9 (replaces version 8)

Revision: 21.10.2021

Trade name: VehiclePro High-Pressure Wash RM 806

(Contd. of page 11) H319 Causes serious eye irritation. **Contact: Regulatory Affairs** Tel.: +49-7195-14-0 productsafety.management.de@karcher.com Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (ÚK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 . * Data compared to the previous version altered. 0.011-350.0 RM806/14 2.457GB

