



K'ARCHER

makes a difference

Please contact us for more information:

Kärcher Philippines

Kärcher Center Manila
8006 ECH Plaza
Dr. A. Santos Ave., Brgy. BF Homes
Sucat, Paranaque City
1720 Philippines

P: +63 2 7 957 0626 / 907 8520
W: www.karcher.com.ph
E: info.ak-ph@ph.karcher.com



www.facebook.com/karcher.inc



[@karcher_philippines](https://www.instagram.com/karcher_philippines)



2022 PRODUCT RANGE

HOME & GARDEN



K'ARCHER

PRODUCT OVERVIEW 2022 | HOME & GARDEN

WET & DRY VACUUM CLEANERS



WD 1 Classic *KAP

Actual suction power* (Air watts)	160
Energy use (W)	1000
Container capacity (l)	15
Container material	Plastic
Power cable (m)	4
Standard accessory ID (mm)	35



WD 1 S

Actual suction power* (Air watts)	160
Energy use (W)	1000
Container capacity (l)	15
Container material	Stainless Steel
Power cable (m)	4
Standard accessory ID (mm)	35



WD 2 Cartridge Filter Kit *EU

Actual suction power* (Air watts)	180
Energy use (W)	1000
Container capacity (l)	12
Container material	Plastic
Power cable (m)	4
Standard accessory ID (mm)	35



WD 3 *EU

Actual suction power* (Air watts)	200
Energy use (W)	1000
Container capacity (l)	17
Container material	Plastic
Power cable (m)	4
Standard accessory ID (mm)	35



WD 3 Car *EU

Actual suction power* (Air watts)	200
Energy use (W)	1000
Container capacity (l)	17
Container material	Plastic
Power cable (m)	4
Standard accessory ID (mm)	35



WD 3 Premium *EU

Actual suction power* (Air watts)	200
Energy use (W)	1000
Container capacity (l)	17
Container material	Stainless Steel
Power cable (m)	4
Standard accessory ID (mm)	35



WD 4 *EU

Actual suction power* (Air watts)	200
Energy use (W)	1000
Container capacity (l)	20
Container material	Plastic
Power cable (m)	5
Standard accessory ID (mm)	35



WD 5 Premium *EU

Actual suction power* (Air watts)	240
Energy use (W)	1100
Container capacity (l)	25
Container material	Stainless Steel
Power cable (m)	5
Standard accessory ID (mm)	35

DRY VACUUM CLEANERS



VCH 2 *CN

Sound power level (dB(A))	75
Battery voltage (V)	7.2
Battery type	Lithium-ion battery
Runtime min. mode (min)	11
Battery charging time 100% (h)	3.5



VC 2 Premium *SEA

Rated input power (W)	1100
Operating radius (m)	7.5
Filter bag capacity (l)	2.8
Sound pressure level (dB(A))	78



VC 3 *ERP

Rated input power (W)	700
Operating radius (m)	7.5
Waste container capacity (l)	0.9
Sound power level (dB(A))	76



VC 3 Plus *KAP

Rated input power (W)	1000
Operating radius (m)	7.5
Waste container capacity (l)	0.9
Sound power level (dB(A))	78



VC 4 Battery

Rated input power (W)	200
Waste container capacity (l)	0.5
Sound pressure level (dB(A))	83
Operating Time (Full Charge)	13-40
Charging time (minutes)	180-240



VC 4i Cordless Plus *SEA

Sound power level (dB(A))	81
Cable length (m)	1.8
Battery voltage (V)	18
Battery type	Lithium-ion battery
Runtime min. mode (min)	60
Battery charging time 100% (h)	3.5



DS 6.000 Mediclean *SEA

Rated input power (W)	900
Water filter (l)	2
Operating radius (m)	11.2
Sound pressure level (dB(A))	66
Filter System	Multi-stage filter system



SE 4001 *EU

Air flow (l/s)	70
Vacuum (mbar/kPa)	210 / 21
Pump capacity (W)	40
Input power turbine/pump (W)	1400 / 40
Working width (mm)	230
Fresh/waste water tank (l)	4 / 4
Standard accessory ID (mm)	35

PRESSURE WASHERS



K 1 Horizontal *KAP

Pressure (bar) max.	100
Flow rate (l/h) 270 -	300
Inlet temperature (°C)	max. 40
Connected load (kW)	1.2
Power cable (m)	5



K 2 Horizontal *KAP

Pressure (bar) max.	110
Flow rate (l/h)	300 - 360
Inlet temperature (°C)	max. 40
Connected load (kW)	1.4
Weight without accessories (kg)	4.7



K 2 Compact *EU

Pressure (bar/MPa)	110
Flow rate (l/h)	360
Area performance (m²/h)	20
Inlet temperature (°C)	max. 40
Connected load (kW)	1.4



K 2 *EU

Pressure (bar/MPa)	110
Flow rate (l/h)	max. 360
Area performance (m²/h)	20
Inlet temperature (°C)	max. 40
Connected load (kW)	1.4



K 2.360

Pressure (bar/MPa)	120
Flow rate (l/h)	max. 360
Inlet temperature (°C)	max. 40
Connection load (kW)	1.4



K 2 Power VPS *KR

Pressure (bar/MPa)	100
Flow rate (l/h)	max. 360
Inlet temperature (°C)	max. 40
Power cable (m)	5



K 4 *KR

Pressure (bar/MPa)	130
Flow rate (l/h)	max. 420
Inlet temperature (°C)	max. 40
Connection load (kW)	1.8



K 5 Premium *KR

Pressure (bar/MPa)	145
Flow rate (l/h)	max. 500
Inlet temperature (°C)	max. 40
Connected load (kW)	2.1

STEAM CLEANER



SC 1 EasyFix Premium *EU

Area performance per tank filling (m²)	approx. 20
Heating output (W)	1200
Max. steam pressure (bar)	3
Cable length (m)	4
Heat-up time (min)	3
Boiler/tank capacity (l)	0.2



SC 2 Deluxe EasyFix *SEA

Area performance per tank filling (m²)	approx. 75
Heating output (W)	1500
Max. steam pressure (bar)	3.2
Cable length (m)	4
Heat-up time (min)	6.5
Boiler/tank capacity (l)	1



SC 2 Upright EasyFix *EU

Area performance per tank filling (m²) approx.	50
Heating output (W)	1600
Cable length (m)	5
Heat-up time (min)	0.5
Tank capacity (l)	0.4



SC 3 Premium EasyFix *EU

Area performance per tank filling (m²)	approx. 75
Heating output (W)	1900
Max. steam pressure (bar)	3.5
Cable length (m)	4
Heat-up time (min)	0.5
Boiler/tank capacity (l)	1



SV 7

Max. performance (W)	2200
Water capacity boiler (l)	0.45
Refill tank (l)	0.5
Max. steam pressure (bar)	1.2
Water filter (l)	210 / 21
Vacuum (mbar/kPa)	6
Cable length (m)	5
Heat-up time (min)	65
Steam flow rate (g/h)	Multi-stage
Filter system	filter system
Heating output (W)	1100
Permanent filling	1
Additional suction capacity (l)	0.6

Test certificate* Kills up to 99.999% of coronavirus* and 99.9% bacteria**