

## SICHERHEITSDATENBLATT

Gemäß der geänderten Fassung Verordnung (EG) Nr. 1907/2006 (REACH) Artikel 31 Anhang II.

### ABSCHNITT 1: Bezeichnung des Stoffes bzw. des Gemisches und des Unternehmens

#### 1.1 Produktidentifikator

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

#### 1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

**Identifizierte Verwendungen:** Schmierstoff

**Verwendungen, von denen abgeraten wird:** Keine Verwendungen, von denen abgeraten wird, identifiziert.

#### 1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

##### Hersteller / Lieferant

Fuchs Schmierstoffe GmbH  
Friesenheimer Str. 19  
68169 Mannheim

Telefon:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

##### Kontaktperson:

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telefon:

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-Mail:

produktsicherheit@fuchs-schmierstoffe.de

#### 1.4 Notrufnummer:

+49 621 3701-1333 / +49 621 3701-0 (Mo-Do 8-17, Fr 8-16)

### ABSCHNITT 2: Mögliche Gefahren

#### 2.1 Einstufung des Stoffs oder Gemischs

Das Produkt wurde gemäß der Verordnung (EG) Nr. 1272/2008 (CLP) nicht als gefährlich eingestuft, ist aber kennzeichnungspflichtig.

##### Gefahrenübersicht

**Physikalische Gefahren:** Es liegen keine Daten vor.

#### 2.2 Kennzeichnungselemente

EUH208: Enthält Ca Sulfonat, Calcium Sulfonat. Kann allergische Reaktionen hervorrufen.

EUH210: Sicherheitsdatenblatt auf Anfrage erhältlich.

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

**2.3 Sonstige Gefahren:** Bei Beachtung der beim Umgang mit Mineralölprodukten und Chemieprodukten üblichen Vorsichtsmaßnahmen sowie der Hinweise zur Handhabung (Pkt 7) und zur persönlichen Schutzausrüstung (Pkt 8) sind keine besonderen Gefahren bekannt. Produkt nicht unkontrolliert in die Umwelt gelangen lassen.

### ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

#### 3.2 Gemische

**Allgemeine Information:** Zubereitung aus hochraffinierten Mineralölen mit Additiven.

Chemische Bezeichnung	Identifikator	Konzentration *	REACH Registrierungs-Nr	Hinweise
Mineralöl	EINECS: 265-157-1	20,00 - <50,00%	01-2119484627-25	
Polyolefinpolyaminsuccinimid	Polymer	1,00 - <5,00%		
Ca Sulfonat	Polymer	1,00 - <5,00%		
ZnDTP	EINECS: 272-238-5	1,00 - <2,50%	01-2119657973-23	

\* Alle Konzentrationen sind als Gewichtsprozent angegeben, wenn der Inhaltstoff kein Gas ist. Gaskonzentrationen werden in Volumenprozent angegeben. PBT: Persistenter, bioakkumulierbarer und toxischer Stoff. vPvB: Sehr persistente und sehr bioakkumulierbare Substanz.

#### Klassifizierung

Chemische Bezeichnung	Identifikator	Klassifizierung	
Mineralöl	EINECS: 265-157-1	CLP:	Asp. Tox. 1;H304
Polyolefinpolyaminsuccinimid	Polymer	CLP:	Aquatic Chronic 4;H413
Ca Sulfonat	Polymer	CLP:	Aquatic Chronic 4;H413
ZnDTP	EINECS: 272-238-5	CLP:	Eye Dam. 1;H318, Aquatic Chronic 2;H411

CLP: Verordnung Nr. 1272/2008.

Der Wortlaut der angeführten Gefahrenhinweise ist dem Abschnitt 16 zu entnehmen.

Die hochraffinierten Mineralöle und Petroleumdestillate in unserem Produkt enthalten nach IP 346 einen DMSO-Extrakt von weniger als 3% (w/w) und sind nach Nota L, Anhang VI der Verordnung EU 1272/2008 nicht als krebserzeugend eingestuft.

### ABSCHNITT 4: Erste-Hilfe-Maßnahmen

**Allgemeines:** Mit Produkt verunreinigte Kleidungsstücke unverzüglich entfernen.

#### 4.1 Beschreibung der Erste-Hilfe-Maßnahmen

**Einatmen:** Frischluftzufuhr, bei Beschwerden Arzt aufsuchen.

**Augenkontakt:** Augen sofort mit viel Wasser spülen, Augenlider dabei hochziehen.

**Hautkontakt:** Mit Wasser und Seife waschen.

**Verschlucken:** Mund gründlich spülen.

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

**4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen:** Kann Haut- und Augenreizungen bewirken.

**4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung** Ärztliche Hilfe hinzuziehen, wenn Symptome auftreten.

#### ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

##### 5.1 Löschmittel

**Geeignete Löschmittel:** CO<sub>2</sub>, Löschpulver oder nebelartiger Wassersprühstrahl. Größeren Brand mit alkoholbeständigem Schaum oder Wassersprühstrahl mit geeignetem Tensidzusatz bekämpfen.

**Ungeeignete Löschmittel:** Wasser im Vollstrahl.

**5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren:** Im Brandfall können sich gesundheitsschädliche Gase entwickeln.

##### 5.3 Hinweise für die Brandbekämpfung

**Hinweise zur Brandbekämpfung:** Behälter aus dem Brandbereich entfernen, soweit dies ohne Gefahr möglich ist. Brandrückstände und kontaminiertes Löschwasser müssen entsprechend den behördlichen Vorschriften entsorgt werden. Kontaminiertes Löschwasser getrennt sammeln, darf nicht in die Kanalisation gelangen.

**Besondere Schutzausrüstungen für die Brandbekämpfung:** Im Brandfall umluftunabhängiges Atemschutzgerät und komplette Schutzausrüstung tragen.

#### ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

**6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren:** Vorsicht! Im Fall eines Austretens des Materials können Fußböden und Oberflächen rutschig werden.

**6.2 Umweltschutzmaßnahmen:** Flächenmäßige Ausdehnung verhindern (z.B. durch Eindämmen oder Ölsperren). Freisetzung in die Umwelt vermeiden. Beim Austritt großer Mengen muss immer der Umweltschutzbeauftragte benachrichtigt werden. Weiteres Auslaufen oder Verschütten vermeiden, wenn dies ohne Gefahr möglich ist. Nicht in die Kanalisation/Oberflächenwasser/Grundwasser gelangen lassen.

**6.3 Methoden und Material für Rückhaltung und Reinigung:** Mit flüssigkeitsbindendem Material wie Sand, Kieselgur, Säurebinder, Universalbinder oder Sägemehl aufnehmen. Das aufgenommene Material vorschriftsmäßig entsorgen. Materialfluss stoppen, falls ohne Gefahr möglich

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

**6.4 Verweis auf andere Abschnitte:** Für persönliche Schutzausrüstung siehe Abschnitt 8 des SDB. Informationen zur sicheren Handhabung siehe Abschnitt 7. Informationen zur Entsorgung siehe Abschnitt 13.

#### ABSCHNITT 7: Handhabung und Lagerung:

- 7.1 Schutzmaßnahmen zur sicheren Handhabung:** Aerosolbildung vermeiden. Bei der Arbeit nicht essen, trinken oder rauchen. Die beim Umgang mit Mineralölprodukten bzw. Chemieprodukten üblichen Vorsichtsmaßnahmen sind zu beachten. Anerkannte industrielle Hygienemaßnahmen beachten. Für ausreichende Lüftung sorgen.
- 7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten:** Die Vorschriften des WHG, der Landeswassergesetze und der Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (VAwS in der jeweiligen Länderfassung) sind zu beachten. Nicht auf Temperaturen in der Nähe des Flammpunktes erwärmen.
- 7.3 Spezifische Endanwendungen:** Es liegen keine Daten vor.
- Lagerungshinweise:** 10, Brennbare Flüssigkeiten

#### ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

##### 8.1 Zu überwachende Parameter Grenzwerte Berufsbedingter Exposition

Für keinen der Bestandteile gelten Arbeitsplatzgrenzwerte.

##### 8.2 Begrenzung und Überwachung der Exposition

**Geeignete technische Steuerungseinrichtungen:** Für ausreichende Lüftung sorgen. Lüftungsgrad muss an die Bedingungen angepasst werden. Gegebenenfalls Prozesskammern, örtliche Abluftsysteme oder andere technische Schutzmaßnahmen zur Kontrolle der Konzentrationen in der Luft einsetzen, um diese unterhalb der empfohlenen Belastungsgrenzen zu halten. Wenn keine Expositionsgrenzen festgesetzt wurden, die Konzentrationen in der Luft auf einem akzeptierbaren Niveau halten.

##### Individuelle Schutzmaßnahmen, zum Beispiel persönliche Schutzausrüstung

**Allgemeine Information:** Vor den Pausen und bei Arbeitsende Hände waschen. Vorgeschriebene persönliche Schutzausrüstung verwenden. Persönliche Schutzausrüstung muss in Übereinstimmung mit den geltenden CEN-Normen und nach Absprache mit dem Lieferanten für persönliche Schutzausrüstung gewählt werden. Die üblichen Vorsichtsmaßnahmen beim Umgang mit Mineralölprodukten oder Chemikalien sind in jedem Fall zubeachten.

**Augen-/Gesichtsschutz:** Beim Umfüllen Schutzbrille (EN 166) empfehlenswert.

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

**Hautschutz**

**Handschutz:**

Material: Nitrilbutylkautschuk (NBR).  
Mind. Durchbruchzeit:  $\geq 480$  min  
Empfohlene Materialstärke:  $\geq 0,38$  mm

Langandauernden oder wiederholten Hautkontakt vermeiden. Geeignete Schutzhandschuhe werden vom Handschuhlieferanten empfohlen. Vorbeugender Hautschutz durch Hautschutzsalbe. Schutzhandschuhe, wo sicherheitstechnisch erlaubt. Die genaue Durchbruchzeit ist beim Schutzhandschuhhersteller zu erfahren und einzuhalten, da sie nicht nur vom Handschuhmaterial, sondern auch von arbeitsplatzspezifischen Faktoren abhängig ist.

**Andere:**

Keine produktgetränkten Putzlappen in den Hosentaschen mitführen. Bei der Arbeit geeignete Schutzkleidung tragen.

**Atemschutz:**

Für gute Belüftung/Absaugung am Arbeitsplatz sorgen. Einatmen von Dampf/ Aerosol vermeiden.

**Thermische Gefahren:**

Nicht bekannt.

**Hygienemaßnahmen:**

Immer gute persönliche Hygiene einhalten, z.B. Waschen nach der Handhabung des Materials und vor dem Essen, Trinken und/oder Rauchen. Arbeitskleidung regelmäßig waschen, um Kontaminationen zu entfernen. Kontaminierte Fußbekleidung, die nicht gesäubert werden kann, entsorgen.

**Umweltschutzmaßnahmen:** Es liegen keine Daten vor.

**ABSCHNITT 9: Physikalische und chemische Eigenschaften**

**9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften**

**Aussehen**

<b>Aggregatzustand:</b>	flüssig
<b>Form:</b>	flüssig
<b>Farbe:</b>	Gelb
<b>Geruch:</b>	Charakteristisch
<b>Geruchsschwelle:</b>	Auf Gemische nicht anwendbar
<b>pH-Wert:</b>	Nicht anwendbar
<b>Erstarrungspunkt:</b>	Auf Gemische nicht anwendbar
<b>Siedepunkt:</b>	Es liegen keine Daten vor.
<b>Flammpunkt:</b>	230 °C
<b>Verdampfungsgeschwindigkeit:</b>	Auf Gemische nicht anwendbar
<b>Entzündbarkeit (fest, gasförmig):</b>	Wert für Einstufung nicht relevant
<b>Explosionsgrenze - obere (%)–:</b>	Auf Gemische nicht anwendbar
<b>Explosionsgrenze - untere (%)–:</b>	Auf Gemische nicht anwendbar
<b>Dampfdruck:</b>	Auf Gemische nicht anwendbar
<b>Dampfdichte (Luft=1):</b>	Auf Gemische nicht anwendbar
<b>Dichte:</b>	0,87 g/cm <sup>3</sup> (15 °C)
<b>Löslichkeit(en)</b>	
<b>Löslichkeit in Wasser:</b>	Nicht wasserlöslich

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

<b>Löslichkeit (andere):</b>	Es liegen keine Daten vor.
<b>Verteilungskoeffizient (n-Octanol/Wasser) - log Pow:</b>	Auf Gemische nicht anwendbar
<b>Selbstentzündungstemperatur:</b>	Wert für Einstufung nicht relevant
<b>Zersetzungstemperatur:</b>	Wert für Einstufung nicht relevant
<b>Viskosität, kinematisch:</b>	96 mm <sup>2</sup> /s (40 °C)
<b>Explosive Eigenschaften:</b>	Wert für Einstufung nicht relevant
<b>Oxidierende Eigenschaften:</b>	Wert für Einstufung nicht relevant
<b>9.2 Sonstige Angaben</b>	Es liegen keine Daten vor.

#### ABSCHNITT 10: Stabilität und Reaktivität

<b>10.1 Reaktivität:</b>	Bei bestimmungsgemäßer Verwendung stabil.
<b>10.2 Chemische Stabilität:</b>	Bei bestimmungsgemäßer Verwendung stabil.
<b>10.3 Möglichkeit Gefährlicher Reaktionen:</b>	Bei bestimmungsgemäßer Verwendung stabil.
<b>10.4 Zu Vermeidende Bedingungen:</b>	Bei bestimmungsgemäßer Verwendung stabil.
<b>10.5 Unverträgliche Materialien:</b>	Stark oxidierende Stoffe. Starke Säuren. Starke Basen.
<b>10.6 Gefährliche Zersetzungsprodukte:</b>	Bei thermischem Zerfall oder Verbrennung können Kohlenstoffoxide sowie andere giftige Gase und Dämpfe freigesetzt werden.

#### ABSCHNITT 11: Toxikologische Angaben

##### 11.1 Angaben zu toxikologischen Wirkungen

###### Akute Toxizität

###### Verschlucken

###### Produkt:

Auf Basis der vorliegenden Daten nicht eingestuft für akute Toxizität.

###### Spezifische(r) Stoff(e)

Mineralöl

LD 50 (Ratte): > 5.000 mg/kg

###### Hautkontakt

###### Produkt:

Auf Basis der vorliegenden Daten nicht eingestuft für akute Toxizität.

###### Spezifische(r) Stoff(e)

Mineralöl

LD 50 (Kaninchen): > 2.001 mg/kg

###### Einatmen

###### Produkt:

Auf Basis der vorliegenden Daten nicht eingestuft für akute Toxizität.

###### Spezifische(r) Stoff(e)

Mineralöl

LC 50 (Ratte, 4 h): > 2.500 mg/l  
Dampf

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

---

**Ätz/Reizwirkung auf die Haut:**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Schwere Augenschädigung/-Reizung:**

**Produkt:** Die Einstufung dieses Produkts beruht vollständig oder teilweise auf Versuchsdaten.

**Atemwegs- oder Hautsensibilisierung:**

**Produkt:** Sensibilisierung der Haut: Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.  
Atemwegssensibilisator: Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Keimzellmutagenität**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Karzinogenität**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Reproduktionstoxizität**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Spezifische Zielorgan-Toxizität - bei Einmaliger Exposition**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Spezifische Zielorgan-Toxizität - bei Wiederholter Exposition**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Aspirationsgefahr**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Andere Schädliche Wirkungen:**

Es liegen keine Daten vor.

**ABSCHNITT 12: Umweltbezogene Angaben**

**12.1 Toxizität**

**Akute Toxizität**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**Chronische Toxizität**

**Produkt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

**12.2 Persistenz und Abbaubarkeit**

**Biologischer Abbau**

**Produkt:** Auf Gemische nicht anwendbar

**12.3 Bioakkumulationspotenzial**

**Produkt:** Auf Gemische nicht anwendbar

**Produktname:** TITAN UNIMAX PLUS MC 10W-40

---

**12.4 Mobilität im Boden:**

**Produkt:** Auf Gemische nicht anwendbar

**12.5 Ergebnisse der PBT- und vPvB-Beurteilung:**

Das Produkt enthält keine Stoffe, die die PBT/vPvB Kriterien erfüllen.

**12.6 Andere Schädliche Wirkungen:**

Es liegen keine Daten vor.

**Wassergefährdungs-  
klasse (WGK):**

WGK 2: wassergefährdend.

**ABSCHNITT 13: Hinweise zur Entsorgung**

**13.1 Verfahren der Abfallbehandlung**

**Allgemeine Information:**

Entsorgung von Abfall und Rückständen in Übereinstimmung mit den jeweiligen lokalen Bestimmungen.

**Entsorgungsmethoden:**

Nicht in die Kanalisation gelangen lassen; Abfälle und Behälter müssen in gesicherter Weise beseitigt werden. Bei Lagerung gebrauchter Produkte Vermischungsverbot beachten.

**Europäische Abfallcodes**

13 02 05\*: nichtchlorierte Maschinen-, Getriebe- und Schmieröle auf Mineralölbasis

**ABSCHNITT 14: Angaben zum Transport**

**ADR/RID**

- 14.1 UN-Nummer: —
- 14.2 Ordnungsgemäße UN-Versandbezeichnung: —
- 14.3 Transportgefahrenklassen
  - Klasse: Kein Gefahrgut
  - Etikett(en): —
  - Gefahr Nr. (ADR): —
  - Tunnelbeschränkungscode: —
- 14.4 Verpackungsgruppe: —
- 14.5 Umweltgefahren: —
- 14.6 Besondere Vorsichtsmaßnahmen für den Verwender: —



**Produktname:** TITAN UNIMAX PLUS MC 10W-40

---

**ADN**

- 14.1 UN-Nummer: –
- 14.2 Ordnungsgemäße UN-Versandbezeichnung: –
- 14.3 Transportgefahrenklassen
  - Klasse: Kein Gefahrgut
  - Etikett(en): –
- 14.3 Verpackungsgruppe: –
- 14.5 Umweltgefahren: –
- 14.6 Besondere Vorsichtsmaßnahmen für den Verwender: –

**IMDG**

- 14.1 UN-Nummer: –
- 14.2 Ordnungsgemäße UN-Versandbezeichnung: –
- 14.3 Transportgefahrenklassen
  - Klasse: Kein Gefahrgut
  - Etikett(en): –
  - EmS-Nr.: –
- 14.3 Verpackungsgruppe: –
- 14.5 Umweltgefahren: –
- 14.6 Besondere Vorsichtsmaßnahmen für den Verwender: –

**IATA**

- 14.1 UN-Nummer: –
- 14.2 Ordnungsgemäße Versandbezeichnung: –
- 14.3 Transportgefahrenklassen:
  - Klasse: Kein Gefahrgut
  - Etikett(en): –
- 14.4 Verpackungsgruppe: –
- 14.5 Umweltgefahren: –
- 14.6 Besondere Vorsichtsmaßnahmen für den Verwender: –

**14.7 Massengutbeförderung gemäß Anhang II des MARPOL-Übereinkommens und gemäß IBC-Code:**  
Nicht anwendbar.

**ABSCHNITT 15: Rechtsvorschriften**

**15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch:**

**EU-Verordnungen**

**Verordnung (EG) Nr. 2037/2000 über Stoffe, die zum Abbau der Ozonschicht führen:** keine



**Produktname:** TITAN UNIMAX PLUS MC 10W-40

**VERORDNUNG (EG) Nr. 850/2004 über persistente organische Schadstoffe:** keine

**Nationale Verordnungen**

**Wassergefährdungs-  
klasse (WGK):** WGK 2: wassergefährdend.

**15.2 Stoffsicherheits-  
beurteilung:** Es wurde keine Stoffsicherheitsbeurteilung durchgeführt.

**ABSCHNITT 16: Sonstige Angaben**

**Informationen zur  
Überarbeitung:** Änderungen sind seitlich mit einem Doppelstrich markiert.

**Wortlaut der H-Sätze in Kapitel 2 und 3**

H304 Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.  
 H318 Verursacht schwere Augenschäden.  
 H411 Giftig für Wasserorganismen, mit langfristiger Wirkung.  
 H413 Kann für Wasserorganismen schädlich sein, mit langfristiger Wirkung.

**Sonstige Angaben:** Die Klassifizierung entspricht den aktuellen EG-Listen, ist jedoch ergänzt durch Angaben aus der Fachliteratur und durch Firmenangaben. Sie ergibt sich aus der Anwendung der sog. Konventionellen Methode nach Verordnung (EU) 1272/2008 (CLP).

**Überarbeitet Am:** 03.07.2017  
**Haftungsausschluss:** Die vorstehenden Angaben im Sicherheitsdatenblatt entsprechen nach bestem Wissen dem derzeitigen Stand unserer Kenntnisse und Erfahrungen und dienen nur dazu, das Produkt bei Umgang, Transport und Entsorgung sicherheitstechnisch zu beschreiben. Die Angaben stellen in keiner Weise eine (technische) Beschreibung der Beschaffenheit der Ware (Produktspezifikation) dar. Eine Eignung des Produktes für einen konkreten Einsatzzweck kann aus unseren Angaben im Sicherheitsdatenblatt nicht abgeleitet werden. Änderungen an diesem Dokument sind nicht zulässig. Die Angaben sind nicht übertragbar auf andere Produkte. Soweit das Produkt mit anderen Materialien vermengt, vermischt oder verarbeitet wird, oder einer Bearbeitung unterzogen wird, können die Angaben in diesem Sicherheitsdatenblatt nicht auf das gefertigte neue Material übertragen werden. Es liegt in der Verantwortlichkeit des Empfängers unseres Produktes, bei seinen Tätigkeiten die geltenden Gesetze auf Bundes-, Landes- und lokaler Ebene zu befolgen. Bitte nehmen Sie mit uns Kontakt auf, wenn Sie aktuelle Sicherheitsdatenblätter benötigen.

Dieses Datenblatt ist ein Sicherheitsdatenblatt nach §5 GefStoffV. Es wurde elektronisch erstellt und trägt keine Unterschrift.

## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name:** TITAN UNIMAX PLUS MC 10W-40

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricant

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer / Supplier**

Fuchs Schmierstoffe GmbH  
Friesenheimer Str. 19  
68169 Mannheim

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

**Contact Person:**

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telephone:

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-mail:

produktsicherheit@fuchs-schmierstoffe.de

#### 1.4 Emergency telephone number:

+49 621 3701-1333 / +49 621 3701-0 (Mo-Do 8-17, Fr 8-16)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation (EU) 1272/2008 (CLP).

**Hazard summary**

**Physical Hazards:**

No data available.

#### 2.2 Label Elements

EUH208: Contains Ca Sulfonate, Calcium Sulfonate. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

#### 2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**General information:** Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
mineral oil	EINECS: 265-157-1	20,00 - <50,00%	01-2119484627-25	
Polyolefin polyamine succinimide	Polymer	1,00 - <5,00%		
Ca Sulfonate	Polymer	1,00 - <5,00%		
ZnDTP	EINECS: 272-238-5	1,00 - <2,50%	01-2119657973-23	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. PBT: persistent, bioaccumulative and toxic substance.  
vPvB: very persistent and very bioaccumulative substance.

**Classification**

Chemical name	Identifier	Classification
mineral oil	EINECS: 265-157-1	CLP: Asp. Tox. 1;H304
Polyolefin polyamine succinimide	Polymer	CLP: Aquatic Chronic 4;H413
Ca Sulfonate	Polymer	CLP: Aquatic Chronic 4;H413
ZnDTP	EINECS: 272-238-5	CLP: Eye Dam. 1;H318, Aquatic Chronic 2;H411

CLP: Regulation No. 1272/2008.

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

**SECTION 4: First aid measures**

**General:** Instantly remove any clothing soiled by the product.

**4.1 Description of first aid measures**

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause skin and eye irritation.

**4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:** Water with a full water jet.

### 5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

### 5.3 Advice for firefighters

**Special fire fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** In case of spills, beware of slippery floors and surfaces.

**6.2 Environmental Precautions:** Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

**6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

## SECTION 7: Handling and storage:

**7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

**7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**7.3 Specific end use(s):** No data available.

**Storage Class:** 10, Combustible liquids

## SECTION 8: Exposure controls/personal protection

### 8.1 Control Parameters

#### Occupational Exposure Limits

None of the components have assigned exposure limits.

### 8.2 Exposure controls

#### Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

##### General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

##### Eye/face protection:

Safety glasses (EN 166) recommended during refilling.

##### Skin protection

##### Hand Protection:

Material: Nitrile butyl rubber (NBR).  
Min. Breakthrough time:  $\geq 480$  min  
Recommended thickness of the material:  $\geq 0,38$  mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

##### Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

##### Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

##### Thermal hazards:

Not known.

##### Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

##### Environmental Controls:

No data available.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	liquid
<b>Color:</b>	Yellow
<b>Odor:</b>	Characteristic
<b>Odor Threshold:</b>	Not applicable for mixtures
<b>pH:</b>	not applicable
<b>Freezing point:</b>	Not applicable for mixtures
<b>Boiling Point:</b>	No data available.
<b>Flash Point:</b>	230 °C
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	Value not relevant for classification
<b>Flammability Limit - Upper (%)-:</b>	Not applicable for mixtures
<b>Flammability Limit - Lower (%)-:</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Vapor density (air=1):</b>	Not applicable for mixtures
<b>Density:</b>	0,87 g/cm <sup>3</sup> (15 °C)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Autoignition Temperature:</b>	Value not relevant for classification
<b>Decomposition Temperature:</b>	Value not relevant for classification
<b>Kinematic viscosity:</b>	96 mm <sup>2</sup> /s (40 °C)
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification
<b>9.2 Other information</b>	No data available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

**Oral**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

mineral oil

LD 50 (Rat): > 5.000 mg/kg

**Dermal**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

mineral oil

LD 50 (Rabbit): > 2.001 mg/kg

**Inhalation**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

mineral oil

LC 50 (Rat, 4 h): > 2.500 mg/l  
Vapour

**Skin Corrosion/Irritation:**

**Product:**

Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation:**

**Product:**

The classification of this product is based all or in part on test data.

**Respiratory or Skin Sensitization:**

**Product:**

Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity**

**Product:**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

**Product:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:**

Based on available data, the classification criteria are not met.



**Product name:** TITAN UNIMAX PLUS MC 10W-40

**Aspiration Hazard**

**Product:** Based on available data, the classification criteria are not met.

**Other adverse effects:** No data available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Chronic ToxicityProduct:** Based on available data, the classification criteria are not met.

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Other adverse effects:**

No data available.

**Water Hazard Class (WGK):**

WGK 2: water-endangering.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**General information:**

Dispose in accordance with all applicable regulations.

**Disposal methods:**

Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

**European Waste Codes**

13 02 05\*: mineral-based non-chlorinated engine, gear and lubricating oils

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 14: Transport information**

**ADR/RID**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - Hazard No. (ADR): —
  - Tunnel restriction code: —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**ADN**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IMDG**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - EmS No.: —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IATA**

- 14.1 UN Number: —
- 14.2 Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** not applicable.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**Product name:** TITAN UNIMAX PLUS MC 10W-40

---

**Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer:** none

**Regulation (EC) No. 850/2004 on persistent organic pollutants:** none

**15.2 Chemical safety assessment:**

No Chemical Safety Assessment has been carried out.

<b>SECTION 16: Other information</b>
--------------------------------------

**Revision Information:**

Vertical lines in the margin indicate an amendment.

**Wording of the H-statements in section 2 and 3**

H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Other information:**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies. The classification results from the Conventional Method mentioned in regulation EU 1272/2008 (CLP).

**Revision Date:**

03.07.2017

**Disclaimer:**

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.

## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name:** TITAN UNIMAX PLUS MC 10W-40

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricant

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer / Supplier**

Fuchs Schmierstoffe GmbH  
Friesenheimer Str. 19  
68169 Mannheim

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

**Contact Person:**

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telephone:

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-mail:

produktsicherheit@fuchs-schmierstoffe.de

#### 1.4 Emergency telephone number:

+49 621 3701-1333 / +49 621 3701-0 (Mo-Do 8-17, Fr 8-16)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation (EU) 1272/2008 (CLP).

**Hazard summary**

**Physical Hazards:**

No data available.

#### 2.2 Label Elements

EUH208: Contains Ca Sulfonate, Calcium Sulfonate. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

#### 2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**General information:** Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
mineral oil	EINECS: 265-157-1	20,00 - <50,00%	01-2119484627-25	
Polyolefin polyamine succinimide	Polymer	1,00 - <5,00%		
Ca Sulfonate	Polymer	1,00 - <5,00%		
ZnDTP	EINECS: 272-238-5	1,00 - <2,50%	01-2119657973-23	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. PBT: persistent, bioaccumulative and toxic substance.  
vPvB: very persistent and very bioaccumulative substance.

**Classification**

Chemical name	Identifier	Classification
mineral oil	EINECS: 265-157-1	CLP: Asp. Tox. 1;H304
Polyolefin polyamine succinimide	Polymer	CLP: Aquatic Chronic 4;H413
Ca Sulfonate	Polymer	CLP: Aquatic Chronic 4;H413
ZnDTP	EINECS: 272-238-5	CLP: Eye Dam. 1;H318, Aquatic Chronic 2;H411

CLP: Regulation No. 1272/2008.

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

**SECTION 4: First aid measures**

**General:** Instantly remove any clothing soiled by the product.

**4.1 Description of first aid measures**

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause skin and eye irritation.

**4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:** Water with a full water jet.

### 5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

### 5.3 Advice for firefighters

**Special fire fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** In case of spills, beware of slippery floors and surfaces.

**6.2 Environmental Precautions:** Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

**6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

## SECTION 7: Handling and storage:

**7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

**7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

---

**7.3 Specific end use(s):** No data available.

**Storage Class:** 10, Combustible liquids

## SECTION 8: Exposure controls/personal protection

### 8.1 Control Parameters

#### Occupational Exposure Limits

None of the components have assigned exposure limits.

### 8.2 Exposure controls

#### Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

##### General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

##### Eye/face protection:

Safety glasses (EN 166) recommended during refilling.

##### Skin protection

##### Hand Protection:

Material: Nitrile butyl rubber (NBR).  
Min. Breakthrough time:  $\geq 480$  min  
Recommended thickness of the material:  $\geq 0,38$  mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

##### Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

##### Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

##### Thermal hazards:

Not known.

##### Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

##### Environmental Controls:

No data available.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	liquid
<b>Color:</b>	Yellow
<b>Odor:</b>	Characteristic
<b>Odor Threshold:</b>	Not applicable for mixtures
<b>pH:</b>	not applicable
<b>Freezing point:</b>	Not applicable for mixtures
<b>Boiling Point:</b>	No data available.
<b>Flash Point:</b>	230 °C
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	Value not relevant for classification
<b>Flammability Limit - Upper (%)-:</b>	Not applicable for mixtures
<b>Flammability Limit - Lower (%)-:</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Vapor density (air=1):</b>	Not applicable for mixtures
<b>Density:</b>	0,87 g/cm <sup>3</sup> (15 °C)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Autoignition Temperature:</b>	Value not relevant for classification
<b>Decomposition Temperature:</b>	Value not relevant for classification
<b>Kinematic viscosity:</b>	96 mm <sup>2</sup> /s (40 °C)
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification
<b>9.2 Other information</b>	No data available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

**Oral**

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s)**  
mineral oil LD 50 (Rat): > 5.000 mg/kg

**Dermal**

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s)**  
mineral oil LD 50 (Rabbit): > 2.001 mg/kg

**Inhalation**

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s)**  
mineral oil LC 50 (Rat, 4 h): > 2.500 mg/l  
Vapour

**Skin Corrosion/Irritation:**

**Product:** Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation:**

**Product:** The classification of this product is based all or in part on test data.

**Respiratory or Skin Sensitization:**

**Product:** Skin sensitizer: Based on available data, the classification criteria are not met.  
Respiratory sensitizer: Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity**

**Product:** Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:** Based on available data, the classification criteria are not met.

**Reproductive toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**Aspiration Hazard**

**Product:** Based on available data, the classification criteria are not met.

**Other adverse effects:** No data available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Chronic ToxicityProduct:** Based on available data, the classification criteria are not met.

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Other adverse effects:**

No data available.

**Water Hazard Class (WGK):**

WGK 2: water-endangering.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**General information:**

Dispose in accordance with all applicable regulations.

**Disposal methods:**

Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

**European Waste Codes**

13 02 05\*: mineral-based non-chlorinated engine, gear and lubricating oils

**Product name:** TITAN UNIMAX PLUS MC 10W-40

**SECTION 14: Transport information**

**ADR/RID**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - Hazard No. (ADR): —
  - Tunnel restriction code: —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**ADN**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IMDG**

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - EmS No.: —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IATA**

- 14.1 UN Number: —
- 14.2 Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** not applicable.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**Product name:** TITAN UNIMAX PLUS MC 10W-40

---

**Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer:** none

**Regulation (EC) No. 850/2004 on persistent organic pollutants:** none

**15.2 Chemical safety assessment:**

No Chemical Safety Assessment has been carried out.

<b>SECTION 16: Other information</b>
--------------------------------------

**Revision Information:**

Vertical lines in the margin indicate an amendment.

**Wording of the H-statements in section 2 and 3**

H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Other information:**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies. The classification results from the Conventional Method mentioned in regulation EU 1272/2008 (CLP).

**Revision Date:**

03.07.2017

**Disclaimer:**

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.