

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 5/4/2022 Version: 1.0

1.1. Identification			
Product form	: Mixture		
Product code	: 1977HOT		
.2. Recommended use and restrictions or	i use		
o additional information available			
I.3. Supplier			
ARCHER NORTH AMERICA			
398 N Karcher Way			
Aurora, 80019			
Jnited States T 303-738-2400			
nfo@karcherna.com			
1.4. Emergency telephone number			
mergency number	: 800-535-505	3	
	For Chemica	I Emergency Ca	ll INFOTRAC 24hr/day 7days/week
		and Canada: 1-8	
	Outside USA (collect calls		11-1-352-323-3500
	(concor cane		
SECTION 2: Hazard(s) identification			
.1. Classification of the substance or mixe			
	ure		
GHS US classification		11007	
Flammable liquids Category 4 Acute toxicity (inhalation:dust,mist) Category 4		H227 H332	Combustible liquid Harmful if inhaled
Skin corrosion/irritation Category 1		H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1		H318	Causes serious eye damage
Hazardous to the aquatic environment - Acute Haza	rd Category 3	H402	Harmful to aquatic life
Full text of H statements : see section 16			
2.2. GHS Label elements, including precau	tionary statem	ents	
GHS US labeling			
Hazard pictograms (GHS US)			
Signal word (GHS US)	: Danger	×	
Hererd statements (CHE HE)	· 1007 Camb	and the transfer	

Precautionary statements (GHS US)

Hazard statements (GHS US)

H318 - Causes serious eye damage

H314 - Causes severe skin burns and eye damage

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

: H227 - Combustible liquid

H332 - Harmful if inhaled H402 - Harmful to aquatic life

smoking.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forerms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact
lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor
P312 - Call a poison center/doctor if you feel unwell
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in
accordance with local regulations

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	30 – 50
BUTHOXYETHANOL	CAS-No.: 111-76-2	30 – 50
ALKYL (C10-C16) BENZENESULFONIC ACID	CAS-No.: 68584-22-5	19.8 – 22
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5
SULFURIC ACID	CAS-No.: 7664-93-9	0.22 – 0.66

: None under normal conditions.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	 Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and e	effects (acute and delayed)
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Dry powder. Foam. Carbon dioxide.	
5.2. Specific hazards arising from the chemical		
Fire hazard Hazardous decomposition products in case of fire	Combustible liquid.Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
Firefighting instructions Protection during firefighting	 Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Do not handle until all safety precautions have been read and understood.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		

 6.3. Methods and material for containment and cleaning up

 For containment
 : Collect spillage.

 Methods for cleaning up
 : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

 Other information
 : Dispose of materials or solid residues at an authorized site.

 6.4. Reference to other sections

For further information refer to section 13.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	ator 20, 2012 / Nuies and Negulations	
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed Precautions for safe handling Hygiene measures	 Not expected to present a significant hazard under anticipated conditions of normal use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. 	
	Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures Storage conditions	Comply with applicable regulations.Store in a well-ventilated place. Keep cool. Store locked up.	
SECTION 8: Exposure controls/persona	al protection	
8.1. Control parameters		
CARBOCHLOR LIQUID ADDITIVE		
No additional information available		
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
No additional information available		
BUTHOXYETHANOL (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH OEL TWA [ppm]	20 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI	
Regulatory reference	ACGIH 2019	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL (TWA) [1]	240 mg/m ³	
OSHA PEL (TWA) [2]	50 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
ALKYL (C10-C16) BENZENESULFONIC AC	D (68584-22-5)	
No additional information available		
SULFURIC ACID (7664-93-9)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.2 mg/m ³ (Thoracic fraction)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM XYLENE SULFONATE (1300-72-7)		
No additional information available		
8.2. Appropriate engineering controls		
Appropriate engineering controls	: Ensure good ventilation of the work station.	
Environmental exposure controls	: Avoid release to the environment.	
8.3. Individual protection measures/Persor	al protective equipment	
o.o. marviada protection measures/r ersor		
Hand protection:		
Protective gloves		
Eye protection:		
Safety glasses		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
Wear respiratory protection.		
Personal protective equipment symbol(s):		



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical prop
--

Physical state	: Liquid
Appearance	: Liquid.
Color	: Amber
Odor	: Characteristic odour
Odor threshold	: No data available
рН	: 0.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties

: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (dermal) :	Not classified Not classified Harmful if inhaled.	
CARBOCHLOR LIQUID ADDITIVE		
ATE US (dust, mist)	4.702 mg/l/4h	
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
LD50 oral rat	> 1000 mg/kg (Rat, Oral)	
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
ALKYL (C10-C16) BENZENESULFONIC ACID) (68584-22-5)
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	> 1.9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
SULFURIC ACID (7664-93-9)	
LD50 oral rat	2140 mg/kg body weight (Rat, Experimental value, Oral)
ATE US (oral)	2140 mg/kg body weight
SODIUM XYLENE SULFONATE (1300-72-7)	
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))
Skin corrosion/irritation :	Causes severe skin burns. pH: 0.5
Serious eye damage/irritation :	Causes serious eye damage. pH: 0.5
Respiratory or skin sensitization :	Not classified
Germ cell mutagenicity :	Not classified
	Not classified
BUTHOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable
SULFURIC ACID (7664-93-9)	
National Toxicity Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
BUTHOXYETHANOL (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	Not classified
BUTHOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ALKYL (C10-C16) BENZENESULFONIC ACID (68584-22-5)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general :	Harmful to aquatic life.
BUTHOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
SULFURIC ACID (7664-93-9)	
LC50 - Fish [1]	42 mg/l (96 h, Gambusia affinis)
EC50 - Daphnia [1]	29 mg/l (24 h, Daphnia magna)
SODIUM XYLENE SULFONATE (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
Persistence and degradability	Readily biodegradable in water.
BUTHOXYETHANOL (111-76-2)	
Persistence and degradability Readily biodegradable in water.	
SULFURIC ACID (7664-93-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SULFURIC ACID (7664-93-9)		
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
SODIUM XYLENE SULFONATE (1300-72-7)		
Persistence and degradability	Readily biodegradable in water.	
12.3. Bioaccumulative potential		
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
Partition coefficient n-octanol/water (Log Pow)	3.01 (Estimated value)	
Bioaccumulative potential	Not bioaccumulative.	
BUTHOXYETHANOL (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
SULFURIC ACID (7664-93-9)		
Partition coefficient n-octanol/water (Log Pow)	-2.2 (Estimated value)	
Bioaccumulative potential	Not bioaccumulative.	
SODIUM XYLENE SULFONATE (1300-72-7)		
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

BUTHOXYETHANOL (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
SODIUM XYLENE SULFONATE (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Regional legislation (waste) Waste treatment methods	Disposal must be done according to official regulations.Dispose of contents/container in accordance with licensed collector's sorting instructions.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information	
14.1. UN number	
DOT NA No	: UN1760
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Corrosive liquids, n.o.s. (SUFONIC ACID DDBSA), 8, II
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8 CORROSIVE
14.4. Packing group	
Packing group (DOT)	: 11
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT)	: UN1760
14.7. Transport in bulk according to Annex	x II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory information	

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SULFURIC ACID (7664-93-9)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
15.2. International regulations	
SULFURIC ACID (7664-93-9)	

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H227	Combustible liquid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled
H402	Harmful to aquatic life

NFPA health hazard NFPA fire hazard NFPA reactivity	 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. 1 - Materials that must be preheated before ignition can occur. 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.