



# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 9/20/2022 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product code : 9707HOT

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

KARCHER NORTH AMERICA  
6398 N Karcher Way  
Aurora, 80019  
United States  
T 303-738-2400  
[info@karcherna.com](mailto:info@karcherna.com)

#### 1.4. Emergency telephone number

Emergency number : 800-535-5053  
For Chemical Emergency Call INFOTRAC 24hr/day 7days/week  
Within USA and Canada: 1-800-535-5053  
Outside USA and Canada: 011-1-352-323-3500  
(collect calls accepted)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Corrosive to metals Category 1	H290	May be corrosive to metals
Skin corrosion/irritation Category 1	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H290 - May be corrosive to metals  
H314 - Causes severe skin burns and eye damage  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P234 - Keep only in original container.  
P260 - Do not breathe dust, fume, gas, mist, spray, vapors.  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.  
P264 - Wash hands, forearms and face thoroughly after handling.

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a POISON CENTER, a doctor.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P363 - Wash contaminated clothing before reuse.  
P390 - Absorb spillage to prevent material-damage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P406 - Store in corrosive resistant container with a resistant inner liner.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	30 – 50
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	5 – 10
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	1 – 5
TETRASODIUM EDTA	CAS-No.: 64-02-8	2.775 – 2.925

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Heating increases the fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Incompatible materials	: Metals.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### CARBONATE POWDER ADDITIVE

No additional information available

##### ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)

No additional information available

##### SODIUM METASILICATE (6834-92-0)

No additional information available

##### SODIUM XYLENE SULFONATE (1300-72-7)

No additional information available

##### TETRASODIUM EDTA (64-02-8)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: White
Odor	: Characteristic odour
Odor threshold	: No data available
pH	: No data available
pH solution	: 11.9 @ 1% SOLUTION
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

metals.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)

LD50 oral rat	> 1000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)

#### SODIUM METASILICATE (6834-92-0)

LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1152 mg/kg body weight

#### SODIUM XYLENE SULFONATE (1300-72-7)

LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))

#### TETRASODIUM EDTA (64-02-8)

LD50 oral rat	> 2000 mg/kg (Rat, Oral)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

#### SODIUM METASILICATE (6834-92-0)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified

#### SODIUM METASILICATE (6834-92-0)

NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

<b>SODIUM METASILICATE (6834-92-0)</b>	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
<b>SODIUM XYLENE SULFONATE (1300-72-7)</b>	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
<b>TETRASODIUM EDTA (64-02-8)</b>	
LC50 - Fish [1]	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 - Crustacea [1]	625 mg/l (24 h, Daphnia magna, Literature study)

#### 12.2. Persistence and degradability

<b>ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>SODIUM METASILICATE (6834-92-0)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>SODIUM XYLENE SULFONATE (1300-72-7)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>TETRASODIUM EDTA (64-02-8)</b>	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O <sub>2</sub> /g substance

#### 12.3. Bioaccumulative potential

<b>ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.01 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM METASILICATE (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.
SODIUM XYLENE SULFONATE (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.
TETRASODIUM EDTA (64-02-8)	
Partition coefficient n-octanol/water (Log Pow)	-2.6
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

SODIUM METASILICATE (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
SODIUM XYLENE SULFONATE (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA No : UN1759

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive solids, n.o.s., (SODIUM METASILICATE), 8, III

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : 8  
Hazard labels (DOT) : 8





# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.4. Packing group

Packing group (DOT) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1759

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

#### WARNING:


This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.  
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating  
Health : 2 Moderate Hazard - Temporary or minor injury may occur  
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)  
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

# CARBONATE POWDER ADDITIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.