

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 7/6/2021 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form Product code	Mixture 1914HOT
1.2. Recommended use and restrictions on u	ISE
Use of the substance/mixture	Cleansing product
1.3. Supplier	
KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80019 United States T 303-738-2400 info@karcherna.com	
1.4. Emergency telephone number	
Emergency number	 800-535-5053 For Chemical Emergency Call INFOTRAC 24hr/day 7days/week Within USA and Canada: 1-800-535-5053 Outside USA and Canada: 011-1-352-323-3500 (collect calls accepted)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mixtur	re
GHS US classification	
Skin corrosion/irritation Category 1 Serious eye damage/eye irritation Category 1 Full text of H statements : see section 16	H314Causes severe skin burns and eye damageH318Causes serious eye damage
2.2. GHS Label elements, including precaution	onary statements
GHS US labeling	
Hazard pictograms (GHS US)	Danger
	H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS US)	 H318 - Causes serious eye damage P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a poison center/doctor
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local regulations

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	5 – 10
BUTHOXYETHANOL	CAS-No.: 111-76-2	1 – 5
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	1 – 5
TETRASODIUM EDTA	CAS-No.: 64-02-8	1.998 – 2.106
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and effects	(acute and delayed)
Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	Burns.Serious damage to eyes.Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	y media
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Specific hazards arising from the chem	nical
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 No fire hazard. No direct explosion hazard. Toxic fumes may be released.
5.3. Special protective equipment and prec	autions for fire-fighters
Firefighting instructions Protection during firefighting	 Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equi	pment and emergency procedures
General measures	: Do not handle until all safety precautions have been read and understood.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up	
For containment Methods for cleaning up Other information	 Absorb spilled material with sand or earth. Take up liquid spill into absorbent material. Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storage	9
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling	 Not expected to present a significant hazard under anticipated conditions of normal use. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	Iding any incompatibilities

Storage conditions

: Store locked up. Store in a well-ventilated place. Keep cool.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal	protection	
8.1. Control parameters		
ENVIRO-CLEAN		
No additional information available		
TETRASODIUM EDTA (64-02-8)		
No additional information available		
SODIUM METASILICATE (6834-92-0)		
No additional information available		
SODIUM XYLENE SULFONATE (1300-72-7)		
No additional information available		
ALCOHOLS, C6-C12, ETHOXYLATED (68439-4	45-2)	
No additional information available		
BUTHOXYETHANOL (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH OEL TWA [ppm]	20 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI	
Regulatory reference	ACGIH 2019	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL (TWA) [1]	240 mg/m ³	
OSHA PEL (TWA) [2]	50 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
8.2. Appropriate engineering controls		
Appropriate engineering controls: Ensure good ventilation of the work station.Environmental exposure controls: Avoid release to the environment.		
8.3. Individual protection measures/Personal protective equipment		
Hand protection:		
Protective gloves		
Eye protection:		
Safety glasses		
Skin and body protection:		
Wear suitable protective clothing		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liguid
	•
Appearance	: Liquid.
Color	: pink
Odor	: characteristic
Odor threshold	: No data available
рН	: 13.1
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC CONTENT:

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information 11.1. Information on toxicological effects Acute toxicity (oral) : Not classified Acute toxicity (dermal) Not classified · Acute toxicity (inhalation) Not classified · **TETRASODIUM EDTA (64-02-8)** I D50 oral rat > 2000 mg/kg (Rat, Oral) SODIUM METASILICATE (6834-92-0) LD50 oral rat 1152 - 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s)) LD50 dermal rat > 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s)) > 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, LC50 inhalation rat (mg/l) Experimental value, Inhalation (vapours), 14 day(s)) ATE US (oral) 1152 mg/kg body weight SODIUM XYLENE SULFONATE (1300-72-7) LD50 oral rat > 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s)) LD50 dermal rabbit > 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s)) ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2) LD50 oral rat > 1000 mg/kg (Rat, Oral) LD50 dermal rabbit > 2000 mg/kg (Rabbit, Dermal) **BUTHOXYETHANOL (111-76-2)** 1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, LD50 oral rat Oral, 14 day(s)) LC50 inhalation rat (mg/l) > 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s)) ATE US (oral) 1414 mg/kg body weight ATE US (dermal) 1100 mg/kg body weight ATE US (gases) 4500 ppmV/4h ATE US (vapors) 11 mg/l/4h ATE US (dust, mist) 1.5 mg/l/4h

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes severe skin burns. pH: 13.1
Serious eye damage/irritation	: Causes serious eye damage.
	pH: 13.1
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
BUTHOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
STOT-single exposure	: Not classified
SODIUM METASILICATE (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.
BUTHOXYETHANOL (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
SODIUM METASILICATE (6834-92-0)	
NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
BUTHOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity		
Ecology - general :	Before neutralisation, the product may represent a danger to aquatic organisms.	
TETRASODIUM EDTA (64-02-8)		
LC50 - Fish [1]	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)	
EC50 - Daphnia [1]	625 mg/l (24 h, Daphnia magna, Literature study)	
SODIUM METASILICATE (6834-92-0)		
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)	
EC50 - Daphnia [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
SODIUM XYLENE SULFONATE (1300-72-7)		
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)	
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

12.2. Persistence and degradability

TETRASODIUM EDTA (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance	
Chemical oxygen demand (COD)	0.54 - 0.58 g O ₂ /g substance	
SODIUM METASILICATE (6834-92-0)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
SODIUM XYLENE SULFONATE (1300-72-7)		
Persistence and degradability	Readily biodegradable in water.	
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
Persistence and degradability Readily biodegradable in water.		
BUTHOXYETHANOL (111-76-2)		
ersistence and degradability Readily biodegradable in water.		

12.3. Bioaccumulative potential

TETRASODIUM EDTA (64-02-8)		
Partition coefficient n-octanol/water (Log Pow) -2.6		
Bioaccumulative potential	Not bioaccumulative.	
SODIUM METASILICATE (6834-92-0)		
Bioaccumulative potential Bioaccumulation: not applicable.		
SODIUM XYLENE SULFONATE (1300-72-7)		
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential Not bioaccumulative.		
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
Partition coefficient n-octanol/water (Log Pow)	artition coefficient n-octanol/water (Log Pow) 3.01 (Estimated value)	
Bioaccumulative potential Not bioaccumulative.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
Partition coefficient n-octanol/water (Log Pow) 0.81 (Experimental value, BASF test, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

SODIUM METASILICATE (6834-92-0)		
Surface tension	No data available in the literature	
Ecology - soil	No (test)data on mobility of the substance available.	
SODIUM XYLENE SULFONATE (1300-72-7)		
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)	
Ecology - soil	No (test)data on mobility of the substance available.	
BUTHOXYETHANOL (111-76-2)		
Surface tension	65.03 mN/m (20 °C, 2 g/l)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Regional legislation (waste) Waste treatment methods	 Disposal must be done according to official regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information		
14.1. UN number		
DOT NA No	: UN1760	
14.2. UN proper shipping name		
Proper Shipping Name (DOT)	: Corrosive liquids, n.o.s. (SODIUM METASILICATE), 8, III	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

44.2 Trememory beyond closes(ac)		
14.3. Transport hazard class(es)		
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8 CORROSIVE	
14.4. Packing group		
Packing group (DOT)	: 10	
14.5. Environmental hazards		
Other information	: No supplementary information available.	
14.6. Special precautions for user		
DOT UN-No.(DOT)	: UN1760	
14.7. Transport in bulk according to	Annex II of MARPOL 73/78 and the IBC Code	

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

A WARNING:

This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases			
H314	Causes severe skin burns and eye damage		
H318	Causes serious eye damage		
NFPA health hazar	d : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.		

		incapacitation or residual injury.
NFPA fire hazard	:	1 - Materials that must be preheated before ignition can occur.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: C - Safety glasses, Gloves, Synthetic apron
Safety Data Sheet (SDS), USA	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.